Agents, and agents talking to agents

A goal, a loop, tools, and a reason to stop. Then one agent handing work to another.

60 min | Recorded | Class 12 of 15

12

What this session covers

01
What makes something an agent
2 slides

02
Where people step in
2 slides

03
One agent handing to another
2 slides

04
Code walkthrough
4 slides

© 2026 Devansh Parapalli

Section 1 of 4

What makes something an agent

Most “agents” are a prompt with a marketing budget.

01

An agent has four things, and missing any one makes it something else

02

A chatbot answers; an agent keeps going until the job’s done or it can’t go on

© 2026 Devansh Parapalli

An agent has four things, and missing any one makes it something else

A goal	Clear the customs hold, not “help with shipping”.
A loop	Look, decide, act, look again. Class 10’s loop is the start of one.
Tools	The ways it can find things out and change things.
A reason to stop	Done, stuck, or out of steps. Without it, it runs until the bill arrives.

© 2026 Devansh Parapalli

A chatbot answers; an agent keeps going until the job's done or it can't go on

Chatbot

- One question, one answer
- A person does the next step
- Easy to check

Agent

- Plans several steps
- Calls tools between them
- Harder to check, so it needs limits

© 2026 Devansh Parapalli

Section 2 of 4

Where people step in

The part that decides whether this is safe.


01

Put a person at the points where a mistake leaves the building


02

Limits are what make an agent safe to leave running

© 2026 Devansh Parapalli



Everything else can run: lookups, searches, drafts. The agent does the legwork; a person makes the call that matters.



Section 3 of 4

One agent handing to another

A supervisor and a specialist.

01

The customs hold from class 1's world, handled by two agents and one person

02

Agent-to-agent (A2A) is how agents on different systems talk

© 2026 Devansh Parapalli

The customs hold from class 1's world, handled by two agents and one person

1

Supervisor reads the ticket: it's a customs hold

2

Hands it to the customs worker

3

Worker looks up the shipment in Tracklane

4

Worker finds the customs runbook step

5

Worker drafts the email to the customer

6

A person reads the draft and sends it, or doesn't

© 2026 Devansh Parapalli

Agent-to-agent (A2A) is how agents on different systems talk

An open protocol, the way MCP is for tools.

01 Agent card
Each agent publishes what it can do and how to reach it.

02 Tasks
One agent sends another a task and gets updates as it progresses.

03 Not MCP
MCP connects a model to tools. A2A connects one agent to another agent.

© 2026 Devansh Parapalli

Section 4 of 4

Code walkthrough

A supervisor, a customs worker, and a person at the end.

01
The worker looks things up and drafts, and never sends

02
The supervisor routes, and a person decides whether anything goes out

03
Where today sits on the card

04
What to do next

© 2026 Devansh Parapalli

The worker looks things up and drafts, and never sends

code/class12/supervisor.py

```
def customs_worker(shipment_id: str) -> str:
    """Worker: look the shipment up, find the runbook step, draft the email. Never sends
it."""
    ship = get_shipment(shipment_id)
    steps = search(f"customs documents {ship.get('reason', '')}", k=2)
    notes = "\n".join(c["text"] for _, c in steps)
    return ask(f"Shipment: {ship}\nRunbook:\n{notes}\n\nDraft a short email ...",
temperature=0.3)
```


© 2026 Devansh Parapalli

The supervisor routes, and a person decides whether anything goes out

code/class12/supervisor.py

```
for step in range(MAX_STEPS):
    decision = ask("... Reply CUSTOMS or HUMAN.\n\n" + ticket,
temperature=0).strip().upper()
    if decision == "CUSTOMS":
        shipment = next((w for w in ticket.split() if w.startswith("LOL-SH-")), None)
        if not shipment: return "handed to a person: no shipment ID in the ticket"
        draft = customs_worker(shipment.strip(","))
        ok = input(f"\n--- draft ---\n{draft}\n--- send? [y/N] ")
        return "sent" if ok.lower() == "y" else "held for a person"
```


© 2026 Devansh Parapalli

Where today sits on the card

1. A script	The steps are known and don't change.
2. A rule	The decision is known and must be explainable line by line.
3. Classical ML	Labelled history, and the input is a table or short text.
4. A small trained model	Lots of text, images or audio, enough labels, cost per call matters.
5. An LLM with a prompt	Varied language in and out, few labels, someone checks the output.
6. An LLM plus retrieval, tools or agents	**Needs private knowledge, has to act, or takes several steps.**
7. Not yet	No ground truth, needs a guarantee, or nobody owns the result.

© 2026 Devansh Parapalli

What to do next

1. Run `supervisor.py` on the Nhava Sheva ticket and read the draft before saying yes.
2. Find two handwritten tickets that should never reach an agent, and say why.
3. Read the class 13 pre-reading on evaluation.

Questions after class: the course channel.

© 2026 Devansh Parapalli