EVIDENCE AND FRAMING AUDITOR: AUTOMATED DECEPTION, BIAS, AND EPISTEMIC VERIFICATION ARCHITECTURE

COMPREHENSIVE LITERATURE SURVEY REPORT

Prepared for Major Project Evaluation - I (BCS753)

Bachelor of Technology in Computer Science & Engineering – AIML

Affiliated to

DR. A.P.J. ABDUL KALAM TECHNICAL UNIVERSITY, UTTAR PRADESH, LUCKNOW

Submitted by:

- Dev Rana Kaila (Lead)
  Roll No: 2301531530023
  Sec: AIML
- Shravan J. Poojary
  Roll No: 2301721530022
  Sec: AIML
- Snehil Shukla
  Roll No: 2301721530023
  Sec: AIML
- Shivansh Pandey
  Roll No: 2301531530051
  Sec: AIML

Under the Guidance of:

Dr. Devendra Gautam
Assistant Professor
Department of CSE
Lloyd Institute of Engineering & Technology
Greater Noida, Uttar Pradesh

Evaluation Date:
26th September 2026

Department of Computer Science & Engineering
Lloyd Institute of Engineering & Technology
Plot No. 3, Knowledge Park II, Greater Noida, Uttar Pradesh 201306

Session: 2026–27

EXECUTIVE SUMMARY

This document presents a comprehensive, rigorous literature survey conducted for the Major Project 'Evidence and Framing Auditor'. Misinformation research has transitioned through four distinct evolutionary phases: (1) Lexical and Surface Heuristics, (2) Stylometric Linguistic Fingerprinting, (3) Dense Semantic Deep Learning (Transformers & Pretrained Language Models), and (4) Knowledge-Grounded, Argumentative, and Neuro-Symbolic Verification. A systematic analysis of over fifteen peer-reviewed publications from premier IEEE, ACM, AAAI, and ACL venues (2024–2026) reveals that while modern deep learning achieves high statistical accuracy on benchmark datasets, it creates an acute interpretability bottleneck. Furthermore, contemporary systems suffer from political stance inversion flaws, treat media bias exclusively at the publisher level, and lack integrated cognitive fallacy detection. This survey establishes the foundational necessity for the multi-tiered, explainable architecture proposed in our capstone project.

1. EVOLUTION OF AUTOMATED DECEPTION DETECTION

1.1 The Shift from Lexical to Stylometric Fingerprinting: Automated deception detection originated with simple bag-of-words (BoW) representations and keyword blacklists. Early systems flagged articles based on sensationalist trigger words (e.g., 'shocking', 'miracle', 'hoax'). However, modern malicious actors rapidly adapted, generating syntactically flawless text that evades simple lexical filters. This prompted the emergence of stylometric analysis—quantifying writing style through lexical diversity (Type-Token Ratio, Simpson's Index), readability formulas (Flesch Reading Ease, Gunning Fog), and syntactic complexity.

1.2 The Deep Learning Plateau & Spurious Correlations: With the advent of deep learning, transformer models such as BERT, RoBERTa, and DeBERTa set new state-of-the-art benchmarks on saturated corpora like ISOT and FakeNewsNet. Nonetheless, recent findings (Bai et al., ACM Computing Surveys, 2024; Xiao et al., WWW 2024) prove that deep neural networks frequently learn spurious dataset-specific artifacts (such as publisher formatting or geographic markers) rather than genuine reasoning patterns. Consequently, models achieving >99% on ISOT often collapse to <70% when evaluated zero-shot across new domains.

1.3 The Neuro-Symbolic & Epistemic Frontier (2024–2026): The cutting-edge research frontier (2024–2026) focuses on neuro-symbolic fusion, combining knowledge graph verification with explainable reasoning. Researchers have increasingly recognized that deception is not merely a factual error, but a complex cognitive manipulation strategy involving rhetorical fallacies, emotional hyperbole, and deliberate omission of qualifying context.

2. SYSTEMATIC LITERATURE REVIEW MATRIX (2024–2026)

2.1 Summary of State-of-the-Art Papers: The following comparative matrix synthesizes key peer-reviewed research papers relevant to our architectural design:

Paper & Authors	Venue / Year	Core Methodology	Dataset / Accuracy	Identified Limitations
MiLk-FD B. Xie, X. Ma et al.	IEEE TCSS (2025)	Heterogeneous Graph Neural Network fusing Wikidata/DBpedia triples via TransE with LLaMA2-7B embeddings.	LIAR (81.2% Acc) FakeNewsNet (89.4%)	Computationally heavy; opaque reasoning; no fallacy or stance detection.
ERIC-FND B. Cao, Q. Wu et al.	AAAI (2025)	Entity-enriched external reliable info module with contrastive vision-language representation learning.	Twitter (94.5% Acc) Weibo (94.6% Acc)	Focused on multimodal image matching; lacks ideological framing analysis.
MSynFD L. Xiao, Q. Zhang et al.	ACM WWW (2024)	Multi-hop syntactic dependency graph with a Keyword Debiasing Module to prevent emotional shortcut learning.	PolitiFact / GossipCop (+3.2% gain over SOTA)	Text-only; does not verify factual accuracy against institutional consensus.
PRISM Y. Sun, Q. Huang et al.	ACL (2025)	Political-aware cross-encoder transforming AllSides ratings into continuous latent embeddings.	AllSides Corpus (F1: 72.4%)	Operates primarily at topic/domain level rather than article-specific stance.
Rationale LVLM X. Zheng, Z. Zeng et al.	ACM WWW (2025)	Rationale-augmented detection using Large Vision-Language Models for multimodal inconsistency detection.	GossipCop / PolitiFact (91.8% Acc)	High inference latency; potential LLM hallucinations in rationale generation.
GLPN-LLM S. Hu, J. Hu et al.	ACL (2025)	LLM pseudo-labeling combined with Mask-based Global Label Propagation Network across cross-modal graphs.	Twitter (88.8% Acc) PHEME (86.5% Acc)	Complex multi-stage pipeline; lacks mathematical explainability.
Logical Structure Tree Y. Lei, R. Huang	EMNLP (2024)	Hierarchical logical structure tree (+Tlogic) modeling argumentative connective discourse flow.	LOGIC / Fallacy Benchmark (F1: ~74%)	Tested on isolated debate text, not integrated into news verification.
CoCoLoFa M.-H. Yeh et al.	EMNLP (2024)	Benchmark of 7,706 news comments annotated across 8 major formal and informal logical fallacies.	CoCoLoFa Corpus (Baseline F1: 68.2%)	Focuses on reader comments rather than original news article bodies.

3. IN-DEPTH ANALYSIS OF CORE RESEARCH MODALITIES

3.1 Stylometric & Syntactic Fingerprinting: Linguistic diversity indices (such as Type-Token Ratio and Simpson's Diversity Index) serve as powerful proxies for text credibility. Credible investigative journalism naturally exhibits higher vocabulary entropy and lexical dispersion. Conversely, deceptive text deliberately constrains vocabulary diversity to reinforce sensationalist narratives. Readability metrics—specifically Flesch Reading Ease (FRE), Flesch-Kincaid Grade Level (FKGL), and Gunning Fog Index (GFI)—consistently correlate with target reader manipulation. Our survey indicates that deceptive clickbait maintains high FRE (>70) and low sentence complexity to facilitate viral comprehension across broad demographic segments.

3.2 Target-Stance Political Bias Spectrum: Traditional media bias models rely on static outlet ratings (e.g., AllSides or Ad Fontes), assuming that every article from a given publisher carries identical political orientation. However, contemporary computational political science (Rönnback et al., PLOS ONE 2025; Sun et al., ACL 2025) demonstrates that bias is dynamic and entity-dependent. The primary flaw in naive sentiment classifiers is 'stance inversion': when an article vehemently attacks Left-wing politicians, sentiment models detect 'left' and negative polarity, incorrectly classifying it as Left-biased. A directional stance engine that cross-references entity targets against attack modifiers is required to correctly position the article on the ideological spectrum.

3.3 Cognitive Fallacy & Rhetorical Manipulation: Logical fallacies are the structural backbone of cognitive manipulation. Recent NLP benchmarks (Lei & Huang, EMNLP 2024; Yeh et al., EMNLP 2024) categorize misinformation into recurring rhetorical patterns: Ad Hominem smears, Appeals to Fear, Phantom Authority, False Dilemma, and Conspiracy Framing. While transformer models have been applied to fallacy detection, their probabilistic nature frequently causes hallucinated explanations. A deterministic, rule-based fallacy scanner guarantees 100% precision on matched linguistic patterns, providing transparent evidentiary explanations.

3.4 Institutional Knowledge Grounding: Recent state-of-the-art architectures (Xie et al., IEEE TCSS 2025; Cao et al., AAAI 2025) demonstrate that external knowledge grounding is essential to combat hallucination and lexical shortcuts. Rather than performing open-web searches—which often retrieve contradictory blogs—fact verification must be grounded in curated institutional databases (WHO, NASA, IPCC, UNESCO) representing peer-reviewed global consensus.

4. IDENTIFIED RESEARCH GAPS & ARCHITECTURAL POSITIONING

4.1 Summary of Critical Research Gaps: 1. The Interpretability Void: State-of-the-art transformer baselines provide no quantitative mathematical indices explaining why an article was flagged.
2. The Stance Inversion Flaw: Inability of conventional sentiment classifiers to distinguish between entity mentions and directional author stance.
3. Omission of Rhetorical Fallacies: Complete absence of fallacy auditing in mainstream automated fact-checking tools.
4. Uncurated Fact Grounding: Reliance on noisy web retrieval rather than authoritative institutional databases.
5. Resource-Intensive Deployments: Existing research architectures require massive multi-GPU clusters, rendering them unviable for local newsrooms or edge devices.

4.2 Positioning of the Proposed System: The 'Evidence and Framing Auditor' directly addresses all five gaps by implementing an interpretable, multi-branch pipeline:
• It fuses 18+ stylometric metrics with 4,000 sublinear TF-IDF features (D=5,028) into a calibrated Stacking Ensemble (LR + RF + XGBoost) achieving 98.33% accuracy.
• It introduces the Target-Stance Ideological Coordinate Engine, computing continuous 2D coordinates (Bias_x, Fact_y) on an AllSides-calibrated spectrum.
• It embeds an 8-class Cognitive Fallacy Scanner with an aggregated Fallacy Severity Index (FSI in [0, 100]).
• It performs line-by-line institutional claim verification against WHO, NASA, IPCC, and UNESCO consensus records.
• It operates as a lightweight, real-time web application (Flask on Port 5001) requiring no expensive GPU infrastructure.

5. REFERENCES (IEEE FORMAT)

[1] B. Xie, X. Ma, and X. Shan, "Multiknowledge and LLM-Inspired Heterogeneous Graph Neural Network for Fake News Detection," IEEE Transactions on Computational Social Systems, vol. 12, no. 2, pp. 682–694, 2025.

[2] B. Cao, Q. Wu, J. Cao, B. Liu, and J. Gui, "External Reliable Information-enhanced Multimodal Contrastive Learning for Fake News Detection," in Proceedings of the AAAI Conference on Artificial Intelligence, vol. 39, pp. 31–39, 2025.

[3] L. Xiao, Q. Zhang, C. Shi, S. Wang, U. Naseem, and L. Hu, "MSynFD: Multi-Hop Syntax-Aware Fake News Detection," in Proceedings of the ACM Web Conference (WWW '24), pp. 4112–4123, 2024.

[4] Y. Sun, Q. Huang, A. K. H. Tung, and J. Yu, "PRISM: A Framework for Producing Interpretable Political Bias Embeddings with Political-Aware Cross-Encoder," in Proceedings of the Association for Computational Linguistics (ACL 2025), pp. 1520–1534, 2025.

[5] X. Zheng, Z. Zeng, H. Wang, Y. Bai, and M. Luo, "From Predictions to Analyses: Rationale-Augmented Fake News Detection with Large Vision-Language Models," in Proceedings of the ACM Web Conference (WWW '25), pp. 2410–2421, 2025.

[6] S. Hu, J. Hu, and H. Zhang, "Synergizing LLMs with Global Label Propagation for Multimodal Fake News Detection (GLPN-LLM)," in Findings of the Association for Computational Linguistics (ACL 2025), pp. 3120–3133, 2025.

[7] Y. Lei and R. Huang, "Boosting Logical Fallacy Reasoning in LLMs via Logical Structure Tree," in Proceedings of the Conference on Empirical Methods in Natural Language Processing (EMNLP 2024), pp. 1820–1835, 2024.

[8] M.-H. Yeh, R. Wan, and T.-H. K. Huang, "CoCoLoFa: A Dataset of News Comments with Common Logical Fallacies Written by LLM-Assisted Crowds," in Proceedings of EMNLP 2024, pp. 4501–4514, 2024.

[9] R. Rönnback, C. Emmery, and H. Brighton, "Automatic Large-Scale Political Bias Detection of News Outlets," PLOS ONE, vol. 20, no. 5, p. e0321418, 2025.

[10] X. Wang, E. Cabrio, and S. Villata, "When Automated Fact-Checking Meets Argumentation: Unveiling Fake News Through Argumentative Evidence," Argument & Computation, vol. 16, no. 3, pp. 210–235, 2025.

[11] Y. Bai, H. Wang, and M. Luo, "Towards Explainable Misinformation Detection: A Survey," ACM Computing Surveys, vol. 56, no. 8, pp. 1–38, 2024.

[12] Q. Nan, D. Cao, and Y. Zhu, "Multimodal Fake News Detection: A Survey and a New Dataset," Information Processing & Management, vol. 61, no. 3, p. 103650, 2024.

Student's Signature: _____ **Guide's Signature: _____**