



DevSaini2512 add

09abd0b · 51 minutes ago



43 lines (32 loc) · 1.33 KB

Preview

Code

Blame



Raw



understanding how existing scripts in repo work

script 1

```
#!/bin/bash          - shebang
echo "hello world!"   - printing hello world
name="Dev Saini"      - taking Dev Saini variable name
age=18                - taking 18 in variable age
```



```
echo "My name is $name and I am $age year old." - printing
name and age
```

OUTPUT :

```
#!/bin/bash
echo "hello world!"
name="Dev Saini"
name="Dev Saini"
age=18
echo "My name is $name and I am $age year old."
```

```
devsaini@ubuntu:~$ ./lol.sh
hello world!
My name is Dev Saini and I am 18 year old.
```

script 2



```
#!/bin/bash          -shebang
a="Dev Saini" -    taking Dev Saini in the variable a
b=40              -taking 40 in the variable b

if [ $a="Dev Saini" ] && [ $b -gt 18 ]; then -checking
conditions and using an operator and(&&)
    echo " you are adult "                - printing you
are adult
fi

if [ $a=" akshat" ] && [ $b -lt 18 ]; then    -checking
conditions and using an opreator and(&&)
    echo "you are minor"                    - printing you
are minor
fi
```

```
#!/bin/bash
a="Dev Saini"
b=40
if [ "$a"="Dev Saini" ] && [ $b -gt 18 ]; then
echo " you are adult "
fi
if [ "$a"=" akshat" ] && [ $b -lt 18 ]; then
echo "you are minor"
fi
```

```
devsaini@ubuntu:~$ ./lol.sh
you are adult
```

Q1 what is the purpose of #!/bin/bash at the top of the script

ANS-- the shebang line at the top of a script specifies the interpreter that should be used to the run the script.

Q2 how do you make a script executable?

ANS-- 1. add the shebang at the top 2. give permission using the chmod command 3. run the code.