



69 lines (37 loc) · 1.8 KB

Preview

Code

Blame



Raw



1. starter_kit.sh – Script to Set Up Project Structure

```
#!/bin/bash

mkdir -p project/scripts
mkdir -p project/docs
mkdir -p project/data

touch project/README.md
touch project/scripts/README.md
touch project/docs/README.md
touch project/data/README.md

echo "Starter Kit Ready!"
```

#!/bin/bash → Shebang line. It tells the system to use bash to execute this script.

.Comments (# ...) → Explain what the script does (not executed)"

."mkdir = "make directory."

.-p = creates parent directories only if they don't exist, preventing errors.

.project/{scripts,docs,data} uses brace expansion to create:

project/scripts/

project/docs/

project/data/ (All inside the project/ folder).

.echo "text" prints text.

.> redirects the output into a file. If the file doesn't exist, it creates it; if it exists, it overwrites it.

.Example:

.echo "# Project Root" > project/README.md creates a file called README.md in the project/ folder with the heading "# Project Root".



output

```
devsaini@ubuntu:~$ ./starter.sh  
devsaini@ubuntu:~$
```



Check the folder structure:



LAB Extra – Starter Kit & Automation

Purpose of the Script

The script starter_kit.sh is designed to automate the creation of a starter project environment.

It ensures a consistent folder structure (scripts/ , docs/ , data/) under the project/ directory and places placeholder README.md files inside each folder. This helps developers begin with an organized workspace without manually creating directories.

Example Run

Command:

```
bash starter_kit.sh"
```





Q1 Why is automation useful in DevoPs?

ans=1.Consistency and reliability



2.Speed and efficiency

3.Scalability

4.Reduced Human Error



Q2 what does mkdir -p do?

ans=".mkdir = "make directory."



.-p = creates parent directories only if they don't exist,
preventing errors.