



Arch Linux • System Administration

# How to Remove a Package and Its Dependencies with Pacman on Arch Linux

1 year ago • by Shahriar Shovon

When you install packages on Arch Linux with Pacman package manager, some other packages are also installed with it. These packages are called the dependencies of the package that you tried to install. It's all good that Pacman resolves all the dependencies and installs them for you. It saves you from manually installing them one by one, which obviously is boring and time consuming. But the problem comes in when you try to remove the package from your Arch Linux system. By default, Pacman package manager will only remove the

package that you tell it to, leaving the dependencies of that package installed. The problem with that is the unnecessary packages takes extra space on the hard drive. Of course that doesn't matter when you have a big hard drive on your local computer, but if it's a server that you rented online, you will have limited disk space. So saving a few megabytes to a few hundreds of megabytes is still worth it.

In this article I will show you how to remove packages on Arch Linux along with their dependencies using Pacman package manager. Let's get started.

## Finding Out the Dependencies of a Certain Package

You can use **pactree** utility to find out the packages the package **xyz** depends on.

NOTE: You don't need **pactree** to remove all the dependencies along with the package. But I find it interesting as it helps you understand how packages on your Arch Linux system are dependent on each other.

For example, you can check the dependency of the package **filezilla** with **pactree** as follows:

```
$ pactree filezilla
```

```
shovon@linuxhint:~  
File Edit View Search Terminal Help  
[shovon@linuxhint ~]$ pactree filezilla
```

As you can see, **pactree** shows you a nicely formatted tree of dependencies of **filezilla** package.


```
shovon@linuxhint:~  
File Edit View Search Terminal Help  
[shovon@linuxhint ~]$ pactree filezilla  
filezilla  
├─dbus  
│   └─libsystemd  
│       ├──glibc  
│       │   ├──linux-api-headers  
│       │   ├──tzdata  
│       │   └─filesystem  
│       │       └─iana-etc  
│       └─libcap  
│           ├──glibc  
│           ├──attr  
│           │   └─glibc  
│       └─libgcrypt  
│           └─libgpg-error  
│               ├──glibc  
│               └─bash provides sh  
│                   └─readline  
│                       ├──glibc  
│                       ├──ncurses  
│                       └─glibc
```

You can pass **-d N** parameter to **pactree** to only print a certain depth of the tree. Here **N** = 1, 2, 3, ...


When **N=1**, the direct dependency tree is printed.

You can run the following command to find out the direct dependencies of **filezilla** with **pactree**:

```
$ pactree -d 1 filezilla
```



As you can see, the direct dependencies of **filezilla** is listed.



You can print the list in plain format (not the tree format) with the following command:


```
$ pactree -d 1 -u filezilla
```

A terminal window titled 'shovon@linuxhint:~' with a menu bar (File, Edit, View, Search, Terminal, Help). The command '[shovon@linuxhint ~]\$ pactree -d 1 -u filezilla' has been executed, resulting in a plain list of dependencies: filezilla, dbus, xdg-utils, wxgtk3, libidn, hicolor-icon-theme, sqlite, gnutls, and libfilezilla. The prompt '[shovon@linuxhint ~]\$' is visible at the bottom.

```
shovon@linuxhint:~  
File Edit View Search Terminal Help  
[shovon@linuxhint ~]$ pactree -d 1 -u filezilla  
filezilla  
dbus  
xdg-utils  
wxgtk3  
libidn  
hicolor-icon-theme  
sqlite  
gnutls  
libfilezilla  
[shovon@linuxhint ~]$
```

If you want, you can export the list to a file, let's say **filezilla.txt** with the following command:

```
$ pactree -d 1 -u filezilla > filezilla.txt
```

A terminal window titled 'shovon@linuxhint:~' with a menu bar (File, Edit, View, Search, Terminal, Help). The command '[shovon@linuxhint ~]\$ pactree -d 1 -u filezilla > filezilla.txt' has been entered, and the cursor is at the end of the line.


```
shovon@linuxhint:~  
File Edit View Search Terminal Help  
[shovon@linuxhint ~]$ pactree -d 1 -u filezilla > filezilla.txt
```

## Removing a Package and All the Dependencies with Pacman

You can remove only a specific package, let's say **filezilla** using Pacman with the following command:

```
$ sudo pacman -R filezilla
```


As you can see in the screenshot below, that command would remove the package, but it would leave all the dependencies of **filezilla** package installed. This is what I was taking about earlier.



```
shovon@linuxhint:~  
File Edit View Search Terminal Help  
[shovon@linuxhint ~]$ sudo pacman -R filezilla  
[sudo] password for shovon:  
checking dependencies...  
  
Packages (1) filezilla-3.32.0-1  
  
Total Removed Size: 16.40 MiB  
  
:: Do you want to remove these packages? [Y/n]
```


You can remove all the dependencies of **filezilla** as well with the following Pacman command:

```
$ sudo pacman -Rcns filezilla
```



```
shovon@linuxhint:~  
File Edit View Search Terminal Help  
[shovon@linuxhint ~]$ sudo pacman -Rcns filezilla
```

As you can see in the screenshot below, all the direct dependencies are going to be removed as well. Just press **y** and then press **<Enter>** to remove all of these packages.



```
shovon@linuxhint:~  
File Edit View Search Terminal Help  
[shovon@linuxhint ~]$ sudo pacman -Rcns filezilla  
[sudo] password for shovon:  
checking dependencies...  
  
Packages (5) libfilezilla-0.12.1-1 wxgtk-common-3.0.4-1 wxgtk3-3.0.4-1  
             xdg-utils-1.1.2-2 filezilla-3.32.0-1  
  
Total Removed Size: 44.73 MiB  
  
:: Do you want to remove these packages? [Y/n]
```

As you can see, all the packages are removed.

```
shovon@linuxhint:~  
File Edit View Search Terminal Help  
Packages (5) libfilezilla-0.12.1-1 wxgtk-common-3.0.4-1 wxgtk3-3.0.4-1  
              xdg-utils-1.1.2-2 filezilla-3.32.0-1  
  
Total Removed Size: 44.73 MiB  
  
:: Do you want to remove these packages? [Y/n] y  
:: Processing package changes...  
(1/5) removing filezilla [#####] 100%  
(2/5) removing xdg-utils [#####] 100%  
(3/5) removing wxgtk3 [#####] 100%  
(4/5) removing wxgtk-common [#####] 100%  
(5/5) removing libfilezilla [#####] 100%  
:: Running post-transaction hooks...  
(1/3) Updating icon theme caches...  
(2/3) Arming ConditionNeedsUpdate...  
(3/3) Updating the desktop file MIME type cache...  
[shovon@linuxhint ~]$
```


## Removing Packages that Don't Depend on Other Packages

If you didn't know what I showed you earlier, and removed packages with **sudo pacman -R** command, then your Arch Linux system may have a lot of unnecessary packages still installed. But don't regret yet. There is a way to remove these unwanted packages and save disk spaces.

You can run the following command to find out all the unnecessary packages (packages that don't depend on other packages):


```
$ pacman -Qdtq
```





```
shovon@linuxhint:~  
File Edit View Search Terminal Help  
[shovon@linuxhint ~]$ pacman -Qdtq
```

As you can see, on my Arch Linux machine, four unnecessary packages are installed.




```
shovon@linuxhint:~  
File Edit View Search Terminal Help  
[shovon@linuxhint ~]$ pacman -Qdtq  
libfilezilla  
wxgtk3  
xdg-utils  
xorg-fonts-misc  
[shovon@linuxhint ~]$
```

If your Arch Linux machine show a longer list, don't be afraid as you don't have to remove them one by one.


You can remove all of these unnecessary packages with the following command:

```
$ sudo pacman -R $(pacman -Qdtq)
```

A terminal window titled 'shovon@linuxhint:~' with a menu bar (File, Edit, View, Search, Terminal, Help). The command '[shovon@linuxhint ~]\$ sudo pacman -R \$(pacman -Qdtq)' is entered at the prompt.

```
shovon@linuxhint:~  
File Edit View Search Terminal Help  
[shovon@linuxhint ~]$ sudo pacman -R $(pacman -Qdtq)
```

Press **y** and then press **<Enter>** to continue.

A terminal window titled 'shovon@linuxhint:~' showing the output of the previous command. It lists four packages to be removed and asks for confirmation.

```
shovon@linuxhint:~  
File Edit View Search Terminal Help  
[shovon@linuxhint ~]$ sudo pacman -R $(pacman -Qdtq)  
checking dependencies...  
  
Packages (4) libfilezilla-0.12.1-1 wxgtk3-3.0.4-1 xdg-utils-1.1.2-2  
             xorg-fonts-misc-1.0.3-5  
  
Total Removed Size: 29.42 MiB  
  
:: Do you want to remove these packages? [Y/n]
```

As you can see, all the unnecessary packages are removed.

```
shovon@linuxhint:~  
File Edit View Search Terminal Help  
  
Packages (4) libfilezilla-0.12.1-1 wxgtk3-3.0.4-1 xdg-utils-1.1.2-2  
xorg-fonts-misc-1.0.3-5  
  
Total Removed Size: 29.42 MiB  
  
:: Do you want to remove these packages? [Y/n] y  
:: Processing package changes...  
(1/4) removing xorg-fonts-misc [#####] 100%  
(2/4) removing xdg-utils [#####] 100%  
(3/4) removing wxgtk3 [#####] 100%  
(4/4) removing libfilezilla [#####] 100%  
:: Running post-transaction hooks...  
(1/3) Updating fontconfig cache...  
(2/3) Arming ConditionNeedsUpdate...  
(3/3) Updating X fontdir indices...  
[shovon@linuxhint ~]$
```

That's how you remove packages along with its dependencies and remove all the unnecessary packages with Pacman package manager on Arch Linux. Thanks for reading this article.

## ABOUT THE AUTHOR

### Shahriar Shovon

Freelancer & Linux System Administrator. Also loves Web API development with Node.js and JavaScript. I was born in Bangladesh. I am currently studying Electronics and Communication Engineering at Khulna University of Engineering & Technology (KUET), one of the demanding



public engineering universities of Bangladesh.

[View all posts](#)

Linux Hint LLC

1669 Holenbeck Ave, #2-244, Sunnyvale, CA

94087

[editor@linuxhint.com](mailto:editor@linuxhint.com)