# IRYS — speaker script

≈3 minute pitch + 2 minute demo. Brackets = stage directions. Each slide: cue → spoken script.

---

## SLIDE 1 — TITLE · 0:00-0:20

[Walk on. Pause. Let the logo sit for a beat.]

> "This is IRYS — a control plane for AI governance and server access. One place where an organisation defines what its AI agents may do, and who may reach its servers — and every harness and every host obeys it."

## SLIDE 2 — THE PROBLEM · 0:20-0:50

- Compliance knowledge lives in wikis and senior engineers' heads — not in the tools people actually use.
- Even experienced developers forget a crucial control; interns and new hires never learned them at all.
- Server access = shared keys, stale authorized_keys, no per-project scope or revocation.

> "Ask anyone here when they last re-read the compliance checklist before shipping. That's the problem: the rules exist, but they don't travel with the work. And SSH access is still shared keys nobody rotates."

## SLIDE 3 — THE IDEA · 0:50-1:20

> "IRYS inverts it. You define the rules once, in a dashboard — in plain language, or by hand. IRYS turns them into the files AI harnesses already read: AGENTS.md, COMMANDCODE.md, IRYS.md. The CLI syncs them into repos, the MCP server feeds them to any coding agent. And on the server side, scoped SSH keys are provisioned and revoked from the same place."

## SLIDE 4 — FOUR SURFACES · 1:20-1:40

- Governance files · scoped SSH keys · deployment procedures · full audit trail.

## SLIDE 5 — HOW IT WORKS · 1:40-2:10

> "Two planes. For keys, the host pulls: a one-line bootstrap installs a tiny agent that fetches authorized_keys every minute — so IRYS never needs inbound SSH to manage access. For deploys, your agent acts: it holds the key IRYS provisioned — only because its project is in scope — SSHes into that server, and runs the reviewed deployment procedure. So IRYS doesn't SSH in; your agent does — scoped, keyed and audited by us."

## SLIDE 6 — LIVE DEMO · 2:10-4:00

[Dashboard at localhost:4000 + terminal side by side. Log in: admin@irys.dev / demo1234.]

> “Let’s prove it. I log in — IRYS discovers my local SSH key, fingerprints it, registers it for my scoped projects. I describe the project — real rules, GDPR checklist, quality bar — and it generates AGENTS.md. Same file comes back through the CLI and through MCP. Add a server to scope and only then do its keys include me. And every step lands in the audit log.”

---

## WHO IT’S FOR

### Universities

[Slide 7] The teaching side.

> “For universities: the module already defines what students can and cannot do — what libraries are banned, how code must be reviewed, what compliance a project must meet. Today that lives in a PDF. With IRYS, the university sets those standards once, per assigned project, and every student’s AI agent follows them by default. Quality and compliance stop being per-student checkboxes and become the environment itself. Lab access is scoped per team and expires at the deadline — no key-hygiene homework, and every agent action on shared infrastructure is attributable.”

### Small businesses

[Slide 8] The shipping side.

> “For a five-person company, IRYS is the compliance team you don’t have. GDPR, secret handling, review gates — encoded once, on by default, for every developer and every agent. The new intern’s AI already knows what the company needs, wants and prefers, straight from the IRYS guidelines — they don’t have to remember it, and they can’t quietly skip it. Log in through the CLI on day one and you’re onboarded: right rules, right scope, nothing shared, everything audited.”

---

## CLOSE · 4:00-4:30

> “Under the hood it’s deliberately lean — Node, React, a bash agent — and what’s new is the control plane: one source of truth for AI behaviour and server access, with the audit trail to prove it. We’re looking for pilots — one course, one small team. Thank you.”

## ANTICIPATED QUESTIONS

- “Is this another policy doc generator?” — No: it is the enforcement path too — files, scope, keys, audit.
- “How do agents authenticate?” — CLI stores a JWT at ~/.irys; the MCP server reuses it. One login.
- “Does IRYS SSH into my servers?” — Not to manage keys: hosts pull. Your agent SSHes in to deploy — with an IRYS-scoped key, following the reviewed procedure, fully audited.
- “What about secrets?” — IRYS governs access and behaviour; secrets stay in your vault, referenced by policy.