```
1) n = int(input("Enter number of transactions: "))
transactions = []
for _ in range(n):
    acc_id, amount = map(int, input().split())
    transactions.append((acc_id, amount))
balances = {}
for acc_id, amount in transactions:
    balances[acc_id] = balances.get(acc_id, 0) + amount
highest_balance_acc = max(balances, key=balances.get)
negative_count = sum(1 for balance in balances.values() if balance < 0)
print(f"Balances: {balances}")
print(f"Highest Balance Account: {highest_balance_acc}")
print(f"Negative Balance Count: {negative_count}")
```

OUTPUT

```
Enter number of transactions: 2
101 5000
102 3000
Balances: {101: 5000, 102: 3000}
Highest Balance Account: 101
Negative Balance Count: 0

=== Code Execution Successful ===
```

Programiz
Python Online Compiler

Programiz PRO ›

main.py

Share Run

```python

n = int(input("Enter number of transactions: "))
transactions = []
for _ in range(n):
    acc_id, amount = map(int, input().split())
    transactions.append((acc_id, amount))
balances = {}
for acc_id, amount in transactions:
    balances[acc_id] = balances.get(acc_id, 0) + amount
highest_balance_acc = max(balances, key=balances.get)
negative_count = sum(1 for balance in balances.values() if balance < 0)
print(f"Balances: {balances}")
print(f"Highest Balance Account: {highest_balance_acc}")
print(f"Negative Balance Count: {negative_count}")

```

Output

Clear

```
Enter number of transactions: 2
101 5000
102 3000
Balances: {101: 5000, 102: 3000}
Highest Balance Account: 101
Negative Balance Count: 0

=== Code Execution Successful ===
```