CIG-Codec.md 10/17/2018

Generic String and Integer Key/Value Device Model

DeviceType: tmaKeyValue

Model: V01

ManufacturerId: TMAKeyValue **ManufacturerName:** TMAKeyValue

Protokoll: CoAP

Device-Model

ServiceName: StringData

```
Attributes
StringKey (length 20)
StringValue (length 200)
Commands
Request
StringParamKey (length 20)
StringParamValue (length 200)
Response
StringResponse (length 200)
```

ServiceName: IntData

```
Attributes
    IntKey (string/length 20)
    IntValue (int)

Commands
    Request
        IntParamKey (string/length 20)
        IntParamValue (int)

Response
        IntResponse (int)
```

CIG Plugin

Data Reports (Device to ALLIoT)

***Message ID: 00 *** StringData

```
00<KEY_LEN><KEY><VALUE_LEN><STRING_VALUE>
```

Response:

AA00

Message ID 01 IntData

01<KEY_LEN><KEY><INT_VALUE>

Response

AA01

Commands (ALLIoT to Device)

Command: StringCmd
Message ID 02 Request:

02<KEY_LEN><KEY><VALUE_LEN><STRING_VALUE><MID>

Message ID 04 Response:

CIG-Codec.md 10/17/2018

04<ERRCODE><MID><STRING_RESPONSE>

Command IntCmd Message ID 03 Request

03<KEY_LEN><KEY><INT_VALUE><MID>

Message ID 05 Response

05<ERRCODE><MID><INT_RESPONSE>

Parameter

Name	Туре	Len [Byte]	Description
KEY_LEN	int8u	1	
KEY	String	0…200	
VALUE_LEN	Int8u	1	
STRING_VALUE	String	0…200	
INT_VALUE	Int16s	2	
ERRCODE	Int8u	1	00 Success, 01 Error
MID	Int16u	2	Command Identifier for Request/Response
STRING_RESPONSE	String	0200	
INT_RESPONSE	Int16s	2	

Examples

 $Ascii\ to\ Hex\ Converter:\ https://www.binaryhexconverter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.com/ascii-text-to-hex-converter.c$

Send Data (Device to ALLIoT)

Send String Message

Key=City (Hex: 43697479 / 4 Byte) Value=Wattens (Hex: 57617474656e73 / 7 Byte)

Commando	Length	Message_ID	Key_len	Key	value_len	value
AT+NMGS=	14,	00	04	43697479	07	57617474656e73

AT+NMGS=14, "0004436974790757617474656e73"

Send Json String

Key=SensorData Value={"Temp":22.3,"Hum":20,"Weight":23}

Commando	Length	Message_ID	Key_len	Key	value_len	value
AT+NMGS=	47,	00	0A	53656e736f7244617461	33	3a32322e332c2248756d223a32302c22576569676874223

Send IntData

Key=Temp (hex: 010454656d7 / 4 Byte) Value=22.3 °C / raw 223

Commando	Length	Message_ID	Key_len	Key	value
AT+NMGS=	08,	01	04	010454656d7	00DF

AT+NMGS=8,"010454656d7000DF"