React – Fundamentals

Session – 4

1. Create a new React component called LikeButton that displays a heart icon and a count starting at 0; use the useState hook to increment the count by 1 each time the button is clicked.

Ans.

LikeButton.js:

```
import React, { useState } from "react";

function LikeButton() {
  const [likes, setLikes] = useState(0);

  const handleLike = () => {
    setLikes(likes + 1);
  };

  return (
    <div>
      <button onClick={handleLike}>
        💜 Like
      </button>
      <p>Likes: {likes}</p>
    </div>
  );
}

export default LikeButton;
```

App.js:

```
import React from "react";
import LikeButton from "./LikeButton";

function App() {
  return (
    <div>
      <LikeButton />
    </div>
  );
}

export default App;
```

2. Build a Flipkart-style cart item quantity manager: in a CartItem component, display the item name and quantity, and add '+' and '-' buttons to increase or decrease the quantity using useState.

Ans.

CartItem.js:

```
import React, { useState } from "react";

function CartItem() {
  const [quantity, setQuantity] = useState(1);

  const increase = () => {
    setQuantity(quantity + 1);
  };

  const decrease = () => {
    if (quantity > 1) {
      setQuantity(quantity - 1);
    }
  };

  return (
    <div>
      <h2>Wireless Mouse</h2>

      <button onClick={decrease}>-</button>
      <span style={{ margin: "0 10px" }}>{quantity}</span>
      <button onClick={increase}>+</button>
    </div>
  );
}

export default CartItem;
```

App.js:

```
import React from "react";
import CartItem from "./CartItem";

function App() {
  return (
    <div>
      <CartItem />
    </div>
  );
}
```

```
export default App;
```

3. Create a SongVote component for a Spotify playlist where users can upvote or downvote a song; display the current vote count and update it using useState when the up or down arrow is clicked.

Hint: Prevent the vote count from going below zero.

Ans.

SongVote.js:

```
import React, { useState } from "react";

function SongVote() {
  const [votes, setVotes] = useState(0);

  const upVote = () => {
    setVotes(votes + 1);
  };

  const downVote = () => {
    if (votes > 0) {
      setVotes(votes - 1);
    }
  };

  return (
    <div>
      <h2>Shape of You</h2>

      <button onClick={upVote}>⬆️</button>
      <span style={{ margin: "0 10px" }}>{votes}</span>
      <button onClick={downVote}>⬇️</button>
    </div>
  );
}

export default SongVote;
```

App.js:

```
import React from "react";
import SongVote from "./SongVote";

function App() {
  return (
    <div>
      <SongVote />
```

```
    </div>
  );
}

export default App;
```

4. Build a Zomato-style rating selector: display 5 stars, and when a user clicks on a star, highlight all stars up to that one using useState to track the selected rating.

Ans.

Rating.js:

```
import React, { useState } from "react";

function Rating() {
  const [rating, setRating] = useState(0);

  return (
    <div>
      <h2>Rate this Restaurant</h2>

      {[1, 2, 3, 4, 5].map((star) => (
        <span
          key={star}
          onClick={() => setRating(star)}
          style={{
            fontSize: "35px",
            cursor: "pointer",
            color: star <= rating ? "gold" : "gray",
          }}
        >
          ★
        </span>
      ))}

      <p>Your Rating: {rating}/5</p>
    </div>
  );
}

export default Rating;
```

App.js:

```
import React from "react";
import Rating from "./Rating";
```

```
function App() {
  return (
    <div>
      <Rating />
    </div>
  );
}

export default App;
```