React – Fundamentals

Session – 6

1. Create a React component called Playlist that takes an array of song objects (with title and artist) as a prop and uses map() to render each song in an unordered list.

Ans.

Playlist.js:

```
import React from "react";

function Playlist({ songs }) {
  return (
    <div>
      <h2>Playlist</h2>

      <ul>
        {songs.map((song, index) => (
          <li key={index}>
            {song.title} - {song.artist}
          </li>
        ))}
      </ul>
    </div>
  );
}

export default Playlist;
```

App.js:

```
import React from "react";
import Playlist from "./Playlist";

function App() {
  const songs = [
    { title: "Shape of You", artist: "Ed Sheeran" },
    { title: "Believer", artist: "Imagine Dragons" },
    { title: "Perfect", artist: "Ed Sheeran" },
  ];

  return (
    <div>
      <Playlist songs={songs} />
    </div>
  );
```

```
}

export default App;
```

2. Build a React component called OrderStatus that receives a prop isDelivered (boolean) and conditionally renders 'Order Delivered 🎉' if true, or 'Order on the way 🚚' if false, using a ternary operator.

Ans.

OrderStatus.js:

```
import React from "react";

function OrderStatus({ isDelivered }) {
  return (
    <div>
      <h2>
        {isDelivered
          ? "Order Delivered 🎉"
          : "Order on the way 🚚"}
      </h2>
    </div>
  );
}

export default OrderStatus;
```

App.js:

```
import React from "react";
import OrderStatus from "./OrderStatus";

function App() {
  return (
    <div>
      <OrderStatus isDelivered={true} />
    </div>
  );
}

export default App;
```

3. In a React component called FollowerList, render a list of followers (array of usernames). If the array is empty, display 'No followers yet' instead of the list.

Hint: Use a conditional check before mapping the array.

Ans.

FollowerList.js:

```
import React from "react";

function FollowerList({ followers }) {
  return (
    <div>
      <h2>Followers</h2>

      {followers.length > 0 ? (
        <ul>
          {followers.map((user, index) => (
            <li key={index}>{user}</li>
          ))}
        </ul>
      ) : (
        <p>No followers yet</p>
      )}
    </div>
  );
}

export default FollowerList;
```

App.js:

```
import React from "react";
import FollowerList from "./FollowerList";

function App() {
  const followers = ["john", "alice", "david"];

  return (
    <div>
      <FollowerList followers={followers} />
    </div>
  );
}

export default App;
```

4. Create a React component called CartSummary that takes an array of cart items (each with name and price). Use map() to display each item, and show 'Cart is empty' if there are no items. Add a button that only appears if there are 3 or more items, labeled 'Checkout Now'.

Ans.

CartSummary.js:

```
import React from "react";

function CartSummary({ cartItems }) {
  return (
    <div>
      <h2>Shopping Cart</h2>

      {cartItems.length > 0 ? (
        <>
          <ul>
            {cartItems.map((item, index) => (
              <li key={index}>
                {item.name} - ₹{item.price}
              </li>
            ))}
          </ul>

          {cartItems.length >= 3 && (
            <button>Checkout Now</button>
          )}
        </>
      ) : (
        <p>Cart is empty</p>
      )}
    </div>
  );
}

export default CartSummary;
```

App.js:

```
import React from "react";
import CartSummary from "./CartSummary";

function App() {
  const cartItems = [
    { name: "Laptop", price: 55000 },
    { name: "Mouse", price: 800 },
    { name: "Keyboard", price: 1500 },
  ];

  return (
    <div>
      <CartSummary cartItems={cartItems} />
```

```
    </div>
  );
}

export default App;
```