```
Enter password:
Welcome to the MariaDB monitor. Commands end with ; or \g.
Your MariaDB connection id is 3
Server version: 10.11.2-MariaDB Arch Linux
Copyright (c) 2000, 2018, Oracle, MariaDB Corporation Ab and others.
Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.
MariaDB [(none)] > show databases;
Database
| class
| class_stuff
| dbms_lab
| information_schema |
| mysql
| performance_schema |
| test
| test_libreoffice
9 rows in set (0.004 sec)
MariaDB [(none)] > use dbms_lab
Reading table information for completion of table and column names
You can turn off this feature to get a quicker startup with -A
Database changed
MariaDB [dbms_lab] > show tables;
| Tables_in_dbms_lab |
| books
course
| new_book_master
l newauthor
| newbook_master
5 rows in set (0.001 sec)
MariaDB [dbms_lab] > create table Hotel (HotelNo int Primary Key, Name varchar(50),
City varchar(50));
Query OK, O rows affected (0.020 sec)
MariaDB [dbms_lab] > describe Hotel;
| Field | Type | Null | Key | Default | Extra |
| HotelNo | int(11) | NO | PRI | NULL |
```

```
3 rows in set (0.002 sec)
MariaDB [dbms_lab] > create table Room (RoomNo int Primary Key, HotelNo int, Type
 varchar(50), Price int, foreign key(HotelNo) references Hotel(HotelNo));
Query OK, 0 rows affected (0.014 sec)
MariaDB [dbms_lab] > describe Room;
| Field | Type | Null | Key | Default | Extra |
| RoomNo | int(11) | NO | PRI | NULL | | HotelNo | int(11) | YES | MUL | NULL |
4 rows in set (0.002 sec)
MariaDB [dbms_lab] > create table Booking (HotelNo int, GuestNo int, DateFrom date,
   DateTo date, RoomNo int, foreign key(HotelNo) references Hotel(HotelNo),
   foreign key(RoomNo) references Room(RoomNo));
Query OK, 0 rows affected (0.011 sec)
MariaDB [dbms_lab] > describe Booking;
| Field | Type | Null | Key | Default | Extra |
                                     - |
| HotelNo | int(11) | YES | MUL | NULL
| GuestNo | int(11) | YES | NULL
5 rows in set (0.002 sec)
MariaDB [dbms_lab] > create table Guest(GuestNo int primary key, GuestName varchar
 (50), GuessAddress varchar(50));
Query OK, 0 rows affected (0.007 sec)
MariaDB [dbms_lab] > alter table Booking add constraint foreign key(GuestNo)
  references Guest(GuestNo);
Query OK, 0 rows affected (0.022 sec)
Records: 0 Duplicates: 0 Warnings: 0
MariaDB [dbms_lab] > describe Booking;
| Field | Type | Null | Key | Default | Extra |
| HotelNo | int(11) | YES | MUL | NULL
| GuestNo | int(11) | YES | MUL | NULL
                                      - 1
| DateTo | date
| RoomNo | int(11) | YES | MUL | NULL
5 rows in set (0.004 sec)
MariaDB [dbms_lab] > describe Guest;
```

```
| Field | Type | Null | Key | Default | Extra |
3 rows in set (0.001 sec)
MariaDB [dbms_lab] > describe Room;
| Field | Type | Null | Key | Default | Extra |
 ------+---
           4 rows in set (0.002 sec)
MariaDB [dbms_lab] > describe Hotel;
| Field | Type
                | Null | Key | Default | Extra |
- 1
3 rows in set (0.002 sec)
ariaDB [dbms_lab] > create table emp(eno int primary key, ename varchar(50), zip
 int check(zip in (400110, 400111)), hdate date unique);
Query OK, 0 rows affected (0.009 sec)
MariaDB [dbms_lab] > describe emp;
| Field | Type | Null | Key | Default | Extra |
| ename | varchar(50) | YES | | NULL | | zip | int(11) | YES | | NULL | | hdate | date | YES | UNI | NULL |
4 rows in set (0.002 sec)
MariaDB [dbms_lab] > create table parts(pno int primary key, pname varchar(50),
 qty_on_hand int not null, price int);
Query OK, 0 rows affected (0.007 sec)
MariaDB [dbms_lab] > describe parts;
| Field | Type | Null | Key | Default | Extra |
+-------------
1
                                          - 1
- 1
| price | int(11)
4 rows in set (0.002 sec)
```

```
MariaDB [dbms_lab] > create table customer(cno primary key, cname varchar(50),
  street varchar(50), Zip int not null, phone int not null unique);
ERROR 4161 (HY000): Unknown data type: 'primary'
MariaDB [dbms_lab] > create table customer(cno int primary key, cname varchar(50),
  street varchar(50), Zip int not null, phone int not null unique);
Query OK, O rows affected (0.009 sec)
MariaDB [dbms_lab] > describe customer;
| Field | Type
                   | Null | Key | Default | Extra |
             ------
5 rows in set (0.002 sec)
MariaDB [dbms_lab] > create table Orders(ono int primary key, cno int, receivedDate
   date, shippedDate date, foreign key(cno) references customer(cno));
Query OK, O rows affected (0.010 sec)
MariaDB [dbms_lab] > describe Orders;
| Field
            | Type | Null | Key | Default | Extra |
4 rows in set (0.002 sec)
MariaDB [dbms_lab] > create table odetails(ono int, pno int, qty int, foreign key(
  ono) references Orders(ono));
Query OK, 0 rows affected (0.009 sec)
MariaDB [dbms_lab] > describe odetails;
| Field | Type | Null | Key | Default | Extra |
       | int(11) | YES | MUL | NULL
| ono
      | int(11) | YES | | NULL
| int(11) | YES | | NULL
| pno
| qty
3 rows in set (0.002 sec)
MariaDB [dbms_lab] > create table zipcode(zip int primary key, city varchar(50) not
null check(city in ('Pune', 'Mumbai')));
Query OK, O rows affected (0.008 sec)
MariaDB [dbms_lab] > describe zipcode;
| Field | Type | Null | Key | Default | Extra |
```