Physe No	
0	
Date	

Devanshy Swana PC-23, 1032210755 Pornel C, CI Batch

MAIOT Lab Assignment 10

Problem Statement:

Write a study report to simulate 'cp' command in Linux Environment.

Objective:

1 Understand the file handling in Assembly language 2. Understand the command line arguments.

Theory:

- File open This function is used to open a file in the as for meading writing or both the system call used to open afile usually takes a file name and a set of flags that specify the intended mode of access such as read-only write--only or read-write.
- File read: this function is used to read data from an open file into a buffer in memory. The system call is used to read data from a file usually takes a file descriptor. a pointer to a buffer in memory, and the number of bytes to read.
- File write: used to write data from a buffer in memory to an open file. System call used to write data to a file usually takes a file descriptor, a pointer to a buffer in memory and the number of bytes to write.

Page No.				
Date				

- File create: used to create a new file in the Os. system call used to create a file usually takes a file name and a set of flags that specify the intended mode of access and the permissions for the file.
- File close: Used to close an open file and release the associated system resourches. When a file is opened the Os assigns a file description to represent the open file memory.

Algorithm.

· Open the source file in read mode.

This operation loads the file from secondary storage using given filename to memory.

· Read the source file optent and it store into buffer. To read records from the file we need to define a temporary buffer in memory where data read from the tile would be written.

· Create a destination file in read and write mode.

Environment:

08-64. bit Ubuntu 18.04 CPU- 64 bit core 2 duo

Conclusion:

Thus, the study has done to simulate (cp' command in Linux by taking flip crossroom activity.

FA & 19

. What is file descriptor?

A file descriptor is a 16-bit integer assigned to a file as a file id. When a new file is created or an existing file is appeal the file is created or an existing the file is opened, the file descriptor is used for accessing the

Page No.	
Date	

file. File descriptor of the standard file streams - stdin, stdout and stderr are 0,1, and 2 resp.

2. What is the copy command in Linux?

To plathe command in Unix and Linux to copy your files or directives. I file directory-sources] specifies the sources of the files or directries you want to copy.

And I destination arguments specifies the location you want to copy the file to.

Name: Devanshu Surana Roll No.: 23

Panel: C Batch: C1

MAIoT Assignment 10

CODE:

pop r8

mov rsi,fname2

```
section .data
msg1 db "Error",10
msgl1 equ $-msg1
msg2 db "File copy successfully",10 msgl2 equ $-msg2
%macro operate 4 mov rax,%1
mov rdi, %2
mov rsi,%3
mov rdx,%4 syscall %endmacro
section .bss fname1 resb 15 fd1 resq 1 fname2 resb 15 fd2 resq 1
buff resb 512 bufflen resq 1
section .txt global start start:
pop r8 cmp r8,3
jne err pop r8 pop r8
mov rsi, fname1
above:
mov al,[r8] cmp al,00
je next mov [rsi], al inc r8
inc rsi
imp above
next:
```

```
above2: mov al,[r8] cmp al,00

je next2 mov [rsi],al inc r8
inc rsi
jmp above2

next2:
operate 2,fname1,000000q,0777q mov [fd1],rax
operate 0, [fd1], buff, 512 mov [bufflen],rax
operate 85,fname2,0777q,0 operate 2,fname2,2,0777q mov [fd2],rax
operate 1,[fd2],buff,[bufflen]
operate 3,[fd2],0,0 operate 3,[fd1],0,0
operate 1,1,msg2,msgl2
```

jmp end err:

operate 1,1,msg1,msgl1 end:operate 60,0,0,0

OUTPUT:

