# AI-Assisted Drainage Report — DHAL_HOSHIARPUR_31235

## 1. Village Overview

| Parameter | Value |
|---|---|
| Total Area | 30.77 ha |
| Terrain Type | Flat |
| Mean Elevation | 217.3 m |
| Mean Slope | 2.0 deg |
| DTM Resolution | 1.0 m |
| CRS | WGS 84 / UTM zone 43N |

The village covers **30.77 hectares** of **flat** terrain with a mean elevation of 217.3 m and mean slope of 2.0 degrees. The DTM was generated at 1.0-m resolution from ground-classified LiDAR returns.

### Pipeline Architecture

The system is organised into an **8-stage automated pipeline**:

• **Stage 1 — Point Cloud Ingestion:** Raw LAS/LAZ drone LiDAR point cloud loading and metadata extraction.

• **Stage 2 — Ground Classification:** Morphological filtering to separate ground returns from vegetation and structures.

• **Stage 3 — DTM Generation:** Rasterisation of ground points into a 1-m Digital Terrain Model with void filling.

• **Stage 4 — Hydrological Surface Derivation:** Sink filling, D8 flow direction, flow accumulation, TWI, and stream extraction.

• **Stage 5 — Waterlogging Susceptibility:** Physics-based multi-criteria scoring (TWI, convergence, relative elevation, slope, distance-to-stream) to classify LOW / MEDIUM / HIGH risk.

• **Stage 6 — Basin Detection:** Connected-component analysis of HIGH-risk zones to identify drainage basins.

• **Stage 7 — Drain Routing:** A* cost-surface routing from each basin centroid to the nearest natural outlet (gravity-first, then pump-assisted fallback).

• **Stage 8 — Engineering Validation & Reporting:** Physics verification, drain design parameter export, and this PDF report.

## 2. Terrain & Hydrology Modeling

A 1.0-m resolution Digital Terrain Model is generated by rasterising ground-classified LiDAR returns and filling voids using inverse-distance weighting. Hydrological surfaces (sink-filled DTM, D8 flow direction, flow accumulation, and TWI) are derived using priority-flood and D8 algorithms. Natural stream networks are extracted at a flow-accumulation threshold calibrated per village.




*Figure 1 — Hillshade terrain context with slope gradient overlay (DHAL_HOSHIARPUR_31235).*

The hillshade rendering above shows the terrain morphology with slope gradient overlaid in warm colours (yellow to red = steeper). Flat or gently sloping areas are more susceptible to waterlogging as surface runoff is slower, allowing ponding.




*Figure 2 — Topographic Wetness Index and flow accumulation (DHAL_HOSHIARPUR_31235).*

The Topographic Wetness Index (TWI) quantifies the tendency of each cell to accumulate water based on upslope contributing area and local slope. High TWI values (dark blue) indicate convergent, flat terrain with large upslope catchments — prime candidates for waterlogging. Flow accumulation shows the cumulative number of upstream cells draining through each pixel, revealing natural drainage corridors.

# 3. Waterlogging Susceptibility Analysis




*Figure 3 — Waterlogging risk classification (DHAL_HOSHIARPUR_31235). Green = LOW, Yellow = MEDIUM, Red = HIGH risk.*

## Risk Distribution

| Risk Class | Area (%) | Area (ha) |
|---|---|---|
| HIGH | 0.9% | 0.28 ha |
| MEDIUM | 1.5% | 0.47 ha |
| LOW | 97.6% | — |

## Scoring Methodology

Waterlogging susceptibility is predicted through a physics-based multi-criteria scoring model. Each pixel receives a composite score from 0 to 1 based on five terrain-derived features. Pixels scoring above the HIGH threshold are classified as HIGH risk; those between the MEDIUM and HIGH thresholds are MEDIUM risk; the remainder are LOW. Thresholds are calibrated automatically per village based on the statistical distribution of scores.

## Feature Weights

| Feature | Weight | Physical Basis |
|---|---|---|
| TWI (Topographic Wetness Index) | 0.30 | Upslope area / slope — wetness tendency |
| Convergence Index | 0.20 | Terrain concavity — flow convergence |
| Relative Elevation | 0.25 | Deviation from neighbourhood mean — depressions |
| Slope Gradient | 0.15 | Steepness — runoff vs. ponding balance |
| Distance to Stream | 0.10 | Proximity to natural outlets — drainage access |

# 4. Optimized Drainage Network




*Figure 4 — Optimized drainage network (DHAL_HOSHIARPUR_31235). Green lines = gravity drains, Red dashed = pump drains, Blue = natural streams, Red shading = HIGH-risk clusters.*

## Routing Summary

| Metric | Value |
|---|---|
| Total Basins Detected | 11 |
| Gravity Drains | 7 |
| Pump-Assisted Drains | 4 |
| Retention Basins | 0 |
| Mean Pump Lift | 3.05 m |
| Max Pump Lift | 3.96 m |
| Total Drain Length | 2.40 km |
| Routing Success Rate | 100.0% |

## A* Routing Algorithm

Each basin centroid is routed to the nearest natural stream outlet using an **A* search algorithm** on the DTM cost surface. The routing engine operates in four passes with progressively relaxed constraints:

• **Pass 1 — Gravity to Primary outlets:** Pure gravity flow with 5 cm or less uphill tolerance for micro-relief noise.

• **Pass 2 — Pump to Primary outlets:** Pump-assisted routing with maximum lift of 6 m for basins unreachable by gravity.

• **Pass 3 — Gravity to Secondary outlets:** Gravity routing to lower-threshold flow-accumulation channels.

• **Pass 4 — Pump to Secondary outlets:** Pump routing to secondary outlets within 300 m search radius.

Basins that cannot be connected within these constraints are classified as **RETENTION** zones requiring on-site water management.

# 5. Engineering Validation

## 5.1 Physics Verification

Six independent physics checks validate that the waterlogging classification and drainage design are physically plausible:

| Check | Status | Detail |
|---|---|---|
| HIGH rel_elev < -0.25m | PASS | mean=-1.213m max=-0.251m |
| HIGH slope < 6° | PASS | mean=0.32° max=4.94° |
| HIGH ∩ top-30% flow_acc | PASS | 16.1% overlap |
| HIGH < 35.0% | PASS | 0.9% |
| No HIGH where slope > 10.0° | PASS | 0 pixels |
| Drains start in HIGH | PASS | 7/11 routed from HIGH clusters |

## 5.2 Priority Zones (Top 10 HIGH-Risk Clusters)

| Rank | Zone ID | Area (ha) | Drain Length (m) | Feasible |
|---|---|---|---|---|
| 1 | 199 | 0.036 | 288.0 | No |
| 2 | 216 | 0.028 | 332.3 | No |
| 3 | 155 | 0.027 | 153.8 | No |
| 4 | 205 | 0.024 | 314.6 | No |
| 5 | 219 | 0.019 | 293.6 | No |
| 6 | 70 | 0.013 | 53.9 | Yes |
| 7 | 75 | 0.010 | 315.9 | Yes |
| 8 | 185 | 0.009 | 291.8 | No |
| 9 | 108 | 0.009 | — | No |
| 10 | 31 | 0.007 | 165.1 | No |

## 5.3 Drain Design Parameters

*[Drain design parameters not available]*

# 6. Summary & Recommendation

## Key Metrics

| Metric | Value |
|---|---|
| Total Village Area | 30.77 ha |
| HIGH-Risk Area | 0.9% (0.28 ha) |
| MEDIUM-Risk Area | 1.5% (0.47 ha) |
| LOW-Risk Area | 97.6% |
| Total Basins | 11 |
| Gravity Drains | 7 |
| Pump Drains | 4 |
| Retention Zones | 0 |
| Total Drain Length | 2.40 km |
| Drainage Connectivity | 100.0% |
| Feasibility Tier | Gravity Feasible |

## Feasibility Assessment

Feasibility Tier: **Gravity Feasible**

## Planning Recommendation

Surface channels are sufficient for this village. Gravity-based flow can drain all identified waterlogging zones without pumping. Recommended action: construct open earthen channels following the optimised drain routes shown in Section 4.

## Conclusion

This report presents a comprehensive AI-assisted drainage analysis for **DHAL_HOSHIARPUR_31235**, covering 30.77 hectares of flat terrain. The automated pipeline identified **11 waterlogging basins** requiring drainage intervention, achieving **100.0% connectivity** through a combination of 7 gravity and 4 pump-assisted drain routes totalling 2.40 km.

All terrain models, waterlogging risk maps, and drainage network shapefiles are exported as GIS-ready outputs for downstream engineering design. The physics verification checks confirm that the risk classification and drain routing obey physical constraints. This analysis can be used directly for preliminary drainage planning and budgeting, or as input to detailed hydraulic design by civil engineers.