

GIT REFERENCE NOTES

By Devayush Bajaj

A Git repository tracks and saves the history of all changes made to the files in a Git project. It saves this data in a directory called `.git`, also known as the repository folder

GIT Repository Types

- 1) Local Repository - Git local repository is the one on which we will make local changes, typically this local repository is on our computer.
- 2) Remote Repository - Git remote repository is the one of the server, typically a machine situated at 42 miles away.

GIT BASH GENERAL QUERIES (For Local Repository)

Step wise queries:-

S1) add global user email :-

```
git config --global user.email devayushbajaj@gmail.com
```

S2) add global username:-

```
git config --global user.name "devayush-bajaj-coditas"
```

S3) To verify user :-

```
git config --list
```

```

coditas@DBajaj-LAP-0765 MINGW64 ~
$ git config --list
diff.astextplain.textconv=astextplain
filter.lfs.clean=git-lfs clean -- %f
filter.lfs.smudge=git-lfs smudge -- %f
filter.lfs.process=git-lfs filter-process
filter.lfs.required=true
http.sslbackend=openssl
http.sslcainfo=C:/Program Files/Git/mingw64/ssl/certs/ca-bundle.crt
core.autocrlf=true
core.fscache=true
core.symlinks=false
pull.rebase=false
credential.helper=manager-core
credential.https://dev.azure.com.usehttppath=true
init.defaultbranch=master
user.email=devayushbajaj@gmail.com
user.name=devayush-bajaj-coditas

```

S4) To make a new folder

mkdir Folder_Name

S5) To enter in that folder

cd Folder_Name

S6) To make that folder repository

git init

S7) To create a file using GitBash

touch FileName.txt

S8) To open that file:-

notepad FileName.txt

```

coditas@DBajaj-LAP-0765 MINGW64 ~
$ git config --global user.email "devayushbajaj@gmail.com"

coditas@DBajaj-LAP-0765 MINGW64 ~
$ git config --global user.name "devayush-bajaj"

coditas@DBajaj-LAP-0765 MINGW64 ~
$ mkdir folder_Name

coditas@DBajaj-LAP-0765 MINGW64 ~
$ git init
Initialized empty Git repository in C:/Users/coditas/.git/

coditas@DBajaj-LAP-0765 MINGW64 ~ (master)
$ touch FileName.txt

coditas@DBajaj-LAP-0765 MINGW64 ~ (master)
$ notepad FileName.txt

```

S9) Add message or update as per work performed using commit:-

git commit -m "This is my first commit and I have updated this repo"

```

coditas@DBajaj-LAP-0765 MINGW64 ~/Git_Demo (master)
$ git add .

coditas@DBajaj-LAP-0765 MINGW64 ~/Git_Demo (master)
$ git commit -m "This is my first commit and I have updated this repo"
[master 0065b54] This is my first commit and I have updated this repo
2 files changed, 3 insertions(+), 1 deletion(-)

```

S10) To get the status of files in the repository (Which file is added, updated and deleted):-
git status

```

coditas@DBajaj-LAP-0765 MINGW64 ~/Git_Demo (master)
$ git status
On branch master


No commits yet

Untracked files:
  (use "git add <file>..." to include in what will be committed)
    master.txt

nothing added to commit but untracked files present (use "git add" to track)

```

Q1 create folder structure



As per the above folder flow we need to create folders in our local repository

```

coditas@DBajaj-LAP-0765 MINGW64 ~ (master)
$ cd assignments

coditas@DBajaj-LAP-0765 MINGW64 ~/assignments (master)
$ mkdir JAVA
m
coditas@DBajaj-LAP-0765 MINGW64 ~/assignments (master)
$ mkdir GIT
coditas@DBajaj-LAP-0765 MINGW64 ~/assignments (master)
$ mkdir DBMS
coditas@DBajaj-LAP-0765 MINGW64 ~/assignments (master)
$ mkdir frameworks
coditas@DBajaj-LAP-0765 MINGW64 ~/assignments (master)
$ cd java
coditas@DBajaj-LAP-0765 MINGW64 ~/assignments/java (master)
$ touch .gitkeep
coditas@DBajaj-LAP-0765 MINGW64 ~/assignments/java (master)
$ cd..

```

Queries used to create the structure in local repository

`mkdir FolderName` —> create empty folder

`cd FolderName` —> Navigate to other folder present in that directory.

`touch .gitkeep` —> used when there is empty folder but still need to be uploaded in remote repository

`cd ..` —> used when we need to go back to the previous folder (as per directory)

Q2 how to add an existing folder into the github repository (using GitBash).

NOTE - Before adding a folder we need to make sure that it is not empty. If it is then use `.gitkeep`

Step wise explanation:-

S1 - First make the repository (Name=RepositoryName) on github.

S2 - Open the terminal and make the new directory (`mkdir NewDirectory`).

S3 - Copy your ProjectFolder to this NewDirectory.

S4 - Change the present work directory to NewDirectory.

S-5 Run these commands

git init	Making folder master(Repo)
git add ProjectFolderName	Adding files(We can use . to add all files)
git commit -m "first commit"	Committing
git remote add origin https://github.com/YourGithubUsername/RepositoryName.git	
git push -u origin master	Pushing the files into the remote repository

GROUP ACTIVITY

Lets-have-fun-git

In this activity, we have understood how conflict problems occurred.

Task: - There was an shared repository between all the team and there were two files

- 1) Name.txt
- 2)Character_Name.txt

We need to type the name in the first file and any fictional character in the character file.

In the very first round, each team member is allocated one time to insert his data and push these files to the remote repository. After that all the remaining 4 rounds everyone has to update without any sequence randomly.

Observation:-

We have observed that in the end while tely the data. Few data seems to be mismatched. Means one name is assigned to the character of another name.

This explains the problem of conflict when multiple users are working on a particular file.

STEPS TO FOLLOW

- 1) Cone the data from the github repository
git clone Repo_Link

- 2) Edit the file and fill the details
- 3) `git add .`
- 4) `git status`
- 5) `Git commit -m"msg"`
- 6) `Git push origin master`