

Documentation on setting up devwmu from scratch.

1. `pnpm create @tanstack/start@latest`
2. Follow CLI prompts and choose what's wanted for the project (e.g. prisma, better-auth, etc)
3. Go into `.env.local` and create a better auth secret using the command: `pnpm dlx @better-auth/cli secret`
4. Follow documentation in [README.md](#). This explains the required setup for the selected packages (When setting up the project with the CLI [step 1]).
5. I had to install prisma in the package even though I had selected prisma in step 1.
 - a. Since we're using postgres, I followed their pnpm installation steps
 - b. <https://www.prisma.io/docs/getting-started/prisma-orm/add-to-existing-project/prisma-postgres>
6. Rename `.env.local` to `.env`
7. I had to import (`import 'dotenv/config'`) in [prisma.config.ts](#) file because prisma wasn't able to read my `.env` file.
8. Ran `pnpm prisma generate` to resolve prisma client errors in the project for `db.ts`
9. Since I'm using macos. I ran `colima start` for creating a postgres instance.
10. I setup the postgres instance for the project with my own credentials and ensured that the details of that were translated into `.env database_url`. This way, the db url has a connection to my postgres instance.
11. Ran `pnpm prisma migrate dev` to create a new migration. I named it "init"
12. Next, I went to [auth.ts](#) and ensured that the file looked like this

```
import { betterAuth } from 'better-auth'
import { tanstackStartCookies } from 'better-auth/tanstack-start'
import { prismaAdapter } from 'better-auth/adapters/prisma'
import { prisma } from '@db'
```

```
export const auth = betterAuth({
  emailAndPassword: {
    enabled: true,
  },

  baseURL: process.env.BETTER_AUTH_URL as string,
  database: prismaAdapter(prisma, {
    provider: 'postgresql',
  }),
  plugins: [tanstackStartCookies()],
})
```

13. I ran `pnpm dlx @better-auth/cli@latest generate` to ensure that the DB has schemas for `oauth`.

14. I ran another migration and called it auth. This is to remove the todo schema and persist it in the DB: `pnpm prisma migrate dev`
15. Generate the types: `pnpm prisma generate`
16. Removed the demo folder in `src/routes`, data folder in `src/data`
17. Ensures that [seed.ts](#) doesn't create a todo (Since we removed it)
18. `Git add . -> git commit -m "Init"`
19. The rest is up to you