

Implementing the Caesar Cipher

Counting Loops

Concept Review: Loops, Indexes

- You've used different loops in solving problems:
 - Finding Codons or Tags in a String
 - **`while(true) {... break ...}`**
 - Reading lines from a FileResource
 - **`for(String s : fr.lines()) {...}`**
- You've used indexes to access strings
 - **`"cgatga".indexOf("atg");`**
 - **`"cgatga".substring(1,4);`**



Accessing Characters in a String

- The reverse of "CGATTA" is "ATTAGC"
 - Useful in genomics to process strand this way
- Palindromes can be source of fun
 - Нажал кабан на баклажан
 - Alli trota la tortilla
 - Eh, ça va, la vache?
 - Draw, O Caesar, erase a coward.
- How do we create the reverse of a string?

Indexing a String

- Must understand for loop with three parts
 - Separated by semi-colons
 - Initialization (happens once, before guard)

```
public String reverse(String s){  
    String ret = "";  
    for(int k=0; k < s.length(); k += 1){  
        ret = s.charAt(k) + ret;  
    }  
    return ret;  
}
```

Indexing a String

- Must understand for loop with three parts
 - Separated by semi-colons
 - Initialization (happens once, before guard)
 - Guard, evaluated before loop body

```
public String reverse(String s){  
    String ret = "";  
    for(int k=0; k < s.length(); k += 1){  
        ret = s.charAt(k) + ret;  
    }  
    return ret;  
}
```


Indexing a String

- Must understand for loop with three parts
 - Separated by semi-colons
 - Initialization (happens once, before guard)
 - Guard, evaluated before loop body
 - Increment, executed after loop body

```
public String reverse(String s){  
    String ret = "";  
    for(int k=0; k < s.length(); k += 1){  
        ret = s.charAt(k) + ret;  
    }  
    return ret;  
}
```

For and While Compared

- For loop: "syntactic sugar" for while loop

```
public String reverse(String s){  
    String ret = "";  
    for(int k=0; k < s.length(); k += 1){  
        ret = s.charAt(k) + ret;  
    }  
    return ret;  
}
```

```
public String reverse(String s){  
    String ret = "";  
    int k=0;  
    while (k < s.length()){  
        ret = s.charAt(k) + ret;  
        k += 1;  
    }  
    return ret;  
}
```

For and While Compared

- For loop: "syntactic sugar" for while loop

```
public String reverse(String s){  
    String ret = "";  
    for(int k=0; k < s.length(); k += 1){  
        ret = s.charAt(k) + ret;  
    }  
    return ret;  
}
```

- initialize

```
public String reverse(String s){  
    String ret = "";  
    int k=0;  
    while (k < s.length()){  
        ret = s.charAt(k) + ret;  
        k += 1;  
    }  
    return ret;  
}
```


For and While Compared

- For loop: "syntactic sugar" for while loop

```
public String reverse(String s){  
    String ret = "";  
    for(int k=0; k < s.length(); k += 1){  
        ret = s.charAt(k) + ret;  
    }  
    return ret;  
}
```

- initialize
- loop guard

```
public String reverse(String s){  
    String ret = "";  
    int k=0;  
    while (k < s.length()){  
        ret = s.charAt(k) + ret;  
        k += 1;  
    }  
    return ret;  
}
```

For and While Compared

- For loop: "syntactic sugar" for while loop


```
public String reverse(String s){  
    String ret = "";  
    for(int k=0; k < s.length(); k += 1){  
        ret = s.charAt(k) + ret;  
    }  
    return ret;  
}
```

- initialize
- loop guard
- increment

```
public String reverse(String s){  
    String ret = "";  
    int k=0;  
    while (k < s.length()){  
        ret = s.charAt(k) + ret;  
        k += 1;  
    }  
    return ret;  
}
```

Anatomy of a For Loop


- Consider the call `reverse("pit")`



```
public String reverse(String s){  
    String ret = "";  
    for(int k=0; k < s.length(); k += 1){  
        ret = s.charAt(k) + ret;  
    }  
    return ret;  
}
```

Anatomy of a For Loop


- Consider the call `reverse("pit")`



```
public String reverse(String s){  
    String ret = "";  
    → for(int k=0; k < s.length(); k += 1){  
        ret = s.charAt(k) + ret;  
    }  
    return ret;  
}
```

Anatomy of a For Loop


- Consider the call `reverse("pit")`



```
public String reverse(String s){  
    String ret = "";  
    → for(int k=0; k < s.length(); k += 1){  
        ret = s.charAt(k) + ret;  
    }  
    return ret;  
}
```


Anatomy of a For Loop


- Consider the call `reverse("pit")`



```
public String reverse(String s){  
    String ret = "";  
    → for(int k=0; k < s.length(); k += 1){  
        ret = s.charAt(k) + ret;  
    }  
    return ret;  
}
```

Anatomy of a For Loop

- Consider the call `reverse("pit")`




`'p' + "" = "p"`

```
public String reverse(String s){  
    String ret = "";  
    for(int k=0; k < s.length(); k += 1){  
        → ret = s.charAt(k) + ret;  
    }  
    return ret;  
}
```

Anatomy of a For Loop


- Consider the call `reverse("pit")`



```
public String reverse(String s){  
    String ret = "";  
    for(int k=0; k < s.length(); k += 1){  
        → ret = s.charAt(k) + ret;  
    }  
    return ret;  
}
```

Anatomy of a For Loop


- Consider the call `reverse("pit")`



```
public String reverse(String s){  
    String ret = "";  
    → for(int k=0; k < s.length(); k += 1){  
        ret = s.charAt(k) + ret;  
    }  
    return ret;  
}
```

Continuing with Loop Tracing

- Continuing with tracing reverse("pit")



```
public String reverse(String s){  
    String ret = "";  
    → for(int k=0; k < s.length(); k += 1){  
        ret = s.charAt(k) + ret;  
    }  
    return ret;  
}
```


Continuing with Loop Tracing

- Continuing with tracing reverse("pit")

s → p i t

ret

k 1


p

'i' + "p" = "ip"

```
public String reverse(String s){  
    String ret = "";  
    for(int k=0; k < s.length(); k += 1){  
        → ret = s.charAt(k) + ret;  
    }  
    return ret;  
}
```

Continuing with Loop Tracing


- Continuing with tracing reverse("pit")



```
public String reverse(String s){  
    String ret = "";  
    for(int k=0; k < s.length(); k += 1){  
        → ret = s.charAt(k) + ret;  
    }  
    return ret;  
}
```

Continuing with Loop Tracing


- Continuing with tracing reverse("pit")



```
public String reverse(String s){  
    String ret = "";  
    ➔ for(int k=0; k < s.length(); k += 1){  
        ret = s.charAt(k) + ret;  
    }  
    return ret;  
}
```

Continuing with Loop Tracing

- Continuing with tracing reverse("pit")



```
public String reverse(String s){  
    String ret = "";  
    ➔ for(int k=0; k < s.length(); k += 1){  
        ret = s.charAt(k) + ret;  
    }  
    return ret;  
}
```

Continuing with Loop Tracing

- Continuing with tracing reverse("pit")

s → p i t

ret → i p


k 2

't' + "ip" = "tip"

```
public String reverse(String s){  
    String ret = "";  
    for(int k=0; k < s.length(); k += 1){  
        → ret = s.charAt(k) + ret;  
    }  
    return ret;  
}
```


Continuing with Loop Tracing


- Continuing with tracing reverse("pit")



```
public String reverse(String s){  
    String ret = "";  
    for(int k=0; k < s.length(); k += 1){  
        → ret = s.charAt(k) + ret;  
    }  
    return ret;  
}
```

Continuing with Loop Tracing


- Continuing with tracing reverse("pit")



```
public String reverse(String s){  
    String ret = "";  
    for(int k=0; k < s.length(); k += 1){  
        → ret = s.charAt(k) + ret;  
    }  
    return ret;  
}
```

Continuing with Loop Tracing

- Continuing with tracing reverse("pit")



```
public String reverse(String s){  
    String ret = "";  
    ➔ for(int k=0; k < s.length(); k += 1){  
        ret = s.charAt(k) + ret;  
    }  
    return ret;  
}
```

Continuing with Loop Tracing

- Continuing with tracing reverse("pit")

s → p i t

ret

k 3


t i p

3 < 3 is false

```
public String reverse(String s){  
    String ret = "";  
    → for(int k=0; k < s.length(); k += 1){  
        ret = s.charAt(k) + ret;  
    }  
    return ret;  
}
```

Continuing with Loop Tracing

- Continuing with tracing reverse("pit")



```
public String reverse(String s){  
    String ret = "";  
    for(int k=0; k < s.length(); k += 1){  
        ret = s.charAt(k) + ret;  
    }  
    return ret;  
}
```


Idiomatic For Loop

- Many programmers use `i` as index variable

```
for(int i=0; i < s.length(); i += 1)
```

- Many programmers use `i++`, not `i += 1`

```
for(int i=0; i < s.length(); i++)
```

- Sometimes declare variable before loop, so scope extends to after loop

```
int i;  
for(i=0; i < s.length(); i += 1){  
}  
// can reference value of i here
```