9/16/25, 9:35 PM NamasteDev

Interview Practice New

Courses

Join Community





Bubble Sort

Bubble Sort

Bubble Sort is a simple sorting algorithm that repeatedly steps through the list, compares adjacent elements, and swaps them if they are in the wrong order.

This process is repeated until the array is sorted.

After each pass, the largest unsorted element "bubbles up" to its correct position at the end of the array. It's called "Bubble Sort"

As smaller elements slowly "bubble" to the top of the list.

Approach:

Iterate through the array multiple times.

In each pass, compare adjacent elements.

If the current element is greater than the next one, swap them.

After each pass, the largest unsorted element bubbles up to its correct position at the end .

Use a boolean flag (isSwapped) to track whether any swapping happened.

If no swaps occurred in a full pass, the array is already sorted \rightarrow early exit (optimization).

Repeat this process for n-1 passes (where n is the array length), or until no swaps are needed.

Time & Space Complexity:

Time Complexity: O(n) (Best Case) when array is already sorted (optimized with isSwapped).

Worst Case: O(n²) When array is in reverse order.

9/16/25, 9:35 PM NamasteDev

Space Complexity: O(1) In-place sorting, no extra space used.

Dry Run

```
Pass 1 (i = 0):
    j = 0 → [4, 5, 1, 3, 9] → 4 < 5 → no swap
    j = 1 → [4, 5, 1, 3, 9] → 5 > 1 → swap → [4, 1, 5, 3, 9]
    j = 2 → [4, 1, 5, 3, 9] → 5 > 3 → swap → [4, 1, 3, 5, 9]
    j = 3 → [4, 1, 3, 5, 9] → 5 < 9 → no swap

Pass 2 (i = 1):
    j = 0 → [4, 1, 3, 5, 9] → 4 > 1 → swap → [1, 4, 3, 5, 9]
    j = 1 → [1, 4, 3, 5, 9] → 4 > 3 → swap → [1, 3, 4, 5, 9]
    j = 2 → [1, 3, 4, 5, 9] → 4 < 5 → no swap

Pass 3 (i = 2):
    j = 0 → [1, 3, 4, 5, 9] → 1 < 3 → no swap
    j = 1 → [1, 3, 4, 5, 9] → 3 < 4 → no swap
    → No swaps → break</pre>
```

Final: arr: [1, 3, 4, 5, 9]

```
JavaScript Python Java C++ C C#
let arr = [4,5,1,3,9]

function bubbleSort(arr){
  let n = arr.length;
  for(let i=0; iarr[j+1]) {
    let temp=arr[j]
    arr[j]=arr[j+1];
}
```

9/16/25, 9:35 PM NamasteDev

```
arr[j+1]=temp;
    isSwapped=true;
}

if(!isSwapped)
    break;
}

return arr;
}

let result = bubbleSort(arr)
console.log("Sorted array", result)
```

Video Course Discuss doubts Contribute Certificate

Bubble Sort - DSA Notes

Bubble Sort - DSA Notes