

# @ality – JavaScript and more

[About](#)[Donate](#)[Subscribe](#)[ES2017](#)[Books \(free online!\)](#)

## Most popular (last 30 days)

[ECMAScript 2017: the final feature set](#)[ECMAScript 6 modules: the final syntax](#)[ES proposal: import\(\) – dynamically importing ES modules](#)[Making transpiled ES modules more spec-compliant](#)[ES proposal: Shared memory and atomics](#)[Classes in ECMAScript 6 \(final semantics\)](#)[Communicating between Web Workers via MessageChannel](#)

## Most popular (all time)

[ECMAScript 6 modules: the final syntax](#)[Classes in ECMAScript 6 \(final semantics\)](#)[Iterating over arrays and objects in JavaScript](#)[ECMAScript 6's new array methods](#)[The final feature set of ECMAScript 2016 \(ES7\)](#)[WebAssembly: a binary format for the web](#)[Basic JavaScript for the impatient programmer](#)[Google Dart to "ultimately ... replace JavaScript"](#)[Six nifty ES6 tricks](#)[Google's Polymer and the future of web UI frameworks](#)

## Blog archive

- [2017](#) (4)
- [2016](#) (38)

Free email newsletter: [“ES.next News”](#)

2014-05-08

## ECMAScript 6's new array methods

Labels: [dev](#), [esnext](#), [javascript](#)

**Check out my book (free online): “Exploring ES6”.** Updated version of this blog post: chapter [“New Array features”](#).

This blog post explains what new array methods ECMAScript 6 will bring and how to use them in current browsers.

Note: I'm using the terms *constructor* and *class* interchangeably.

### 1. Class methods

Array has gained methods of its own.

#### 1.1. `Array.from(arrayLike, mapFunc?, thisArg?)`

`Array.from()`'s basic functionality is to convert two kinds of objects to arrays:

- **Array-like objects**, which have a property `length` and indexed elements. Examples include the results of DOM operations such as `document.getElementsByClassName()`.
- **Iterable objects**, whose contents can be retrieved one element at a time. Arrays are iterable, as are ECMAScript's new data structures `Map` and `Set`.

The following code is an example of converting an array-like object to an array:

```
let lis = document.querySelectorAll('ul.fancy li');
Array.from(lis).forEach(function (li) {
  console.log(node);
});
```

The result of `querySelectorAll()` is not an array and does not have a `forEach()` method, which is why we need to convert it to an array before we can use that method.

#### Mapping via `Array.from()`

`Array.from()` is also a convenient alternative to using `map()` **generically**:

```
let spans = document.querySelectorAll('span.name');

// map(), generically:
let names1 = Array.prototype.map.call(spans, s => s.textContent);

// Array.from():
let names2 = Array.from(spans, s => s.textContent);
```

The second parameter of both methods is an **arrow function**.

In this example, the result of `document.querySelectorAll()` is again an array-like object, not an array, which is why we couldn't invoke `map()` on it. Previously, we converted the array-like object to an array in order to call `forEach()`. Here, we skipped

(Ad, please don't block.)



90% Unlimited Downloads Choose from Over 300,000 Vectors, Graphics & Photos.  
ads via Carbon



Dr. Axel Rauschmayer

## Free online books by Axel

[Speaking JavaScript \[up to ES5\]](#)

[Exploring ES6](#)

**JavaScript training:**  
[Ecmanauten](#)

- 2015 (65)
- ▼ 2014 (55)
  - December (4)
  - November (1)
  - October (2)
  - September (4)
  - August (3)
  - July (7)
  - June (7)
- ▼ May (8)
  - Checking whether a value is an integer in JavaScript...
  - Implementing a raffle in JavaScript
  - Understanding the four layers of JavaScript OOP
  - We're doing syntax highlighting wrong
  - ECMAScript 6's new array methods
  - Meet the site of the Web Components community
  - Identifying the current <script> element
  - JavaScript's "this": how it works, where it can tr...
- April (6)
- March (1)
- February (5)
- January (7)

- 2013 (98)
- 2012 (177)
- 2011 (380)
- 2010 (174)
- 2009 (68)
- 2008 (46)
- 2007 (12)
- 2006 (1)
- 2005 (2)

## Labels

- dev (592)
- 
- javascript (400)
- computers (316)
- 
- life (194)
- jslang (179)
- 
- esnext (156)
- apple (107)

that intermediate step via a generic method call and via the two-parameter version of `Array.from()`.

### Holes

`Array.from()` ignores holes [3] in arrays, it treats them as if they were undefined elements:

```
> Array.from([0,,2])
[ 0, undefined, 2 ]
```

That means that you can use `Array.from()` to create and fill an array:

```
> Array.from(new Array(5), () => 'a')
[ 'a', 'a', 'a', 'a', 'a' ]
> Array.from(new Array(5), (x,i) => i)
[ 0, 1, 2, 3, 4 ]
```

If you want to fill an array with a fixed value (first one of the previous two examples) then `Array.prototype.fill()` (see below) is a better choice.

### from() in subclasses of Array

Another use case for `Array.from()` is to convert an array-like or iterable object to an instance of a subclass of `Array`. For example, if you create a subclass `MyArray` of `Array` (subclassing arrays is explained in [1]) and want to convert such an object to an instance of `MyArray`, you simply use `MyArray.from()`. The reason that that works is because constructors inherit from each other in ECMAScript 6 (a super-constructor is the prototype of its sub-constructors).

```
class MyArray extends Array {
  ...
}
let instanceOfMyArray = MyArray.from(anIterable);
```

You can also combine this functionality with mapping, to get a map operation where you control the result's constructor:

```
// from() - determine the result's constructor via the receiver
// (in this case, MyArray)
let instanceOfMyArray = MyArray.from([1, 2, 3], x => x * x);

// map(): the result is always an instance of Array
let instanceOfArray = [1, 2, 3].map(x => x * x);
```

### 1.2. Array.of(...items)

If you want to turn several values into an array, you should always use an array literal, especially since the array constructor doesn't work properly if there is a single value that is a number ([more information](#) on this quirk):

```
> new Array(3, 11, 8)
[ 3, 11, 8 ]
> new Array(3)
[ , , ]
> new Array(3.1)
RangeError: Invalid array length
```

But how are you supposed to turn values into an instance of a sub-constructor of `Array` then? This is where `Array.of()` helps (remember that sub-constructors of `Array` inherit all of `Array`'s methods, including `of()`).

```
class MyArray extends Array {
  ...
}
console.log(MyArray.of(3, 11, 8) instanceof MyArray); // true
console.log(MyArray.of(3).length === 1); // true
```


## Tweets by @rauschma




Enjoying "Troll Hunters":  
 – "Let's call him 'Gnome Chomsky'"  
 – "Juliet dies in this? Nooo!"

10h

Axel Rauschmayer  
Retweeted



A nice little shout out to  
[@rauschma...](#)  
[infoworld.com/article/316483...#es2017#async](http://infoworld.com/article/316483...#es2017#async)



13h



Not a physics book!  
[twitter.com/ManningBooks/s...](https://twitter.com/ManningBooks/s...)


02 Feb

Axel Rauschmayer  
Retweeted



Making our React  
 components forbid extra  
 props has caught SO many  
 bugs. I highly recommend it.

[npmjs.com/airbnb-prop-ty...](https://npmjs.com/airbnb-prop-ty...)



02 Feb

Axel Rauschmayer  
Retweeted



Open strong. Be bold. Tell a  
 story. Do something to get  
 me interested. Opening w/  
 the "obligatory 'about me'  
 slide" puts me to sleep :)

02 Feb

Google

webdev (95)  
mobile (83)  
scitech (50)  
hack (49)  
mac (47)  
google (39)  
java (37)  
ios (33)  
business (32)  
video (32)  
clientjs (31)  
hci (27)  
entertainment (26)  
nodejs (26)  
society (26)  
browser (25)  
firefox (25)  
html5 (24)  
ipad (24)  
movie (23)  
psychology (22)  
2ality (18)  
tv (18)  
android (17)  
social (17)  
chrome (16)  
fun (16)  
jsmodules (16)  
tablet (16)  
humor (15)  
politics (15)  
web (15)  
cloud (14)  
hardware (14)  
microsoft (14)  
software engineering (13)  
blogging (12)  
gaming (12)  
eclipse (11)  
gwt (11)  
numbers (11)  
programming languages (11)  
app store (10)  
media (10)  
nature (10)  
security (10)  
semantic web (10)  
software (10)  
twitter (10)  
webos (10)  
12quirks (9)  
education (9)  
jstools (9)

Array.of() is also handy as a function that doesn't have Array()'s quirk related to wrapping values in arrays. However, be careful about an Array.prototype.map() peculiarity that can trip you up here:

```
> ['a', 'b'].map(Array.of)
[ [ 'a', 0, [ 'a', 'b' ] ],
  [ 'b', 1, [ 'a', 'b' ] ] ]
> ['a', 'b'].map(x => Array.of(x)) // better
[ [ 'a' ], [ 'b' ] ]
> ['a', 'b'].map(x => [x]) // best (in this case)
[ [ 'a' ], [ 'b' ] ]
```

As you can see above, map() passes three parameters to its callback, the last two are simply often ignored (details).

## 2. Prototype methods

Several new methods are available for array instances.

### 2.1. Iterating over arrays

The following methods help with iterating over arrays:

- Array.prototype.entries()
- Array.prototype.keys()
- Array.prototype.values()

The result of each of the aforementioned methods is a sequence of values, but they are not returned as an array; they are revealed one by one, via an iterator. Let's look at an example (I'm using Array.from() to put the iterators' contents into arrays):

```
> Array.from([ 'a', 'b' ].keys())
[ 0, 1 ]
> Array.from([ 'a', 'b' ].values())
[ 'a', 'b' ]
> Array.from([ 'a', 'b' ].entries())
[ [ 0, 'a' ],
  [ 1, 'b' ] ]
```

You can combine entries() with ECMAScript 6's for-of loop [2] and destructuring to conveniently iterate over (index, element) pairs:

```
for (let [index, elem] of ['a', 'b'].entries()) {
  console.log(index, elem);
}
```

Note: this code already works in the current Firefox.

### 2.2. Searching for array elements

Array.prototype.find(predicate, thisArg?) returns the first array element for which the callback predicate returns true. If there is no such element, it returns undefined. Example:

```
> [6, -5, 8].find(x => x < 0)
-5
> [6, 5, 8].find(x => x < 0)
undefined
```

Array.prototype.findIndex(predicate, thisArg?) returns the index of the first element for which the callback predicate returns true. If there is no such element, it returns -1. Example:

```
> [6, -5, 8].findIndex(x => x < 0)
1
> [6, 5, 8].findIndex(x => x < 0)
-1
```

Both find\* methods ignore holes [3]. The full signature of the callback predicate is:

photo (9)

webcomponents (9)

windows 8 (9)

async (8)

idea (8)

iphone (8)

itunes (8)

scifi-fantasy (8)

app (7)

babel (7)

bookmarklet (7)

chromeos (7)

english (7)

es proposal (7)

fringe (7)

html (7)

jsint (7)

jsshell (7)

thunderbolt (7)

webapp (7)

advancedjs (6)

blogger (6)

crowdsourcing (6)

latex (6)

lion (6)

promises (6)

ted (6)

book (5)

environment (5)

gadget (5)

googleio (5)

intel (5)

jsarrays (5)

jshistory (5)

layout (5)

light peak (5)

michael j. fox (5)

music (5)

pdf (5)

polymer (5)

shell (5)

tc39 (5)

template literals (5)

underscorejs (5)

vlc (5)

\_\_proto\_\_ (4)

coffeescript (4)

concurrency (4)

dart (4)

facebook (4)

gimp (4)

googleplus (4)

health (4)

howto (4)

```
predicate(element, index, array)
```

Finding NaN via `findIndex()`

A well-known [limitation](#) of `Array.prototype.indexOf()` is that it can't find NaN, because it searches for elements via `===`:

```
> [NaN].indexOf(NaN)
-1
```

With `findIndex()`, you can use `Object.is()` [\[4\]](#) and will have no such problem:

```
> [NaN].findIndex(y => Object.is(NaN, y))
0
```

You can also adopt a more general approach, by creating a helper function `elemIs()`:

```
> function elemIs(x) { return Object.is.bind(Object, x) }
> [NaN].findIndex(elemIs(NaN))
0
```

### 2.3. `Array.prototype.fill(value, start?, end?)`

Fills an array with the given value:

```
> ['a', 'b', 'c'].fill(7)
[ 7, 7, 7 ]
```

Holes [\[3\]](#) get no special treatment:

```
> new Array(3).fill(7)
[ 7, 7, 7 ]
```

Optionally, you can restrict where the filling starts and ends:

```
> ['a', 'b', 'c'].fill(7, 1, 2)
[ 'a', 7, 'c' ]
```

### 3. When can I use the new array methods?

- Some of them are already available in browsers. As usual, check kangax's [ECMAScript 6 compatibility table](#).
- Paul Miller's [es6-shim](#) library has backported them to ECMAScript 5.

### 4. References

[\[1\]: Subclassing builtins in ECMAScript 6](#) [\[2\]: Iterators and generators in ECMAScript 6](#)  
[\[3\]: "Holes in Arrays" \(Speaking JavaScript\)](#) [\[4\]: Stricter equality in JavaScript](#)

11 Comments    The 2ality blog

 Login ▾

♥ Recommend 6     Share

Sort by Best ▾



Join the discussion...

**Sime Vidas** • 3 years ago

Good overview!

1. Instead of "constructor methods", how about the term "static Array functions"? It's a good complement to the term "Array methods", I think.

2. In section 1.2., could you first explicitly define what `Array.of()` does? That section is a bit confusing without the definition.

4 ^ | v • Reply • Share ›

hp (4)

javafx (4)

kindle (4)

leopard (4)

macbook (4)

motorola (4)

münchen (4)

occupy (4)

pl fundamentals (4)

presenting (4)

publishing (4)

series (4)

textbook (4)

web design (4)

amazon (3)

asmjs (3)

back to the future (3)

bitwise\_ops (3)

css (3)

es2016 (3)

flatrr (3)

fluentconf (3)

food (3)

foreign languages (3)

house (3)

icloud (3)

info mgmt (3)

jsfuture (3)

jsstyle (3)

linux (3)

mozilla (3)

python (3)

regexp (3)

samsung (3)

tizen (3)

traffic (3)

typedjs (3)

unix (3)

adobe (2)

angry birds (2)

angularjs (2)

astronomy (2)

audio (2)

comic (2)

design (2)

dom (2)

ecommerce (2)

eval (2)

exploring es6 (2)

facebook flow (2)

facets (2)

flash (2)

free (2)

futurama (2)

**Šime Vidas** → Šime Vidas • 3 years ago

Correction: "Static Array methods" is best, I think.

2 ^ | v • Reply • Share ›

**Axel Rauschmayer** Mod → Šime Vidas • 3 years ago

Good point. My current favorite is "class methods". I changed the term in the post.

^ | v • Reply • Share ›

**jcrben** • a year ago

"But how are you supposed to turn values into an instance of a sub-constructor of Array then?"

Could you elaborate on where this is helpful?

^ | v • Reply • Share ›

**Florian F.** • 2 years ago

No mention of Array#copyWithin :) ?

^ | v • Reply • Share ›

**Axel Rauschmayer** Mod → Florian F. • a year ago

I missed in when I wrote this blog post (maybe it wasn't in the spec yet, back then). But it is described in "Exploring ES6":

[http://exploringjs.com/es6/ch\\_...](http://exploringjs.com/es6/ch_...)

^ | v • Reply • Share ›

**vrunoa** • 2 years ago

+1

^ | v • Reply • Share ›

**Colin May** • 3 years ago

Thanks, as always, for the clear and useful article. Note that the footnote markers within the article appear as links (e.g. change style on mouseover) but do nothing.

^ | v • Reply • Share ›

**Henrique Silvério** • 3 years ago

Thanks for this nice article.

Exciting ES6 news! =]

^ | v • Reply • Share ›

**azu** • 3 years ago




s/es5-shim/es6-shim/

^ | v • Reply • Share ›

**Axel Rauschmayer** Mod → azu • 3 years ago

Indeed. Fixed, thanks!

^ | v • Reply • Share ›

 [Subscribe](#)  [Add Disqus to your site](#) [Add Disqus](#) [Add](#)  [Privacy](#)

[Newer Post](#)

[Home](#)

[Older Post](#)

Subscribe to: [Post Comments \(Atom\)](#)

-----  
guide (2)  
-----  
history (2)  
-----  
hyena (2)  
-----  
internet explorer (2)  
-----  
iteration (2)  
-----  
journalism (2)  
-----  
jquery (2)  
-----  
jsengine (2)  
-----  
jslib (2)  
-----  
law (2)  
-----  
lightning (2)  
-----  
markdown (2)  
-----  
math (2)  
-----  
meego (2)  
-----  
month (2)  
-----  
nike (2)  
-----  
nokia (2)  
-----  
npm (2)  
-----  
programming (2)  
-----  
raffle (2)  
-----  
repl (2)  
-----  
servo (2)  
-----  
sponsor (2)  
-----  
steve jobs (2)  
-----  
travel (2)  
-----  
typescript (2)  
-----  
usb (2)  
-----  
winphone (2)  
-----  
wwdc (2)  
-----  
airbender (1)  
-----  
amdefine (1)  
-----  
aol (1)  
-----  
app urls (1)  
-----  
architecture (1)  
-----  
atscript (1)  
-----  
basic income (1)  
-----  
biology (1)  
-----  
blink (1)  
-----  
bluetooth (1)  
-----  
canada (1)  
-----  
clip (1)  
-----  
coding (1)  
-----  
community (1)  
-----  
cross-platform (1)  
-----  
deutsch (1)  
-----  
diaspora (1)  
-----  
distributed-social-  
network (1)  
-----  
dsl (1)  
-----  
dvd (1)  
-----  
dzone (1)  
-----  
emacs (1)  
-----  
emberjs (1)  
-----  
energy (1)  
-----  
esnext news (1)

esprop (1)  
-----  
example (1)  
-----  
facetator (1)  
-----  
feedback (1)  
-----  
firefly (1)  
-----  
firefoxos (1)  
-----  
fritzbox (1)  
-----  
german (1)  
-----  
git (1)  
-----  
guest (1)  
-----  
guice (1)  
-----  
h.264 (1)  
-----  
home entertainment (1)  
-----  
hosting (1)  
-----  
htc (1)  
-----  
ical (1)  
-----  
jsdom (1)  
-----  
jsmyth (1)  
-----  
library (1)  
-----  
location (1)  
-----  
marketing (1)  
-----  
mars (1)  
-----  
meta-data (1)  
-----  
middle east (1)  
-----  
mpaa (1)  
-----  
msl (1)  
-----  
mssurface (1)  
-----  
netflix (1)  
-----  
nsa (1)  
-----  
obama (1)  
-----  
openoffice (1)  
-----  
opinion (1)  
-----  
oracle (1)  
-----  
organizing (1)  
-----  
philosophy (1)  
-----  
pixar (1)  
-----  
pnacl (1)  
-----  
prism (1)  
-----  
privacy (1)  
-----  
proxies (1)  
-----  
puzzle (1)  
-----  
raspberry pi (1)  
-----  
read (1)  
-----  
rodney (1)  
-----  
rust (1)  
-----  
safari (1)  
-----  
sponsoring (1)  
-----  
star trek (1)  
-----  
static generation (1)  
-----  
talk (1)  
-----  
technique (1)  
-----  
theora (1)  
-----  
thunderbird (1)  
-----  
typography (1)

-----  
unicode (1)  
-----  
v8 (1)  
-----  
voice control (1)  
-----  
webassembly (1)  
-----  
webkit (1)  
-----  
webm (1)  
-----  
webpack (1)  
-----  
yahoo (1)