

@ality – JavaScript and more

[About](#)[Donate](#)[Subscribe](#)[ES2017](#)[Books \(free online!\)](#)

Most popular (last 30 days)

[ECMAScript 2017: the final feature set](#)[ECMAScript 6 modules: the final syntax](#)[ES proposal: import\(\) – dynamically importing ES modules](#)[Making transpiled ES modules more spec-compliant](#)[ES proposal: Shared memory and atomics](#)[Classes in ECMAScript 6 \(final semantics\)](#)[Communicating between Web Workers via MessageChannel](#)

Most popular (all time)

[ECMAScript 6 modules: the final syntax](#)[Classes in ECMAScript 6 \(final semantics\)](#)[Iterating over arrays and objects in JavaScript](#)[ECMAScript 6's new array methods](#)[The final feature set of ECMAScript 2016 \(ES7\)](#)[WebAssembly: a binary format for the web](#)[Basic JavaScript for the impatient programmer](#)[Google Dart to "ultimately ... replace JavaScript"](#)[Six nifty ES6 tricks](#)[Google's Polymer and the future of web UI frameworks](#)

Blog archive

[► 2017 \(4\)](#)[► 2016 \(38\)](#)

Free email newsletter: [“ES.next News”](#)

2012-06-13

JavaScript: sparse arrays vs. dense arrays

Labels: [dev](#), [javascript](#), [jsarrays](#), [jslang](#), [underscorejs](#)

In general, arrays in JavaScript are *sparse* – they can have holes in them, because an array is simply a map from indices to values. This blog post explains how to create *dense* arrays, arrays without holes.

1. Sparse arrays

Creating a sparse array of a given length is simple:

```
> var a = new Array(3);
> a
[ , , ]
> a.length
3
> a[0]
undefined
```

When you iterate over it, you can see that it has no elements. JavaScript skips the holes.

```
> a.forEach(function (x, i) { console.log(i+" "+x) });

> a.map(function (x, i) { return i })
[ , , ]
```

2. Dense arrays

Brandon Benvie recently [mentioned](#) a trick for creating a dense array on the es-discuss mailing list:

```
> var a = Array.apply(null, Array(3));
> a
[ undefined, undefined, undefined ]
```

The above invocation is equivalent to

```
Array(undefined, undefined, undefined)
```


For many things, there is not much of a difference between this array and the previous sparse array:

```
> a.length
3
> a[0]
undefined
```

However, you can now iterate over the elements, e.g. to fill the array with values:

```
> a.forEach(function (x, i) { console.log(i+" "+x) });
0. undefined
1. undefined
2. undefined
```

(Ad, please don't block.)



90% Unlimited
Downloads Choose from
Over 300,000 Vectors,
Graphics & Photos.
[ads via Carbon](#)



Dr. Axel Rauschmayer

Free online books by Axel

[Speaking JavaScript
\[up to ES5\]](#)

[Exploring ES6](#)

[JavaScript training:
Ecmanauten](#)

- 2015 (65)
- 2014 (55)
- 2013 (98)
- ▼ 2012 (177)
 - December (14)
 - November (14)
 - October (15)
 - September (14)
 - August (17)
 - July (15)
 - ▼ June (16)
 - Google I/O 2012, keynote day 2: the highlights
 - Google I/O 2012, keynote day 1: the highlights
 - Mozilla's next-generation web browser Servo is making...
 - The iPhone 5 to support NFC?
 - Do we need a crisis to change?
 - Asynchronous programming and continuation-passing ...
 - Windows Phone Summit: the highlights
 - Microsoft's new tablets: overview and thoughts
 - GIMP 2.8.0 on Mac OS X
 - Reading RSS and Atom feeds on the iPad
 - JavaScript: sparse arrays vs. dense arrays
 - Apple's WWDC announcements : a summary
 - ECMAScript.next: for-of, iterators, generators
 - A wish list for iOS 6
 - A closer look at Underscore templates
 - Notes from the Fluent JavaScript conference
- May (1)
- April (14)
- March (18)
- February (20)

```
> a.map(function (x, i) { return i })
[ 0, 1, 2 ]
```

3. One more trick

The email also mentions the following trick:

```
> Array.apply(null, Array(3)).map(Function.prototype.call.bind(Number))
[ 0, 1, 2 ]
```

This is roughly the same as

```
Array.apply(null, Array(3)).map(
  function (x,i,...) { return Number.call(x,i,...) })
```

Note that `x` is the first parameter of `call` and specifies the value of `this`. `Number` being a function, that value is ignored. I prefer the more explicit variant shown above:

```
Array.apply(null, Array(3)).map(function (x,i) { return i })
```

4. Useful in practice?

In practice, creating a dense array in the manner described above will make your code difficult to understand for others. It is thus better to use utility functions such as `_.range`:

```
> _.range(3)
[ 0, 1, 2 ]
```

Combine it with `map`, in order to fill an array with a given value.

```
> _.range(3).map(function () { return "a" })
[ 'a', 'a', 'a' ]
```

5. Related posts

- [1] [Iterating over arrays and objects in JavaScript](#)
- [2] [Trying out Underscore on Node.js](#)

6 Comments

The 2ality blog

1 Login ▾

♥ Recommend 4

🔗 Share

Sort by Best ▾



Join the discussion...

Dmitri Pavlutin • a year ago

Nice article! Short and clean :).

`Array.prototype.filter` function skips non exist elements, thus it can be used to transform sparse to dense arrays.

For example:

```
var sparse = [0, , ,];
var dense = sparse.filter(function() {
  return true;
});
```

2 ^ | ▾ • Reply • Share ▸

Šime Vidas • 4 years ago

I've found that other values also work. E.g.

```
Array.apply(0, Array(3))
```

Since, 0 is only one character, maybe use it instead of null? Or is there a particular reason why null is used?

^ | ▾ • Reply • Share ▸

Cory Gross • 4 years ago

Hi there, nice article! I just wanted to let you know that you have a minor

Tweets by @rauschma



Axel Rauschmayer
@rauschma

Enjoying "Troll Hunters":

- "Let's call him 'Gnome Chomsky'"
- "Juliet dies in this? Nooo!"

10h

Axel Rauschmayer
Retweeted



Jonathan Creamer
@jcreamer898

A nice little shout out to
[@rauschma...](#)
infoworld.com/article/316483...#es2017#async



JavaScript...
ECMASc...
infoworld...

14h



Axel Rauschmayer
@rauschma

Not a physics book!
twitter.com/ManningBooks/s...

02 Feb

Axel Rauschmayer
Retweeted



Jordan Harband
@ljharb

Making our React
components forbid extra
props has caught SO many
bugs. I highly recommend it.

npmjs.com/airbnb-prop-ty...



npm: air...
Custom ...
npmjs.com

02 Feb

Axel Rauschmayer
Retweeted



Seth Petry-Johnson
@spetryjohnson

Open strong. Be bold. Tell a
story. Do something to get
me interested. Opening w/
the "obligatory 'about me'
slide" puts me to sleep :)

02 Feb

Google

- [January](#) (19)
- [2011](#) (380)
- [2010](#) (174)
- [2009](#) (68)
- [2008](#) (46)
- [2007](#) (12)
- [2006](#) (1)
- [2005](#) (2)

Labels

- [dev](#) (592)
- [javascript](#) (400)
- [computers](#) (316)
- [life](#) (194)
- [jslang](#) (179)
- [esnext](#) (156)
- [apple](#) (107)
- [webdev](#) (95)
- [mobile](#) (83)
- [scitech](#) (50)
- [hack](#) (49)
- [mac](#) (47)
- [google](#) (39)
- [java](#) (37)
- [ios](#) (33)
- [business](#) (32)
- [video](#) (32)
- [clientjs](#) (31)
- [hci](#) (27)
- [entertainment](#) (26)
- [nodejs](#) (26)
- [society](#) (26)
- [browser](#) (25)
- [firefox](#) (25)
- [html5](#) (24)
- [ipad](#) (24)
- [movie](#) (23)
- [psychology](#) (22)
- [2ality](#) (18)
- [tv](#) (18)
- [android](#) (17)
- [social](#) (17)
- [chrome](#) (16)
- [fun](#) (16)
- [jsmodules](#) (16)
- [tablet](#) (16)
- [humor](#) (15)
- [politics](#) (15)
- [web](#) (15)
- [cloud](#) (14)
- [hardware](#) (14)
- [microsoft](#) (14)

error at the very beginning. Believe it or not, `new Array(3);` will actually produce an array equivalent to `[, , ,]`, rather than an array equivalent to `[, ,]`. Also in your second code block, `a.map` would also return an array that looks like this `[, , ,]` as well. Take the following code:

```
var a = [ , , ];
console.log(a.length); // prints 2
var a = new Array(3);
console.log(a.length); // prints 3
var a = [ , , , ];
console.log(a.length); // prints 3
```

This is not what you would expect, but it leads from the following:

```
var a = [ ];
console.log(a.length); // prints 0
a = [ , ];
console.log(a.length); // prints 1
```

Basically there is an implied `undefined` before each comma you add, but not there is not an implied `undefined` after the last comma. I didn't know this myself until I messed with this in the console just now.

^ | v • Reply • Share ›

KHS ➔ Cory Gross • 3 years ago

It's because, as you correctly noted, the value after the last comma is not an implied `undefined`. Try this:

```
a = [0, 1, 2, ]
console.log(a.length); // 3
console.log(a); // [0, 1, 2]
```

^ | v • Reply • Share ›

Axel Rauschmayer Mod ➔ Cory Gross • 4 years ago

Indeed! But that's an issue with how the Node.js REPL prints arrays. Everything that is typed in is correct. Example interaction in the REPL:

```
> [ , , , ]
[ , , ]
```

Maybe I should manually “fix” the output, I'll think about it.



^ | v • Reply • Share ›

Cory Gross ➔ Axel Rauschmayer • 4 years ago

Ah I see, I was experimenting in Chrome's console. In Chrome it returns:

```
> [ , , , ]
[undefined x 3]
```

^ | v • Reply • Share ›

✉ [Subscribe](#)  [Add Disqus to your site](#) [Add Disqus](#) [Add](#)  [Privacy](#)

[Newer Post](#)

[Home](#)

[Older Post](#)

software engineering (13)

blogging (12)

gaming (12)

eclipse (11)

gwt (11)

numbers (11)

programming languages (11)

app store (10)

media (10)

nature (10)

security (10)

semantic web (10)

software (10)

twitter (10)

webos (10)

12quirks (9)

education (9)

jstools (9)

photo (9)

webcomponents (9)

windows 8 (9)

async (8)

idea (8)

iphone (8)

itunes (8)

scifi-fantasy (8)

app (7)

babel (7)

bookmarklet (7)

chromeos (7)

english (7)

es proposal (7)

fringe (7)

html (7)

jsint (7)

jsshell (7)

thunderbolt (7)

webapp (7)

advancedjs (6)

blogger (6)

crowdsourcing (6)

latex (6)

lion (6)

promises (6)

ted (6)

book (5)

environment (5)

gadget (5)

googleio (5)

intel (5)

jsarrays (5)

jshistory (5)

layout (5)

Subscribe to: [Post Comments \(Atom\)](#)

light peak (5)

michael j. fox (5)

music (5)

pdf (5)

polymer (5)

shell (5)

tc39 (5)

template literals (5)

underscorejs (5)

vlc (5)

__proto__ (4)

coffeescript (4)

concurrency (4)

dart (4)

facebook (4)

gimp (4)

googleplus (4)

health (4)

howto (4)

hp (4)

javafx (4)

kindle (4)

leopard (4)

macbook (4)

motorola (4)

münchen (4)

occupy (4)

pl fundamentals (4)

presenting (4)

publishing (4)

series (4)

textbook (4)

web design (4)

amazon (3)

asmjs (3)

back to the future (3)

bitwise_ops (3)

css (3)

es2016 (3)

flattr (3)

fluentconf (3)

food (3)

foreign languages (3)

house (3)

icloud (3)

info mgmt (3)

jsfuture (3)

jstyle (3)

linux (3)

mozilla (3)

python (3)

regexp (3)

samsung (3)

tizen (3)

traffic (3)

typedjs (3)

unix (3)

adobe (2)

angry birds (2)

angularjs (2)

astronomy (2)

audio (2)

comic (2)

design (2)

dom (2)

ecommerce (2)

eval (2)

exploring es6 (2)

facebook flow (2)

facets (2)

flash (2)

free (2)

futurama (2)

guide (2)

history (2)

hyena (2)

internet explorer (2)

iteration (2)

journalism (2)

jquery (2)

jsengine (2)

jslib (2)

law (2)

lightning (2)

markdown (2)

math (2)

meego (2)

month (2)

nike (2)

nokia (2)

npm (2)

programming (2)

raffle (2)

repl (2)

servo (2)

sponsor (2)

steve jobs (2)

travel (2)

typescript (2)

usb (2)

winphone (2)

wwdc (2)

airbender (1)

amdefine (1)

aol (1)

app urls (1)

architecture (1)

atscript (1)

basic income (1)

biology (1)

blink (1)

bluetooth (1)

canada (1)

clip (1)

coding (1)

community (1)

cross-platform (1)

deutsch (1)

diaspora (1)

distributed-social-
network (1)

dsl (1)

dvd (1)

dzone (1)

emacs (1)

emberjs (1)

energy (1)

esnext news (1)

esprop (1)

example (1)

facetator (1)

feedback (1)

firefly (1)

firefoxos (1)

fritzbox (1)

german (1)

git (1)

guest (1)

guice (1)

h.264 (1)

home entertainment (1)

hosting (1)

htc (1)

ical (1)

jsdom (1)

jsmyth (1)

library (1)

location (1)

marketing (1)

mars (1)

meta-data (1)

middle east (1)

mpaa (1)

msl (1)

mssurface (1)

netflix (1)

nsa (1)

obama (1)

openoffice (1)

opinion (1)

oracle (1)

organizing (1)

philosophy (1)

[pixar](#) (1)

[pnac1](#) (1)

[prism](#) (1)

[privacy](#) (1)

[proxies](#) (1)

[puzzle](#) (1)

[raspberry pi](#) (1)

[read](#) (1)

[rodney](#) (1)

[rust](#) (1)

[safari](#) (1)

[sponsoring](#) (1)

[star trek](#) (1)

[static generation](#) (1)

[talk](#) (1)

[technique](#) (1)

[theora](#) (1)

[thunderbird](#) (1)

[typography](#) (1)

[unicode](#) (1)

[v8](#) (1)

[voice control](#) (1)

[webassembly](#) (1)

[webkit](#) (1)

[webm](#) (1)

[webpack](#) (1)

[yahoo](#) (1)