

# @ality – JavaScript and more

[About](#)[Donate](#)[Subscribe](#)[ES2017](#)[Books \(free online!\)](#)

## Most popular (last 30 days)

[ECMAScript 2017: the final feature set](#)[ECMAScript 6 modules: the final syntax](#)[ES proposal: import\(\) – dynamically importing ES modules](#)[Making transpiled ES modules more spec-compliant](#)[ES proposal: Shared memory and atomics](#)[Classes in ECMAScript 6 \(final semantics\)](#)[Communicating between Web Workers via MessageChannel](#)

## Most popular (all time)

[ECMAScript 6 modules: the final syntax](#)[Classes in ECMAScript 6 \(final semantics\)](#)[Iterating over arrays and objects in JavaScript](#)[ECMAScript 6's new array methods](#)[The final feature set of ECMAScript 2016 \(ES7\)](#)[WebAssembly: a binary format for the web](#)[Basic JavaScript for the impatient programmer](#)[Google Dart to "ultimately ... replace JavaScript"](#)[Six nifty ES6 tricks](#)[Google's Polymer and the future of web UI frameworks](#)

## Blog archive

[► 2017 \(4\)](#)[► 2016 \(38\)](#)

Free email newsletter: ["ES.next News"](#)

2011-08-24

## Spreading arrays into arguments in JavaScript

Labels: [dev](#), [javascript](#), [jslang](#)

**Update 2012-02-01:** Complete rewrite of the section on spreading constructor arguments.

Sometimes, one needs to *spread* the elements of an array, to use them as the arguments of a function call. JavaScript allows you to do that via `Function.prototype.apply`, but that does not work for constructor invocations. This post explains spreading and how to make it work in the presence of the `new` operator.

### 1. Spreading

*Spreading* means making a function call, method call or constructor invocation and supplying the arguments via an array. In Python, one calls this *unpacking*. ECMAScript.next will have the **spread operator** (prefix `...`) for this purpose. In current JavaScript, you can perform this operation via `Function.prototype.apply`.

### 2. Spreading function arguments

`Math.max()` returns the maximum among its 0 or more numeric parameters. With the spread operator, you can use it for arrays:

```
Math.max(...[13, 7, 30])
```

This is the equivalent of

```
Math.max(13, 7, 30)
```

In current JavaScript, you have to use `apply()`.

```
> Math.max.apply(null, [13, 7, 30])
30
```

Explanation: An `apply` invocation looks as follows:

```
func.apply(thisValue, [param1, param2, ...])
```

which is equivalent to

```
thisValue.func(param1, param2, ...)
```

Note that `func` does not have to be a method of `thisValue` – `apply` temporarily turns it into one.

### 3. Spreading constructor arguments

The `Date` constructor takes several numeric parameters and produces a date. With the spread operator, you can hand in an array.

```
new Date(...[2011, 11, 24]) // Christmas Eve 2011
```

However, this time we cannot use `apply` to implement spreading, because it does not work with `new`:

(Ad, please don't block.)



90% Unlimited Downloads Choose from Over 300,000 Vectors, Graphics & Photos.

[ads via Carbon](#)



Dr. Axel Rauschmayer

## Free online books by Axel

[Speaking JavaScript \[up to ES5\]](#)

[Exploring ES6](#)

[JavaScript training: Ecmanauten](#)

► 2015 (65)  
► 2014 (55)  
► 2013 (98)  
► 2012 (177)  
▼ 2011 (380)  
► December (22)  
► November (25)  
► October (27)  
► September (15)  
▼ August (24)  
Twitter  
bookmarklet tip:  
associate a  
name with a  
w...  
How to write and  
unit-test  
universal  
JavaScript  
mo...  
Team sizes:  
webOS versus  
Android versus  
OS X  
Spreading arrays  
into arguments  
in JavaScript  
Chrome Native  
Client: write  
C++ apps  
against  
HTML5...  
Firefox's  
extensions get  
a security  
review,  
Chrome...  
HP lost its way  
Google's options  
for Motorola in  
light of its  
Andr...  
HP will spin off PC  
division, stop  
making webOS  
ha...  
Firefox: the  
disappearing  
version number  
TV: Alphas  
An introduction to  
JSDoc  
What is the correct  
media type for  
JavaScript  
sour...  
Press review:  
Google buys  
Motorola  
Mobility  
Bluetooth low  
energy – two  
years on a coin-  
cell ba...  
JavaScript's JSON  
API  
Patents: Google  
versus Microsoft

```
> new Date.apply(null, [2011, 11, 24])  
TypeError: function apply() { [native code] } is not a constructor
```

new expects Date.apply to be a constructor function. No matter how you parenthesize the above expression, the fundamental problem remains: apply performs a function call, it does not hand arguments to the new operator.

### 3.1. A manual work-around

**First step.** Let's get the result right first, we'll worry later about handing in an array instead of separate arguments.

```
new (Date.bind(null, 2011, 11, 24))
```

We used bind() to produce a function with zero parameters (by providing them ahead of time) and then invoked that nullary function via new. bind has the following signature:

```
func.bind(thisValue, arg1, arg2, ...)
```

It turns func into a fresh function whose implicit this parameter is thisValue and whose initial arguments are always as given. When one invokes the fresh function, the arguments of such an invocation are appended to what has already been provided via bind. MDN has [more details](#). Note that in the previous example, the first argument was null, because bind turns Date into a function that does not need a thisValue: It is only invoked as a constructor and new overrides the thisValue from bind.

**Second step.** We want to hand an array to bind. So we again use apply to turn an array into arguments for a function call.

```
new (Function.prototype.bind.apply(  
  Date, [null].concat([2011, 11, 24])))
```

We invoked apply on the function Function.prototype.bind, with two arguments:

- 1st argument: this has the value Date, as in Date.bind(...), above.
- 2nd argument: The arguments for bind are created by prepending null to the array [2011, 11, 24].

### 3.2. A library method

Mozilla suggests turning the above work-around into a library method. The following is a slightly edited version of [their suggestion](#):

```
if (!Function.prototype.construct) {  
  Function.prototype.construct = function(argArray) {  
    if (!Array.isArray(argArray)) {  
      throw new TypeError("Argument must be an array");  
    }  
    var constr = this;  
    var nullaryFunc = Function.prototype.bind.apply(  
      constr, [null].concat(argArray));  
    return new nullaryFunc();  
  };  
}
```

Interaction:

```
> Date.construct([2011, 11, 24])  
Sat Dec 24 2011 00:00:00 GMT+0100 (CET)
```

### 3.3. A seemingly simpler solution

You can manually perform the actions of the new operator. For example:

```
var foo = new Foo("abc");
```

Is equivalent to

```
var foo = Object.create(Foo.prototype);  
Foo.call(foo, "abc");
```

With that work-around, we can write a simpler library method (checks are omitted):

```
Function.prototype.construct = function(argArray) {  
  var constr = this;  
  var inst = Object.create(constr.prototype);  
  constr.apply(inst, argArray);  
}
```


## Tweets by @rauschma

 **Axel Rauschm...**  
@rauschma


Enjoying "Troll Hunters":  
– "Let's call him 'Gnome Chomsky'"  
– "Juliet dies in this? Nooo!"

10h

Axel Rauschmayer  
Retweeted

 **Jonathan Creamer**  
@jcreamer898

A nice little shout out to  
[@rauschma...](#)  
[infoworld.com/article/316483...#es2017#async](http://infoworld.com/article/316483...#es2017#async)

	<b>JavaScr...</b> ECMASc... infoworld...
---	--

14h

 **Axel Rauschmayer**  
@rauschma

Not a physics book!  
[twitter.com/ManningBooks/s...](https://twitter.com/ManningBooks/s...)


02 Feb

Axel Rauschmayer  
Retweeted

 **Jordan Harband**  
@ljharb

Making our React  
components forbid extra  
props has caught SO many  
bugs. I highly recommend it.

[npmjs.com/airbnb-prop-ty...](https://npmjs.com/airbnb-prop-ty...)

	<b>npm: air...</b> Custom ... npmjs.com
---	---

02 Feb

Axel Rauschmayer  
Retweeted

 **Seth Petry-Johnson**  
@spetryjohnson

Open strong. Be bold. Tell a  
story. Do something to get  
me interested. Opening w/  
the "obligatory 'about me'  
slide" puts me to sleep :)

02 Feb

Google

Preventing the next Breivik

What's next for our economy?

iCloud icon versus classic Mac icon

Adobe Edge: a Flash-like tool for HTML5

JavaScript performance: Array.prototype versus []

Water reservoir in space: 140 trillion times our o...

Eight words not to use in your Twitter bio

- July (18)
- June (29)
- May (23)
- April (33)
- March (40)
- February (47)
- January (77)
- 2010 (174)
- 2009 (68)
- 2008 (46)
- 2007 (12)
- 2006 (1)
- 2005 (2)

## Labels

- dev (592)
- javascript (400)
- computers (316)
- life (194)
- jslang (179)
- esnext (156)
- apple (107)
- webdev (95)
- mobile (83)
- scitech (50)
- hack (49)
- mac (47)
- google (39)
- java (37)
- ios (33)
- business (32)
- video (32)
- clientjs (31)
- hci (27)
- entertainment (26)
- nodejs (26)
- society (26)

```
        return inst;
    };

    Alas, Date invoked as a function works the same as Date invoked as a constructor: It ignores the first parameter of call() and apply() and always produces a new instance.

    > Date.construct([2011, 11, 24])
    {}

    You can see that the result of construct() has not been set up. Several built-in constructors work the same as Date. But the library method will work properly with most non-built-in constructors (handling constructors that actively return values require a bit more work).
```

browser (25)  
firefox (25)  
html5 (24)  
ipad (24)  
movie (23)  
psychology (22)  
2ality (18)  
tv (18)  
android (17)  
social (17)  
chrome (16)  
fun (16)  
jsmodules (16)  
tablet (16)  
humor (15)  
politics (15)  
web (15)  
cloud (14)  
hardware (14)  
microsoft (14)  
software engineering (13)  
blogging (12)  
gaming (12)  
eclipse (11)  
gwt (11)  
numbers (11)  
programming languages (11)  
app store (10)  
media (10)  
nature (10)  
security (10)  
semantic web (10)  
software (10)  
twitter (10)  
webos (10)  
12quirks (9)  
education (9)  
jstools (9)  
photo (9)  
webcomponents (9)  
windows 8 (9)  
async (8)  
idea (8)  
iphone (8)  
itunes (8)  
scifi-fantasy (8)  
app (7)  
babel (7)  
bookmarklet (7)  
chromeos (7)  
english (7)  
es proposal (7)  
fringe (7)

6 Comments    The 2ality blog

Login ▾

Recommend 1    Share

Sort by Best ▾



Join the discussion...

**igauravsehrawat** • 3 months ago

In the note section [developer.mozilla.org/en-US/do...](https://developer.mozilla.org/en-US/docs/Function.prototype.bind) MDN says  
...

Note: This non-native Function.construct method will not work with some native constructors (like Date, for example). In these cases you have to use the Function.prototype.bind method (for example, imagine having an array like the following, to be used with Date constructor: [2012, 11, 4]; in this case you have to write something like: new (Function.prototype.bind.apply(Date, [null].concat([2012, 11, 4])))()  
)  
...

And then adds "anyhow this is not the best way to do things and probably should not be used in any production environment."

Any idea why?

^ | ▾ • Reply • Share ›

**Serge Zarouski** • a year ago

Another good use case is to use spread instead of Array.from - results seems to be the same, while code is shorter. What do you think?

^ | ▾ • Reply • Share ›

**Axel Rauschmayer** Mod ➔ **Serge Zarouski** • a year ago

Yes, but note that this is a blog post about ES5, not about ES6.

1 ^ | ▾ • Reply • Share ›

**Vasyl Zuzyak** • 4 years ago

Hi!

Sorry for bothering so old post but...

I faced with case where I need to pass values (that are in array) as parameters into function call. That function (and object it belongs to) is quite tricky. Due to this I am not able to use apply() method. I have checked this precisely and its sad but true. That function is not a constructor and I am also limited to JavaScript 1.5/ECMA-262 3rd edition so bind() will not help me either.

Do you know any trick that can help me? Otherwise I am forced to support large block of absolutely stupid code in my app..

Thanks in advance

^ | ▾ • Reply • Share ›

**Robert Kuzelj** • 4 years ago

Wouldn't it be nice if javascript supported Function.prototype.construct as callback into "new"

^ | ▾ • Reply • Share ›

**Axel Rauschmayer** Mod ➔ **Robert Kuzelj** • 4 years ago

Can you explain what you mean by that?

^ | ▾ • Reply • Share ›

Subscribe    Add Disqus to your site Add Disqus Add    Privacy

- html (7)
- jsint (7)
- jsshell (7)
- thunderbolt (7)
- webapp (7)
- advancedjs (6)
- blogger (6)
- crowdsourcing (6)
- latex (6)
- lion (6)
- promises (6)
- ted (6)
- book (5)
- environment (5)
- gadget (5)
- googleio (5)
- intel (5)
- jsarrays (5)
- jshistory (5)
- layout (5)
- light peak (5)
- michael j. fox (5)
- music (5)
- pdf (5)
- polymer (5)
- shell (5)
- tc39 (5)
- template literals (5)
- underscorejs (5)
- vlc (5)
- \_\_proto\_\_ (4)
- coffeescript (4)
- concurrency (4)
- dart (4)
- facebook (4)
- gimp (4)
- googleplus (4)
- health (4)
- howto (4)
- hp (4)
- javafx (4)
- kindle (4)
- leopard (4)
- macbook (4)
- motorola (4)
- münchen (4)
- occupy (4)
- pl fundamentals (4)
- presenting (4)
- publishing (4)
- series (4)
- textbook (4)
- web design (4)
- amazon (3)

Newer Post

Home

Older Post

Subscribe to: [Post Comments \(Atom\)](#)

asmjs (3)

back to the future (3)

bitwise\_ops (3)

css (3)

es2016 (3)

flatrr (3)

fluentconf (3)

food (3)

foreign languages (3)

house (3)

icloud (3)

info mgmt (3)

jsfuture (3)

jsstyle (3)

linux (3)

mozilla (3)

python (3)

regexp (3)

samsung (3)

tizen (3)

traffic (3)

typedjs (3)

unix (3)

adobe (2)

angry birds (2)

angularjs (2)

astronomy (2)

audio (2)

comic (2)

design (2)

dom (2)

ecommerce (2)

eval (2)

exploring es6 (2)

facebook flow (2)

facets (2)

flash (2)

free (2)

futurama (2)

guide (2)

history (2)

hyena (2)

internet explorer (2)

iteration (2)

journalism (2)

jquery (2)

jsengine (2)

jslib (2)

law (2)

lightning (2)

markdown (2)

math (2)

meego (2)

month (2)

-----  
nike (2)  
-----  
nokia (2)  
-----  
npm (2)  
-----  
programming (2)  
-----  
raffle (2)  
-----  
repl (2)  
-----  
servo (2)  
-----  
sponsor (2)  
-----  
steve jobs (2)  
-----  
travel (2)  
-----  
typescript (2)  
-----  
usb (2)  
-----  
winphone (2)  
-----  
wwdc (2)  
-----  
airbender (1)  
-----  
amdefine (1)  
-----  
aol (1)  
-----  
app urls (1)  
-----  
architecture (1)  
-----  
atscript (1)  
-----  
basic income (1)  
-----  
biology (1)  
-----  
blink (1)  
-----  
bluetooth (1)  
-----  
canada (1)  
-----  
clip (1)  
-----  
coding (1)  
-----  
community (1)  
-----  
cross-platform (1)  
-----  
deutsch (1)  
-----  
diaspora (1)  
-----  
distributed-social-  
network (1)  
-----  
dsl (1)  
-----  
dvd (1)  
-----  
dzone (1)  
-----  
emacs (1)  
-----  
emberjs (1)  
-----  
energy (1)  
-----  
esnext news (1)  
-----  
esprop (1)  
-----  
example (1)  
-----  
facetator (1)  
-----  
feedback (1)  
-----  
firefly (1)  
-----  
firefoxos (1)  
-----  
fritzbox (1)  
-----  
german (1)  
-----  
git (1)  
-----  
guest (1)  
-----  
guice (1)  
-----  
h.264 (1)  
-----  
home entertainment (1)  
-----  
hosting (1)  
-----  
htc (1)

ical (1)  
-----  
jsdom (1)  
-----  
jsmyth (1)  
-----  
library (1)  
-----  
location (1)  
-----  
marketing (1)  
-----  
mars (1)  
-----  
meta-data (1)  
-----  
middle east (1)  
-----  
mpaa (1)  
-----  
msl (1)  
-----  
mssurface (1)  
-----  
netflix (1)  
-----  
nsa (1)  
-----  
obama (1)  
-----  
openoffice (1)  
-----  
opinion (1)  
-----  
oracle (1)  
-----  
organizing (1)  
-----  
philosophy (1)  
-----  
pixar (1)  
-----  
pnacl (1)  
-----  
prism (1)  
-----  
privacy (1)  
-----  
proxies (1)  
-----  
puzzle (1)  
-----  
raspberry pi (1)  
-----  
read (1)  
-----  
rodney (1)  
-----  
rust (1)  
-----  
safari (1)  
-----  
sponsoring (1)  
-----  
star trek (1)  
-----  
static generation (1)  
-----  
talk (1)  
-----  
technique (1)  
-----  
theora (1)  
-----  
thunderbird (1)  
-----  
typography (1)  
-----  
unicode (1)  
-----  
v8 (1)  
-----  
voice control (1)  
-----  
webassembly (1)  
-----  
webkit (1)  
-----  
webm (1)  
-----  
webpack (1)  
-----  
yahoo (1)  
-----