



Asynchronous Error Handling in Express with Promises, Generators and ES7

April 21, 2015 / in Community, Express, How-To / by Marc Harter

Like 20

Tweet

Share

Share

[\[https://www.addtoany.com/share?url=https%3A%2F%2Fstrongloop.com/error-handling-express-es7-promises-generators%2F&title=Asynchronous%20Error%20handling%20in%20Express\]](https://www.addtoany.com/share?url=https%3A%2F%2Fstrongloop.com/error-handling-express-es7-promises-generators%2F&title=Asynchronous%20Error%20handling%20in%20Express)

[\[http://strongloop.com/strongblog/robust-node-applications-error-handling/\]](http://strongloop.com/strongblog/robust-node-applications-error-handling/). Promises are better

[\[http://strongloop.com/strongblog/promises-in-node-js-with-q-an-alternative-to-callbacks/\]](http://strongloop.com/strongblog/promises-in-node-js-with-q-an-alternative-to-callbacks/). Marry the built-in

error handling in Express with promises and

significantly lower the chances of an uncaught

exception. Promises are native ES6, can be used with

generators, and ES7 proposals like [async/await](#)

[\[https://github.com/tc39/ecmascript-asyncawait\]](https://github.com/tc39/ecmascript-asyncawait) through

compilers like [Babel](#) [\[http://babeljs.io/\]](http://babeljs.io/).

This article focuses on effective ways to capture and handle errors using [error-handling middleware](#)

[\[https://github.com/tc39/ecmascript-asyncawait\]](https://github.com/tc39/ecmascript-asyncawait) in Express^[1] [\[#foot1\]](#). The article also includes a sample repository of

Questions?

[Contact us](#)

for training and professional services to see how Node.js can accelerate your mobile, IoT and next-generation web API.

Recent Posts

Introducing Raymon
Cat Person who Occ
Evangelizes

January 31, 2017 - 7:01

The Future of Node.js
"Community Focus
and Inclusive Node

January 24, 2017 - 3:21

Introducing Joe Sep
Lead Developer Evar
Friends Call Me Joe
Can Too"

January 24, 2017 - 2:41

Categories

[API Connect](#) (15)

[API Tip](#) (11)

[Arc](#) (24)

[BACN](#) (3)

[Case Studies](#) (3)

[Cloud](#) (11)

[Community](#) (251)

these concepts on [GitHub \[https://github.com/strongloop-community/express-example-error-handling\]](https://github.com/strongloop-community/express-example-error-handling).



First, let's look at what Express handles out of the box and then we will look at using promises, promise generators and ES7 `async/await` to simplify things further.

Express has built-in synchronous handling

By default, Express will catch any exception thrown within the initial *synchronous* execution of a route and pass it along to the next error-handling middleware:

```
app.get('/', function (req, res) {
  throw new Error('oh no!')
})
app.use(function (err, req, res, next) {
  console.log(err.message) // oh no!
})
```

Yet in asynchronous code, Express cannot catch exceptions as you've lost your stack once you have entered a callback:

```
app.get('/', function (req, res) {
  queryDb(function (er, data) {
    if (er) throw er
  })
})
app.use(function (err, req, res, next) {
  // error never gets here
})
```

For these cases, use the `next` function to propagate errors:

```
app.get('/', function (req, res, next) {
  queryDb(function (err, data) {
    if (err) return next(err)
    // handle data
  })
})
```

[Espanol](#) (7)
[Events](#) (30)
[Express](#) (21)
[How-To](#) (162)
[JavaScript Language](#) (20)
[ES2015/ES6](#) (6)
[LoopBack](#) (127)
[Mobile](#) (32)
[News](#) (125)
[Node core](#) (6)
[Node DevOps](#) (22)
[Node.js v0.12](#) (17)
[Performance Tip](#) (11)
[Portuguese](#) (31)
[Press](#) (14)
[Product](#) (30)
[API Gateway](#) (2)
[Resources](#) (8)
[StrongNode](#) (7)
[Uncategorized](#) (2)

Archives

[February 2017](#)
[January 2017](#)
[December 2016](#)
[November 2016](#)
[October 2016](#)
[September 2016](#)
[August 2016](#)
[July 2016](#)
[June 2016](#)
[May 2016](#)
[April 2016](#)
[March 2016](#)
[February 2016](#)
[January 2016](#)
[December 2015](#)
[November 2015](#)
[October 2015](#)
[September 2015](#)
[August 2015](#)
[July 2015](#)
[June 2015](#)
[May 2015](#)
[April 2015](#)

```

    makeCsv(data, function (err, csv) {
      if (err) return next(err)
      // handle csv
    })
  })
  app.use(function (err, req, res, next) {
    // handle error
  })

```

Still, this isn't bulletproof. There are two problems with this approach:

1. You must explicitly handle every `error` argument.
2. Implicit exceptions aren't handled (like trying to access a property that isn't available on the `data` object).

Asynchronous error propagation with promises

Promises [<http://strongloop.com/strongblog/promises-in-node-js-with-q-an-alternative-to-callbacks/>] handle any exception (explicit and implicit) within asynchronous code blocks (inside `then`) like Express does for us in synchronous code blocks. Just add `.catch(next)` to the end of promise chains.

```

app.get('/', function (req, res, next) {
  // do some sync stuff
  queryDb()
    .then(function (data) {
      // handle data
      return makeCsv(data)
    })
    .then(function (csv) {
      // handle csv
    })
    .catch(next)
})
app.use(function (err, req, res, next) {
  // handle error
})

```

Now all errors asynchronous and synchronous get propagated to the error middleware. Hurrah!

[March 2015](#)

[February 2015](#)

[January 2015](#)

[December 2014](#)

[November 2014](#)

[October 2014](#)

[September 2014](#)

[August 2014](#)

[July 2014](#)

[June 2014](#)

[May 2014](#)

[April 2014](#)

[March 2014](#)

[February 2014](#)

[January 2014](#)

[December 2013](#)

[November 2013](#)

[October 2013](#)

[September 2013](#)

[August 2013](#)

[July 2013](#)

[June 2013](#)

[May 2013](#)

[April 2013](#)

[March 2013](#)

Well, almost. Promises are a decent asynchronous primitive, but they are kinda verbose despite the welcomed error propagation. Let's fix this using promise generators.

Cleaner code with generators

If you use [io.js](http://iojs.org) [<http://iojs.org>] or Node ≥ 0.12 , you can improve on this workflow using native generators [<https://strongloop.com/strongblog/how-to-generators-node-is-yield-use-cases/>] [2] [#foot2]. For this, let's use a helper to make promise generators called `Bluebird.coroutine`.

This example uses bluebird [<https://github.com/petkaantonov/bluebird>], but promise generators exist in all the major promise libraries

First, let's make Express compatible with promise generators by creating a little `wrap` function:

```
var Promise = require('bluebird')
function wrap (genFn) { // 1
  var cr = Promise.coroutine(genFn) // 2
  return function (req, res, next) { // 3
    cr(req, res, next).catch(next) // 4
  }
}
```

The `wrap` function:

1. Takes a generator
2. Teaches it how to yield promises (through `Promise.coroutine`)
3. Returns a normal Express route function
4. When this function executes, it will call the coroutine, catch any errors, and pass them to `next`.

This `wrap` boilerplate hopefully will go away with Express 5 custom routers [<https://github.com/strongloop/express/pull/2431>] but write it

once and keep it as a utility. With it, we can write route functions like this:

```
app.get('/', wrap(function *(req, res) {
  var data = yield queryDb()
  // handle data
  var csv = yield makeCsv(data)
  // handle csv
}))
app.use(function (err, req, res, next) {
  // handle error
})
```

This is pretty clean and reads well. All normal control structures (like `if/else`) work the same regardless if asynchronously or synchronous executed. Just remember to `yield` the promises.

Let's look next at the ES7 `async/await` proposal and clean things up even more.

Using ES7 `async/await`

The [async/await proposal](https://github.com/tc39/ecmascript-asyncawait)

<https://github.com/tc39/ecmascript-asyncawait> behaves just like a promise generator but it can be used in more places (like class methods and arrow functions).

We still need a `wrap` function but it's simpler as we don't need `Bluebird.coroutine` or generators. Below is semantically the same as the previous `wrap` function, written in ES6:

```
let wrap = fn => (...args) => fn(...args).catch(args[2])
```

Then, we make routes like this:

```
app.get('/', wrap(async function (req, res) {
  let data = await queryDb()
  // handle data
  let csv = await makeCsv(data)
  // handle csv
}))
```

Or with arrow functions:

```
app.get('/', wrap(async (req, res) => { ... })))
```

Now, to run this code, you will need the Babel [\[http://babeljs.io\]](http://babeljs.io) JavaScript compiler. There are many ways to use Babel with Node, but to keep things simple, install the `babel-node` command by running:

```
npm i babel -g
```

Then run your app using:

```
babel-node --stage 0 myapp.js
```

Bonus: Since this code compiles to ES5, you can use this solution with older versions of Node.

Throw me a party!

With error handling covered both synchronously and asynchronously you can develop Express code differently. Mainly, **DO** use `throw`. The intent of `throw` is clear. If you use `throw` it will bypass execution until it hits a `catch`. In other words, it will behave just like `throw` in synchronous code. You can use `throw` and `try/catch` meaningfully again with promises, promise generators, and `async/await`:

```
app.get('/', wrap(async (req, res) => {
  if (!req.params.id) {
    throw new BadRequestError('Missing Id')
  }
  let companyLogo
  try {
    companyLogo = await getBase64Logo(req.params.id)
  } catch (err) {
    console.error(err)
    companyLogo = genericBase64Logo
  }
}))
```

Also **DO** use custom error classes

[\[http://dailyjs.com/2014/01/30/exception-error/\]](http://dailyjs.com/2014/01/30/exception-error/) like `BadRequestError` as it makes sorting errors out easier:

```
app.use(function (err, req, res, next) {
  if (err instanceof BadRequestError) {
    res.status(400)
```

```
    return res.send(err.message)
  }
  ...
})
```

Caveats

There are two caveats with this approach:

1. You must have all your asynchronous code return promises (except emitters). Raw callbacks simply don't have the facilities [\[http://strongloop.com/strongblog/promises-in-node-js-with-q-an-alternative-to-callbacks/\]](http://strongloop.com/strongblog/promises-in-node-js-with-q-an-alternative-to-callbacks/) for this to work. This is getting easier as promises are legit now in ES6. If a particular library does not return promises, it's trivial to convert using a helper function like `Bluebird.promisifyAll`.
2. Event emitters (like streams) can still cause uncaught exceptions. So make sure you are handling the `error` event properly.

```
app.get('/', wrap(async (req, res, next) => {
  let company = await getCompanyById(req.query.id)
  let stream = getLogoStreamById(company.id)
  stream.on('error', next).pipe(res)
}))
```

Alternatives to promises

An alternative to promises is to capture errors using generators and thunks [\[http://en.wikipedia.org/wiki/Thunk\]](http://en.wikipedia.org/wiki/Thunk).

One way to accomplish this is using co [\[https://github.com/tj/co\]](https://github.com/tj/co) and a `wrap` function like co-express [\[https://github.com/mcipayelli/co-express\]](https://github.com/mcipayelli/co-express).

-
1. I am assuming you *are* propagating errors there. If you are not, it will save you maintenance time and code duplication to do so.
↪ [\[#ref1\]](#)

2. Faux generators [<https://facebook.github.io/regenerator/>] work in older versions of Node using a JavaScript compiler like Babel. I personally find the `async/await` syntax more compelling if I am already using a compiler. [← \[#fref2\]](#)

You may also be interested in...

- How to Deploy Express Apps with StrongLoop Process Manager
[<https://strongloop.com/strongblog/best-practices-express-js-process-manager/>]
- Writing Modular Node.js Projects for Express and Beyond
[<https://strongloop.com/strongblog/modular-node-js-express/>]
- Express 3.x to 4.x Migration Guide
[<https://strongloop.com/strongblog/express-3-to-4-migration-guide/>]

Like 20

Tweet

G+ Share

Share

[<https://www.addtoany.com/share?url=https%3A%2F%2Fstrongloop.com/error-handling-expressjs-es7-promises-generators%2F&title=Asynchronous%20Error%20Handling%20in%20Ex>]

< Previous Post

Next Post >

Compose APIs, Build, Deploy and Monitor Node

Install API Connect

```
$ npm install -g apiconnect
```

Create your API Connect project

```
$ apic loopback
```

Launch API Designer

```
$ cd your-project
```

```
$ apic edit
```

API Designer will run on your local browser

An IBM Bluemix account is required to use the Designer. [Register for IBM Bluemix](#)

[Click To Get Started](#)



It's FREE!