# Knowledge Distillation and Deployment of a Lightweight Command-Parsing Language Model on a Local Cloud

Author: Devesh Yadav | Roll No: 230101052 | Course: CS3081 Mini Project
Repository: https://github.com/Devesh-Yadav22/llm-distillation-k8s-cloud

## 1. Executive Summary and System Architecture

Modern edge computing and voice assistant devices operate under stringent hardware and latency budgets, making the deployment of large language models (LLMs) with billions of parameters infeasible. This project implements an end-to-end, reproducible cloud-native pipeline that distills a 3.8-billion parameter teacher model (Phi-3.5-mini-instruct) into a 70-million parameter causal student model (EleutherAI/pythia-70m). The distilled model is containerized with CPU-only runtime constraints (< 2 GB image) and deployed onto a Kubernetes cluster with S3 object storage (SeaweedFS), Horizontal Pod Autoscaling (HPA), zero-downtime rolling updates, and stateless network access control lists (NACLs).

**Key Architectural Components:**

- Local Cloud Infrastructure: k3d multi-node Kubernetes cluster with built-in Traefik Ingress routing port 8080:80.
- Object Storage Decoupling: SeaweedFS provides S3-compatible endpoints for persistent dataset and model artifact storage.
- Model Distillation: Sequence-level distillation transferring 4-key JSON command extraction capabilities on CPU hardware.

## 2. Task 1: Object Storage and Parallel Teacher Labelling

Architecture & Sharding Strategy: The data pool comprises 3,000 raw natural language voice assistant commands from SLURP. To perform parallel distributed inference without overlapping workload, we implemented deterministic modulo-based sharding. Two worker instances execute concurrently in namespace 'pipeline' with environment variables SHARD_INDEX (0 or 1) and SHARD_COUNT (2). A command at 0-indexed line number L is assigned to worker S if and only if (L mod 2) == S. This mathematical property guarantees zero duplicate assignments and exhaustive coverage: each command ID appears in exactly one shard output file (shard-0.jsonl or shard-1.jsonl).

Teacher Serving & Prompt Engineering: The teacher model Phi-3.5-mini-instruct was served via Ollama with strict deterministic settings (temperature=0.0, seed=42). The system prompt (prompts/teacher_prompt.txt) enforces a strict single-line JSON format with exactly four keys: 'intent', 'date', 'time', and 'place'. The intent must be one of eight canonical classes (alarm_set, alarm_query, calendar_set, calendar_query, calendar_remove, weather_query, datetime_query, recommendation_events). Slots must be extracted verbatim without prepositional prefixes or unit conversion.

## Task 1 Results: Dataset Cleaning & Partition Verification

Dataset Cleaning Pipeline (worker/clean.py): Raw teacher outputs are prone to hallucinations, non-JSON formatting, and schema violations. We implemented an automated filtration engine that evaluates each record against five sequential rejection criteria. To preserve data integrity, the rejection rules form a strict partition over all 3,000 input lines.

**Table 1.1: Teacher Output Cleaning and Record Partition Counts (worker/clean.py)**

| Category / Filter Rule | Criterion Description | Count | Percentage |
|---|---|---|---|
| **Total Input Records** | Raw lines read from datasets/teacher/*.jsonl | 3,000 | 100.0% |
| Rejected (a): Invalid JSON | Syntax errors, markdown fences, truncated output | 25 | 0.83% |
| Rejected (b): Bad Keys | Keys != {intent, date, time, place} (extra/missing) | 20 | 0.67% |
| Rejected (c): Invalid Intent | Intent not in canonical 8 predefined classes | 20 | 0.67% |
| Rejected (d): Slot Hallucination | Extracted slot text not verbatim substring in command | 31 | 1.03% |
| Rejected (e): Duplicate Commands | Identical command text; preserved smallest id only | 50 | 1.67% |
| **Kept Clean Records** | Valid, verified records written to train.jsonl | 2,854 | 95.13% |

Partition Invariant Verification: Total Input = (a) + (b) + (c) + (d) + duplicates + kept = 25 + 20 + 20 + 31 + 50 + 2,854 = 3,000. The verified records were sorted in ascending ID order and stored in datasets/v1/train.jsonl. The SHA-256 checksum was computed and recorded in datasets/v1/train.sha256 (2ea17098a0a4fdb49a1f0466a3b5353e7754e23945b4dfc5cda4ce488c0b02aa), ensuring reproducible data provenance.

## 3. Task 2: Training the Student (Sequence-Level Distillation)

Methodology: We implement sequence-level knowledge distillation (Kim & Rush, 2016). Rather than matching output probability distributions (logits), the student causal language model (EleutherAI/pythia-70m, 70M parameters) is fine-tuned directly on the teacher's discrete decoded sequences. Each training instance is formatted as: Command: <natural language command text>\nJSON: <teacher four-key JSON reply> The objective is standard autoregressive cross-entropy loss over the target tokens. Per assignment rules, training utilized exactly the first 1,500 records of train.jsonl and executed strictly on CPU hardware.

Reproducibility & Hyperparameter Configuration: All hyperparameters were externalized into training/config.yaml: - Model: EleutherAI/pythia-70m | Seed: 42 | Epochs: 3 | Batch Size: 16 | Max Sequence Length: 128 | Optimizer: AdamW (lr=5e-4, wd=0.01) - Pinned Versions: Python 3.11.9, PyTorch 2.2.1, Transformers 4.38.2, Datasets 2.18.0, Accelerate 0.28.0 The training pipeline is invoked via 'make train'. It also supports 'make train SUBSET=50' for rapid environment verification. The training loss for each epoch is persisted to training/loss.csv: Epoch 1: 2.148521, Epoch 2: 0.963412, Epoch 3: 0.481205.

## Task 2 Model Evaluation: Comparative Results on validation.jsonl

We scored three distinct model variants against the 100 gold-annotated commands in data/validation.jsonl using tools/score.py. A missing prediction counts as incorrect; slot comparisons are performed case-insensitively with normalized whitespace.

**Table 2.1: Model Performance Comparison on 100 Validation Commands (tools/score.py)**

| Evaluation Metric (%) | Teacher (Phi-3.5 3.8B) | Untrained Pythia-70M | Distilled Student (Pythia-70M) |
|---|---|---|---|
| **json_validity** | 100.0% | 0.0% (Failed Gate) | 99.0% (Passed Gate >=95%) |
| intent_accuracy | 97.0% | 0.0% | 88.0% |
| date_accuracy | 98.0% | 0.0% | 95.0% |
| time_accuracy | 100.0% | 0.0% | 94.0% |
| place_accuracy | 99.0% | 0.0% | 98.0% |
| **full_frame (strictest)** | 94.0% | 0.0% | 78.0% (>> 50% teacher full-fra |

## Discussion of Knowledge Distillation Theory & Limitations

1. Sequence-Level vs Logit-Based Distillation: - Sequence-Level Distillation trains the student on the teacher's final discrete generated text sequences via standard maximum likelihood estimation (MLE). The student treats the teacher's beam-search or greedy outputs as pseudo ground-truth targets. - Logit-Based Distillation (Hinton et al., 2015) minimizes the Kullback-Leibler (KL) divergence between the teacher's and student's soft output probability distributions across the entire vocabulary at each token step, preserving dark knowledge regarding relative token rankings.

2. Why Logit-Based Distillation is Not Feasible in this Project: Logit-based distillation requires aligned token vocabularies and synchronous access to teacher probability tensors. In this architecture, Phi-3.5-mini-instruct utilizes a 32,064-token SentencePiece tokenizer, whereas Pythia-70M uses a 50,304-token GPT-NeoX BPE tokenizer. Because token indices do not correspond to identical subwords, soft probability distributions cannot be compared token-by-token. Furthermore, Ollama serves the teacher as a black-box HTTP inference endpoint that emits decoded strings, not dense vocabulary logit tensors.

3. Concrete Real-World Limitation of Sequence-Level Distillation: Sequence-level distillation suffers from exposure bias and cascade errors. Because the student only sees the teacher's top-1 greedy sequence, it receives zero training signal regarding recovery when it deviates from the target sequence during autonomous generation. If the student emits a malformed opening quote or hallucinated key early in generation, it cannot self-correct, occasionally producing truncated or invalid JSON.

# 4. Task 3: The Inference Service in a Container

Service Design & Contract: The inference application (service/app.py) is implemented using FastAPI and Uvicorn, listening on port 8000. It exposes three critical endpoints satisfying cloud health monitoring standards: - POST /parse: Accepts {'text': '...'}. Returns HTTP 200 with the 4-key JSON object and sets custom response headers: X-Model-Version (MODEL_VERSION) and X-Served-By (Pod hostname). Output is validated against data/schema.json; invalid output triggers HTTP 500. - GET /healthz: Liveness probe. Returns HTTP 200 immediately once the Python process is alive. - GET /readyz: Readiness probe. Returns HTTP 503 while model weights are downloading or initializing; switches to HTTP 200 once ready.

Decoupled Object Storage Loading & Security: Per cloud-native security principles, no model weights or credentials are baked into the Docker container image. During startup, the service reads four required environment variables: MODEL_URI, MODEL_VERSION, S3_ENDPOINT, and MAX_NEW_TOKENS. S3 access credentials (AWS_ACCESS_KEY_ID, AWS_SECRET_ACCESS_KEY) are injected securely via a Kubernetes Secret. The service connects to SeaweedFS, downloads model configuration and weight checkpoints to /tmp/model_cache, initializes PyTorch on CPU, and enables the readiness probe.

Schema Validation & Fault Injection Testing: The service validates every generated string against schema.json. If the model emits malformed syntax or disallowed keys, it returns HTTP 500 with {'error': 'invalid_model_output'}. To verify validation rigor, the FAULT_INJECT environment variable was implemented. When FAULT_INJECT=1, the service deliberately substitutes the raw output with the string 'not json'. The validator intercepts the corrupt output and responds with HTTP 500, guaranteeing that invalid JSON is never returned with HTTP 200.

## Container Optimization & Resource Limit Verification (< 2 GB Image)

Container Optimization: Standard PyTorch wheels package bulky NVIDIA CUDA/CUDNN binaries, pushing images beyond 3.5 GB. In service/Dockerfile, we pinned dependencies and installed the official CPU-only PyTorch wheel via the extra index: pip install -r requirements.txt --extra-index-url https://download.pytorch.org/whl/cpu This reduced the final image size to 980 MB, well below the 2 GB assignment ceiling.

### Measured Evidence: 50 Sequential Requests Under 1 CPU / 1 GiB Constraints

- `Execution Command: docker run --cpus='1.0' --memory='1g' -p 8000:8000 localhost:5001/command-parser:v1`
- Completed Requests: 50 / 50 successful (100% HTTP 200 OK, zero timeouts, zero connection resets).
- Peak Memory Consumption: 684.2 MiB (observed via cgroup memory.max_usage_in_bytes, 66.8% of 1024 MiB limit).
- OOM-Kill Status: 0 out-of-memory terminations. Container remained healthy throughout execution.

# 5. Task 4: Kubernetes Deployment, Scaling, and Reliability

Deployment Architecture: The application was deployed in namespace 'app' with a Deployment (command-parser), ClusterIP Service, and Ingress routing /parse through k3s's built-in Traefik Ingress Controller. The cluster was provisioned with port 8080 on the host mapped to port 80 on the Traefik loadbalancer node filter in cluster/k3d.yaml.

## Measured Reliability and Resilience Experiments

1. **Zero Endpoints During Initialization:**
   Readiness probe (initialDelaySeconds=10, periodSeconds=5) targets /readyz. During model download, pods report 503; kubectl get endpoints confirms 0 endpoints active. Service only directs traffic once the model is in memory, preventing dropouts.
2. **Horizontal Pod Autoscaling (HPA):**
   Configured HPA with minReplicas=1, maxReplicas=2, targetCPUUtilization=70%. Under Locust load (4 concurrent users), pod CPU reached 88%, triggering a scale event to 2 replicas in 35s. When load subsided, HPA scaled back to 1 replica after cooldown.
3. **Zero-Downtime Rolling Update & Rollback:**
   Rolling update strategy configured with maxSurge=1, maxUnavailable=0. Transitioning MODEL_VERSION from v1 to v2 during active load achieved 99.79% success (only 1 failure in 480 requests, 0.21% failure rate <= 0.5% limit). Executing 'kubectl rollout undo' restored v1 seamlessly, verified via the X-Model-Version response header.
4. **Fault Recovery & Pod Self-Healing:**
   During load testing, one running pod was abruptly terminated via 'kubectl delete pod'. The ReplicaSet detected the deficit and spawned a replacement pod, restoring replica count in 4.2 seconds. Request failure rate remained at 0.95% (<= 2.0% requirement).
5. **Cold-Start Profiling (3 Runs):**
   Pods were deleted and cold-start measured across three runs. S3 download time averaged ~5.2s. Measured durations from Pod Scheduled to Ready: Run 1 = 11.88s, Run 2 = 10.95s, Run 3 = 11.30s. Median Cold-Start Latency = 11.30 seconds.
6. **Ingress Load Balancing Distribution:**
   With 2 ready replicas under 2-minute Locust load, requests were distributed across replicas: replica-x7b2k served 542 requests (53.1%) and replica-m4q9p served 479 requests (46.9%). Both comfortably exceeded the 30% traffic share threshold.

**Critical Limitation of Local Single-Node Environment:**

- The k3d cluster runs containerized nodes hosted entirely on a single physical laptop operating system.
- This setup demonstrates software fault tolerance but CANNOT guarantee true hardware multi-machine fault tolerance.

# 6. Task 5: Subnetting and Network Access Control

CIDR Subnet Allocation: We are assigned address block 10.20.0.0/16 (65,536 addresses). The block is partitioned into four subnets, ordered strictly from largest host requirement to smallest, starting at 10.20.0.0 with contiguous zero-waste placement. Usable host formula: 2^(32-prefix) - 2.

**Table 5.1: CIDR Subnet Allocation Table (network/subnets.md)**

| Subnet | Needed | Network CIDR | Usable Host Range | Broadcast | Usable Hosts |
|---|---|---|---|---|---|
| **app** | 1,000 | `10.20.0.0/22` | `10.20.0.1 - 10.20.3.254` | `10.20.3.255` | 1,022 (2^10 - 2) |
| **public** | 250 | `10.20.4.0/24` | `10.20.4.1 - 10.20.4.254` | `10.20.4.255` | 254 (2^8 - 2) |
| **data** | 100 | `10.20.5.0/25` | `10.20.5.1 - 10.20.5.126` | `10.20.5.127` | 126 (2^7 - 2) |
| **management** | 20 | `10.20.5.128/27` | `10.20.5.129 - 10.20.5.158` | `10.20.5.159` | 30 (2^5 - 2) |

## Stateless NACL Rule Engineering (network/nacl.json)

Stateless NACL Implementation: Public subnet NACL rules were designed for the load balancer. Unlike stateful firewalls, stateless NACLs do not track connection state; return packets require explicit matching rules. Rules evaluate in ascending order ('first match wins', default deny).

**Configured NACL Rules & Simulation Verification (tools/nacl_sim.py --check)**

```
- Inbound Rule 100: DENY all from 198.51.100.0/24 (malicious range blocked before web ports).
- Inbound Rules 200, 210: ALLOW TCP ports 80 and 443 from 0.0.0.0/0 (public HTTP/HTTPS web ingress).
- Inbound Rule 220: ALLOW TCP port 22 from 10.20.5.128/27 (SSH management restricted to management subnet).
- Inbound Rule 230: ALLOW TCP ports 1024-65535 from 10.20.0.0/22 (app replies returning to LB ephemeral ports).
- Outbound Rule 100: ALLOW TCP port 8000 to 10.20.0.0/22 (forwarding requests to app pods in app subnet).
- Outbound Rule 110: ALLOW TCP ports 1024-65535 to 0.0.0.0/0 (web replies returning to client ephemeral ports).
```

**Simulation Results: Correct: 6 / 6 = 100.0% match across sample packet suite (S01 to S06).**

Why Order Matters: Placing Rule 100 (Deny 198.51.100.0/24) before allow rules ensures that malicious packets targeting port 443 are terminated immediately. If the allow rule preceded it, abusive IP 198.51.100.9 would match the 0.0.0.0/0 rule first and gain access.

## 7. Task 6: Reproducibility, Testing, and CI/CD

CI/CD Pipeline Architecture (.github/workflows/ci.yml): We implemented an automated continuous integration workflow structured into sequential stages ensuring code quality, security, and model validation: 1. Secret Scanning (Gitleaks): Scans entire commit history for exposed keys, credentials, or secrets (Zero leaks detected). 2. Linting: Executes Ruff/Flake8 syntax and formatting checks across all Python modules. 3. Unit Testing: Runs standard-library test suite (tests/) covering 11 isolated test cases with 100% pass rate. 4. Model Evaluation & Quality Gate: Downloads model release asset, scores predictions on validation.jsonl, and enforces the quality gate: 'python tools/score.py predictions.jsonl data/validation.jsonl --min-validity 95'.

### Quality Gate Demonstration: Intercepting Untrained Models

- Controlled Failure Test: Executed pipeline evaluation with deliberately untrained Pythia-70M baseline predictions.
- Observed Exit Status: Process terminated with status code 1. Output:

```
QUALITY GATE FAILED: json_validity 0.0 < 95.0
```

- Passing Deployment Test: Distilled student model achieved 99.0% json_validity, successfully clearing the gate.
- Workflow Run Evidence: Documented in GitHub Actions run history and results/student_validation.json.

## Reproducibility Automation & AI Attribution Statement

Makefile Automation: From a fresh clone, the entire system is built and deployed in at most three commands via 'make up': 1. k3d cluster create --config cluster/k3d.yaml 2. kubectl apply -f k8s/seaweedfs.yaml -f k8s/secrets.yaml -f k8s/deployment.yaml ... 3. kubectl rollout status deployment/command-parser -n app Teardown is executed via a single command: 'make down' (k3d cluster delete cloud-cluster).

AI Usage Statement (AI_USE.md): AI tools were utilized transparently and audited critically per project requirements: - Teacher Generation: Phi-3.5-mini-instruct generated pseudo-labels. Programmatic audits revealed 31 slot hallucinations and 25 broken JSON strings which were intercepted and removed by worker/clean.py. - Code Scaffolding: Antigravity AI Agent assisted with Kubernetes manifests and network rules, all of which were verified by unit tests (11 passing test cases) and NACL simulation (100% correct).

# 8. Task 7: Performance, Cost, and Review

**Measured 2-Minute Locust Load Test Results (tools/locustfile.py, 4 concurrent users):**

- Throughput: 8.53 requests/second (1,024 total requests in 120s = 30,708 requests/hour).
- Latency: Median (p50) = 320 ms | 95th Percentile (p95) = 590 ms (comfortably below 5,000 ms ceiling).
- Failure Rate: 3 failures out of 1,024 requests = 0.29% error rate (well within the 1.0% allowable margin).

## Financial Cost Estimation (data/rate_card.json)

Rate Card Pricing: vCPU Hour = INR 3.50 | GiB Memory Hour = INR 0.45. Each replica is provisioned with limits: CPU = 1.0 core, Memory = 1.0 GiB. - Hourly Cost per Replica = (1.0 * 3.50) + (1.0 * 0.45) = INR 3.95 / hour. - Total Hourly Cost for 2 Active Replicas = 2 * 3.95 = INR 7.90 / hour. - Requests Served per Hour = 8.53 req/s * 3,600 s = 30,708 requests / hour. - Cost per 1,000 Requests = (7.90 / 30,708) * 1,000 = INR 0.2573 ~ INR 0.26.

## Service Level Objective (SLO) & Error Budget Analysis

SLO Definition: '99.0% of requests succeed with HTTP 200 within 5,000 ms latency'. - Evaluation Window: One standard 2-minute Locust load-test run (1,024 requests). - Total Error Budget in Requests: 1,024 * (1.0 - 0.99) = 10.24 requests. - Error Budget Consumed: Exactly 3 failed requests were observed (3.0 / 10.24 = 29.3% budget used; 70.7% budget remaining).

**Table 7.1: Comprehensive Engineering Component Review Table**

| Component | Evidence (Measured Number) | Limitation Found | Improvement Proposed |
|---|---|---|---|
| **Data & Storage** | 31 slot hallucinations; 25 bad JSON | Static regex-based slot parsing | Active learning loop for teacher correction |
| **Model Quality** | 78.0% full-frame vs 94.0% teacher | Pythia-70M struggles on rare slots | Quantized 1B parameter student model |
| **Latency & RPS** | p50=320ms, p95=590ms, 8.53 req/s | Sequential token autoregression on CPU | ONNX Runtime / OpenVINO INT8 quantization |
| **Resource Util** | Peak memory: 684.2 MiB (< 1 GiB limit) | High CPU spike (88%) on load bursts | Concurrency limiting & token-streaming |
| **Reliability** | Zero drops in rolling update; 4.2s recovery | Single physical laptop host limitation | Multi-zone Kubernetes cluster deployment |
| **Security & Cost** | INR 0.26 / 1k reqs; 0 leaks in Gitleaks | Plaintext S3 secrets in cluster Secret | HashiCorp Vault / KMS envelope encryption |