

EXP:13 ADD AN ARRAY OF 16-BIT NO.

The screenshot displays the Keil uVision IDE interface during a debugging session. The main window shows the source code for a C program named `exp20.c`. The program defines an array of 5 unsigned integers and calculates their sum.

```

1: void main(void)
2: {
3:     unsigned int i;
4:     unsigned int array[5] = {0x1111, 0x2222, 0x8888, 0x4444, 0xABCD};
5:     unsigned long sum = 0;
6:     for (i = 0; i < 5; i++)
7:     {
8:         sum = sum + array[i];
9:     }
10: }

```

The **Registers** window on the left shows the state of the microcontroller's registers. The **Watch** window on the right displays the values of variables and expressions being monitored during execution.

Name	Value	Type
<code>0x00</code>	0x0000	int
<code>sum</code>	0x0001ABCC	ulong
<code>array[0]</code>	0x1111	uint
<code>array[1]</code>	0x2222	uint
<code>array[2]</code>	0x8888	uint
<code>array[3]</code>	0x4444	uint
<code>array[4]</code>	0xABCD	uint
<code>array[5]</code>	0x0001	uint
<code>Address: 0x00</code>	Cannot evaluate:	uchar
<code>Address: 0x00</code>	Cannot evaluate:	uchar
<Enter expression>		

The status bar at the bottom indicates the current file is `exp20.c` and shows various debugging options like `ASH`, `ASSTON`, `BreakDisable`, `BreakEnable`, `BreakFull`, `BreakList`, `BreakSet`, `BreakAccess`, `COVERAGE`, and `COVTOFILE`.