AgentScope 0.4.0 — terminal tour

These screenshots render actual interactive PTY output in a terminal emulator. Chat and monitored LLM calls use a genuine local CPU model. Incident and recovery examples are explicitly synthetic. No cloud API credentials or private project records are included.

1. First launch and model setup

Actual first-run setup. A real local compatible model was selected; no cloud key was needed.

AgentScope 0.4.0 / First launch and model setup — ACTUAL TERMINAL OUTPUT

```
+-------------------------------------------------------------------------------------------+
  AGENTSCOPE / 0.4.0
  Observe. Investigate. Understand.
+-------------------------------------------------------------------------------------------+
  Directory   /workspace/AgentScope/.local/terminal-tour/sample-agent
  API target  http://127.0.0.1:8000
API target is configured; connectivity has not been checked.

START HERE
  configure     Choose AgentScope's chat model before asking questions
  Who are you?  Meet AgentScope through your configured model
  watch         Start monitoring this repository
  guide         Walk through your first monitoring session
  help          Browse commands and examples

Tip: /help also works. Tab completes commands. Ctrl-D exits.
Watch captures metadata. Factual accuracy needs a grounding evaluation.

Configure AgentScope's chat model first: configure, or agentscope configure PROVIDER.

CONFIGURE AGENTSCOPE'S CHAT MODEL
  1   openai
  2   openai-codex
  3   anthropic
  4   gemini
  5   openrouter
  6   groq
  7   deepseek
  8   ollama
  9   compatible
  10  codex
  11  claude-cli
Choose a provider. Codex and Claude CLI use their existing login. Enter 0 for monitoring without
chat.
Provider [openai]: compatible
Model [required]: SmolLM2-135M-Instruct
Profile name [compatible]: local-demo
API base [required]: http://127.0.0.1:42015/v1
API key (hidden; optional for local compatible servers):
Chat model configured: local-demo · SmolLM2-135M-Instruct. Type Who are you? to begin.
agentscope [ready] >
```

Actual first-run setup. A real local compatible model was selected; no cloud key was needed.

2. Chat with AgentScope

Real SmolLM2 local inference. Answers are generated by the configured model.

AgentScope 0.4.0 / Chat with AgentScope — ACTUAL TERMINAL OUTPUT

```
agentscope [ready] > Who are you?
AgentScope is thinking…

AGENTSCOPE
local-demo · SmolLM2-135M-Instruct
I am AgentScope, a conversational AI assistant for AgentScope observability software. I am a
conversational AI that assists users in monitoring and analyzing AI agents. I am a
conversational AI that assists users in understanding the nuances of AI interactions and the
various types of AI interactions. I am a conversational AI that assists users in understanding
the various types of AI interactions and the various types of interactions. I am a
conversational AI that assists users in understanding the various types of interactions and the
various types
agentscope [ready] > model status

AGENTSCOPE'S CHAT MODEL
  Profile          local-demo
  Provider         compatible
  Model            SmolLM2-135M-Instruct
  Readiness        Credential or CLI available; connection not tested
  Project context  off
agentscope [ready] >
```

Real SmolLM2 local inference. Answers are generated by the configured model.

3. Learn the monitoring workflow

Offline guide and command usage, captured from the running REPL.

AgentScope 0.4.0 / Learn the monitoring workflow — ACTUAL TERMINAL OUTPUT

```
agentscope [ready] > guide

YOUR FIRST SESSION
  1. Configure    configure, then model check; ask Who are you? to meet AgentScope
  2. Start        watch . --no-open (leave off --no-open to launch the browser)
  3. Launch       In another terminal: agentscope run -- python app.py or agentscope run -- npm
                  start
  4. Inspect      status -> agents -> runs -> incidents -> open
  5. Investigate  investigate INCIDENT_ID, then investigation to read the evidence
  6. Finish       stop keeps telemetry; exit closes this session

USEFUL NOTES
You can also start an app with watch -- python app.py, or use run -- COMMAND here for a
foreground run. Ctrl+C interrupts that run and returns to the REPL.
Start existing apps through watch/run to enable capture. Python OpenAI/Anthropic create calls
and Node fetch-based compatible endpoints are supported. Tool boundaries need SDK
instrumentation.
Prompts and response bodies are excluded from automatic capture. Unsupported claims show Not
evaluated until your application supplies a grounding assessment.
Already have a server? projects, then use PROJECT_ID. To practice incident handling, demo
creates an isolated synthetic project.
agentscope [ready] > help watch

WATCH
watch [DIRECTORY] [-- APPLICATION]: monitor a local project in the background. Use stop to
finish.
Examples: watch . --no-open | watch -- python app.py | watch -- npm start
agentscope [ready] >
```

Offline guide and command usage, captured from the running REPL.

4. Start monitoring and run an application

Actual local API/dashboard startup and a genuine successful LLM call.

AgentScope 0.4.0 / Start monitoring and run an application — ACTUAL TERMINAL OUTPUT

```
agentscope [ready] > watch --runtime /workspace/AgentScope --no-open --port 0 --api-port 0
Watching project: sample-agent
Dashboard: http://127.0.0.1:48065/dashboard?project=8eb917e7-b6bd-4e01-94e3-920518d8d323
Automatic capture: Python OpenAI/Anthropic; Node.js fetch-based OpenAI/Anthropic-compatible call
s.
Prompt and response content is excluded. Hallucinations require explicit grounding evaluations.
Use stop or exit to stop monitoring.
Waiting for instrumented activity. Launch your app with: agentscope run -- YOUR_COMMAND
Monitoring continues in the background. Use status, incidents, or open to inspect this project.
agentscope [sample-agent | watch] > run -- node ask-model.cjs

APPLICATION
Repository: /workspace/AgentScope/.local/terminal-tour/sample-agent
Running in the foreground. Ctrl+C returns here; monitoring continues.
Calling SmolLM2-135M-Instruct through the OpenAI SDK (local CPU model).
Model response: A software dashboard displays a collection of visualizations that provide a comp
rehensive view of a system's performance, including metrics, charts, and other data elements.
Tokens: 30 input / 30 output.
Application exited with code 0. Next: status, runs, or open.
agentscope [sample-agent | watch] >
```

Actual local API/dashboard startup and a genuine successful LLM call.

5. Inspect model usage, failures, and runs

One successful local LLM call and one deliberately invalid model request. Grounding remains Not evaluated.

AgentScope 0.4.0 / Inspect model usage, failures, and runs — ACTUAL TERMINAL OUTPUT

```
agentscope [sample-agent | watch] > run -- node ask-model.cjs --bad-model

APPLICATION
Repository: /workspace/AgentScope/.local/terminal-tour/sample-agent
Running in the foreground. Ctrl+C returns here; monitoring continues.
Calling model-not-installed through the OpenAI SDK (local CPU model).
Deliberate demo failure: HTTP 404 (model not installed).
Application exited with code 0. Next: status, runs, or open.
agentscope [sample-agent | watch] > status

WORKSPACE
Connected to http://127.0.0.1:49221; 2 projects.
  Project     sample-agent
  Project ID  8eb917e7-b6bd-4e01-94e3-920518d8d323

ACTIVITY
Last 24 hours; status refreshes when you run it.
  Agents                 1
  Runs / active / failed  2 / 0 / 1
  LLM calls / errors      2 / 1
  Tokens / in / out       60 / 30 / 30
  Estimated cost          Unavailable (pricing or usage incomplete)
  Active incidents        0
  Unsupported claims      Not evaluated
  Watch  sample-agent / waiting
Next: runs to inspect executions; incidents to find issues; open for the dashboard.
agentscope [sample-agent | watch] > runs

RECENT RUNS
2 records returned
openai.chat.completions
failed / 0 tokens / 18 ms / observed telemetry
ID: 77e22407-c572-414c-9208-8dcb8637aa0c

openai.chat.completions
completed / 60 tokens / 740 ms / observed telemetry
ID: 7220171f-70ad-4e48-96fc-4143df4aa71c

agentscope [sample-agent | watch] > agents

AGENTS
1 records returned
sample-agent
Automatic LLM instrumentation / observed telemetry
ID: 6791d3ad-c0b7-4d95-9977-4c9a479fa0ac

agentscope [sample-agent | watch] >
```

One successful local LLM call and one deliberately invalid model request. Grounding remains Not evaluated.

6. Manage the assistant and project context

Supported provider options and explicit control over sharing project summary metrics.

AgentScope 0.4.0 / Manage the assistant and project context — ACTUAL TERMINAL OUTPUT

```
agentscope [sample-agent | watch] > model providers

CHAT PROVIDERS
  openai         gpt-4.1-mini · OPENAI_API_KEY
  openai-codex   gpt-5-codex · OPENAI_API_KEY
  anthropic      claude-sonnet-4-5 · ANTHROPIC_API_KEY
  gemini         gemini-2.5-flash · GEMINI_API_KEY
  openrouter     openai/gpt-4.1-mini · OPENROUTER_API_KEY
  groq           llama-3.3-70b-versatile · GROQ_API_KEY
  deepseek       deepseek-chat · DEEPSEEK_API_KEY
  ollama         qwen3:8b · local, no key
  compatible     choose a model · AGENTSCOPE_CHAT_API_KEY
  codex          default · existing CLI login
  claude-cli     default · existing CLI login
Claude aliases Anthropic; codex uses the Codex CLI; openai-codex uses the OpenAI API. Models
depend on your account or local installation.
agentscope [sample-agent | watch] > model list

SAVED CHAT MODELS
  local-demo *   compatible · SmolLM2-135M-Instruct
agentscope [sample-agent | watch] > context on
Project summary context enabled; it will be sent to your selected chat provider.
agentscope [sample-agent | watch] > model status

AGENTSCOPE'S CHAT MODEL
  Profile          local-demo
  Provider         compatible
  Model            SmolLM2-135M-Instruct
  Readiness        Credential or CLI available; connection not tested
  Project context  on: summary metrics
agentscope [sample-agent | watch] > context off
Project context disabled. Conversation cleared.
agentscope [sample-agent | watch] > chat reset
Conversation cleared; telemetry is preserved.
agentscope [sample-agent | watch] >
```

Supported provider options and explicit control over sharing project summary metrics.

7. Detect and investigate an incident

SYNTHETIC DEMO: generated tool-loop telemetry; real detection and persisted investigation.

AgentScope 0.4.0 / Detect and investigate an incident — ACTUAL TERMINAL OUTPUT

```
agentscope [sample-agent | watch] > demo tool_loop
SYNTHETIC DEMO · project 8f422414-87cb-4dd2-ac9a-fe6075dc4799 · scenario tool_loop · seed 42
Persisted 25 runs. Open http://127.0.0.1:48065/dashboard and select this project.
Incident 49c85b66-e172-4b16-b909-32b2a7b695e4: Repeated tool calls without progress
Investigation bcd8855c-2d0b-4a10-ae80-cc67820b4908; waiting for evidence collection.

INVESTIGATION
bcd8855c-2d0b-4a10-ae80-cc67820b4908 / complete

SUMMARY
Repeated tool calls without progress for demo/research-agent. Measurements were evaluated
against rule tool_loop v1.0.

DECISION SUMMARY
The retry path is reprocessing unchanged results without a recorded progress event.

RECOMMENDATION
Introduce deduplication, a bounded retry budget, and progress checkpoints.
Evidence references: 8

PROPOSAL
  ID            0cf59a94-dd1a-4c58-a951-191652eb2887
  Status        proposed
  Verification  not started
Explicit controls: approve 0cf59a94-dd1a-4c58-a951-191652eb2887 ; execute
0cf59a94-dd1a-4c58-a951-191652eb2887
Demo control is opt-in: policy demo on. Real agents remain recommendation-only.
agentscope [REPL synthetic demo f2edeb8a | watch] > incidents

INCIDENTS
1 records returned
Repeated tool calls without progress
ACTION_REQUIRED / investigate 49c85b66-e172-4b16-b909-32b2a7b695e4
ID: 49c85b66-e172-4b16-b909-32b2a7b695e4

agentscope [REPL synthetic demo f2edeb8a | watch] >
```

SYNTHETIC DEMO: generated tool-loop telemetry; real detection and persisted investigation.

8. Approve, execute, and verify demo recovery

SYNTHETIC DEMO ONLY: approval and execution are separate; recovery is checked after the observation window.

AgentScope 0.4.0 / Approve, execute, and verify demo recovery — ACTUAL TERMINAL OUTPUT

```
agentscope [REPL synthetic demo f2edeb8a | watch] > policy demo on
Isolated demo control enabled. Approval is still required.
agentscope [REPL synthetic demo f2edeb8a | watch] > approve 0cf59a94-dd1a-4c58-a951-191652eb2887

Proposal 0cf59a94-dd1a-4c58-a951-191652eb2887: approved. Execution requires the separate execute
 command.
agentscope [REPL synthetic demo f2edeb8a | watch] > execute 0cf59a94-dd1a-4c58-a951-191652eb2887

Proposal 0cf59a94-dd1a-4c58-a951-191652eb2887: verifying. Recovery requires the server's observa
tion window; use verify INVESTIGATION_ID.
agentscope [REPL synthetic demo f2edeb8a | watch] > verify bcd8855c-2d0b-4a10-ae80-cc67820b4908
Waiting for persisted recovery measurements after the observation window…

INVESTIGATION
bcd8855c-2d0b-4a10-ae80-cc67820b4908 / complete

SUMMARY
Repeated tool calls without progress for demo/research-agent. Measurements were evaluated
against rule tool_loop v1.0.

DECISION SUMMARY
The retry path is reprocessing unchanged results without a recorded progress event.

RECOMMENDATION
Introduce deduplication, a bounded retry budget, and progress checkpoints.
Evidence references: 8

PROPOSAL
  ID            0cf59a94-dd1a-4c58-a951-191652eb2887
  Status        executed
  Verification  VERIFIED_RECOVERED
Explicit controls: approve 0cf59a94-dd1a-4c58-a951-191652eb2887 ; execute
0cf59a94-dd1a-4c58-a951-191652eb2887
Demo control is opt-in: policy demo on. Real agents remain recommendation-only.
agentscope [REPL synthetic demo f2edeb8a | watch] >
```

SYNTHETIC DEMO ONLY: approval and execution are separate; recovery is checked after the observation window.

9. Complete REPL command reference

All current command groups, including chat, monitoring, investigations, and session controls.

AgentScope 0.4.0 / Complete REPL command reference — ACTUAL TERMINAL OUTPUT

```
agentscope [REPL synthetic demo f2edeb8a | watch] > help

CHAT WITH AGENTSCOPE
  configure [PROVIDER]      Set up your assistant model and credentials
  model [list|providers|check]  Inspect profiles and test the selected model
  model use PROFILE         Switch your assistant provider/model
  chat MESSAGE / ask MESSAGE  Ask a question; ordinary sentences work too
  chat reset                Clear the in-memory conversation
  context on|off            Choose whether chat receives project summary metrics

MONITOR
  watch [PATH]     Start local monitoring in the background
  run -- COMMAND   Launch an app with capture; waits until it exits
  status [--json]  View activity, usage, and watch health
  stop             Stop local services and keep your records
  open             Open the selected project's dashboard

EXPLORE
  projects [--json]   List workspaces
  use PROJECT_ID      Switch the selected workspace
  agents [--json]     List registered agents
  runs [--json]       Inspect recent executions
  incidents [--json]  List incidents and their IDs

INVESTIGATE
  investigate INCIDENT_ID  Collect evidence and recommendations
  investigation [ID]       Read the latest investigation
  demo [SCENARIO]          Practice with labeled synthetic telemetry

DEMO CONTROLS
  policy demo on|off   Configure isolated synthetic control
  approve PROPOSAL_ID  Approve a proposal separately
  execute PROPOSAL_ID  Execute an approved synthetic proposal
  verify [ID]          Wait for observed recovery evidence

SESSION
  guide / tips  Step-by-step monitoring workflow
  clear         Clear the visible terminal
  help COMMAND  Read command usage
  exit / quit   Close the REPL and its local services
Slash aliases work too: /watch, /status, /help. Use --json for complete API data.
agentscope [REPL synthetic demo f2edeb8a | watch] >
```

All current command groups, including chat, monitoring, investigations, and session controls.

10. Stop safely and keep recorded telemetry

Actual stop and exit; locally recorded telemetry is preserved.

AgentScope 0.4.0 / Stop safely and keep recorded telemetry — ACTUAL TERMINAL OUTPUT

```
agentscope [REPL synthetic demo f2edeb8a | watch] > stop
Watch stopped; recorded telemetry is preserved.
Next: watch to resume this repository, or exit to finish.
agentscope [REPL synthetic demo f2edeb8a] > exit
Session closed. Recorded telemetry is preserved.
```

Actual stop and exit; locally recorded telemetry is preserved.