Supplementary material

Channel attention in few-label hyperspectral CNNs: an equivalence-tested comparison




Figure S1: The SNSM probe inside a residual block. Per-channel descriptors of the feature map $\mathbf{h}$ (mean, variance, cross-channel gradient) are filtered along the channel axis by two one-dimensional convolutions, whose output sets a bounded scale γ_c and a shift β_c for each channel. The second convolution starts at zero, so the block is initially the identity.

Table S1: Random 5% splits: OA and AA (%, mean ± std) of all models, including an FC (γ+β) gate and two external baselines trained under the same protocol, HybridSN (original layer configuration) and SSFTT (four tokens, one transformer layer with eight heads). The eight backbone variants use 15 seeds on IP and five elsewhere; the other models use five.

Method	IP		KSC		PU		BW	
	OA	AA	OA	AA	OA	AA	OA	AA
Plain CNN	96.28±0.79	89.49±2.44	99.65±0.34	99.51±0.36	**99.59±0.07**	99.01±0.16	99.09±0.55	98.87±0.90
SE (γ)	96.34±0.62	90.04±2.18	99.61±0.28	99.43±0.38	99.53±0.19	98.80±0.56	98.95±0.82	98.76±1.07
ECA (γ)	96.28±0.68	90.87±2.53	99.61±0.47	99.40±0.66	99.58±0.10	99.00±0.20	**99.13±0.76**	**98.90±1.08**
CBAM	96.19±0.60	91.58±1.49	99.54±0.56	99.23±0.83	99.58±0.06	**99.11±0.18**	98.99±0.87	98.78±1.20
GCT	96.28±0.80	90.07±2.34	**99.69±0.26**	**99.55±0.28**	99.58±0.08	98.99±0.18	99.11±0.56	98.88±0.91
SRM	96.20±0.71	93.04±2.14	99.69±0.36	99.51±0.49	99.55±0.07	98.92±0.17	98.87±0.63	98.67±0.97
SNSM (γ)	96.17±0.73	92.89±2.00	99.69±0.26	99.50±0.39	99.49±0.05	98.91±0.16	99.10±0.62	98.89±0.96
SNSM (γ+β)	96.27±0.67	**93.33±1.68**	99.63±0.55	99.45±0.73	99.47±0.05	98.93±0.16	99.04±0.69	98.85±1.03
FC (γ+β)	96.24±0.52	92.51±1.60	99.63±0.40	99.48±0.47	99.51±0.06	98.88±0.14	98.80±0.70	98.63±0.98
HybridSN	88.30±4.91	73.64±8.28	95.00±3.02	91.20±5.32	97.84±1.52	95.46±4.12	77.16±37.92	75.56±38.31
SSFTT	**96.71±0.79**	92.35±1.81	99.38±0.28	99.15±0.32	–	–	–	–

Table S2: Paired AA differences SNSM (γ+β) − block (points) with 95% t intervals, for every setting of the main paper's paired table.

Setting	Plain	SE	ECA	CBAM	GCT	SRM	SNSM (γ)	Seeds
IP, random 5%	+3.84 [+2.4, +5.3]	+3.29 [+2.2, +4.4]	+2.45 [+0.9, +4.0]	+1.75 [+0.9, +2.6]	+3.26 [+2.0, +4.6]	+0.29 [-0.8, +1.4]	+0.44 [-0.3, +1.2]	15
IP, random 50/15	-0.01 [-0.2, +0.2]	-0.08 [-0.2, +0.1]	+0.04 [-0.1, +0.2]	+0.05 [-0.1, +0.2]	+0.01 [-0.2, +0.2]	+0.07 [-0.1, +0.2]	+0.06 [-0.2, +0.3]	15
IP, smallest 15	+0.39 [+0.1, +0.7]	+0.50 [+0.3, +0.7]	+0.33 [+0.1, +0.6]	+0.60 [+0.3, +0.9]	+0.35 [+0.0, +0.7]	+0.41 [+0.0, +0.8]	+0.30 [+0.1, +0.5]	15
IP, standard	+0.24 [+0.0, +0.4]	+0.23 [+0.0, +0.4]	+0.33 [+0.2, +0.5]	+0.04 [-0.2, +0.2]	+0.25 [+0.1, +0.4]	-0.02 [-0.2, +0.2]	+0.12 [-0.1, +0.3]	15
PU, smallest 1/1/2	-0.59 [-1.6, +0.4]	-0.74 [-1.6, +0.1]	-1.19 [-1.9, -0.5]	-0.30 [-1.1, +0.5]	-1.14 [-2.2, -0.1]	-0.55 [-1.2, +0.2]	-1.59 [-2.6, -0.5]	15
KSC, smallest 1/1/2	-0.24 [-0.9, +0.5]	+0.79 [+0.1, +1.4]	+0.39 [-0.6, +1.4]	+0.54 [-0.7, +1.8]	-0.21 [-1.0, +0.5]	+1.41 [+0.3, +2.5]	+0.03 [-1.3, +1.3]	15
PU, patch-disjoint	+0.31 [-1.9, +2.5]	-0.47 [-2.7, +1.8]	-0.39 [-2.4, +1.7]	+1.03 [-0.7, +2.8]	+0.92 [-1.0, +2.8]	+1.33 [-0.4, +3.1]	+0.03 [-2.0, +2.0]	15
KSC, patch-disjoint	+3.46 [+1.5, +5.4]	-0.19 [-2.3, +1.9]	+1.86 [+0.3, +3.4]	+0.91 [-0.9, +2.7]	+3.51 [+1.5, +5.5]	+4.25 [+1.7, +6.8]	+1.40 [-1.0, +3.8]	15

Table S3: Paired OA differences SNSM (γ+β) − block (points). *: Holm-corrected Wilcoxon $p < 0.05$ within the row; †: equivalent within ±1 point (paired TOST).

Setting	Plain	SE	ECA	CBAM	GCT	SRM	SNSM (γ)	Seeds
IP, random 5%	-0.01†	-0.06†	-0.01†	+0.08†	-0.00†	+0.07†	+0.11†	15
IP, random 50/15	+0.04†	-0.15†	+0.09†	+0.12†	+0.06†	+0.10†	+0.01†	15
IP, smallest 15	-0.14†	-0.12†	-0.11†	+0.04†	-0.12†	+0.02†	+0.09†	15
IP, standard	+0.08†	+0.34†	+0.31†	+0.14†	+0.15†	+0.03†	+0.16†	15
PU, smallest 1/1/2	-0.25†	-0.26†	-0.39*†	-0.10†	-0.39†	-0.18†	-0.47*†	15
KSC, smallest 1/1/2	-0.20†	+0.23†	+0.17†	+0.19†	-0.19†	+0.50†	-0.03†	15
PU, patch-disjoint	+1.50	+0.89	+0.51	+0.69	+2.21	+0.79	+1.39	15
KSC, patch-disjoint	+1.98	+0.32	+0.72	+0.43	+1.91	+2.75	+0.25	15

Table S4: AA (%, mean ± std) of random 5% splits and of the same splits with only the three smallest classes changed (15 seeds; the unchanged PU and KSC splits use five). The last row is the range of the block means.

Block	IP, 5%	IP, smallest 15	PU, 5%	PU, smallest 1/1/2	KSC, 5%	KSC, smallest 1/1/2
Plain CNN	89.49±2.44	96.03±0.76	99.01±0.16	84.20±3.43	99.51±0.36	**93.12±3.44**
SE (γ)	90.04±2.18	95.93±0.64	98.80±0.56	84.35±3.29	99.43±0.38	92.09±3.25
ECA (γ)	90.87±2.53	96.10±0.76	99.00±0.20	84.80±3.23	99.40±0.66	92.48±3.19
CBAM	91.58±1.49	95.83±0.67	**99.11±0.18**	83.91±2.11	99.23±0.83	92.34±4.15
GCT	90.07±2.34	96.07±0.75	98.99±0.18	84.74±3.75	**99.55±0.28**	93.09±3.24
SRM	93.04±2.14	96.01±0.81	98.92±0.17	84.15±3.45	99.51±0.49	91.47±3.62
SNSM (γ)	92.89±2.00	96.13±0.72	98.91±0.16	**85.19±3.48**	99.50±0.39	92.84±3.64
SNSM (γ+β)	**93.33±1.68**	**96.43±0.66**	98.93±0.16	83.60±2.96	99.45±0.73	92.88±3.12
Range of block means	3.84	0.60	0.31	1.59	0.32	1.65

Table S5: Model size and cost for a $15 \times 15 \times 60$ IP patch. Training time is the mean per run (100 epochs, random 5% splits). MMACs: multiply–accumulates of convolution and linear layers counted by `thop` (attention products and descriptor statistics excluded). Latency: batch size 1 on a Tesla T4.

Method	Params (M)	MMACs	Latency (ms)	Train IP (s)	Train PU (s)
Plain CNN	0.184	41.2	0.69	4.2	17.6
SE (γ)	0.188	41.2	1.17	4.5	19.3
ECA (γ)	0.184	41.2	0.98	4.8	19.8
CBAM	0.185	41.3	1.55	5.9	24.9
GCT	0.184	41.2	1.11	4.7	20.0
SRM	0.184	41.2	1.22	4.8	20.2
SNSM (γ)	0.184	41.3	2.54	7.1	29.5
SNSM (γ+β)	0.184	41.3	2.54	7.2	30.2
FC (γ+β)	0.190	41.2	1.31	4.7	19.8
HybridSN	1.743	137.4	0.71	26.2	115.3
SSFTT	0.291	34.9	1.25	7.6	–