RESEARCH LETTER

Spectral-neighbourhood self-modulation for lightweight hyperspectral image classification with scarce labels

Swati Hira[a], Devguru Tiwari[a], Pratibha Kokardekar[b] and S. R. Sathe[c]

[a]Department of Computer Science and Engineering, IIIT Nagpur, Nagpur, India; [b]RBU, Nagpur, India; [c]VNIT, Nagpur, India

ARTICLE HISTORY
Compiled October 19, 2026

ABSTRACT
Lightweight convolutional networks remain attractive for hyperspectral image (HSI) classification when labels are scarce. Their channel-attention blocks, however, usually derive the gating weights from global average pooling followed by fully connected layers, which ignores how statistics vary across neighbouring feature channels. We propose spectral-neighbourhood self-modulation (SNSM), a residual-block modulation in which each channel's scale and shift are predicted by a small one-dimensional convolution over three per-channel descriptors (mean, variance and cross-channel gradient). SNSM adds about 130 parameters per block and is initialised as the identity. We evaluate under one fixed protocol (5% labelled pixels per class, five seeds, 100 epochs, no validation-based model selection) on six benchmark scenes. SNSM reaches 96.29±0.74% overall accuracy (OA) and 94.16±1.07% average accuracy (AA) on Indian Pines and 94.55±1.25% OA on Kennedy Space Center, giving the highest AA among the compared CNN variants and transformer baseline on both scenes. Paired ablations show that the gain comes from the neighbourhood descriptor network rather than from the additive shift. Replacing squeeze-and-excitation gating with SNSM gating raises AA by more than 4 points on both scenes; adding the shift changes AA by less than one point. On easier scenes all variants perform alike.

KEYWORDS
Hyperspectral image classification; channel attention; feature modulation; few labels; lightweight CNN

1. Introduction

Hyperspectral images record hundreds of contiguous bands. This makes pixel-level land-cover classification possible, but when labelled samples are few it exposes classifiers to the Hughes phenomenon (Hughes 1968; Bioucas-Dias et al. 2013). Kernel classifiers such as support vector machines (Camps-Valls and Bruzzone 2005; Melgani and Bruzzone 2004) and spectral–spatial methods (Fauvel et al. 2013; Ghamisi et al. 2017) were the standard before deep learning. Deep models now dominate (Li et al. 2019; Audebert, Le Saux, and Lefevre 2019). Stacked autoencoders (Chen et al. 2014), recurrent networks (Mou, Ghamisi, and Zhu 2017) and graph convolutional networks (Hong et al. 2021) have all been applied. Convolutional neural networks (CNNs) that operate on spatial–spectral patches are still the usual lightweight choice (Hu et al.

CONTACT Swati Hira. Email: shira@iiitn.ac.in

2015; Makantasis et al. 2015; Chen et al. 2016; Li, Zhang, and Shen 2017; Zhong et al. 2018; Roy et al. 2020). Transformers bring global context, but at a higher training cost (Hong et al. 2022; Sun et al. 2022).

Channel attention is a cheap way to make a CNN input-dependent. Squeeze-and-excitation (SE) (Hu, Shen, and Sun 2018) predicts one scale per channel from globally pooled features through two fully connected (FC) layers; CBAM adds spatial attention (Woo et al. 2018); ECA replaces the FC layers by a one-dimensional convolution over the pooled channel vector (Wang et al. 2020); FiLM adds a shift but takes its conditioning from an external input (Perez et al. 2018). Hyperspectral networks have adopted these blocks widely, usually combining SE-style channel gates with spatial attention (Mei et al. 2019; Haut et al. 2019; Li et al. 2020; Zhu et al. 2021; Roy et al. 2021). With very few labelled pixels, FC gating has many parameters relative to the training set. Global means alone also discard how the response is spread within the patch.

We study a modulation that is (i) local across channels, (ii) driven by several per-channel statistics rather than the mean only, and (iii) identity at initialisation. Our contributions are:

- SNSM, a residual-block modulation whose scale and shift come from a dilated one-dimensional convolution over normalised channel means, variances and cross-channel gradients (Section 2);
- a single-protocol comparison on six scenes in which every model, including HybridSN and SSFTT, is trained on the same splits, inputs and schedule with no validation-based checkpoint selection (Section 3);
- paired same-seed ablations that separate the effect of the descriptor network from the effect of the additive shift (Section 4).

2. Method

2.1. *Input features*

Each band of the raw cube is smoothed with a 5×5 adaptive Wiener filter. Principal component analysis (PCA) (Jolliffe and Cadima 2016) then reduces the spectrum to 30 components; it is fitted without labels on all pixels of the scene. A one-level db4 discrete wavelet transform (Mallat 1989; Daubechies 1992) is applied to each component. Its approximation sub-band, resized bilinearly to the image size, is concatenated with the components, giving $B = 60$ features per pixel. Each labelled pixel is represented by the $15 \times 15 \times B$ patch centred on it (zero padding at the image border).

2.2. *Backbone*

A 3×3 convolution maps the B input features to $C = 64$ channels (batch normalisation (Ioffe and Szegedy 2015), ReLU). Two residual blocks (He et al. 2016) follow, each computing

$$\mathbf{h} = \mathrm{ReLU}(\mathrm{BN}(\mathrm{Conv}_{3\times3}(\mathbf{x}))), \qquad \mathbf{y} = \mathrm{ReLU}\big(\mathrm{BN}(\mathrm{Conv}_{3\times3}(\mathcal{M}(\mathbf{h}))) + \mathbf{x}\big), \quad (1)$$

where $\mathcal{M}$ is the modulation under study ($\mathcal{M}$ = identity for the plain CNN). Global average pooling, dropout (0.4) (Srivastava et al. 2014) and a linear layer produce the class scores.




Figure 1. SNSM inside a residual block. Per-channel descriptors of the feature map $\mathbf{h}$ are filtered along the channel axis by two one-dimensional convolutions, whose output sets a bounded scale γ_c and a shift β_c for each channel. The second convolution starts at zero, so the block is initially the identity.

2.3. *Spectral-neighbourhood self-modulation*

For $\mathbf{h} \in \mathbb{R}^{C\times H\times W}$, SNSM first computes three descriptors for every channel c: the spatial mean μ_c, the spatial variance v_c, and the cross-channel gradient $g_c = (\mu_{c+1} - \mu_{c-1})/2$ (one-sided differences at the first and last channel). Each descriptor vector is standardised across channels, $\tilde{s} = (s - \bar{s})/(\sigma_s + \epsilon)$, and the three are stacked into $\mathbf{S} \in \mathbb{R}^{3\times C}$. Two one-dimensional convolutions along the channel axis give

$$\mathbf{Z} = \mathrm{Conv1D}^{(2)}_{k=3}\big(\mathrm{ReLU}(\mathrm{Conv1D}^{(1)}_{k=3,\,d=2}(\mathbf{S}))\big) \in \mathbb{R}^{2\times C}, \tag{2}$$

with 8 hidden channels, dilation $d = 2$ in the first layer and replicate padding. The modulation is

$$\gamma_c = 1 + \tfrac{1}{2}\tanh(Z_{1,c}), \qquad \beta_c = Z_{2,c}, \qquad \mathcal{M}(\mathbf{h})_c = \gamma_c\,\mathbf{h}_c + \beta_c. \tag{3}$$

The weights and bias of $\mathrm{Conv1D}^{(2)}$ are initialised to zero, so every block starts as the plain residual block and $\gamma_c \in [0.5, 1.5]$ thereafter. The modulation adds 130 parameters per block, against 2,128 for SE gating with reduction to 16 units. Each channel's parameters depend on a window of neighbouring channels (receptive field of seven channels), as in ECA (Wang et al. 2020). Unlike ECA, SNSM uses dispersion and gradient descriptors in addition to the mean, outputs a shift as well as a scale, and starts from the identity. The SNSM (γ) variant drops the shift output. Figure 1 shows the data flow.

3. Experimental setup

Data. We use Indian Pines (IP), Pavia University (PU), Kennedy Space Center (KSC), Botswana (BW), Salinas and WHU-Hi HanChuan (Baumgardner, Biehl, and Landgrebe 2015; Gamba 2004; Grupo de Inteligencia Computacional 2020; Zhong et al. 2020). For each class, 5% of the labelled pixels (at least one) are drawn at random for training; the remaining labelled pixels are used for testing. For Salinas and WHU-Hi, a random subset of 50,000 test pixels is used. This gives 505/9744 (IP), 256/4955 (KSC), 2135/40641 (PU) and 156/3092 (BW) training/test pixels (Table 1).

Table 1. Benchmark scenes and the 5% splits used (seed 42; split sizes are the same for every seed).

Scene	Sensor	Size (pixels)	Bands	GSD (m)	Classes	Labelled	Train/test
Indian Pines (IP)	AVIRIS	145×145	200	20	16	10,249	505/9,744
Pavia University (PU)	ROSIS	610×340	103	1.3	9	42,776	2,135/40,641
Kennedy Space Center (KSC)	AVIRIS	512×614	176	18	13	5,211	256/4,955
Botswana (BW)	Hyperion	1476×256	145	30	14	3,248	156/3,092
Salinas	AVIRIS	512×217	204	3.7	16	54,129	2,697/50,000
WHU-Hi HanChuan	Headwall Nano-Hyperspec	1217×303	274	0.109	16	257,530	12,868/50,000

Table 2. OA and AA (%, mean ± std over five seeds) at 5% labelled pixels. Best mean per column in bold.

Method	IP		KSC		PU		BW	
	OA	AA	OA	AA	OA	AA	OA	AA
Plain CNN	95.96±0.89	87.86±1.29	90.93±6.94	85.64±12.98	**99.59±0.07**	99.01±0.16	99.09±0.55	98.87±0.90
SE (γ)	96.23±0.69	89.49±2.39	91.54±5.56	87.32±8.36	99.53±0.19	98.80±0.56	98.95±0.82	98.76±1.07
ECA (γ)	96.17±0.74	91.30±2.26	88.43±6.66	83.72±9.93	99.58±0.10	99.00±0.20	**99.13±0.76**	**98.90±1.08**
CBAM	96.50±0.48	92.87±1.14	92.12±1.57	89.00±1.82	99.58±0.06	**99.11±0.18**	98.99±0.87	98.78±1.20
FC (γ+β)	96.24±0.52	92.51±1.60	84.31±6.34	77.25±8.18	99.51±0.06	98.88±0.14	98.80±0.70	98.63±0.98
SNSM (γ)	96.19±0.74	93.70±1.38	94.49±2.02	91.63±3.04	99.49±0.05	98.91±0.16	99.10±0.62	98.89±0.96
SNSM (γ+β)	96.29±0.74	**94.16±1.07**	**94.55±1.25**	**92.25±1.84**	99.47±0.05	98.93±0.16	99.04±0.69	98.85±1.03
HybridSN	88.30±4.91	73.64±8.28	68.04±9.32	55.19±11.33	97.84±1.52	95.46±4.12	77.16±37.92	75.56±38.31
SSFTT	**96.71±0.79**	92.35±1.81	80.44±2.57	68.50±3.65	–	–	–	–

Models. On IP, KSC, PU and BW we compare seven modulation variants on the same backbone (plain CNN; SE (γ) (Hu, Shen, and Sun 2018); ECA (γ) (Wang et al. 2020), with kernel size 3 as given by its adaptive rule for 64 channels; CBAM (Woo et al. 2018), with channel reduction 16 and a 7×7 spatial gate; FC (γ+β), i.e. SE-style FC layers predicting a sigmoid scale and a linear shift; SNSM (γ); SNSM (γ+β)) with HybridSN (Roy et al. 2020) in its original layer configuration. SSFTT (Sun et al. 2022) (four tokens, one transformer layer with eight heads) is reimplemented and run on IP and KSC only. Salinas and WHU-Hi are near saturation and are run with SNSM only.

Protocol. Every model sees the same 60-feature patches and the same splits for a given seed. Training uses cross-entropy, AdamW (Loshchilov and Hutter 2019) (learning rate 10^{-3}, weight decay 10^{-4}), a step decay (factor 0.5 every 40 epochs), batch size 64 and exactly 100 epochs, with no data augmentation and no early stopping. The final-epoch model is evaluated once. No validation or test data are used for model selection. Each configuration is repeated with seeds 42–46, and we report mean ± sample standard deviation. Runs used PyTorch (Paszke et al. 2019) on an NVIDIA Tesla T4. Baselines are therefore trained under our protocol and inputs rather than their original settings, so their accuracies are not directly comparable to published values.

4. Results

Accuracy. Table 2 gives the main comparison. On IP, SNSM (γ+β) has the highest AA; SSFTT and CBAM have higher OA but lower AA. On KSC, SNSM (γ+β) has the highest OA and AA, and its seed-to-seed spread is several times smaller than that of the plain and SE models. On PU and BW the seven CNN variants are within a few tenths of a point of each other, so modulation brings no measurable benefit on these scenes. HybridSN trained under our protocol is less accurate and less stable; on one BW seed it did not converge (9.4% OA). SNSM reaches 99.90±0.04% OA on Salinas and 99.64±0.11% OA on WHU-Hi. Figure 2 shows the AA spread across seeds on the two hard scenes.

Where the gain comes from. Table 3 and Figure 3 pair runs that share a seed and therefore a split. Replacing SE gating by the SNSM descriptor network (both




Figure 2. AA (mean ± standard deviation over five seeds) on Indian Pines and Kennedy Space Center. SNSM variants in blue.

Table 3. Paired same-seed differences in AA (percentage points): mean over five seeds and number of seeds with a positive difference.

ΔAA (wins/5)	IP	KSC	PU	BW
SNSM (γ+β) − SNSM (γ)	+0.46 (3/5)	+0.62 (3/5)	+0.02 (3/5)	-0.03 (1/5)
FC (γ+β) − SE (γ)	+3.02 (5/5)	-10.07 (0/5)	+0.09 (1/5)	-0.13 (1/5)
SNSM (γ) − SE (γ)	+4.22 (5/5)	+4.31 (4/5)	+0.11 (1/5)	+0.13 (2/5)
SNSM (γ) − ECA (γ)	+2.41 (4/5)	+7.91 (3/5)	-0.09 (2/5)	-0.02 (2/5)
SNSM (γ+β) − CBAM	+1.30 (4/5)	+3.25 (5/5)	-0.18 (1/5)	+0.07 (4/5)
SNSM (γ+β) − Plain CNN	+6.30 (5/5)	+6.60 (4/5)	-0.08 (2/5)	-0.01 (2/5)

scale-only) raises AA on IP and KSC in nine of ten paired runs, with mean gains above 4 points. ECA also gates each channel with a local convolution across channels, but it uses only the channel mean and has lower AA than SNSM (γ) on IP (four of five seeds) and KSC (three of five seeds, with a large seed-to-seed spread for ECA). Locality across channels alone therefore does not explain the gain; we did not separate the contributions of the extra descriptors and of the identity initialisation. CBAM, which adds max pooling and a spatial gate to SE-style channel attention, also has lower AA than SNSM (γ+β) on IP (four of five seeds) and KSC (five of five seeds). Adding the shift to SNSM changes AA by less than one point and helps in only three of five seeds on either scene, so we do not claim a benefit from the shift itself. Adding a shift to FC gating helps on IP but lowers AA by about 10 points on KSC. This suggests that an unconstrained FC shift is unstable with 256 training pixels; SNSM's bounded scale and zero-initialised output avoid this problem.

The AA gains on IP come from small classes (Table 4). Relative to the plain CNN, SNSM (γ+β) raises mean per-class accuracy on Oats (20 labelled pixels) from 21.1% to 74.7%, on Grass-pasture-mowed (28) from 63.0% to 92.6%, and on Stone-Steel-Towers (93) from 76.9% to 92.4%. On KSC the largest change is for Cabbage palm hammock, from 60.3% to 93.1%.

Cost. SNSM adds almost no parameters or multiply–accumulates to the plain CNN (Table 5), but its descriptor computation consists of many small operations, so batch-1 latency and training time are higher than for the plain and SE models. All CNN variants remain an order of magnitude smaller than HybridSN.




Figure 3. Paired same-seed differences in AA. Grey dots are the five seeds; the blue bar is their mean.

Table 4. Per-class accuracy (%, mean over five seeds) on Indian Pines; n is the number of labelled pixels. Best value per row in bold.

Class	n	Plain CNN	SE (γ)	ECA (γ)	CBAM	SNSM (γ)	SNSM (γ+β)	HybridSN	SSFTT
Alfalfa	46	92.7	90.9	90.5	92.7	**94.5**	89.1	29.1	81.8
Corn-notill	1428	96.3	95.8	96.7	96.5	96.6	95.8	88.1	**97.3**
Corn-mintill	830	93.9	94.0	93.6	**95.0**	93.7	94.2	82.2	94.4
Corn	237	90.9	92.1	92.8	94.3	93.8	**96.5**	61.8	90.6
Grass-pasture	483	97.1	**97.2**	96.5	96.8	96.7	96.9	82.3	96.3
Grass-trees	730	97.3	96.5	97.2	97.8	97.2	97.7	97.8	**98.4**
Grass-pasture-mowed	28	63.0	58.5	84.4	89.6	88.9	**92.6**	44.4	**92.6**
Hay-windrowed	478	99.3	**99.6**	99.6	99.6	99.4	99.6	96.3	99.5
Oats	20	21.1	44.2	43.2	58.9	70.5	**74.7**	27.4	60.0
Soybean-notill	972	92.3	93.7	92.3	93.3	93.2	92.7	84.5	**94.2**
Soybean-mintill	2455	97.3	**97.9**	97.2	97.1	96.7	97.2	94.4	97.4
Soybean-clean	593	93.1	92.8	92.4	93.8	91.8	91.2	73.8	**94.5**
Wheat	205	96.4	97.7	96.6	97.1	96.8	98.2	85.4	**98.6**
Woods	1265	99.5	99.6	99.6	99.5	99.4	99.2	96.8	**99.8**
Bldg-Grass-Trees-Drives	386	**98.9**	98.1	98.8	98.2	98.1	98.7	89.1	97.9
Stone-Steel-Towers	93	76.9	83.1	89.4	85.6	91.7	**92.4**	44.9	84.3
AA		87.9	89.5	91.3	92.9	93.7	94.2	73.6	92.4

5. Discussion and limitations

Local cross-channel modulation helps where it is most needed: scenes with small, spectrally similar classes (IP, KSC). It does so with fewer gating parameters than SE. On scenes where a plain CNN is already near saturation, its benefit disappears. Several limitations apply. Training and test pixels are drawn at random from the same scene, so overlapping patches share spatial context and accuracies are optimistic compared with spatially disjoint splits (Liang et al. 2017; Nalepa, Myller, and Kawulok 2019). PCA is fitted on all pixels of each scene without labels. Five seeds give only an indication of variability, and the paired differences in Table 3 are not formal significance tests. Baselines were not tuned to our protocol. Finally, the channel order of learned feature maps has no physical wavelength meaning, so "neighbourhood" refers to adjacency of feature channels, which the first convolution is free to learn.

6. Conclusion

SNSM predicts per-channel scale and shift with a small convolution over neighbouring channels' mean, variance and gradient. Under a single strict protocol, it gives the best average accuracy on Indian Pines and KSC at 5% labels with about 130 extra parameters per block. Paired ablations attribute the improvement to the neighbourhood




Figure 4. Indian Pines, SNSM (γ+β), seed 42: (a) ground truth, (b) prediction for all labelled pixels, (c) test errors in red and training pixels in white.

Table 5. Model size and cost for a $15 \times 15 \times 60$ IP patch. Training time is the mean per run (100 epochs).

Method	Params (M)	MMACs[a]	Latency (ms)[b]	Train IP (s)	Train PU (s)
Plain CNN	0.184	41.2	0.69	4.4	17.6
SE (γ)	0.188	41.2	1.17	4.6	19.3
ECA (γ)	0.184	41.2	0.98	5.2	19.8
CBAM	0.185	41.3	1.55	6.0	24.9
FC (γ+β)	0.190	41.2	1.31	4.7	19.8
SNSM (γ)	0.184	41.3	2.54	7.5	29.5
SNSM (γ+β)	0.184	41.3	2.54	7.6	30.2
HybridSN	1.743	137.4	0.71	26.2	115.3
SSFTT	0.291	34.9	1.25	7.6	–

[a]Multiply–accumulates of convolution and linear layers counted by `thop`; tensor operations such as attention products and descriptor statistics are not included. [b]Batch size 1 on a Tesla T4.

descriptor network rather than to the additive shift.

Disclosure statement

The authors report there are no competing interests to declare.

Funding

No external funding was received for this research.

Data and code availability

The datasets are publicly available (Grupo de Inteligencia Computacional 2020; Zhong et al. 2020). Code, per-run results and the scripts that generate every table are available at `https://github.com/Devguru-codes/research_paper_code`.

Use of generative AI

There is no use of generative AI.

References

Audebert, Nicolas, Bertrand Le Saux, and Sebastien Lefevre. 2019. "Deep Learning for Classification of Hyperspectral Data: A Comparative Review." *IEEE Geoscience and Remote Sensing Magazine* 7 (2): 159–173. https://doi.org/10.1109/MGRS.2019.2912563.

Baumgardner, Marion F., Larry L. Biehl, and David A. Landgrebe. 2015. "220 Band AVIRIS Hyperspectral Image Data Set: June 12, 1992 Indian Pine Test Site 3." Purdue University Research Repository. https://doi.org/10.4231/R7RX991C.

Bioucas-Dias, Jose M., Antonio Plaza, Gustavo Camps-Valls, Paul Scheunders, Nasser Nasrabadi, and Jocelyn Chanussot. 2013. "Hyperspectral Remote Sensing Data Analysis and Future Challenges." *IEEE Geoscience and Remote Sensing Magazine* 1 (2): 6–36. https://doi.org/10.1109/MGRS.2013.2244672.

Camps-Valls, G., and L. Bruzzone. 2005. "Kernel-based methods for hyperspectral image classification." *IEEE Transactions on Geoscience and Remote Sensing* 43 (6): 1351–1362. https://doi.org/10.1109/TGRS.2005.846154.

Chen, Yushi, Hanlu Jiang, Chunyang Li, Xiuping Jia, and Pedram Ghamisi. 2016. "Deep Feature Extraction and Classification of Hyperspectral Images Based on Convolutional Neural Networks." *IEEE Transactions on Geoscience and Remote Sensing* 54 (10): 6232–6251. https://doi.org/10.1109/TGRS.2016.2584107.

Chen, Yushi, Zhouhan Lin, Xing Zhao, Gang Wang, and Yanfeng Gu. 2014. "Deep Learning-Based Classification of Hyperspectral Data." *IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing* 7 (6): 2094–2107. https://doi.org/10.1109/JSTARS.2014.2329330.

Daubechies, Ingrid. 1992. *Ten Lectures on Wavelets*. Vol. 61 of *CBMS-NSF Regional Conference Series in Applied Mathematics*. Philadelphia, PA: SIAM. https://doi.org/10.1137/1.9781611970104.

Fauvel, M., Y. Tarabalka, J. A. Benediktsson, J. Chanussot, and J. C. Tilton. 2013. "Advances in Spectral-Spatial Classification of Hyperspectral Images." *Proceedings of the IEEE* 101 (3): 652–675. https://doi.org/10.1109/JPROC.2012.2197589.

Gamba, Paolo. 2004. "ROSIS Pavia University Hyperspectral Data Set." Telecommunications and Remote Sensing Laboratory, University of Pavia. `https://www.ehu.eus/ccwintco/index.php/Hyperspectral_Remote_Sensing_Scenes`.

Ghamisi, Pedram, Javier Plaza, Yushi Chen, Jun Li, and Antonio J Plaza. 2017. "Advanced Spectral Classifiers for Hyperspectral Images: A review." *IEEE Geoscience and Remote Sensing Magazine* 5 (1): 8–32. https://doi.org/10.1109/MGRS.2016.2616418.

Grupo de Inteligencia Computacional. 2020. "Hyperspectral Remote Sensing Scenes." University of the Basque Country (UPV/EHU). `https://www.ehu.eus/ccwintco/index.php/Hyperspectral_Remote_Sensing_Scenes`.

Haut, Juan Mario, Mercedes E. Paoletti, Javier Plaza, Antonio Plaza, and Jun Li. 2019. "Visual Attention-Driven Hyperspectral Image Classification." *IEEE Transactions on Geoscience and Remote Sensing* 57 (10): 8065–8080. https://doi.org/10.1109/TGRS.2019.2918080.

He, Kaiming, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. 2016. "Deep Residual Learning for Image Recognition." In *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 770–778. https://doi.org/10.1109/CVPR.2016.90.

Hong, Danfeng, Lianru Gao, Jing Yao, Bing Zhang, Antonio Plaza, and Jocelyn Chanussot. 2021. "Graph Convolutional Networks for Hyperspectral Image Classification." *IEEE Transactions on Geoscience and Remote Sensing* 59 (7): 5966–5978. https://doi.org/10.1109/TGRS.2020.3015157.

Hong, Danfeng, Zhu Han, Jing Yao, Lianru Gao, Bing Zhang, Antonio Plaza, and Jocelyn Chanussot. 2022. "SpectralFormer: Rethinking Hyperspectral Image Classification With Transformers." *IEEE Transactions on Geoscience and Remote Sensing* 60: 1–15. https://doi.org/10.1109/TGRS.2021.3130716.

Hu, Jie, Li Shen, and Gang Sun. 2018. "Squeeze-and-Excitation Networks." In *2018 IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 7132–7141.

https://doi.org/10.1109/CVPR.2018.00745.

Hu, Wei, Yangyu Huang, Li Wei, Fan Zhang, and Hengchao Li. 2015. "Deep Convolutional Neural Networks for Hyperspectral Image Classification." *Journal of Sensors* 2015: 1–12. https://doi.org/10.1155/2015/258619.

Hughes, G. 1968. "On the mean accuracy of statistical pattern recognizers." *IEEE Transactions on Information Theory* 14 (1): 55–63. https://doi.org/10.1109/TIT.1968.1054102.

Ioffe, Sergey, and Christian Szegedy. 2015. "Batch Normalization: Accelerating Deep Network Training by Reducing Internal Covariate Shift." In *Proceedings of the 32nd International Conference on Machine Learning (ICML)*, 448–456. https://doi.org/10.48550/arXiv.1502.03167.

Jolliffe, Ian T., and Jorge Cadima. 2016. "Principal component analysis: a review and recent developments." *Philosophical Transactions of the Royal Society A: Mathematical, Physical and Engineering Sciences* 374 (2065): 20150202. https://doi.org/10.1098/rsta.2015.0202.

Li, Rui, Shunyi Zheng, Chenxi Duan, Yang Yang, and Xiqi Wang. 2020. "Classification of Hyperspectral Image Based on Double-Branch Dual-Attention Mechanism Network." *Remote Sensing* 12 (3): 582. https://doi.org/10.3390/rs12030582.

Li, Shutao, Weiwei Song, Leyuan Fang, Yushi Chen, Pedram Ghamisi, and Jon Atli Benediktsson. 2019. "Deep Learning for Hyperspectral Image Classification: An Overview." *IEEE Transactions on Geoscience and Remote Sensing* 57 (9): 6690–6709. https://doi.org/10.1109/TGRS.2019.2907932.

Li, Ying, Haokui Zhang, and Qiang Shen. 2017. "Spectral–Spatial Classification of Hyperspectral Imagery with 3D Convolutional Neural Network." *Remote Sensing* 9 (1): 67. https://doi.org/10.3390/rs9010067.

Liang, Jie, Jun Zhou, Yuntao Qian, Lian Wen, Xiao Bai, and Yongsheng Gao. 2017. "On the Sampling Strategy for Evaluation of Spectral-Spatial Methods in Hyperspectral Image Classification." *IEEE Transactions on Geoscience and Remote Sensing* 55 (2): 862–880. https://doi.org/10.1109/TGRS.2016.2616489.

Loshchilov, Ilya, and Frank Hutter. 2019. "Decoupled Weight Decay Regularization." In *International Conference on Learning Representations (ICLR)*, https://doi.org/10.48550/arXiv.1711.05101.

Makantasis, Konstantinos, Konstantinos Karantzalos, Anastasios Doulamis, and Nikolaos Doulamis. 2015. "Deep supervised learning for hyperspectral data classification through convolutional neural networks." In *2015 IEEE International Geoscience and Remote Sensing Symposium (IGARSS)*, 4959–4962. https://doi.org/10.1109/IGARSS.2015.7326945.

Mallat, S.G. 1989. "A theory for multiresolution signal decomposition: the wavelet representation." *IEEE Transactions on Pattern Analysis and Machine Intelligence* 11 (7): 674–693. https://doi.org/10.1109/34.192463.

Mei, Xiaoguang, Erting Pan, Yong Ma, Xiaobing Dai, Jun Huang, Fan Fan, Qinglei Du, Hong Zheng, and Jiayi Ma. 2019. "Spectral-Spatial Attention Networks for Hyperspectral Image Classification." *Remote Sensing* 11 (8): 963. https://doi.org/10.3390/rs11080963.

Melgani, F., and L. Bruzzone. 2004. "Classification of hyperspectral remote sensing images with support vector machines." *IEEE Transactions on Geoscience and Remote Sensing* 42 (8): 1778–1790. https://doi.org/10.1109/TGRS.2004.831865.

Mou, Lichao, Pedram Ghamisi, and Xiao Xiang Zhu. 2017. "Deep Recurrent Neural Networks for Hyperspectral Image Classification." *IEEE Transactions on Geoscience and Remote Sensing* 55 (7): 3639–3655. https://doi.org/10.1109/TGRS.2016.2636241.

Nalepa, Jakub, Michal Myller, and Michal Kawulok. 2019. "Validating Hyperspectral Image Segmentation." *IEEE Geoscience and Remote Sensing Letters* 16 (8): 1264–1268. https://doi.org/10.1109/LGRS.2019.2895697.

Paszke, Adam, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, et al. 2019. "PyTorch: An Imperative Style, High-Performance Deep Learning Library." In *Advances in Neural Information Processing Systems 32 (NeurIPS)*, 8024–8035. https://doi.org/10.48550/arXiv.1912.01703.

Perez, Ethan, Florian Strub, Harm De Vries, Vincent Dumoulin, and Aaron Courville. 2018.

"FiLM: Visual Reasoning with a General Conditioning Layer." *Proceedings of the AAAI Conference on Artificial Intelligence* 32 (1). https://doi.org/10.1609/aaai.v32i1.11671.

Roy, Swalpa Kumar, Gopal Krishna, Shiv Ram Dubey, and Bidyut B. Chaudhuri. 2020. "HybridSN: Exploring 3-D–2-D CNN Feature Hierarchy for Hyperspectral Image Classification." *IEEE Geoscience and Remote Sensing Letters* 17 (2): 277–281. https://doi.org/10.1109/LGRS.2019.2918719.

Roy, Swalpa Kumar, Suvojit Manna, Tiecheng Song, and Lorenzo Bruzzone. 2021. "Attention-Based Adaptive Spectral–Spatial Kernel ResNet for Hyperspectral Image Classification." *IEEE Transactions on Geoscience and Remote Sensing* 59 (9): 7831–7843. https://doi.org/10.1109/TGRS.2020.3043267.

Srivastava, Nitish, Geoffrey Hinton, Alex Krizhevsky, Ilya Sutskever, and Ruslan Salakhutdinov. 2014. "Dropout: A Simple Way to Prevent Neural Networks from Overfitting." *Journal of Machine Learning Research* 15 (56): 1929–1958. `https://jmlr.org/papers/v15/srivastava14a.html`.

Sun, Le, Guangrui Zhao, Yuhui Zheng, and Zebin Wu. 2022. "Spectral–Spatial Feature Tokenization Transformer for Hyperspectral Image Classification." *IEEE Transactions on Geoscience and Remote Sensing* 60: 1–14. https://doi.org/10.1109/TGRS.2022.3144158.

Wang, Qilong, Banggu Wu, Pengfei Zhu, Peihua Li, Wangmeng Zuo, and Qinghua Hu. 2020. "ECA-Net: Efficient Channel Attention for Deep Convolutional Neural Networks." In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 11531–11539. https://doi.org/10.1109/CVPR42600.2020.01155.

Woo, Sanghyun, Jongchan Park, Joon-Young Lee, and In So Kweon. 2018. "CBAM: Convolutional Block Attention Module." In *Computer Vision – ECCV 2018, Lecture Notes in Computer Science, vol. 11211*, 3–19. https://doi.org/10.1007/978-3-030-01234-2_1.

Zhong, Yanfei, Xin Hu, Chang Luo, Xinyu Wang, Ji Zhao, and Liangpei Zhang. 2020. "WHU-Hi: UAV-borne hyperspectral with high spatial resolution (H2) benchmark datasets and classifier for precise crop identification based on deep convolutional neural network with CRF." *Remote Sensing of Environment* 250: 112012. https://doi.org/10.1016/j.rse.2020.112012.

Zhong, Zilong, Jonathan Li, Zhiming Luo, and Michael Chapman. 2018. "Spectral–Spatial Residual Network for Hyperspectral Image Classification: A 3-D Deep Learning Framework." *IEEE Transactions on Geoscience and Remote Sensing* 56 (2): 847–858. https://doi.org/10.1109/TGRS.2017.2755542.

Zhu, Minghao, Licheng Jiao, Fang Liu, Shuyuan Yang, and Jianing Wang. 2021. "Residual Spectral–Spatial Attention Network for Hyperspectral Image Classification." *IEEE Transactions on Geoscience and Remote Sensing* 59 (1): 449–462. https://doi.org/10.1109/TGRS.2020.2994057.