RESEARCH LETTER

Spectral-neighbourhood self-modulation for lightweight hyperspectral image classification with scarce labels

Swati Hira[a], Devguru Tiwari[a], Pratibha Kokardekar[b] and S. R. Sathe[c]

[a]Department of Computer Science and Engineering, IIIT Nagpur, Nagpur, India; [b]RBU, Nagpur, India; [c]VNIT, Nagpur, India

ARTICLE HISTORY
Compiled October 18, 2026

ABSTRACT
Lightweight convolutional networks remain attractive for hyperspectral image (HSI) classification when labels are scarce, but their channel-attention blocks usually derive the gating weights from global average pooling followed by fully connected layers, which ignores how statistics vary across neighbouring feature channels. We propose spectral-neighbourhood self-modulation (SNSM), a residual-block modulation in which each channel's scale and shift are predicted by a small one-dimensional convolution over three per-channel descriptors (mean, variance and cross-channel gradient). SNSM adds about 130 parameters per block and is initialised as the identity. Under one fixed protocol (5% labelled pixels per class, five seeds, 100 epochs, no validation-based model selection) on six benchmark scenes, SNSM reaches 96.29±0.74% overall accuracy (OA) and 94.16±1.07% average accuracy (AA) on Indian Pines and 94.55±1.25% OA on Kennedy Space Center, giving the highest AA among the compared CNN variants and transformer baseline on both scenes. Paired ablations show that the gain comes from the neighbourhood descriptor network rather than from the additive shift: replacing squeeze-and-excitation gating with SNSM gating raises AA by more than 4 points on both scenes, whereas adding the shift changes AA by less than one point. On easier scenes all variants perform alike.

KEYWORDS
Hyperspectral image classification; channel attention; feature modulation; few labels; lightweight CNN

1. Introduction

Hyperspectral images record hundreds of contiguous bands, which makes pixel-level land-cover classification possible but also exposes classifiers to the Hughes phenomenon when labelled samples are few (Hughes 1968; Melgani and Bruzzone 2004). Convolutional neural networks (CNNs) that operate on spatial–spectral patches are the standard lightweight choice (Hu et al. 2015; Makantasis et al. 2015; Li, Zhang, and Shen 2017; Roy et al. 2019), while transformer models offer global context at a higher training cost (Hong et al. 2021; Sun et al. 2022).

Channel attention is a cheap way to make a CNN input-dependent. Squeeze-and-excitation (SE) (Hu, Shen, and Sun 2018) predicts one scale per channel from globally pooled features through two fully connected (FC) layers; CBAM adds spatial attention

CONTACT Swati Hira. Email: shira@iiitn.ac.in

(Woo et al. 2018); ECA replaces the FC layers by a one-dimensional convolution over the pooled channel vector (Wang et al. 2020); FiLM adds a shift but takes its conditioning from an external input (Perez et al. 2018). With very few labelled pixels, FC gating has many parameters relative to the training set, and global means alone discard how the response is spread within the patch.

We study a modulation that is (i) local across channels, (ii) driven by several per-channel statistics rather than the mean only, and (iii) identity at initialisation. Our contributions are:

- SNSM, a residual-block modulation whose scale and shift come from a dilated one-dimensional convolution over normalised channel means, variances and cross-channel gradients (Section 2);
- a single-protocol comparison on six scenes in which every model, including HybridSN and SSFTT, is trained on the same splits, inputs and schedule with no validation-based checkpoint selection (Section 3);
- paired same-seed ablations that separate the effect of the descriptor network from the effect of the additive shift (Section 4).

2. Method

2.1. *Input features*

Each band of the raw cube is smoothed with a 5×5 adaptive Wiener filter. Principal component analysis (PCA) then reduces the spectrum to 30 components; it is fitted without labels on all pixels of the scene. A one-level db4 discrete wavelet transform (Daubechies 1992) is applied to each component, and its approximation sub-band, resized bilinearly to the image size, is concatenated with the components, giving $B = 60$ features per pixel. Each labelled pixel is represented by the $15 \times 15 \times B$ patch centred on it (zero padding at the image border).

2.2. *Backbone*

A 3×3 convolution maps the B input features to $C = 64$ channels (batch normalisation, ReLU). Two residual blocks follow, each computing

$$\mathbf{h} = \mathrm{ReLU}(\mathrm{BN}(\mathrm{Conv}_{3\times3}(\mathbf{x}))), \qquad \mathbf{y} = \mathrm{ReLU}\big(\mathrm{BN}(\mathrm{Conv}_{3\times3}(\mathcal{M}(\mathbf{h}))) + \mathbf{x}\big), \quad (1)$$

where $\mathcal{M}$ is the modulation under study ($\mathcal{M}$ = identity for the plain CNN). Global average pooling, dropout (0.4) and a linear layer produce the class scores.

2.3. *Spectral-neighbourhood self-modulation*

For $\mathbf{h} \in \mathbb{R}^{C\times H\times W}$, SNSM first computes three descriptors for every channel c: the spatial mean μ_c, the spatial variance v_c, and the cross-channel gradient $g_c = (\mu_{c+1} - \mu_{c-1})/2$ (one-sided differences at the first and last channel). Each descriptor vector is standardised across channels, $\tilde{s} = (s - \bar{s})/(\sigma_s + \epsilon)$, and the three are stacked into $\mathbf{S} \in \mathbb{R}^{3\times C}$. Two one-dimensional convolutions along the channel axis give

$$\mathbf{Z} = \mathrm{Conv1D}^{(2)}_{k=3}\big(\mathrm{ReLU}(\mathrm{Conv1D}^{(1)}_{k=3,\,d=2}(\mathbf{S}))\big) \in \mathbb{R}^{2\times C}, \quad (2)$$

with 8 hidden channels, dilation $d = 2$ in the first layer and replicate padding. The modulation is

$$\gamma_c = 1 + \tfrac{1}{2}\tanh(Z_{1,c}), \qquad \beta_c = Z_{2,c}, \qquad \mathcal{M}(\mathbf{h})_c = \gamma_c\,\mathbf{h}_c + \beta_c. \tag{3}$$

The weights and bias of $\text{Conv1D}^{(2)}$ are initialised to zero, so every block starts as the plain residual block and $\gamma_c \in [0.5, 1.5]$ thereafter. The modulation adds 130 parameters per block, against 2,128 for SE gating with reduction to 16 units. Each channel's parameters depend on a window of neighbouring channels (receptive field of seven channels), as in ECA (Wang et al. 2020); unlike ECA, SNSM uses dispersion and gradient descriptors in addition to the mean, outputs a shift as well as a scale, and starts from the identity. The SNSM (γ) variant drops the shift output.

3. Experimental setup

Data. We use Indian Pines (IP), Pavia University (PU), Kennedy Space Center (KSC), Botswana (BW), Salinas and WHU-Hi HanChuan (Baumgardner, Biehl, and Landgrebe 2015; Gamba 2004; Grupo de Inteligencia Computacional (GIC) 2020; Zhong et al. 2020). For each class, 5% of the labelled pixels (at least one) are drawn at random for training and the remaining labelled pixels are used for testing; for Salinas and WHU-Hi a random subset of 50,000 test pixels is used. This gives 505/9744 (IP), 256/4955 (KSC), 2135/40641 (PU) and 156/3092 (BW) training/test pixels.

Models. On IP, KSC, PU and BW we compare six modulation variants on the same backbone (plain CNN; SE (γ) (Hu, Shen, and Sun 2018); ECA (γ) (Wang et al. 2020), with kernel size 3 as given by its adaptive rule for 64 channels; FC (γ+β), i.e. SE-style FC layers predicting a sigmoid scale and a linear shift; SNSM (γ); SNSM (γ+β)) with HybridSN (Roy et al. 2019) in its original layer configuration. SSFTT (Sun et al. 2022) (four tokens, one transformer layer with eight heads) is reimplemented and run on IP and KSC only. Salinas and WHU-Hi are near saturation and are run with SNSM only.

Protocol. Every model sees the same 60-feature patches and the same splits for a given seed. Training uses cross-entropy, AdamW (Loshchilov and Hutter 2019) (learning rate 10^{-3}, weight decay 10^{-4}), a step decay (factor 0.5 every 40 epochs), batch size 64 and exactly 100 epochs, with no data augmentation and no early stopping. The final-epoch model is evaluated once; no validation or test data are used for model selection. Each configuration is repeated with seeds 42–46, and we report mean ± sample standard deviation. Runs used PyTorch (Paszke et al. 2019) on an NVIDIA Tesla T4. Baselines are therefore trained under our protocol and inputs rather than their original settings, so their accuracies are not directly comparable to published values.

4. Results

Accuracy. Table 1 gives the main comparison. On IP, SNSM (γ+β) has the highest AA; SSFTT has the highest OA but a lower AA. On KSC, SNSM (γ+β) has the highest OA and AA, and its seed-to-seed spread is several times smaller than that of the plain and SE models. On PU and BW the six CNN variants are within a few tenths of a point of each other (the plain CNN is marginally best on PU), so modulation brings no measurable benefit on these scenes. HybridSN trained under our protocol is

Table 1. OA and AA (%, mean ± std over five seeds) at 5% labelled pixels. Best mean per column in bold.

Method	IP		KSC		PU		BW	
	OA	AA	OA	AA	OA	AA	OA	AA
Plain CNN	95.96±0.89	87.86±1.29	90.93±6.94	85.64±12.98	**99.59±0.07**	**99.01±0.16**	99.09±0.55	98.87±0.90
SE (γ)	96.23±0.69	89.49±2.39	91.54±5.56	87.32±8.36	99.53±0.19	98.80±0.56	98.95±0.82	98.76±1.07
ECA (γ)	96.17±0.74	91.30±2.26	88.43±6.66	83.72±9.93	99.58±0.10	99.00±0.20	**99.13±0.76**	**98.90±1.08**
FC (γ+β)	96.24±0.52	92.51±1.60	84.31±6.34	77.25±8.18	99.51±0.06	98.88±0.14	98.80±0.70	98.63±0.98
SNSM (γ)	96.19±0.74	93.70±1.38	94.49±2.02	91.63±3.04	99.49±0.05	98.91±0.16	99.10±0.62	98.89±0.96
SNSM (γ+β)	96.29±0.74	**94.16±1.07**	**94.55±1.25**	**92.25±1.84**	99.47±0.05	98.93±0.16	99.04±0.69	98.85±1.03
HybridSN	88.30±4.91	73.64±8.28	68.04±9.32	55.19±11.33	97.84±1.52	95.46±4.12	77.16±37.92	75.56±38.31
SSFTT	**96.71±0.79**	92.35±1.81	80.44±2.57	68.50±3.65	–	–	–	–

Table 2. Paired same-seed differences in AA (percentage points): mean over five seeds and number of seeds with a positive difference.

ΔAA (wins/5)	IP	KSC	PU	BW
SNSM (γ+β) − SNSM (γ)	+0.46 (3/5)	+0.62 (3/5)	+0.02 (3/5)	-0.03 (1/5)
FC (γ+β) − SE (γ)	+3.02 (5/5)	-10.07 (0/5)	+0.09 (1/5)	-0.13 (1/5)
SNSM (γ) − SE (γ)	+4.22 (5/5)	+4.31 (4/5)	+0.11 (1/5)	+0.13 (2/5)
SNSM (γ) − ECA (γ)	+2.41 (4/5)	+7.91 (3/5)	-0.09 (2/5)	-0.02 (2/5)
SNSM (γ+β) − Plain CNN	+6.30 (5/5)	+6.60 (4/5)	-0.08 (2/5)	-0.01 (2/5)

less accurate and less stable; on one BW seed it did not converge (9.4% OA). SNSM reaches 99.90±0.04% OA on Salinas and 99.64±0.11% OA on WHU-Hi.

Where the gain comes from. Table 2 pairs runs that share a seed and therefore a split. Replacing SE gating by the SNSM descriptor network (both scale-only) raises AA on IP and KSC in nine of ten paired runs, with mean gains above 4 points. ECA, which also gates each channel with a local convolution across channels but uses only the channel mean, has lower AA than SNSM (γ) on IP (four of five seeds) and KSC (three of five seeds, with a large seed-to-seed spread for ECA), so locality across channels alone does not explain the gain; we did not separate the contributions of the extra descriptors and of the identity initialisation. Adding the shift to SNSM changes AA by less than one point and helps in only three of five seeds on either scene, so we do not claim a benefit from the shift itself. Adding a shift to FC gating helps on IP but lowers AA by about 10 points on KSC, which suggests that an unconstrained FC shift is unstable with 256 training pixels, whereas SNSM's bounded scale and zero-initialised output avoid this.

The AA gains on IP come from small classes. Relative to the plain CNN, SNSM (γ+β) raises mean per-class accuracy on Oats (20 labelled pixels) from 21.1% to 74.7%, on Grass-pasture-mowed (28) from 63.0% to 92.6%, and on Stone-Steel-Towers (93) from 76.9% to 92.4%. On KSC the largest change is for Cabbage palm hammock, from 60.3% to 93.1%.

Cost. SNSM adds almost no parameters or multiply–accumulates to the plain CNN (Table 3), but its descriptor computation consists of many small operations, so batch-1 latency and training time are higher than for the plain and SE models. All CNN variants remain an order of magnitude smaller than HybridSN.

5. Discussion and limitations

Local cross-channel modulation helps where it is most needed: scenes with small, spectrally similar classes (IP, KSC), and it does so with fewer gating parameters than SE. Its benefit disappears on scenes where a plain CNN is already near saturation. Several limitations apply. Training and test pixels are drawn at random from the same scene, so overlapping patches share spatial context and accuracies are optimistic




Figure 1. Indian Pines, SNSM (γ+β), seed 42: (a) ground truth, (b) prediction for all labelled pixels, (c) test errors in red and training pixels in white.

Table 3. Model size and cost for a $15 \times 15 \times 60$ IP patch. Training time is the mean per run (100 epochs).

Method	Params (M)	MMACs[a]	Latency (ms)[b]	Train IP (s)	Train PU (s)
Plain CNN	0.184	41.2	0.69	4.4	17.6
SE (γ)	0.188	41.2	1.17	4.6	19.3
ECA (γ)	0.184	41.2	0.98	5.2	19.8
FC (γ+β)	0.190	41.2	1.31	4.7	19.8
SNSM (γ)	0.184	41.3	2.54	7.5	29.5
SNSM (γ+β)	0.184	41.3	2.54	7.6	30.2
HybridSN	1.743	137.4	0.71	26.2	115.3
SSFTT	0.291	34.9	1.25	7.6	–

[a] Multiply–accumulates of convolution and linear layers counted by `thop`; tensor operations such as attention products and descriptor statistics are not included. [b] Batch size 1 on a Tesla T4.

compared with spatially disjoint splits. PCA is fitted on all pixels of each scene without labels. Five seeds give only an indication of variability, and the paired differences in Table 2 are not formal significance tests. Baselines were not tuned to our protocol, and CBAM was not included in the unified comparison. Finally, the channel order of learned feature maps has no physical wavelength meaning, so "neighbourhood" refers to adjacency of feature channels, which the first convolution is free to learn.

6. Conclusion

SNSM predicts per-channel scale and shift with a small convolution over neighbouring channels' mean, variance and gradient. Under a single strict protocol it gives the best average accuracy on Indian Pines and KSC at 5% labels with about 130 extra parameters per block. Paired ablations attribute the improvement to the neighbourhood descriptor network rather than to the additive shift.

Disclosure statement

The authors report there are no competing interests to declare.

Funding

No external funding was received for this research.

Data and code availability

The datasets are publicly available (Grupo de Inteligencia Computacional (GIC) 2020; Zhong et al. 2020). Code, per-run results and the scripts that generate every table are available at `https://github.com/Devguru-codes/research_paper_code`.

Use of generative AI

Generative AI (Claude, Anthropic) was used to help write and check experiment code and to draft and edit the text. The authors reviewed all outputs and take full responsibility for the content.

References

Baumgardner, Marion F, Larry L Biehl, and David A Landgrebe. 2015. "220 Band AVIRIS Hyperspectral Image Data Set: June 12, 1992 Indian Pine Test Site 3." *Purdue University Research Repository* .

Daubechies, Ingrid. 1992. "Ten lectures on wavelets." In *CBMS-NSF regional conference series in applied mathematics*, SIAM.

Gamba, Paolo. 2004. "Pavia University and Pavia Centre datasets." *Telecommunications and Remote Sensing Laboratory, Pavia university* .

Grupo de Inteligencia Computacional (GIC). 2020. "Hyperspectral remote sensing scenes." *Universidad del Pais Vasco* .

Hong, Danfeng, Zhu Han, Jing Yao, Lianru Gao, Bing Zhang, Antonio Plaza, and Jocelyn Chanussot. 2021. "SpectralFormer: Rethinking hyperspectral image classification with transformers." *IEEE Transactions on Geoscience and Remote Sensing* 60: 1–15.

Hu, Jie, Li Shen, and Gang Sun. 2018. "Squeeze-and-excitation networks." In *Proceedings of the IEEE conference on computer vision and pattern recognition*, 7132–7141.

Hu, Wei, Yangyu Huang, Li Wei, Fan Zhang, and Hengchao Li. 2015. "Deep convolutional neural networks for hyperspectral image classification." *Journal of Sensors* 2015.

Hughes, Gordon. 1968. "On the mean accuracy of statistical pattern recognizers." *IEEE transactions on information theory* 14 (1): 55–63.

Li, Yushi, Haokui Zhang, and Qiang Shen. 2017. "Spectral-spatial classification of hyperspectral imagery with 3D convolutional neural network." *Remote Sensing* 9 (1): 67.

Loshchilov, Ilya, and Frank Hutter. 2019. "Decoupled weight decay regularization." *ICLR* .

Makantasis, Konstantinos, Konstantinos Karantzalos, Anastasios Doulamis, and Nikolaos Doulamis. 2015. "Deep supervised learning for hyperspectral data classification through convolutional neural networks." In *2015 IEEE International Geoscience and Remote Sensing Symposium (IGARSS)*, 4959–4962. IEEE.

Melgani, Farid, and Lorenzo Bruzzone. 2004. "Classification of hyperspectral remote sensing images with support vector machines." *IEEE Transactions on geoscience and remote sensing* 42 (8): 1778–1790.

Paszke, Adam, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, et al. 2019. "Pytorch: An imperative style, high-performance deep learning library." In *Advances in neural information processing systems*, 8026–8037.

Perez, Ethan, Florian Strub, Harm De Vries, Vincent Dumoulin, and Aaron Courville. 2018. "Film: Visual reasoning with a general conditioning layer." In *Proceedings of the AAAI Conference on Artificial Intelligence*, Vol. 32.

Roy, Swalpa Kumar, Gopal Krishna, Shiv Ram Dubey, and Bidyut B Chaudhuri. 2019. "HybridSN: Exploring 3-D-2-D CNN feature hierarchy for hyperspectral image classification." *IEEE Geoscience and Remote Sensing Letters* 17 (2): 277–281.

Sun, Le, Guang Zhao, Yuhui Zheng, and Zebin Wu. 2022. "Spectral-spatial feature tokenization transformer for hyperspectral image classification." *IEEE Transactions on Geoscience and Remote Sensing* 60: 1–14.

Wang, Qilong, Banggu Wu, Pengfei Zhu, Peihua Li, Wangmeng Zuo, and Qinghua Hu. 2020. "ECA-Net: Efficient channel attention for deep convolutional neural networks." In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, 11534–11542.

Woo, Sanghyun, Jongchan Park, Joon-Young Lee, and In So Kweon. 2018. "Cbam: Convolutional block attention module." In *Proceedings of the European conference on computer vision (ECCV)*, 3–19.

Zhong, Yanfei, Xin Hu, Chang Luo, Xinyu Wang, Ji Zhao, and Liangpei Zhang. 2020. "WHU-Hi: UAV-borne hyperspectral with high spatial resolution (H2) benchmark datasets and classifier for precise crop identification based on deep convolutional neural network with CRF." *Remote Sensing of Environment* 250: 112012.