

Engineering Cryptographic Software

Elliptic-curve arithmetic

Radboud University, Nijmegen, The Netherlands



Winter 2023/24

Diffie-Hellman

- ▶ Let G be a cyclic, finite, abelian Group (written additively) and let P be a generator of G

Diffie-Hellman

- ▶ Let G be a cyclic, finite, abelian Group (written additively) and let P be a generator of G
- ▶ Alice chooses random $a \in \{0, \dots, |G| - 1\}$, computes aP , sends to Bob
- ▶ Bob chooses random $b \in \{0, \dots, |G| - 1\}$, computes bP , sends to Alice

Diffie-Hellman

- ▶ Let G be a cyclic, finite, abelian Group (written additively) and let P be a generator of G
- ▶ Alice chooses random $a \in \{0, \dots, |G| - 1\}$, computes aP , sends to Bob
- ▶ Bob chooses random $b \in \{0, \dots, |G| - 1\}$, computes bP , sends to Alice
- ▶ Alice computes joint key $a(bP)$
- ▶ Bob computes joint key $b(aP)$

Diffie-Hellman

- ▶ Let G be a cyclic, finite, abelian Group (written additively) and let P be a generator of G
- ▶ Alice chooses random $a \in \{0, \dots, |G| - 1\}$, computes aP , sends to Bob
- ▶ Bob chooses random $b \in \{0, \dots, |G| - 1\}$, computes bP , sends to Alice
- ▶ Alice computes joint key $a(bP)$
- ▶ Bob computes joint key $b(aP)$
- ▶ DLP in G : given $kP \in G$ and P , find k
- ▶ Solving the DLP breaks security of Diffie-Hellman

Diffie-Hellman

- ▶ Let G be a cyclic, finite, abelian Group (written additively) and let P be a generator of G
- ▶ Alice chooses random $a \in \{0, \dots, |G| - 1\}$, computes aP , sends to Bob
- ▶ Bob chooses random $b \in \{0, \dots, |G| - 1\}$, computes bP , sends to Alice
- ▶ Alice computes joint key $a(bP)$
- ▶ Bob computes joint key $b(aP)$
- ▶ DLP in G : given $kP \in G$ and P , find k
- ▶ Solving the DLP breaks security of Diffie-Hellman

Groups with hard DLP

- ▶ Traditional answer: \mathbb{Z}_p^* with large prime-order subgroup

Diffie-Hellman

- ▶ Let G be a cyclic, finite, abelian Group (written additively) and let P be a generator of G
- ▶ Alice chooses random $a \in \{0, \dots, |G| - 1\}$, computes aP , sends to Bob
- ▶ Bob chooses random $b \in \{0, \dots, |G| - 1\}$, computes bP , sends to Alice
- ▶ Alice computes joint key $a(bP)$
- ▶ Bob computes joint key $b(aP)$
- ▶ DLP in G : given $kP \in G$ and P , find k
- ▶ Solving the DLP breaks security of Diffie-Hellman

Groups with hard DLP

- ▶ Traditional answer: \mathbb{Z}_p^* with large prime-order subgroup
- ▶ Modern answer: Elliptic curve over \mathbb{F}_q with large prime-order subgroup

Diffie-Hellman

- ▶ Let G be a cyclic, finite, abelian Group (written additively) and let P be a generator of G
- ▶ Alice chooses random $a \in \{0, \dots, |G| - 1\}$, computes aP , sends to Bob
- ▶ Bob chooses random $b \in \{0, \dots, |G| - 1\}$, computes bP , sends to Alice
- ▶ Alice computes joint key $a(bP)$
- ▶ Bob computes joint key $b(aP)$
- ▶ DLP in G : given $kP \in G$ and P , find k
- ▶ Solving the DLP breaks security of Diffie-Hellman

Groups with hard DLP

- ▶ Traditional answer: \mathbb{Z}_p^* with large prime-order subgroup
- ▶ Modern answer: Elliptic curve over \mathbb{F}_q with large prime-order subgroup
- ▶ Sophisticated answer (not in this lecture): hyperelliptic curves of genus 2

Diffie-Hellman

- ▶ Let G be a cyclic, finite, abelian Group (written additively) and let P be a generator of G
- ▶ Alice chooses random $a \in \{0, \dots, |G| - 1\}$, computes aP , sends to Bob
- ▶ Bob chooses random $b \in \{0, \dots, |G| - 1\}$, computes bP , sends to Alice
- ▶ Alice computes joint key $a(bP)$
- ▶ Bob computes joint key $b(aP)$
- ▶ DLP in G : given $kP \in G$ and P , find k
- ▶ Solving the DLP breaks security of Diffie-Hellman

Groups with hard DLP

- ▶ Traditional answer: \mathbb{Z}_p^* with large prime-order subgroup
- ▶ Modern answer: Elliptic curve over \mathbb{F}_q with large prime-order subgroup
- ▶ Sophisticated answer (not in this lecture): hyperelliptic curves of genus 2

Typical view on elliptic curves

Definition

Let K be a field and let $a_1, a_2, a_3, a_4, a_6 \in K$. Then the following equation defines an elliptic curve E :

$$E : y^2 + a_1xy + a_3y = x^3 + a_2x^2 + a_4x + a_6$$

if the discriminant Δ of E is not equal to zero. This equation is called the *Weierstrass form* of an elliptic curve.

Typical view on elliptic curves

Definition

Let K be a field and let $a_1, a_2, a_3, a_4, a_6 \in K$. Then the following equation defines an elliptic curve E :

$$E : y^2 + a_1xy + a_3y = x^3 + a_2x^2 + a_4x + a_6$$

if the discriminant Δ of E is not equal to zero. This equation is called the *Weierstrass form* of an elliptic curve.

Characteristic $\neq 2, 3$

If $\text{char}(K) \neq 2, 3$ we can use a simplified equation:

$$E : y^2 = x^3 + ax + b$$

Typical view on elliptic curves

Definition

Let K be a field and let $a_1, a_2, a_3, a_4, a_6 \in K$. Then the following equation defines an elliptic curve E :

$$E : y^2 + a_1xy + a_3y = x^3 + a_2x^2 + a_4x + a_6$$

if the discriminant Δ of E is not equal to zero. This equation is called the *Weierstrass form* of an elliptic curve.

Characteristic $\neq 2, 3$

If $\text{char}(K) \neq 2, 3$ we can use a simplified equation:

$$E : y^2 = x^3 + ax + b$$

Characteristic 2

If $\text{char}(K) = 2$ we can (usually) use a simplified equation:

$$E : y^2 + xy = x^3 + ax^2 + b$$

Rational points

Setup for cryptography

- ▶ Choose $K = \mathbb{F}_q$
- ▶ Consider the set of \mathbb{F}_q -rational points:
$$E(\mathbb{F}_q) = \{(x, y) \in \mathbb{F}_q \times \mathbb{F}_q : y^2 + a_1xy + a_3y = x^3 + a_2x^2 + a_4x + a_6\} \cup \{\mathcal{O}\}$$

Rational points

Setup for cryptography

- ▶ Choose $K = \mathbb{F}_q$
- ▶ Consider the set of \mathbb{F}_q -rational points:
$$E(\mathbb{F}_q) = \{(x, y) \in \mathbb{F}_q \times \mathbb{F}_q : y^2 + a_1xy + a_3y = x^3 + a_2x^2 + a_4x + a_6\} \cup \{\mathcal{O}\}$$
- ▶ The element \mathcal{O} is the “point at infinity”

Rational points

Setup for cryptography

- ▶ Choose $K = \mathbb{F}_q$
- ▶ Consider the set of \mathbb{F}_q -rational points:
$$E(\mathbb{F}_q) = \{(x, y) \in \mathbb{F}_q \times \mathbb{F}_q : y^2 + a_1xy + a_3y = x^3 + a_2x^2 + a_4x + a_6\} \cup \{\mathcal{O}\}$$
- ▶ The element \mathcal{O} is the “point at infinity”
- ▶ This set forms a group (together with addition law)

Rational points


Setup for cryptography

- ▶ Choose $K = \mathbb{F}_q$
- ▶ Consider the set of \mathbb{F}_q -rational points:
$$E(\mathbb{F}_q) = \{(x, y) \in \mathbb{F}_q \times \mathbb{F}_q : y^2 + a_1xy + a_3y = x^3 + a_2x^2 + a_4x + a_6\} \cup \{\mathcal{O}\}$$
- ▶ The element \mathcal{O} is the “point at infinity”
- ▶ This set forms a group (together with addition law)
- ▶ Order of this group: $|E(\mathbb{F}_q)| \approx |\mathbb{F}_q|$

The group law

Example curve: $y^2 = x^3 - x$ over \mathbb{R}

Graph of E over \mathbb{R}



The group law

Example curve: $y^2 = x^3 - x$ over \mathbb{R}


Addition of points

► Add points

$P = (-0, 9; -0, 4135)$ and

$Q = (-0, 1; 0, 3146)$

Graph of E over \mathbb{R}




The group law

Example curve: $y^2 = x^3 - x$ over \mathbb{R}

Addition of points

- ▶ Add points
 $P = (-0, 9; -0, 4135)$ and
 $Q = (-0, 1; 0, 3146)$
- ▶ Compute line through the two points

Graph of E over \mathbb{R}




The group law

Example curve: $y^2 = x^3 - x$ over \mathbb{R}

Addition of points

- ▶ Add points
 $P = (-0, 9; -0, 4135)$ and
 $Q = (-0, 1; 0, 3146)$
- ▶ Compute line through the two points
- ▶ Determine third intersection
 $T = (x_T, y_T)$ with the elliptic curve

Graph of E over \mathbb{R}




The group law

Example curve: $y^2 = x^3 - x$ over \mathbb{R}

Addition of points

- ▶ Add points
 $P = (-0, 9; -0, 4135)$ and
 $Q = (-0, 1; 0, 3146)$
- ▶ Compute line through the two points
- ▶ Determine third intersection
 $T = (x_T, y_T)$ with the elliptic curve
- ▶ Result of the addition:
 $P + Q = (x_T, -y_T)$


Graph of E over \mathbb{R}



The group law

Example curve: $y^2 = x^3 - x$ over \mathbb{R}

Graph of E over \mathbb{R}



The group law


Example curve: $y^2 = x^3 - x$ over \mathbb{R}

Point doubling

- Double the point

$$P = (-0.7, 0.5975)$$

Graph of E over \mathbb{R}




The group law

Example curve: $y^2 = x^3 - x$ over \mathbb{R}

Point doubling

- ▶ Double the point
 $P = (-0.7, 0.5975)$
- ▶ Compute the tangent on P

Graph of E over \mathbb{R}




The group law

Example curve: $y^2 = x^3 - x$ over \mathbb{R}

Point doubling

- ▶ Double the point
 $P = (-0.7, 0.5975)$
- ▶ Compute the tangent on P
- ▶ Determine second intersection
 $T = (x_T, y_T)$ with the elliptic curve

Graph of E over \mathbb{R}




The group law

Example curve: $y^2 = x^3 - x$ over \mathbb{R}

Point doubling

- ▶ Double the point
 $P = (-0.7, 0.5975)$
- ▶ Compute the tangent on P
- ▶ Determine second intersection
 $T = (x_T, y_T)$ with the elliptic curve
- ▶ Result of the addition:
 $P + Q = (x_T, -y_T)$

Graph of E over \mathbb{R}



Group law in formulas

Curve equation: $y^2 = x^3 + ax + b$

Group law in formulas

Curve equation: $y^2 = x^3 + ax + b$

Point addition

► $P = (x_P, y_P), Q = (x_Q, y_Q) \rightarrow P + Q = R = (x_R, y_R)$ with

Group law in formulas

Curve equation: $y^2 = x^3 + ax + b$

Point addition

- ▶ $P = (x_P, y_P), Q = (x_Q, y_Q) \rightarrow P + Q = R = (x_R, y_R)$ with
- ▶ $x_R = \left(\frac{y_Q - y_P}{x_Q - x_P} \right)^2 - x_P - x_Q$
- ▶ $y_R = \left(\frac{y_Q - y_P}{x_Q - x_P} \right) (x_P - x_R) - y_P$

Group law in formulas

Curve equation: $y^2 = x^3 + ax + b$

Point addition

- ▶ $P = (x_P, y_P), Q = (x_Q, y_Q) \rightarrow P + Q = R = (x_R, y_R)$ with
- ▶ $x_R = \left(\frac{y_Q - y_P}{x_Q - x_P} \right)^2 - x_P - x_Q$
- ▶ $y_R = \left(\frac{y_Q - y_P}{x_Q - x_P} \right) (x_P - x_R) - y_P$

Point doubling

- ▶ $P = (x_P, y_P), 2P = (x_R, y_R)$ with

Group law in formulas

Curve equation: $y^2 = x^3 + ax + b$

Point addition

- ▶ $P = (x_P, y_P), Q = (x_Q, y_Q) \rightarrow P + Q = R = (x_R, y_R)$ with
- ▶ $x_R = \left(\frac{y_Q - y_P}{x_Q - x_P} \right)^2 - x_P - x_Q$
- ▶ $y_R = \left(\frac{y_Q - y_P}{x_Q - x_P} \right) (x_P - x_R) - y_P$

Point doubling

- ▶ $P = (x_P, y_P), 2P = (x_R, y_R)$ with
- ▶ $x_R = \left(\frac{3x_P^2 + a}{2y_P} \right)^2 - 2x_P$
- ▶ $y_R = \left(\frac{3x_P^2 + a}{2y_P} \right) (x_P - x_R) - y_P$

More Weierstrass curve group law

- ▶ Neutral element is \mathcal{O}
- ▶ Inverse of a point (x, y) is $(x, -y)$

More Weierstrass curve group law

- ▶ Neutral element is \mathcal{O}
- ▶ Inverse of a point (x, y) is $(x, -y)$
- ▶ Note: Formulas don't work for $P + (-P)$, also don't work for \mathcal{O}
- ▶ Need to distinguish these cases!

More Weierstrass curve group law

- ▶ Neutral element is \mathcal{O}
- ▶ Inverse of a point (x, y) is $(x, -y)$
- ▶ Note: Formulas don't work for $P + (-P)$, also don't work for \mathcal{O}
- ▶ Need to distinguish these cases!
- ▶ “Uniform” addition law in Hıslıl's Ph.D. thesis, Section 5.5.2 (<http://eprints.qut.edu.au/33233/>):
 - ▶ Move special cases to other points
 - ▶ Not safe to use on arbitrary input points!

More Weierstrass curve group law

- ▶ Neutral element is \mathcal{O}
- ▶ Inverse of a point (x, y) is $(x, -y)$
- ▶ Note: Formulas don't work for $P + (-P)$, also don't work for \mathcal{O}
- ▶ Need to distinguish these cases!
- ▶ “Uniform” addition law in Hıřıl’s Ph.D. thesis, Section 5.5.2 (<http://eprints.qut.edu.au/33233/>):
 - ▶ Move special cases to other points
 - ▶ Not safe to use on arbitrary input points!
- ▶ Formulas for curves over \mathbb{F}_{2^k} look slightly different, but same special cases

Finding a suitable curve

Security requirements for ECC

- ▶ $\ell = |E(\mathbb{F}_q)|$ must have large prime-order subgroup
- ▶ For n bits of security we need $2n$ -bit prime-order subgroup

Finding a suitable curve

Security requirements for ECC

- ▶ $\ell = |E(\mathbb{F}_q)|$ must have large prime-order subgroup
- ▶ For n bits of security we need $2n$ -bit prime-order subgroup
- ▶ Impossible to transfer DLP to less secure groups:
 - ▶ ℓ must not be equal to q
 - ▶ We need $\ell \nmid p^k - 1$ for small k

Finding a suitable curve

Security requirements for ECC

- ▶ $\ell = |E(\mathbb{F}_q)|$ must have large prime-order subgroup
- ▶ For n bits of security we need $2n$ -bit prime-order subgroup
- ▶ Impossible to transfer DLP to less secure groups:
 - ▶ ℓ must not be equal to q
 - ▶ We need $\ell \nmid p^k - 1$ for small k

Finding a curve

- ▶ Fix finite field \mathbb{F}_q of suitable size
- ▶ Fix curve parameter a (quite common: $a = -3$)
- ▶ Pick curve parameter b until E fulfills desired properties
- ▶ This requires efficient “point counting”
- ▶ This requires efficient factorization or primality proving

Standardized curves

"The nice thing about standards is that you have so many to choose from."
– Andrew S. Tanenbaum

Standardized curves

“The nice thing about standards is that you have so many to choose from.”
– Andrew S. Tanenbaum

- ▶ Various standardized curves, most well-known: NIST curves:
 - ▶ Big-prime field curves with 192, 224, 256, 384, and 521 bits
 - ▶ Binary curves with 163, 233, 283, 409, and 571 bits
 - ▶ Binary Koblitz curves with 163, 233, 283, 409, and 571 bits

Standardized curves

“The nice thing about standards is that you have so many to choose from.”
– Andrew S. Tanenbaum

- ▶ Various standardized curves, most well-known: NIST curves:
 - ▶ Big-prime field curves with 192, 224, 256, 384, and 521 bits
 - ▶ Binary curves with 163, 233, 283, 409, and 571 bits
 - ▶ Binary Koblitz curves with 163, 233, 283, 409, and 571 bits
- ▶ SECG curves (Certicom), prime-field and binary curves

Standardized curves

“The nice thing about standards is that you have so many to choose from.”
– Andrew S. Tanenbaum

- ▶ Various standardized curves, most well-known: NIST curves:
 - ▶ Big-prime field curves with 192, 224, 256, 384, and 521 bits
 - ▶ Binary curves with 163, 233, 283, 409, and 571 bits
 - ▶ Binary Koblitz curves with 163, 233, 283, 409, and 571 bits
- ▶ SECG curves (Certicom), prime-field and binary curves
- ▶ Brainpool curves (BSI), only prime-field curves

Standardized curves

“The nice thing about standards is that you have so many to choose from.”
– Andrew S. Tanenbaum

- ▶ Various standardized curves, most well-known: NIST curves:
 - ▶ Big-prime field curves with 192, 224, 256, 384, and 521 bits
 - ▶ Binary curves with 163, 233, 283, 409, and 571 bits
 - ▶ Binary Koblitz curves with 163, 233, 283, 409, and 571 bits
- ▶ SECG curves (Certicom), prime-field and binary curves
- ▶ Brainpool curves (BSI), only prime-field curves
- ▶ FRP256v1 (ANSSI), one prime-field curve (256 bits)

Binary vs. big prime

Curves over big-prime fields

- ▶ Many fields of a given size \Rightarrow many curves
- ▶ Efficient in software (can use hardware multipliers)
- ▶ Less efficient in hardware

Binary vs. big prime

Curves over big-prime fields

- ▶ Many fields of a given size \Rightarrow many curves
- ▶ Efficient in software (can use hardware multipliers)
- ▶ Less efficient in hardware

Curves over binary fields

- ▶ Important for security: exponent k in \mathbb{F}_{p^k} has to be prime
- ▶ Not many fields (not that many curves)
- ▶ More efficient in hardware
- ▶ Efficient in software only on some microarchitectures
- ▶ A hell to implement securely in software on some other microarchitectures

Putting it together

- ▶ Choose security level (e.g., 128 bits)

Putting it together

- ▶ Choose security level (e.g., 128 bits)
- ▶ Decide whether you want binary or big-prime field arithmetic, let's say big prime

Putting it together

- ▶ Choose security level (e.g., 128 bits)
- ▶ Decide whether you want binary or big-prime field arithmetic, let's say big prime
- ▶ Pick corresponding standard curve, e.g., NIST-P256

Putting it together

- ▶ Choose security level (e.g., 128 bits)
- ▶ Decide whether you want binary or big-prime field arithmetic, let's say big prime
- ▶ Pick corresponding standard curve, e.g., NIST-P256
- ▶ Implement field arithmetic

Putting it together

- ▶ Choose security level (e.g., 128 bits)
- ▶ Decide whether you want binary or big-prime field arithmetic, let's say big prime
- ▶ Pick corresponding standard curve, e.g., NIST-P256
- ▶ Implement field arithmetic
- ▶ Implement ECC addition and doubling

Putting it together

- ▶ Choose security level (e.g., 128 bits)
- ▶ Decide whether you want binary or big-prime field arithmetic, let's say big prime
- ▶ Pick corresponding standard curve, e.g., NIST-P256
- ▶ Implement field arithmetic
- ▶ Implement ECC addition and doubling
- ▶ Implement scalar multiplication (Amber's lecture)

Putting it together

- ▶ Choose security level (e.g., 128 bits)
- ▶ Decide whether you want binary or big-prime field arithmetic, let's say big prime
- ▶ Pick corresponding standard curve, e.g., NIST-P256
- ▶ Implement field arithmetic
- ▶ Implement ECC addition and doubling
- ▶ Implement scalar multiplication (Amber's lecture)
- ▶ You're done with ECDH software

Putting it together

- ▶ Choose security level (e.g., 128 bits)
- ▶ Decide whether you want binary or big-prime field arithmetic, let's say big prime
- ▶ Pick corresponding standard curve, e.g., NIST-P256
- ▶ Implement field arithmetic
- ▶ Implement ECC addition and doubling
- ▶ Implement scalar multiplication (Amber's lecture)
- ▶ You're done with **BAD (!)** ECDH software

Problem I: inversions

Inversions

- ▶ Adding $P = (x_P, y_P)$ and $Q = (x_Q, y_Q)$ needs an inversion in \mathbb{F}_q
- ▶ Inversions are expensive
- ▶ Constant-time inversions are even more expensive

Problem I: inversions

Inversions

- ▶ Adding $P = (x_P, y_P)$ and $Q = (x_Q, y_Q)$ needs an inversion in \mathbb{F}_q
- ▶ Inversions are expensive
- ▶ Constant-time inversions are even more expensive

Solution: projective coordinates

- ▶ Store fractions of elements of \mathbb{F}_q , invert only once at the end

Problem I: inversions

Inversions

- ▶ Adding $P = (x_P, y_P)$ and $Q = (x_Q, y_Q)$ needs an inversion in \mathbb{F}_q
- ▶ Inversions are expensive
- ▶ Constant-time inversions are even more expensive

Solution: projective coordinates

- ▶ Store fractions of elements of \mathbb{F}_q , invert only once at the end
- ▶ Represent points in *projective coordinates*: $P = (X_P : Y_P : Z_P)$ with $x_P = X_P/Z_P$ and $y_P = Y_P/Z_P$
- ▶ The point $(1 : 1 : 0)$ is the point at infinity

Problem I: inversions

Inversions

- ▶ Adding $P = (x_P, y_P)$ and $Q = (x_Q, y_Q)$ needs an inversion in \mathbb{F}_q
- ▶ Inversions are expensive
- ▶ Constant-time inversions are even more expensive

Solution: projective coordinates

- ▶ Store fractions of elements of \mathbb{F}_q , invert only once at the end
- ▶ Represent points in *projective coordinates*: $P = (X_P : Y_P : Z_P)$ with $x_P = X_P/Z_P$ and $y_P = Y_P/Z_P$
- ▶ The point $(1 : 1 : 0)$ is the point at infinity
- ▶ Also possible: weighted projective coordinates:
 - ▶ Jacobian coordinates: $P = (X_P : Y_P : Z_P)$ with $x_P = X_P/Z_P^2$ and $y_P = Y_P/Z_P^3$
 - ▶ López-Dahab coordinates (for binary curves): $P = (X_P : Y_P : Z_P)$ with $x_P = X_P/Z_P$ and $y_P = Y_P/Z_P^2$

Problem I: inversions

Inversions

- ▶ Adding $P = (x_P, y_P)$ and $Q = (x_Q, y_Q)$ needs an inversion in \mathbb{F}_q
- ▶ Inversions are expensive
- ▶ Constant-time inversions are even more expensive

Solution: projective coordinates

- ▶ Store fractions of elements of \mathbb{F}_q , invert only once at the end
- ▶ Represent points in *projective coordinates*: $P = (X_P : Y_P : Z_P)$ with $x_P = X_P/Z_P$ and $y_P = Y_P/Z_P$
- ▶ The point $(1 : 1 : 0)$ is the point at infinity
- ▶ Also possible: weighted projective coordinates:
 - ▶ Jacobian coordinates: $P = (X_P : Y_P : Z_P)$ with $x_P = X_P/Z_P^2$ and $y_P = Y_P/Z_P^3$
 - ▶ López-Dahab coordinates (for binary curves): $P = (X_P : Y_P : Z_P)$ with $x_P = X_P/Z_P$ and $y_P = Y_P/Z_P^2$
- ▶ Important: Never send projective representation, always convert to affine!

Problem II: group-law special cases

- ▶ Addition of $P + Q$ needs to distinguish different cases:
 - ▶ If $P = \mathcal{O}$ return Q
 - ▶ Else if $Q = \mathcal{O}$ return P
 - ▶ Else if $P = Q$ call doubling routine
 - ▶ Else if $P = -Q$ return \mathcal{O}
 - ▶ Else use addition formulas

Problem II: group-law special cases

- ▶ Addition of $P + Q$ needs to distinguish different cases:
 - ▶ If $P = \mathcal{O}$ return Q
 - ▶ Else if $Q = \mathcal{O}$ return P
 - ▶ Else if $P = Q$ call doubling routine
 - ▶ Else if $P = -Q$ return \mathcal{O}
 - ▶ Else use addition formulas
- ▶ Similar for doubling P :
 - ▶ If $P = \mathcal{O}$ return P
 - ▶ Else if $y_P = 0$ return \mathcal{O}
 - ▶ Else use doubling formulas

Problem II: group-law special cases

- ▶ Addition of $P + Q$ needs to distinguish different cases:
 - ▶ If $P = \mathcal{O}$ return Q
 - ▶ Else if $Q = \mathcal{O}$ return P
 - ▶ Else if $P = Q$ call doubling routine
 - ▶ Else if $P = -Q$ return \mathcal{O}
 - ▶ Else use addition formulas
- ▶ Similar for doubling P :
 - ▶ If $P = \mathcal{O}$ return P
 - ▶ Else if $y_P = 0$ return \mathcal{O}
 - ▶ Else use doubling formulas
- ▶ Constant-time implementations of this are horrible

Problem II: group-law special cases

- ▶ Addition of $P + Q$ needs to distinguish different cases:
 - ▶ If $P = \mathcal{O}$ return Q
 - ▶ Else if $Q = \mathcal{O}$ return P
 - ▶ Else if $P = Q$ call doubling routine
 - ▶ Else if $P = -Q$ return \mathcal{O}
 - ▶ Else use addition formulas
- ▶ Similar for doubling P :
 - ▶ If $P = \mathcal{O}$ return P
 - ▶ Else if $y_P = 0$ return \mathcal{O}
 - ▶ Else use doubling formulas
- ▶ Constant-time implementations of this are horrible
- ▶ Good news: Can avoid the checks when computing $k \cdot P$ and $k < |E(\mathbb{F}_q)|$

Problem II: group-law special cases

- ▶ Addition of $P + Q$ needs to distinguish different cases:
 - ▶ If $P = \mathcal{O}$ return Q
 - ▶ Else if $Q = \mathcal{O}$ return P
 - ▶ Else if $P = Q$ call doubling routine
 - ▶ Else if $P = -Q$ return \mathcal{O}
 - ▶ Else use addition formulas
- ▶ Similar for doubling P :
 - ▶ If $P = \mathcal{O}$ return P
 - ▶ Else if $y_P = 0$ return \mathcal{O}
 - ▶ Else use doubling formulas
- ▶ Constant-time implementations of this are horrible
- ▶ Good news: Can avoid the checks when computing $k \cdot P$ and $k < |E(\mathbb{F}_q)|$
- ▶ Bad news: Side-channel countermeasures use $k > |E(\mathbb{F}_q)|$

Problem II: group-law special cases

- ▶ Addition of $P + Q$ needs to distinguish different cases:
 - ▶ If $P = \mathcal{O}$ return Q
 - ▶ Else if $Q = \mathcal{O}$ return P
 - ▶ Else if $P = Q$ call doubling routine
 - ▶ Else if $P = -Q$ return \mathcal{O}
 - ▶ Else use addition formulas
- ▶ Similar for doubling P :
 - ▶ If $P = \mathcal{O}$ return P
 - ▶ Else if $y_P = 0$ return \mathcal{O}
 - ▶ Else use doubling formulas
- ▶ Constant-time implementations of this are horrible
- ▶ Good news: Can avoid the checks when computing $k \cdot P$ and $k < |E(\mathbb{F}_q)|$
- ▶ Bad news: Side-channel countermeasures use $k > |E(\mathbb{F}_q)|$
- ▶ More bad news: Doesn't work for multi-scalar multiplication (next lecture)

Problem II: group-law special cases

- ▶ Addition of $P + Q$ needs to distinguish different cases:
 - ▶ If $P = \mathcal{O}$ return Q
 - ▶ Else if $Q = \mathcal{O}$ return P
 - ▶ Else if $P = Q$ call doubling routine
 - ▶ Else if $P = -Q$ return \mathcal{O}
 - ▶ Else use addition formulas
- ▶ Similar for doubling P :
 - ▶ If $P = \mathcal{O}$ return P
 - ▶ Else if $y_P = 0$ return \mathcal{O}
 - ▶ Else use doubling formulas
- ▶ Constant-time implementations of this are horrible
- ▶ Good news: Can avoid the checks when computing $k \cdot P$ and $k < |E(\mathbb{F}_q)|$
- ▶ Bad news: Side-channel countermeasures use $k > |E(\mathbb{F}_q)|$
- ▶ More bad news: Doesn't work for multi-scalar multiplication (next lecture)
- ▶ Baseline: *simple* implementations are likely to be wrong or insecure

Solution I: Montgomery ladder

- ▶ Use Montgomery curve: $E_M : By^2 = x^3 + Ax^2 + x$.
- ▶ Use x -coordinate-only differential addition chain (“Montgomery ladder”, next lecture)

Solution I: Montgomery ladder

- ▶ Use Montgomery curve: $E_M : By^2 = x^3 + Ax^2 + x$.
- ▶ Use x -coordinate-only differential addition chain ("Montgomery ladder", next lecture)
- ▶ Advantages:
 - ▶ Works on all inputs, no special cases
 - ▶ Very regular structure, easy to protect against timing attacks
 - ▶ Point compression/decompression for free

Solution 1: Montgomery ladder

- ▶ Use Montgomery curve: $E_M : By^2 = x^3 + Ax^2 + x$.
- ▶ Use x -coordinate-only differential addition chain ("Montgomery ladder", next lecture)
- ▶ Advantages:
 - ▶ Works on all inputs, no special cases
 - ▶ Very regular structure, easy to protect against timing attacks
 - ▶ Point compression/decompression for free
 - ▶ Easy to implement, harder to screw up in hard-to-detect ways
 - ▶ Simple implementations are likely to be correct and secure

Solution 1: Montgomery ladder

- ▶ Use Montgomery curve: $E_M : By^2 = x^3 + Ax^2 + x$.
- ▶ Use x -coordinate-only differential addition chain ("Montgomery ladder", next lecture)
- ▶ Advantages:
 - ▶ Works on all inputs, no special cases
 - ▶ Very regular structure, easy to protect against timing attacks
 - ▶ Point compression/decompression for free
 - ▶ Easy to implement, harder to screw up in hard-to-detect ways
 - ▶ Simple implementations are likely to be correct and secure
- ▶ Disadvantages:
 - ▶ Not all curves can be converted to Montgomery shape
 - ▶ Always have a cofactor of at least 4
 - ▶ Ladders on general Weierstrass curves are much less efficient

Solution 1: Montgomery ladder

- ▶ Use Montgomery curve: $E_M : By^2 = x^3 + Ax^2 + x$.
- ▶ Use x -coordinate-only differential addition chain ("Montgomery ladder", next lecture)
- ▶ Advantages:
 - ▶ Works on all inputs, no special cases
 - ▶ Very regular structure, easy to protect against timing attacks
 - ▶ Point compression/decompression for free
 - ▶ Easy to implement, harder to screw up in hard-to-detect ways
 - ▶ Simple implementations are likely to be correct and secure
- ▶ Disadvantages:
 - ▶ Not all curves can be converted to Montgomery shape
 - ▶ Always have a cofactor of at least 4
 - ▶ Ladders on general Weierstrass curves are much less efficient
 - ▶ We only get the x coordinate of the result, tricky for signatures
 - ▶ Can reconstruct y , but that involves some additional cost

Solution II: (twisted) Edwards curves

- ▶ Edwards, 2007: New form for elliptic curves ("Edwards curves")
- ▶ Bernstein, Lange, 2007: very fast addition and doubling on these curves
- ▶ Bernstein, Birkner, Joye, Lange, Peters, 2008: generalize the idea to "twisted Edwards curves"

Solution II: (twisted) Edwards curves

- ▶ Edwards, 2007: New form for elliptic curves ("Edwards curves")
- ▶ Bernstein, Lange, 2007: very fast addition and doubling on these curves
- ▶ Bernstein, Birkner, Joye, Lange, Peters, 2008: generalize the idea to "twisted Edwards curves"
- ▶ Core advantage of (twisted) Edwards curves: **complete group law**
- ▶ No need to handle special cases
- ▶ No "point at infinity" to work with

Solution II: (twisted) Edwards curves

- ▶ Edwards, 2007: New form for elliptic curves ("Edwards curves")
- ▶ Bernstein, Lange, 2007: very fast addition and doubling on these curves
- ▶ Bernstein, Birkner, Joye, Lange, Peters, 2008: generalize the idea to "twisted Edwards curves"
- ▶ Core advantage of (twisted) Edwards curves: **complete group law**
- ▶ No need to handle special cases
- ▶ No "point at infinity" to work with
- ▶ Can speed up doubling, but addition formulas work for $P + P$

Solution II: (twisted) Edwards curves

- ▶ Edwards, 2007: New form for elliptic curves (“Edwards curves”)
- ▶ Bernstein, Lange, 2007: very fast addition and doubling on these curves
- ▶ Bernstein, Birkner, Joye, Lange, Peters, 2008: generalize the idea to “twisted Edwards curves”
- ▶ Core advantage of (twisted) Edwards curves: **complete group law**
- ▶ No need to handle special cases
- ▶ No “point at infinity” to work with
- ▶ Can speed up doubling, but addition formulas work for $P + P$
- ▶ Efficient (for cryptography) transformation from Weierstrass to (twisted) Edwards only for some curves

Solution II: (twisted) Edwards curves

- ▶ Edwards, 2007: New form for elliptic curves (“Edwards curves”)
- ▶ Bernstein, Lange, 2007: very fast addition and doubling on these curves
- ▶ Bernstein, Birkner, Joye, Lange, Peters, 2008: generalize the idea to “twisted Edwards curves”
- ▶ Core advantage of (twisted) Edwards curves: **complete group law**
- ▶ No need to handle special cases
- ▶ No “point at infinity” to work with
- ▶ Can speed up doubling, but addition formulas work for $P + P$
- ▶ Efficient (for cryptography) transformation from Weierstrass to (twisted) Edwards only for some curves
- ▶ Always efficient: transformation between Montgomery curves and twisted Edwards curves


Solution II: (twisted) Edwards curves

- ▶ Edwards, 2007: New form for elliptic curves (“Edwards curves”)
- ▶ Bernstein, Lange, 2007: very fast addition and doubling on these curves
- ▶ Bernstein, Birkner, Joye, Lange, Peters, 2008: generalize the idea to “twisted Edwards curves”
- ▶ Core advantage of (twisted) Edwards curves: **complete group law**
- ▶ No need to handle special cases
- ▶ No “point at infinity” to work with
- ▶ Can speed up doubling, but addition formulas work for $P + P$
- ▶ Efficient (for cryptography) transformation from Weierstrass to (twisted) Edwards only for some curves
- ▶ Always efficient: transformation between Montgomery curves and twisted Edwards curves
- ▶ Again: simple implementations are likely to be correct and secure

Solution II: (twisted) Edwards curves

- ▶ Edwards, 2007: New form for elliptic curves (“Edwards curves”)
- ▶ Bernstein, Lange, 2007: very fast addition and doubling on these curves
- ▶ Bernstein, Birkner, Joye, Lange, Peters, 2008: generalize the idea to “twisted Edwards curves”
- ▶ Core advantage of (twisted) Edwards curves: **complete group law**
- ▶ No need to handle special cases
- ▶ No “point at infinity” to work with
- ▶ Can speed up doubling, but addition formulas work for $P + P$
- ▶ Efficient (for cryptography) transformation from Weierstrass to (twisted) Edwards only for some curves
- ▶ Always efficient: transformation between Montgomery curves and twisted Edwards curves
- ▶ Again: simple implementations are likely to be correct and secure
- ▶ Disadvantage: always have a cofactor of at least 4

So, what's the deal with the cofactor?

 **MONERO**

[Forum Funding System](#) [Vulnerability Response](#) [The Monero Project](#) [English](#)

[Get Started](#) [Downloads](#) [Recent News](#) [Community](#) [Resources](#)

Disclosure of a Major Bug in CryptoNote Based Currencies

Posted by Iug1111 and Riccardo "fluffypony" Spagni
May 17, 2017

Overview

In Monero we've discovered and patched a critical bug that affects all CryptoNote-based cryptocurrencies, and allows for the creation of an unlimited number of coins in a way that is undetectable to an observer unless they know about the fatal flaw and can search for it.

Recent Posts

[Logs for the Community Meeting Held on 2019-02-16](#)

[Logs for the Community Meeting Held on 2019-02-02](#)

[Monero Adds Blockchain Pruning and Improves Transaction Efficiency](#)

[Logs for the Community Meeting Held on 2019-01-19](#)

So, what's the deal with the cofactor?

- ▶ Protocols need to be careful to avoid subgroup attacks
- ▶ Monero screwed this up, which allowed double-spending
- ▶ Elegant solution: “Ristretto” encoding by Hamburg, see: <https://github.com/otrv4/libgoldilocks>

Solution III: Complete group law on Weierstrass curves

- ▶ Bosma, Lenstra, 1995: complete group law for Weierstrass curves
- ▶ Problem: Extremely inefficient

Solution III: Complete group law on Weierstrass curves

- ▶ Bosma, Lenstra, 1995: complete group law for Weierstrass curves
- ▶ Problem: Extremely inefficient
- ▶ Renes, Costello, Batina, 2016: Much faster complete group law for Weierstrass curves
- ▶ Less efficient than (twisted) Edwards
- ▶ Overhead quite architecture-dependent (Schwabe, Sprenkels, 2019)
- ▶ Covers all curves

Problem III: Wrong-curve attacks

ECDH attack scenario

- ▶ Alice sends point on different (insecure) curve with small subgroup
- ▶ Bob computes “shared key” in that small subgroup
- ▶ Alice learns “shared key” through brute force
- ▶ Alice learns Bob’s secret scalar modulo the order of the small subgroup

Problem III: Wrong-curve attacks

ECDH attack scenario

- ▶ Alice sends point on different (insecure) curve with small subgroup
- ▶ Bob computes “shared key” in that small subgroup
- ▶ Alice learns “shared key” through brute force
- ▶ Alice learns Bob’s secret scalar modulo the order of the small subgroup

Countermeasures

- ▶ Check that input point is on the curve (functional tests will miss this!)

Problem III: Wrong-curve attacks

ECDH attack scenario

- ▶ Alice sends point on different (insecure) curve with small subgroup
- ▶ Bob computes “shared key” in that small subgroup
- ▶ Alice learns “shared key” through brute force
- ▶ Alice learns Bob’s secret scalar modulo the order of the small subgroup

Countermeasures

- ▶ Check that input point is on the curve (functional tests will miss this!)
- ▶ Send compressed points $(x, \text{parity}(y))$; decompression returns (x, y) on the curve or fails

Problem III: Wrong-curve attacks

ECDH attack scenario

- ▶ Alice sends point on different (insecure) curve with small subgroup
- ▶ Bob computes “shared key” in that small subgroup
- ▶ Alice learns “shared key” through brute force
- ▶ Alice learns Bob’s secret scalar modulo the order of the small subgroup

Countermeasures

- ▶ Check that input point is on the curve (functional tests will miss this!)
- ▶ Send compressed points $(x, \text{parity}(y))$; decompression returns (x, y) on the curve or fails
- ▶ Send only x (Montgomery ladder); but: x could still be on the “twist” of E
- ▶ Make sure that the twist is also secure (“twist security”)

Problem IV: Backdoors in standards?

"I no longer trust the [NIST Elliptic Curves] constants. I believe the NSA has manipulated them through their relationships with industry."
– Bruce Schneier, 2013.

Problem IV: Backdoors in standards?

"[I] no longer trust the [NIST Elliptic Curves] constants. I believe the NSA has manipulated them through their relationships with industry."
– Bruce Schneier, 2013.

- ▶ It is pretty clear that NSA put a backdoor in Dual_EC_DRBG
- ▶ Constants of NIST curves have been obtained by hashing random values
- ▶ No-backdoor claim: We know the preimages

Problem IV: Backdoors in standards?

"[I] no longer trust the [NIST Elliptic Curves] constants. I believe the NSA has manipulated them through their relationships with industry."
– Bruce Schneier, 2013.

- ▶ It is pretty clear that NSA put a backdoor in Dual_EC_DRBG
- ▶ Constants of NIST curves have been obtained by hashing random values
- ▶ No-backdoor claim: We know the preimages
- ▶ Possible attack if you know a class of vulnerable curves: Generate random seeds until you have found a vulnerable (and seemingly secure) curve

Problem IV: Backdoors in standards?

"[I] no longer trust the [NIST Elliptic Curves] constants. I believe the NSA has manipulated them through their relationships with industry."
– Bruce Schneier, 2013.

- ▶ It is pretty clear that NSA put a backdoor in Dual_EC_DRBG
- ▶ Constants of NIST curves have been obtained by hashing random values
- ▶ No-backdoor claim: We know the preimages
- ▶ Possible attack if you know a class of vulnerable curves: Generate random seeds until you have found a vulnerable (and seemingly secure) curve
- ▶ Fact: There are no known insecurities of NIST curves

Problem IV: Backdoors in standards?

"[I] no longer trust the [NIST Elliptic Curves] constants. I believe the NSA has manipulated them through their relationships with industry."
– Bruce Schneier, 2013.

- ▶ It is pretty clear that NSA put a backdoor in Dual_EC_DRBG
- ▶ Constants of NIST curves have been obtained by hashing random values
- ▶ No-backdoor claim: We know the preimages
- ▶ Possible attack if you know a class of vulnerable curves: Generate random seeds until you have found a vulnerable (and seemingly secure) curve
- ▶ Fact: There are no known insecurities of NIST curves
- ▶ Fact: There is no proof that there are no intentional vulnerabilities in NIST curves

Problem IV: Backdoors in standards?

"[I] no longer trust the [NIST Elliptic Curves] constants. I believe the NSA has manipulated them through their relationships with industry."
– Bruce Schneier, 2013.

- ▶ It is pretty clear that NSA put a backdoor in Dual_EC_DRBG
- ▶ Constants of NIST curves have been obtained by hashing random values
- ▶ No-backdoor claim: We know the preimages
- ▶ Possible attack if you know a class of vulnerable curves: Generate random seeds until you have found a vulnerable (and seemingly secure) curve
- ▶ Fact: There are no known insecurities of NIST curves
- ▶ Fact: There is no proof that there are no intentional vulnerabilities in NIST curves
- ▶ For more details, see [BADA55 elliptic curves](#)

Choosing a safe curve

Overview of various elliptic curves and thorough security analysis by Bernstein and Lange:

<https://safecurves.cr.yp.to>

(doesn't list cofactor-1 curves, so best to combine with Ristretto)

Point representation and arithmetic

Collection of elliptic-curve shapes, point representations and group-operation formulas by Bernstein and Lange:

<https://www.hyperelliptic.org/EFD/>