

Q.1 Read from a terminal using scanf function and print using printf function.

```
#include<stdio.h>

int main( )
{
    char str[40];

    printf("Enter text : \n");

    scanf("%s", str);

    printf("\n");

    printf("Entered text = %s", str);

}
```

```
Enter text Devi Prasanna Mishra
Entered text = Devi
```

Q2. Read lines of text from a terminal using fgets function and print using puts function.

```
#include <stdio.h>

int main()
{
    int b;

    int size = 10;

    char *string;

    printf ("Please enter a string: ");

    string = (char *) malloc (size);

    b = getline (&string, &size, stdin); //stdin- standard input

    if (b == -1)
    {
        puts ("ERROR!");
    }
}
```

```

else
{
    puts ("You entered the following string:");
    puts (string);
}

return 0;
}

```

```

Please enter a string: Devi Prasanna Mishra
You entered the following string:
Devi Prasanna Mishra

```

Q3. Convert

- a. Upper case to Lower case
- b. Lower case to Upper case
- c. Toggle case
- d. Sentence case.

a.

```

#include<stdio.h>

#include<string.h>

int main()
{
    char str[25];

    int i;

    printf("Enter the string: ");

    scanf("%s",str);

    for(i=0;i<=strlen(str);i++)
    {
        if(str[i]>=65&&str[i]<=90) // A-Z ASCII value(65-90)

            str[i]=str[i]+32; // Upper case+32= lower case
    }
}

```

```
}

printf("\nLower Case String is: %s",str);

return 0;

}
```

```
Enter the string: DEVI
Lower Case String is: devi
```

b.

```
#include<stdio.h>

#include<string.h>

int main()

{

    char str[25];

    int i;

    printf("Enter the string:");

    scanf("%s",str);

    for(i=0;i<=strlen(str);i++)

    {

        if(str[i]>=97&&str[i]<=122) //(a-z) ASCII value 97-122

            str[i]=str[i]-32; //lower case-32 = Upper case

    }

    printf("\nUpper Case String is: %s",str);

    return 0;

}
```

```
Enter the string:devi
Upper Case String is: DEVI
```

C.

```
#include <stdio.h>

#include <string.h>

int main()
{
    char Str1[100];

    int i;

    printf("\n Please Enter any String to Toggle : ");

    gets(Str1);

    for (i = 0; Str1[i]!='\0'; i++)
    {
        if(Str1[i] >= 'a' && Str1[i] <= 'z')
        {
            Str1[i]=Str1[i]-32;
        }
        else if(Str1[i]>= 'A' && Str1[i]<= 'Z')
        {
            Str1[i]=Str1[i]+32;
        }
    }

    printf("\n The Given String after Toggling Case of all Characters = %s", Str1);

    return 0;
}
```

Please Enter any String to Toggle : devi Prasanna

The Given String after Toggling Case of all Characters = DEVI pRASANNA

d.

```
#include <stdio.h>
```

```
#include <string.h>
```

```
int main()
```

```
{
```

```
    char str[50]={0};
```

```
    int length=0,i=0,j=0,k=0;
```

```
    printf("\nEnter the string : ");
```

```
    gets(str);
```

```
    length = strlen(str);
```

```
    for(i=0;i<length;i++)
```

```
    {
```

```
        if( (i==0) && (str[i]>='a' && str[i]<='z'))
```

```
        {
```

```
            str[i] = str[i] - 32;
```

```
        }
```

```
        else if(str[i]=='.')

```

```
        {
```

```
            if(string[i+1] == ' ')

```

```
            {
```

```
                if(str[i+2]>='a' && str[i+2]<='z')

```

```
                {
```

```
                    str[i+2] = str[i+2] - 32;
```

```
                }
```

```
            }
```

```
            else

```

```
            {
```

```

        if(str[i+1]>='a' && str[i+1]<='z')
        {
            str[i+1] = str[i+1] - 32;
        }
    }

}

printf("Final string is : %s",str);
}

```

```

Enter the string : devi mishra
Final string is : Devi mishra

```

Q4. Perform string Concatenation(With and without string handling functions).

Without:

```

#include <stdio.h>

int main()
{
    char str1[50], str2[50],i,j;

    printf("Enter first string: ");

    scanf("%s",str1);

    printf("Enter second string: ");

    scanf("%s",str2);

    for(i=0; str1[i]!='\0'; ++i);

    for(j=0; str2[j]!='\0'; ++j, ++i)

    {
        str1[i]=str2[j];
    }
}

```

```
str1[i]='\0';  
  
printf("Output: %s",str1);  
  
return 0;  
  
}
```

```
Enter first string: Devi  
Enter second string: prasanna  
Output: Deviprasanna
```

With:

```
#include <stdio.h>  
  
#include<string.h>  
  
int main()  
{  
  
    char s1[20];  
  
    char s2[20];  
  
    printf("Enter the first string : ");  
  
    scanf("%s", s1);  
  
    printf("\nEnter the second string :");  
  
    scanf("%s",s2);  
  
    strcat(s1,s2);  
  
    printf("The concatenated string is : %s",s1);  
  
    return 0;  
  
}
```

```
Enter the first string : devi  
Enter the second string :Prasanna  
The concatenated string is : deviPrasanna
```

Q5. Perform String Reversal (With and without string handling function)

Without:

```
#include<stdio.h>

#include<conio.h>

int main()

{

    int i, j, k;

    char str[100];

    char rev[100];

    printf("Enter a string:\t");

    scanf("%s",str);

    printf("The original string is %s\n", str);

    for(i = 0; str[i] != '\0'; i++);

    {

        k = i-1;

    }

    for(j = 0; j <= i-1; j++)

    {

        rev[j] = str[k];

        k--;

    }

    printf("The reverse string is %s\n", rev);

    return 0;

}
```

```
Enter a string: devi
The original string is devi
The reverse string is ived
```

With:


```

#include<stdio.h>

#include<string.h>

int main()
{
    char name[30] = "Hello";

    printf("String before strrev: %s\n",name);

    printf("String after strrev: %s",strrev(name));

    return 0;
}

```

Q6. Perform Substring Extraction (With and Without String Handling Functions)

Without:

```

#include <stdio.h>

int main()
{
    char string[1000], sub[1000];

    int position, length, c = 0;

    printf("Input a string\n");

    gets(string);

    printf("Enter the position and length of substring\n");

    scanf("%d%d", &position, &length);

    while (c < length) {
        sub[c] = string[position+c-1];

        c++;
    }

    sub[c] = '\0';

    printf("Required substring is \"%s\"\n", sub);
}

```

```
return 0;

}
```

```
Input a string
Devi Prasanna
Mishra
Enter the position and length of substring
2
1
Required substring is "e"
```

With:

```
#include <stdio.h>

#include <string.h>

int main()

{

const char* lineConst = "Devi \"Prasanna \" Mishra";

char line[256];

char *subString;

strcpy(line, lineConst);

subString = strtok(line, "\"");

subString=strtok(NULL, "\"");

printf("the thing in between quotes is '%s'\n", subString);

return 0;

}
```

```
the thing in between quotes is 'Prasanna'
```

Q7. Copy one string into another and count the no of elements copied. (With and without string handling function).

Without:

```
#include <stdio.h>

int main()

{
```

```

char s1[100], s2[100], i;

int count;

printf("Enter string s1: ");

fgets(s1, sizeof(s1), stdin);

for (i = 0; s1[i] != '\0'; ++i) {

    s2[i] = s1[i];

    count++;

}

s2[i] = '\0';

printf("String s2: %s", s2);

printf("Number of string copied:%d",count);

return 0;

}

```

O/p:

Enter string s1: Devi PM

String s2: Devi PM

Number of string copied: 6

With:

```

#include<stdio.h>

#include<string.h>

int main()

{

    char c[100];

    char o[100];

    printf("\n\nEnter the string: ");

    gets(o);

    strcpy(c,o);

```

```
printf("\n\nThe copied string is: %s\n\n", c);  
  
return 0;  
  
}
```

O/p

Enter the string: Devi P

The copied string is: Devi P

Q8. Read a string and prints if it is a palindrome or not.

```
#include <stdio.h>  
  
#include <string.h>  
  
int main()  
{  
  
    char string1[20];  
  
    int i, length;  
  
    int flag = 0;  
  
    printf("Enter a string:");  
  
    scanf("%s", string1);  
  
    length = strlen(string1);  
  
    for(i=0;i < length ;i++)  
    {  
  
        if(string1[i] != string1[length-i-1])  
  
        {  
  
            flag = 1;  
  
            break;  
  
        }  
  
    }  
  
    if(flag)  
  
    {
```

```

        printf("%s is not a palindrome", string1);
    }
    else
    {
        printf("%s is a palindrome", string1);
    }

    return 0;
}

```

O/p:

Enter a string: It's Devi

It's Devi is not a palindrome

Q9. Read a line of text and count all occurrences of particular word.

```

#include<stdio.h>

#include<string.h>

int main()
{
    int strln,wordln,i,j,k,flag,count=0;

    char str[200],word[20];

    printf("Enter line of text:n");

    gets(str);

    printf("Enter the word to count:n");

    scanf("%s",word);

    strln=strlen(str);

    wordln=strlen(word);

    for(i=0;i<strln;i++)
    {
        if(str[i]==word[0]&&((str[i-1]!=' ' || i==0)&&(str[i+wordln]!=' ' || str[i+wordln]==")))

```

```

{
    for(flag=0,k=i+1,j=1;j<wordln;j++,k++)
    {
        if(str[k]==word[j])
        {
            flag++;
        }
    }
    if(flag==wordln-1)
    {
        count++;
    }
}

printf("Number of occurence of '%s' = %dn",word,count);

return 0;
}

```

Enter line of text:ndevvii Enter the word to count:nprasanna Number of occurence of 'prasanna' = 0n

Q10. Read a string and rewrite it in the alphabetical order.

```

#include <stdio.h>

#include <string.h>

int main ()
{
    char string[100];

    printf("\n\t Enter the string : ");

    scanf("%s",string);

```

```

char temp;

int i, j;

int n = strlen(string);

for (i = 0; i < n-1; i++) {
    for (j = i+1; j < n; j++) {
        if (string[i] > string[j]) {
            temp = string[i];
            string[i] = string[j];
            string[j] = temp;
        }
    }
}

printf("The sorted string is : %s", string);

return 0;
}

```

Enter the string : devi p mishra
The sorted string is : deiv

Q11. Print the words ending with letter S.

```

#include <stdio.h>

#include <string.h>

char str[100];

int main()
{
    int i, t, j, len;

    printf("Enter a string : ");

    scanf("%[^\n]s", str);

    len = strlen(str);

```

```

str[len] = ' ';
for (t = 0, i = 0; i < strlen(str); i++)
{
    if ((str[i] == ' ') && (str[i - 1] == 's'))
    {
        for (j = t; j < i; j++)
            printf("%c", str[j]);

        t = i + 1;

        printf("\n");
    }
    else
    {
        if (str[i] == ' ')
        {
            t = i + 1;
        }
    }
}

return 0;
}

```

Enter a string : devi mishra devi

Q12. Delete all repeated words in the line of text.

```
#include <stdio.h>
```

```
#include <string.h>
```

```
#define SIZE 500
```

```
void duplicateRemover(char *, const int);
```

```
int main(void)
```



```

{
    char someString[SIZE];

    puts("Enter text: ");

    fgets(someString, SIZE, stdin);

    someString[strcspn(someString, "\n")] = 0;

    printf("\n%s", "Text without repeated words: ");

    duplicateRemover(someString, SIZE);
}

void duplicateRemover(char *arrayPtr, const int sizeP)
{
    char wordTable[sizeP][sizeP], *tokPtr;

    size_t i, j, k, l;

    tokPtr = strtok(arrayPtr, " ");

    strcpy(wordTable[0], tokPtr);

    for(i = 1; (tokPtr = strtok(NULL, " ")) != NULL; i++)

        strcpy(wordTable[i], tokPtr);

    for(j = 0; j <= i; j++)

        for(k = j + 1; k <= i; k++)

            if(strcmp(wordTable[j], wordTable[k]) == 0)

                {

                    for(l = k; l < i; l++)

                        strcpy(wordTable[l], wordTable[l + 1]);

                    k = j;

                    i--;

                }

    for(l = 0; l <= i; l++)

        printf("%s ", wordTable[l]);

```

}

Enter text:

devi pm pm

Text without repeated words: devi pm