

COSC 350 System Software Lab#4

(submission due day: 3/3/21)

(submit by email to cosc350@gmail.com)

How to submit

- For each program, you need write detailed comments for each statement.
- You need demonstrate each task in front of instructor during the next lab hours.

Task #1. In Task#8 in Lab3, you wrote a program to encode a file with character to a file with ASCII code number. Write decoding program which covert output of Task#8 in Lab3 to original input file.

Task #2: Write a C main function that takes one command-line argument, the name of an input file. The input file contains exactly one integer spread out over a single line of up to 80 characters. For example, the integer 3579 is embedded in the line az3mqrm5t?7!z*&qmzt9v. Your program uses system calls to do the following:

- a. open and read the input file, accumulating the discovered digit characters into a character array (string).
- b. Convert the string to an integer./taskdr (do not use atoi function).
- c. Add 10 to the integer
- d. convert the sum back to a string (using function convIntToStr)
- e. make a system call to write the string to standard output.

```

/*****
Convert integer to string
Params: x is the int to be converted,
        str is the string into which to write
Returns: length of the string
*****/

int convIntToStr(char * str, int x)
{
    sprintf(str, "%d", x);
    return (strlen(str));
}

```

```
/* Returns a non-zero value if character c is a digit, zero otherwise. */
int isdigit(int c)
```


You need include five headers <unistd.h>, <fcntl.h>, <ctype.h>, <stdio.h> and <string.h> for read write open system calls and sprint return strlen library functions.

Task #3. A **palindrome** is a word, phrase, number or other sequence of units that can be read the same way in either direction. Write a C-function **int palind(int fd1, int fd2)** that takes two independent file descriptors fd1 and fd2 that are already opened to the same file. The function palind() uses lseek to scan the file and returns 1 if the file contains a palindrome (reads the same forward and reverse) and 0 if not. You may assume that the file is well-formed and contains just lower-case alphabetic characters on a single line. You also need write a main function to test your palind() function works properly. The main function accept a file name as a argument. The main() function open the file once and create duplicate file descriptor. And call the function palind() to check whether the file contains palindrome or not.


Task #4.1. Write a simple program called hello.c and compile it and create executable file named hello.

Write a C program for sequence of following task.

- By using system call, build following directory structure



- By using system calls, copy hello file under ~/Dir2/Dir21/
- By using system calls, make a symbolic link named toDir21 to directory Dir21
- By using system calls, make a symbolic link named toHello to executable file ~/Dir21/hello



Task#4.2. (Test for Task #4.1) Execute hello by using symbolic link toHello. Try to delete a file, make directory by using symbolic link toDir21.

Task 5. Write your own mv named MyMv

By using bash command mv, you can move a file from current directory to another directory. Write your own mv called MyMv by using system calls link() and unlink(). Your program named **MyMv** can move a file from a current directory to a directory. Your program receives two arguments: file name and path to a directory where the file need to move, or file name and path to directory with a file name.

If the second argument is a directory, move a file to the directory. If the second argument is not a directory, move file to directory as a file name.

Ex)

- Move a file **foo** to under directory **~/separk/cosc350**
 - `./MyMv foo ~/separk/cosc350`
- Move a file **foo** to under directory **~/separk/cosc350** named **abc** if there is no directory named abc
 - `./MyMv foo ~/separk/cosc350/abc`
- Move a file foo to under directory **~/separk/cosc350** named **foo** if there is no directory named foo
 - `./MyMv foo ~/separk/cosc350/foo`