NAME	JACOB JOHN
REGISTER NO.	16BCE2205
E-MAIL	jacob.john2016@vitstudent.ac.in
COURSE	Java Programming

LAB ASSESSMENT #2

Exception Handling

Read the Register Number and Mobile Number of a student. If the Register Number does not contain exactly 9 characters or if the Mobile Number does not contain exactly 10 characters, throw an IllegalArgumentException. If the Mobile Number contains any character other than a digit, raise a NumberFormatException. If the Register Number contains any character other than digits and alphabets, throw a NoSuchElementException. If they are valid, print the message 'valid' else 'invalid'


Code

```
import java.util.NoSuchElementException;
import java.util.Scanner;
import java.util.regex.Matcher;
import java.util.regex.Pattern;
public class ExcepHandle{
   static void validate(String r, String n){
        if(r.length() != 9){
            System.out.println("Invalid");
            throw new IllegalArgumentException("Register Number does not contain
        if(n.length() != 10){
            System.out.println("Invalid");
            throw new IllegalArgumentException("Mobile Number does not contain
        String pattern = "^[6|7|8|9]{1}\\d{9}";
        Pattern a = Pattern.compile(pattern);
       Matcher m1 = a.matcher(n);
        if(!m1.find()){
            throw new NumberFormatException("Mobile Number cannot contain any
        String pattern2 = "^[1-9]{2}[A-Z]{3}[0-9]{4}$";
        Pattern b = Pattern.compile(pattern2);
       Matcher m2 = b.matcher(r);
        if(!m2.find()){
            throw new NoSuchElementException("Registration Number cannot contain
iny character other than digits and alphabets'
```

```
}

public static void main(String args[]){
    Scanner sc = new Scanner(System.in);
    String reg = sc.nextLine();
    String no = sc.nextLine();
    sc.close();
    validate(reg, no);
    System.out.println("Valid");
}
```

Output



Multithreading

Three students A, B and C of B.Tech- II year contest for the PR election. With the total strength of 240 students in II year, simulate the vote casting by generating 240 random numbers (1 for student A, 2 for B and 3 for C) and store them in an array. Create four threads to equally share the task of counting the number of votes cast for all the three candidates. Use synchronized method or synchronized block to update the three count variables. The main thread should receive the final vote count for all three contestants and hence decide the PR based on the values received.


Code

```
import elections.Vote;
import elections.count;
import java.util.Vector;
public class MultiThreadVote {
   public static void main(String[] args) {
       Vector votevec = new Vector(240); // creating a vote array for 240
       Vote a = new Vote(1, votevec);
       a.start();
       Vote b = new Vote(2, votevec);
       b.start();
       Vote c = new Vote(3, votevec);
       c.start();
        try{
            a.join();
           b.join();
            c.join();
            System.out.println("Voting has ended!");
       }catch(Exception e){System.out.println(e);}
        count ac = new count(1, votevec);
        count bc = new count(2, votevec);
        count cc = new count(3, votevec);
       ac.start();
       bc.start();
       cc.start();
        try{
            ac.join();
           bc.join();
            cc.join();
            System.out.println("Counting has ended!");
       }catch(Exception e){System.out.println(e);}
        int bv = bc.count;
        int cv = cc.count;
```

```
System.out.println("elections.Vote Vector:" + "\n" + votevec);
System.out.println(av + " votes for A");
System.out.println(bv + " votes for B");
System.out.println(cv + " votes for C");

if(av >= bv && av >= cv){
    if(av == bv || av == cv)
        System.out.println("Tie in elections!");
    else
        System.out.println("A has won the elections!");
}
else if(bv >= av && bv >= cv){
    if(av == bv || bv == cv)
        System.out.println("Tie in elections!");
    else
        System.out.println("B has won the elections!");
}
else if(cv >= av && cv >= bv){
    if(cv == bv || cv == av)
        System.out.println("Tie in elections!");
    else
        System.out.println("Tie in elections!");
    else
        System.out.println("Tie in elections!");
}
```

Output



File Handling

Define a class 'Donor' to store the below mentioned details of a blood donor. Name, age, Address, Contact number, blood group, date of last donation Create 'n' objects of this class for all the regular donors at Vellore. Write these objects to a file. Read these objects from the file and display only those donors' details whose blood group is 'A+ve' and had not donated for the recent six months.

Code

```
import java.io.*;
import java.nio.file.Files;
import java.nio.file.NoSuchFileException;
import java.nio.file.Paths;
import java.text.ParseException;
import java.text.SimpleDateFormat;
import org.joda.time.LocalDate;
import org.joda.time.DateTime;
import org.joda.time.Period;
import java.util.Date;
import java.util.Scanner;
import java.util.regex.Matcher;
import java.util.regex.Pattern;
public class Donor {
    String name,addr,contact,bldgrp;
   Date date;
    public static void main(String[] args) throws IOException{
        SimpleDateFormat ft = new SimpleDateFormat("MM-dd-yyyy");
        String temp;
        String pattern = "[A|B|O|AB][+|-]";
       Matcher m;
        Pattern r = Pattern.compile(pattern);
        try{
            Files.deleteIfExists(Paths.get("donations.txt"));
        catch(NoSuchFileException e)
            System.out.println("No such file/directory exists");
        catch(IOException e)
            System.out.println("Invalid permissions.");
        System.out.println("Deletion successful.");
        Scanner sc = new Scanner(System. in);
        System.out.print("Enter number of donors: ");
        n = sc.nextInt();
        sc.nextLine();
        Donor arr[] = new Donor[n];
                                                                    // creating
irray of n donors
```

```
ByteArrayOutputStream outputstream = new ByteArrayOutputStream();
FileOutputStream fos = new FileOutputStream("donations.txt");
for(i = 0; i < n; i++){</pre>
    arr[i] = new Donor();
    System.out.print("Name: ");
    arr[i].name = sc.nextLine();
    System.out.print("Address: ");
    arr[i].addr = sc.nextLine();
System.out.print("Contact: ");
    arr[i].contact = sc.nextLine();
    arr[i].bldgrp = "";
    m = r.matcher(arr[i].bldgrp);
    while(!m.find()){
        System.out.print("Blood Group: ");
        arr[i].bldgrp = sc.nextLine();
        m = r.matcher(arr[i].bldgrp);
    boolean flag = false;
    while(!flag){
        System.out.print("Date: ");
        temp = sc.nextLine();
             arr[i].date = ft.parse(temp);
             flag = true;
        } catch (ParseException e) {
             flag = false;
             System.out.println("Unparseable using " + ft);
    outputstream.write(("Donor " + (i+1) + "\n").getBytes());
    outputstream.write("-----\n".getBytes());
    outputstream.write("Name: ".getBytes());
    outputstream.write(arr[i].name.getBytes());
    outputstream.write("\n".getBytes());
outputstream.write("Address: ".getBytes());
    outputstream.write(arr[i].addr.getBytes());
    outputstream.write("\n".getBytes());
    outputstream.write("Contact: ".getBytes());
    outputstream.write(arr[i].contact.getBytes());
    outputstream.write("\n".getBytes());
outputstream.write("Blood Group: ".getBytes());
    outputstream.write(arr[i].bldgrp.getBytes());
    outputstream.write("\n".getBytes());
    outputstream.write("Date: ".getBytes());
    outputstream.write(arr[i].date.toString().getBytes());
    outputstream.write("\n".getBytes());
    outputstream.write("\n".getBytes());
```

```
byte c[] = outputstream.toByteArray();
        fos.write(c);
array to file
        fos.close();
        // reading data from file
        byte[] fileContent = Files.readAllBytes(Paths.get("donations.txt"));
        String fileInput = new String(fileContent);
        String[] content = fileInput.split("\n");
        Date dt2:
        String[] fileDate, fileGrp;
        SimpleDateFormat ft2 = new SimpleDateFormat("E MMM dd HH:mm:ss z yyyy");
        LocalDate current = LocalDate.now();
        for(i = 5; i < content.length; i += 8){</pre>
            fileGrp = content[i].split(": ");
            fileDate = content[i+1].split(": ");
            System.out.println("\n" + "Donors who haven't donated in 6 months and
\"A+\"" + "\n");
            try {
                dt2 = ft2.parse(fileDate[1]);
                DateTime dt3 = new DateTime(dt2);
                LocalDate dt1 = new LocalDate(dt3);
                Period p = new Period(dt1, current);
                // if more than 6 months and blood group is A+, print details
                if((p.getMonths() > 6 | p.getYears() >= 1) &&
fileGrp[1].equals("A+"))
                     System.out.println(content[i-3]); // name
                     System.out.println(content[i-2]); // address
                     System.out.println(content[i-1]); // contact
                     System.out.println(content[i]); // blood group
System.out.println(content[i+1]); // date
                     System.out.println("\n");
            } catch (ParseException e) {
                e.printStackTrace();
```

Output

