

Amazon Translate API Reference



Amazon Translate API Reference:

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

\maz	zon Translate API Reference	1
Ac	tions	. 1
	CreateParallelData	3
	DeleteParallelData	8
	DeleteTerminology	11
	DescribeTextTranslationJob	13
	GetParallelData	16
	GetTerminology	20
	ImportTerminology	24
	ListLanguages	29
	ListParallelData	33
	ListTagsForResource	37
	ListTerminologies	40
	ListTextTranslationJobs	44
	StartTextTranslationJob	48
	StopTextTranslationJob	55
	TagResource	58
	TranslateDocument	61
	TranslateText	67
	UntagResource	73
	UpdateParallelData	76
Da	ta Types	80
	AppliedTerminology	82
	Document	83
	EncryptionKey	85
	InputDataConfig	86
	JobDetails	88
	Language	89
	OutputDataConfig	90
	ParallelDataConfig	91
	ParallelDataDataLocation	92
	ParallelDataProperties	94
	Tag	98
	Term	99
	TerminologyData	00

TerminologyDataLocation	102
TerminologyProperties	104
TextTranslationJobFilter	108
TextTranslationJobProperties	110
TranslatedDocument	114
TranslationSettings	115
Common Parameters	
Common Errors	

Amazon Translate API Reference

This document provides detailed information about the Amazon Translate API actions and their parameters.

For information about the IAM access control permissions you need to use this API, see <u>Using IAM</u> identity policies to manage permissions.

You can use <u>AWS SDKs</u> to access Amazon Translate APIs using your favorite programming language. The SDKs automatically perform useful tasks for you, such as:

- Cryptographically sign your service requests
- Retry requests
- · Handle error responses

The following resources provide additional information about the Amazon Translate API.

- Amazon Web Services General Reference
 - Amazon Translate Endpoints for each region.
- AWS Command Line Interface
 - Amazon Translate CLI commands.

Topics

- Actions
- Data Types
- Common Parameters
- Common Errors

Actions

The following actions are supported:

- CreateParallelData
- DeleteParallelData
- DeleteTerminology

Actions 1

- DescribeTextTranslationJob
- GetParallelData
- GetTerminology
- ImportTerminology
- ListLanguages
- ListParallelData
- ListTagsForResource
- ListTerminologies
- ListTextTranslationJobs
- StartTextTranslationJob
- StopTextTranslationJob
- TagResource
- TranslateDocument
- TranslateText
- <u>UntagResource</u>
- UpdateParallelData

Actions 2

CreateParallelData

Creates a parallel data resource in Amazon Translate by importing an input file from Amazon S3. Parallel data files contain examples that show how you want segments of text to be translated. By adding parallel data, you can influence the style, tone, and word choice in your translation output.

Request Syntax

```
{
   "ClientToken": "string",
   "Description": "string",
   "EncryptionKey": {
      "Id": "string",
      "Type": "string"
   },
   "Name": "string",
   "ParallelDataConfig": {
      "Format": "string",
      "S3Uri": "string"
   },
   "Tags": [
      {
         "Key": "string",
         "Value": "string"
   ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see <u>Common Parameters</u>.

The request accepts the following data in JSON format.

ClientToken

A unique identifier for the request. This token is automatically generated when you use Amazon Translate through an AWS SDK.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[a-zA-Z0-9-]+\$

Required: Yes

Description

A custom description for the parallel data resource in Amazon Translate.

Type: String

Length Constraints: Maximum length of 256.

Pattern: [\P{M}\p{M}]{0,256}

Required: No

EncryptionKey

The encryption key used to encrypt this object.

Type: EncryptionKey object

Required: No

Name

A custom name for the parallel data resource in Amazon Translate. You must assign a name that is unique in the account and region.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^([A-Za-z0-9-]_?)+\$

Required: Yes

ParallelDataConfig

Specifies the format and S3 location of the parallel data input file.

Type: ParallelDataConfig object

Required: Yes

Tags

Tags to be associated with this resource. A tag is a key-value pair that adds metadata to a resource. Each tag key for the resource must be unique. For more information, see <u>Tagging your resources</u> in the Amazon Translate Developer Guide.

Type: Array of <u>Tag</u> objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

Response Syntax

```
{
    "Name": "string",
    "Status": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Name

The custom name that you assigned to the parallel data resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^([A-Za-z0-9-]_?)+\$

Status

The status of the parallel data resource. When the resource is ready for you to use, the status is ACTIVE.

Type: String

Valid Values: CREATING | UPDATING | ACTIVE | DELETING | FAILED

Errors

For information about the errors that are common to all actions, see Common Errors.

ConcurrentModificationException

Another modification is being made. That modification must complete before you can make your change.

HTTP Status Code: 400

ConflictException

There was a conflict processing the request. Try your request again.

HTTP Status Code: 400

InternalServerException

An internal server error occurred. Retry your request.

HTTP Status Code: 500

InvalidParameterValueException

The value of the parameter is not valid. Review the value of the parameter you are using to correct it, and then retry your operation.

HTTP Status Code: 400

InvalidRequestException

The request that you made is not valid. Check your request to determine why it's not valid and then retry the request.

HTTP Status Code: 400

LimitExceededException

The specified limit has been exceeded. Review your request and retry it with a quantity below the stated limit.

HTTP Status Code: 400

TooManyRequestsException

You have made too many requests within a short period of time. Wait for a short time and then try your request again.

HTTP Status Code: 400

TooManyTagsException

You have added too many tags to this resource. The maximum is 50 tags.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DeleteParallelData

Deletes a parallel data resource in Amazon Translate.

Request Syntax

```
{
    "Name": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Name

The name of the parallel data resource that is being deleted.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^([A-Za-z0-9-]_?)+\$

Required: Yes

Response Syntax

```
{
    "Name": "string",
    "Status": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DeleteParallelData

Name

The name of the parallel data resource that is being deleted.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^([A-Za-z0-9-]_?)+\$

Status

The status of the parallel data deletion.

Type: String

Valid Values: CREATING | UPDATING | ACTIVE | DELETING | FAILED

Errors

For information about the errors that are common to all actions, see Common Errors.

ConcurrentModificationException

Another modification is being made. That modification must complete before you can make your change.

HTTP Status Code: 400

InternalServerException

An internal server error occurred. Retry your request.

HTTP Status Code: 500

ResourceNotFoundException

The resource you are looking for has not been found. Review the resource you're looking for and see if a different resource will accomplish your needs before retrying the revised request.

HTTP Status Code: 400

TooManyRequestsException

You have made too many requests within a short period of time. Wait for a short time and then try your request again.

DeleteParallelData 9

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DeleteParallelData 10

DeleteTerminology

A synchronous action that deletes a custom terminology.

Request Syntax

```
{
    "Name": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Name

The name of the custom terminology being deleted.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^([A-Za-z0-9-]_?)+\$

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see **Common Errors**.

InternalServerException

An internal server error occurred. Retry your request.

HTTP Status Code: 500

DeleteTerminology 11

InvalidParameterValueException

The value of the parameter is not valid. Review the value of the parameter you are using to correct it, and then retry your operation.

HTTP Status Code: 400

ResourceNotFoundException

The resource you are looking for has not been found. Review the resource you're looking for and see if a different resource will accomplish your needs before retrying the revised request.

HTTP Status Code: 400

TooManyRequestsException

You have made too many requests within a short period of time. Wait for a short time and then try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DeleteTerminology 12

DescribeTextTranslationJob

Gets the properties associated with an asynchronous batch translation job including name, ID, status, source and target languages, input/output S3 buckets, and so on.

Request Syntax

```
{
    "JobId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

JobId

The identifier that Amazon Translate generated for the job. The <u>StartTextTranslationJob</u> operation returns this identifier in its response.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: $^([\p{L}\p{X}\p{N}_.:/=+\-%@]*)$

Required: Yes

Response Syntax

```
{
   "TextTranslationJobProperties": {
        "DataAccessRoleArn": "string",
        "EndTime": number,
        "InputDataConfig": {
             "ContentType": "string",
             "S3Uri": "string"
        },
        "JobDetails": {
```

DescribeTextTranslationJob 13

```
"DocumentsWithErrorsCount": number,
         "InputDocumentsCount": number,
         "TranslatedDocumentsCount": number
      },
      "JobId": "string",
      "JobName": "string",
      "JobStatus": "string",
      "Message": "string",
      "OutputDataConfig": {
         "EncryptionKey": {
            "Id": "string",
            "Type": "string"
         },
         "S3Uri": "string"
      },
      "ParallelDataNames": [ "string" ],
      "Settings": {
         "Brevity": "string",
         "Formality": "string",
         "Profanity": "string"
      },
      "SourceLanguageCode": "string",
      "SubmittedTime": number,
      "TargetLanguageCodes": [ "string" ],
      "TerminologyNames": [ "string" ]
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

TextTranslationJobProperties

An object that contains the properties associated with an asynchronous batch translation job.

Type: <u>TextTranslationJobProperties</u> object

Errors

For information about the errors that are common to all actions, see Common Errors.

DescribeTextTranslationJob 14

InternalServerException

An internal server error occurred. Retry your request.

HTTP Status Code: 500

ResourceNotFoundException

The resource you are looking for has not been found. Review the resource you're looking for and see if a different resource will accomplish your needs before retrying the revised request.

HTTP Status Code: 400

TooManyRequestsException

You have made too many requests within a short period of time. Wait for a short time and then try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DescribeTextTranslationJob 15

GetParallelData

Provides information about a parallel data resource.

Request Syntax

```
{
    "Name": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Name

The name of the parallel data resource that is being retrieved.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^([A-Za-z0-9-]_?)+\$

Required: Yes

Response Syntax

```
{
    "AuxiliaryDataLocation": {
        "Location": "string",
        "RepositoryType": "string"
},
    "DataLocation": {
        "Location": "string",
        "RepositoryType": "string"
},
    "LatestUpdateAttemptAuxiliaryDataLocation": {
```

```
"Location": "string",
      "RepositoryType": "string"
   },
   "ParallelDataProperties": {
      "Arn": "string",
      "CreatedAt": number,
      "Description": "string",
      "EncryptionKey": {
         "Id": "string",
         "Type": "string"
      },
      "FailedRecordCount": number,
      "ImportedDataSize": number,
      "ImportedRecordCount": number,
      "LastUpdatedAt": number,
      "LatestUpdateAttemptAt": number,
      "LatestUpdateAttemptStatus": "string",
      "Message": "string",
      "Name": "string",
      "ParallelDataConfig": {
         "Format": "string",
         "S3Uri": "string"
      },
      "SkippedRecordCount": number,
      "SourceLanguageCode": "string",
      "Status": "string",
      "TargetLanguageCodes": [ "string" ]
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AuxiliaryDataLocation

The Amazon S3 location of a file that provides any errors or warnings that were produced by your input file. This file was created when Amazon Translate attempted to create a parallel data resource. The location is returned as a presigned URL to that has a 30-minute expiration.

Type: ParallelDataDataLocation object

DataLocation

The Amazon S3 location of the most recent parallel data input file that was successfully imported into Amazon Translate. The location is returned as a presigned URL that has a 30minute expiration.

Important

Amazon Translate doesn't scan all input files for the risk of CSV injection attacks. CSV injection occurs when a .csv or .tsv file is altered so that a record contains malicious code. The record begins with a special character, such as =, +, -, or @. When the file is opened in a spreadsheet program, the program might interpret the record as a formula and run the code within it.

Before you download an input file from Amazon S3, ensure that you recognize the file and trust its creator.

Type: ParallelDataDataLocation object

LatestUpdateAttemptAuxiliaryDataLocation

The Amazon S3 location of a file that provides any errors or warnings that were produced by your input file. This file was created when Amazon Translate attempted to update a parallel data resource. The location is returned as a presigned URL to that has a 30-minute expiration.

Type: ParallelDataDataLocation object

ParallelDataProperties

The properties of the parallel data resource that is being retrieved.

Type: ParallelDataProperties object

Errors

For information about the errors that are common to all actions, see Common Errors.

InternalServerException

An internal server error occurred. Retry your request.

HTTP Status Code: 500

InvalidParameterValueException

The value of the parameter is not valid. Review the value of the parameter you are using to correct it, and then retry your operation.

HTTP Status Code: 400

ResourceNotFoundException

The resource you are looking for has not been found. Review the resource you're looking for and see if a different resource will accomplish your needs before retrying the revised request.

HTTP Status Code: 400

TooManyRequestsException

You have made too many requests within a short period of time. Wait for a short time and then try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetTerminology

Retrieves a custom terminology.

Request Syntax

```
{
    "Name": "string",
    "TerminologyDataFormat": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Name

The name of the custom terminology being retrieved.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^([A-Za-z0-9-]_?)+\$

Required: Yes

TerminologyDataFormat

The data format of the custom terminology being retrieved.

If you don't specify this parameter, Amazon Translate returns a file with the same format as the file that was imported to create the terminology.

If you specify this parameter when you retrieve a multi-directional terminology resource, you must specify the same format as the input file that was imported to create it. Otherwise, Amazon Translate throws an error.

Type: String

Valid Values: CSV | TMX | TSV

Required: No

Response Syntax

```
{
   "AuxiliaryDataLocation": {
      "Location": "string",
      "RepositoryType": "string"
   },
   "TerminologyDataLocation": {
      "Location": "string",
      "RepositoryType": "string"
   },
   "TerminologyProperties": {
      "Arn": "string",
      "CreatedAt": number,
      "Description": "string",
      "Directionality": "string",
      "EncryptionKey": {
         "Id": "string",
         "Type": "string"
      },
      "Format": "string",
      "LastUpdatedAt": number,
      "Message": "string",
      "Name": "string",
      "SizeBytes": number,
      "SkippedTermCount": number,
      "SourceLanguageCode": "string",
      "TargetLanguageCodes": [ "string" ],
      "TermCount": number
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AuxiliaryDataLocation

The Amazon S3 location of a file that provides any errors or warnings that were produced by your input file. This file was created when Amazon Translate attempted to create a terminology resource. The location is returned as a presigned URL to that has a 30-minute expiration.

Type: TerminologyDataLocation object

TerminologyDataLocation

The Amazon S3 location of the most recent custom terminology input file that was successfully imported into Amazon Translate. The location is returned as a presigned URL that has a 30minute expiration.

Important

Amazon Translate doesn't scan all input files for the risk of CSV injection attacks. CSV injection occurs when a .csv or .tsv file is altered so that a record contains malicious code. The record begins with a special character, such as =, +, -, or @. When the file is opened in a spreadsheet program, the program might interpret the record as a formula and run the code within it.

Before you download an input file from Amazon S3, ensure that you recognize the file and trust its creator.

Type: TerminologyDataLocation object

TerminologyProperties

The properties of the custom terminology being retrieved.

Type: TerminologyProperties object

Errors

For information about the errors that are common to all actions, see Common Errors.

InternalServerException

An internal server error occurred. Retry your request.

HTTP Status Code: 500

InvalidParameterValueException

The value of the parameter is not valid. Review the value of the parameter you are using to correct it, and then retry your operation.

HTTP Status Code: 400

ResourceNotFoundException

The resource you are looking for has not been found. Review the resource you're looking for and see if a different resource will accomplish your needs before retrying the revised request.

HTTP Status Code: 400

TooManyRequestsException

You have made too many requests within a short period of time. Wait for a short time and then try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ImportTerminology

Creates or updates a custom terminology, depending on whether one already exists for the given terminology name. Importing a terminology with the same name as an existing one will merge the terminologies based on the chosen merge strategy. The only supported merge strategy is OVERWRITE, where the imported terminology overwrites the existing terminology of the same name.

If you import a terminology that overwrites an existing one, the new terminology takes up to 10 minutes to fully propagate. After that, translations have access to the new terminology.

Request Syntax

```
{
   "Description": "string",
   "EncryptionKey": {
      "Id": "string",
      "Type": "string"
   },
   "MergeStrategy": "string",
   "Name": "string",
   "Tags": [
      {
         "Key": "string",
         "Value": "string"
      }
   ],
   "TerminologyData": {
      "Directionality": "string",
      "File": blob,
      "Format": "string"
   }
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Description

The description of the custom terminology being imported.

Type: String

Length Constraints: Maximum length of 256.

Pattern: $[\P{M}\p{M}]{0,256}$

Required: No

EncryptionKey

The encryption key for the custom terminology being imported.

Type: EncryptionKey object

Required: No

MergeStrategy

The merge strategy of the custom terminology being imported. Currently, only the OVERWRITE merge strategy is supported. In this case, the imported terminology will overwrite an existing terminology of the same name.

Type: String

Valid Values: OVERWRITE

Required: Yes

Name

The name of the custom terminology being imported.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^([A-Za-z0-9-]_?)+\$

Required: Yes

Tags

Tags to be associated with this resource. A tag is a key-value pair that adds metadata to a resource. Each tag key for the resource must be unique. For more information, see <u>Tagging your resources</u> in the Amazon Translate Developer Guide.

Type: Array of **Tag** objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

TerminologyData

The terminology data for the custom terminology being imported.

Type: TerminologyData object

Required: Yes

Response Syntax

```
{
   "AuxiliaryDataLocation": {
      "Location": "string",
      "RepositoryType": "string"
   "TerminologyProperties": {
      "Arn": "string",
      "CreatedAt": number,
      "Description": "string",
      "Directionality": "string",
      "EncryptionKey": {
         "Id": "string",
         "Type": "string"
      },
      "Format": "string",
      "LastUpdatedAt": number,
      "Message": "string",
      "Name": "string",
      "SizeBytes": number,
      "SkippedTermCount": number,
      "SourceLanguageCode": "string",
      "TargetLanguageCodes": [ "string" ],
      "TermCount": number
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Auxiliary DataLocation

The Amazon S3 location of a file that provides any errors or warnings that were produced by your input file. This file was created when Amazon Translate attempted to create a terminology resource. The location is returned as a presigned URL to that has a 30 minute expiration.

Type: TerminologyDataLocation object

TerminologyProperties

The properties of the custom terminology being imported.

Type: TerminologyProperties object

Errors

For information about the errors that are common to all actions, see Common Errors.

ConcurrentModificationException

Another modification is being made. That modification must complete before you can make your change.

HTTP Status Code: 400

InternalServerException

An internal server error occurred. Retry your request.

HTTP Status Code: 500

InvalidParameterValueException

The value of the parameter is not valid. Review the value of the parameter you are using to correct it, and then retry your operation.

HTTP Status Code: 400

LimitExceededException

The specified limit has been exceeded. Review your request and retry it with a quantity below the stated limit.

HTTP Status Code: 400

TooManyRequestsException

You have made too many requests within a short period of time. Wait for a short time and then try your request again.

HTTP Status Code: 400

TooManyTagsException

You have added too many tags to this resource. The maximum is 50 tags.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListLanguages

Provides a list of languages (RFC-5646 codes and names) that Amazon Translate supports.

Request Syntax

```
{
    "DisplayLanguageCode": "string",
    "MaxResults": number,
    "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

DisplayLanguageCode

The language code for the language to use to display the language names in the response. The language code is en by default.

```
Type: String
```

```
Valid Values: de | en | es | fr | it | ja | ko | pt | zh | zh-TW
```

Required: No

MaxResults

The maximum number of results to return in each response.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 500.

Required: No

NextToken

Include the NextToken value to fetch the next group of supported languages.

Type: String

Length Constraints: Maximum length of 8192.

Pattern: \p{ASCII}{0,8192}

Required: No

Response Syntax

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DisplayLanguageCode

The language code passed in with the request.

```
Type: String
```

Valid Values: de | en | es | fr | it | ja | ko | pt | zh | zh-TW

Languages

The list of supported languages.

Type: Array of Language objects

NextToken

If the response does not include all remaining results, use the NextToken in the next request to fetch the next group of supported languages.

Type: String

Length Constraints: Maximum length of 8192.

Pattern: \p{ASCII}{0,8192}

Errors

For information about the errors that are common to all actions, see Common Errors.

InternalServerException

An internal server error occurred. Retry your request.

HTTP Status Code: 500

InvalidParameterValueException

The value of the parameter is not valid. Review the value of the parameter you are using to correct it, and then retry your operation.

HTTP Status Code: 400

TooManyRequestsException

You have made too many requests within a short period of time. Wait for a short time and then try your request again.

HTTP Status Code: 400

Unsupported Display Language Code Exception

Requested display language code is not supported.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET

- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListParallelData

Provides a list of your parallel data resources in Amazon Translate.

Request Syntax

```
{
    "MaxResults": number,
    "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

MaxResults

The maximum number of parallel data resources returned for each request.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 500.

Required: No

NextToken

A string that specifies the next page of results to return in a paginated response.

Type: String

Length Constraints: Maximum length of 8192.

Pattern: \p{ASCII}{0,8192}

Required: No

Response Syntax

```
{
```

```
"NextToken": "string",
   "ParallelDataPropertiesList": [
      {
         "Arn": "string",
         "CreatedAt": number,
         "Description": "string",
         "EncryptionKey": {
            "Id": "string",
            "Type": "string"
         },
         "FailedRecordCount": number,
         "ImportedDataSize": number,
         "ImportedRecordCount": number,
         "LastUpdatedAt": number,
         "LatestUpdateAttemptAt": number,
         "LatestUpdateAttemptStatus": "string",
         "Message": "string",
         "Name": "string",
         "ParallelDataConfig": {
            "Format": "string",
            "S3Uri": "string"
         },
         "SkippedRecordCount": number,
         "SourceLanguageCode": "string",
         "Status": "string",
         "TargetLanguageCodes": [ "string" ]
      }
   ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The string to use in a subsequent request to get the next page of results in a paginated response. This value is null if there are no additional pages.

Type: String

Length Constraints: Maximum length of 8192.

Pattern: \p{ASCII}{0,8192}

<u>ParallelDataPropertiesList</u>

The properties of the parallel data resources returned by this request.

Type: Array of ParallelDataProperties objects

Errors

For information about the errors that are common to all actions, see Common Errors.

InternalServerException

An internal server error occurred. Retry your request.

HTTP Status Code: 500

InvalidParameterValueException

The value of the parameter is not valid. Review the value of the parameter you are using to correct it, and then retry your operation.

HTTP Status Code: 400

TooManyRequestsException

You have made too many requests within a short period of time. Wait for a short time and then try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2

- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListTagsForResource

Lists all tags associated with a given Amazon Translate resource. For more information, see Tagging your resources in the Amazon Translate Developer Guide.

Request Syntax

```
{
    "ResourceArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

ResourceArn

The Amazon Resource Name (ARN) of the given Amazon Translate resource you are querying.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: Yes

Response Syntax

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

ListTagsForResource 37

The following data is returned in JSON format by the service.

Tags

Tags associated with the Amazon Translate resource being queried. A tag is a key-value pair that adds as a metadata to a resource used by Amazon Translate. For example, a tag with "Sales" as the key might be added to a resource to indicate its use by the sales department.

Type: Array of Tag objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Errors

For information about the errors that are common to all actions, see Common Errors.

InternalServerException

An internal server error occurred. Retry your request.

HTTP Status Code: 500

InvalidParameterValueException

The value of the parameter is not valid. Review the value of the parameter you are using to correct it, and then retry your operation.

HTTP Status Code: 400

ResourceNotFoundException

The resource you are looking for has not been found. Review the resource you're looking for and see if a different resource will accomplish your needs before retrying the revised request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

• AWS Command Line Interface

ListTagsForResource 38

- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListTagsForResource 39

ListTerminologies

Provides a list of custom terminologies associated with your account.

Request Syntax

```
{
    "MaxResults": number,
    "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

MaxResults

The maximum number of custom terminologies returned per list request.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 500.

Required: No

NextToken

If the result of the request to ListTerminologies was truncated, include the NextToken to fetch the next group of custom terminologies.

Type: String

Length Constraints: Maximum length of 8192.

Pattern: \p{ASCII}{0,8192}

Required: No

Response Syntax

```
{
```

```
"NextToken": "string",
   "TerminologyPropertiesList": [
      {
         "Arn": "string",
         "CreatedAt": number,
         "Description": "string",
         "Directionality": "string",
         "EncryptionKey": {
            "<u>Id</u>": "string",
            "Type": "string"
         },
         "Format": "string",
         "LastUpdatedAt": number,
         "Message": "string",
         "Name": "string",
         "SizeBytes": number,
         "SkippedTermCount": number,
         "SourceLanguageCode": "string",
         "TargetLanguageCodes": [ "string" ],
         "TermCount": number
      }
   ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

If the response to the ListTerminologies was truncated, the NextToken fetches the next group of custom terminologies.

Type: String

Length Constraints: Maximum length of 8192.

Pattern: \p{ASCII}{0,8192}

TerminologyPropertiesList

The properties list of the custom terminologies returned on the list request.

Type: Array of TerminologyProperties objects

Errors

For information about the errors that are common to all actions, see Common Errors.

InternalServerException

An internal server error occurred. Retry your request.

HTTP Status Code: 500

InvalidParameterValueException

The value of the parameter is not valid. Review the value of the parameter you are using to correct it, and then retry your operation.

HTTP Status Code: 400

TooManyRequestsException

You have made too many requests within a short period of time. Wait for a short time and then try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python

• AWS SDK for Ruby V3

ListTextTranslationJobs

Gets a list of the batch translation jobs that you have submitted.

Request Syntax

```
{
    "Filter": {
        "JobName": "string",
        "JobStatus": "string",
        "SubmittedAfterTime": number,
        "SubmittedBeforeTime": number
},
    "MaxResults": number,
    "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

<u>Filter</u>

The parameters that specify which batch translation jobs to retrieve. Filters include job name, job status, and submission time. You can only set one filter at a time.

Type: TextTranslationJobFilter object

Required: No

MaxResults

The maximum number of results to return in each page. The default value is 100.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 500.

Required: No

NextToken

The token to request the next page of results.

Type: String

Length Constraints: Maximum length of 8192.

Pattern: \p{ASCII}{0,8192}

Required: No

Response Syntax

```
{
   "NextToken": "string",
   "TextTranslationJobPropertiesList": [
         "DataAccessRoleArn": "string",
         "EndTime": number,
         "InputDataConfig": {
            "ContentType": "string",
            "S3Uri": "string"
         },
         "JobDetails": {
            "DocumentsWithErrorsCount": number,
            "InputDocumentsCount": number,
            "TranslatedDocumentsCount": number
         },
         "JobId": "string",
         "JobName": "string",
         "JobStatus": "string",
         "Message": "string",
         "OutputDataConfig": {
            "EncryptionKey": {
               "Id": "string",
               "Type": "string"
            },
            "S3Uri": "string"
         },
         "ParallelDataNames": [ "string" ],
         "Settings": {
            "Brevity": "string",
            "Formality": "string",
            "Profanity": "string"
         },
         "SourceLanguageCode": "string",
```

```
"SubmittedTime": number,

"TargetLanguageCodes": [ "string" ],

"TerminologyNames": [ "string" ]
}
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token to use to retrieve the next page of results. This value is null when there are no more results to return.

Type: String

Length Constraints: Maximum length of 8192.

Pattern: \p{ASCII}{0,8192}

TextTranslationJobPropertiesList

A list containing the properties of each job that is returned.

Type: Array of <u>TextTranslationJobProperties</u> objects

Errors

For information about the errors that are common to all actions, see Common Errors.

InternalServerException

An internal server error occurred. Retry your request.

HTTP Status Code: 500

InvalidFilterException

The filter specified for the operation is not valid. Specify a different filter.

HTTP Status Code: 400

InvalidRequestException

The request that you made is not valid. Check your request to determine why it's not valid and then retry the request.

HTTP Status Code: 400

TooManyRequestsException

You have made too many requests within a short period of time. Wait for a short time and then try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

StartTextTranslationJob

Starts an asynchronous batch translation job. Use batch translation jobs to translate large volumes of text across multiple documents at once. For batch translation, you can input documents with different source languages (specify auto as the source language). You can specify one or more target languages. Batch translation translates each input document into each of the target languages. For more information, see <u>Asynchronous batch processing</u> in the Amazon Translate Developer Guide.

Batch translation jobs can be described with the <u>DescribeTextTranslationJob</u> operation, listed with the <u>ListTextTranslationJob</u> operation, and stopped with the <u>StopTextTranslationJob</u> operation.

Request Syntax

```
{
   "ClientToken": "string",
   "DataAccessRoleArn": "string",
   "InputDataConfig": {
      "ContentType": "string",
      "S3Uri": "string"
   },
   "JobName": "string",
   "OutputDataConfig": {
      "EncryptionKey": {
         "Id": "string",
         "Type": "string"
      "S3Uri": "string"
   },
   "ParallelDataNames": [ "string" ],
   "Settings": {
      "Brevity": "string",
      "Formality": "string",
      "Profanity": "string"
   },
   "SourceLanguageCode": "string",
   "TargetLanguageCodes": [ "string" ],
   "TerminologyNames": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

ClientToken

A unique identifier for the request. This token is generated for you when using the Amazon Translate SDK.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[a-zA-Z0-9-]+\$

Required: Yes

DataAccessRoleArn

The Amazon Resource Name (ARN) of an AWS Identity Access and Management (IAM) role that grants Amazon Translate read access to your input data. For more information, see Perequisite permissions in the Amazon Translate Developer Guide.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: arn:aws(-[^:]+)?:iam::[0-9]{12}:role/.+

Required: Yes

InputDataConfig

Specifies the format and location of the input documents for the translation job.

Type: InputDataConfig object

Required: Yes

JobName

The name of the batch translation job to be performed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: $^([\p{L}\p{Z}\p{N}_.:/=+\-%@]*)$

Required: No

OutputDataConfig

Specifies the S3 folder to which your job output will be saved.

Type: OutputDataConfig object

Required: Yes

ParallelDataNames

The name of a parallel data resource to add to the translation job. This resource consists of examples that show how you want segments of text to be translated. If you specify multiple target languages for the job, the parallel data file must include translations for all the target languages.

When you add parallel data to a translation job, you create an Active Custom Translation job.

This parameter accepts only one parallel data resource.

Note

Active Custom Translation jobs are priced at a higher rate than other jobs that don't use parallel data. For more information, see Amazon Translate pricing.

For a list of available parallel data resources, use the <u>ListParallelData</u> operation.

For more information, see <u>Customizing your translations with parallel data</u> in the Amazon Translate Developer Guide.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^([A-Za-z0-9-]_?)+\$

Required: No

Settings

Settings to configure your translation output. You can configure the following options:

- Brevity: not supported.
- Formality: sets the formality level of the output text.
- Profanity: masks profane words and phrases in your translation output.

Type: TranslationSettings object

Required: No

SourceLanguageCode

The language code of the input language. Specify the language if all input documents share the same language. If you don't know the language of the source files, or your input documents contains different source languages, select auto. Amazon Translate auto detects the source language for each input document. For a list of supported language codes, see Supported languages in the Amazon Translate Developer Guide.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 5.

Required: Yes

TargetLanguageCodes

The target languages of the translation job. Enter up to 10 language codes. Each input file is translated into each target language.

Each language code is 2 or 5 characters long. For a list of language codes, see <u>Supported</u> <u>languages</u> in the Amazon Translate Developer Guide.

Type: Array of strings

Array Members: Minimum number of 1 item.

Length Constraints: Minimum length of 2. Maximum length of 5.

Required: Yes

TerminologyNames

The name of a custom terminology resource to add to the translation job. This resource lists examples source terms and the desired translation for each term.

This parameter accepts only one custom terminology resource.

If you specify multiple target languages for the job, translate uses the designated terminology for each requested target language that has an entry for the source term in the terminology file.

For a list of available custom terminology resources, use the ListTerminologies operation.

For more information, see Custom terminology in the Amazon Translate Developer Guide.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^([A-Za-z0-9-] ?)+\$

Required: No

Response Syntax

```
{
   "JobId": "string",
   "JobStatus": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

JobId

The identifier generated for the job. To get the status of a job, use this ID with the DescribeTextTranslationJob operation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: $^([\p{L}\p{Z}\p{N}_.:/=+\-%@]*)$

JobStatus

The status of the job. Possible values include:

- SUBMITTED The job has been received and is gueued for processing.
- IN_PROGRESS Amazon Translate is processing the job.
- COMPLETED The job was successfully completed and the output is available.
- COMPLETED_WITH_ERROR The job was completed with errors. The errors can be analyzed in the job's output.
- FAILED The job did not complete. To get details, use the DescribeTextTranslationJob operation.
- STOP_REQUESTED The user who started the job has requested that it be stopped.
- STOPPED The job has been stopped.

Type: String

Valid Values: SUBMITTED | IN_PROGRESS | COMPLETED | COMPLETED_WITH_ERROR | FAILED | STOP_REQUESTED | STOPPED

Errors

For information about the errors that are common to all actions, see Common Errors.

InternalServerException

An internal server error occurred. Retry your request.

HTTP Status Code: 500

InvalidParameterValueException

The value of the parameter is not valid. Review the value of the parameter you are using to correct it, and then retry your operation.

HTTP Status Code: 400

InvalidRequestException

The request that you made is not valid. Check your request to determine why it's not valid and then retry the request.

HTTP Status Code: 400

ResourceNotFoundException

The resource you are looking for has not been found. Review the resource you're looking for and see if a different resource will accomplish your needs before retrying the revised request.

HTTP Status Code: 400

TooManyRequestsException

You have made too many requests within a short period of time. Wait for a short time and then try your request again.

HTTP Status Code: 400

UnsupportedLanguagePairException

Amazon Translate does not support translation from the language of the source text into the requested target language. For more information, see <u>Supported languages</u> in the Amazon Translate Developer Guide.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

StopTextTranslationJob

Stops an asynchronous batch translation job that is in progress.

If the job's state is IN_PROGRESS, the job will be marked for termination and put into the STOP_REQUESTED state. If the job completes before it can be stopped, it is put into the COMPLETED state. Otherwise, the job is put into the STOPPED state.

Asynchronous batch translation jobs are started with the <u>StartTextTranslationJob</u> operation. You can use the <u>DescribeTextTranslationJob</u> or <u>ListTextTranslationJobs</u> operations to get a batch translation job's JobId.

Request Syntax

```
{
    "JobId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

<u>JobId</u>

The job ID of the job to be stopped.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: $^([\p{L}\p{Z}\p{N}_.:/=+\-\%e]*)$

Required: Yes

Response Syntax

```
{
    "JobId": "string",
    "JobStatus": "string"
```

StopTextTranslationJob 55

}

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

JobId

The job ID of the stopped batch translation job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: $^([\p{L}\p{Z}\p{N}_.:/=+\-%@]*)$

JobStatus

The status of the designated job. Upon successful completion, the job's status will be STOPPED.

Type: String

Valid Values: SUBMITTED | IN_PROGRESS | COMPLETED | COMPLETED_WITH_ERROR | FAILED | STOP_REQUESTED | STOPPED

Errors

For information about the errors that are common to all actions, see Common Errors.

InternalServerException

An internal server error occurred. Retry your request.

HTTP Status Code: 500

ResourceNotFoundException

The resource you are looking for has not been found. Review the resource you're looking for and see if a different resource will accomplish your needs before retrying the revised request.

HTTP Status Code: 400

StopTextTranslationJob 56

TooManyRequestsException

You have made too many requests within a short period of time. Wait for a short time and then try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

StopTextTranslationJob 57

TagResource

Associates a specific tag with a resource. A tag is a key-value pair that adds as a metadata to a resource. For more information, see <u>Tagging your resources</u> in the Amazon Translate Developer Guide.

Request Syntax

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

ResourceArn

The Amazon Resource Name (ARN) of the given Amazon Translate resource to which you want to associate the tags.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: Yes

Tags

Tags being associated with a specific Amazon Translate resource. There can be a maximum of 50 tags (both existing and pending) associated with a specific resource.

Type: Array of **Tag** objects

TagResource 58

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Errors.

ConcurrentModificationException

Another modification is being made. That modification must complete before you can make your change.

HTTP Status Code: 400

InternalServerException

An internal server error occurred. Retry your request.

HTTP Status Code: 500

InvalidParameterValueException

The value of the parameter is not valid. Review the value of the parameter you are using to correct it, and then retry your operation.

HTTP Status Code: 400

ResourceNotFoundException

The resource you are looking for has not been found. Review the resource you're looking for and see if a different resource will accomplish your needs before retrying the revised request.

HTTP Status Code: 400

TooManyTagsException

You have added too many tags to this resource. The maximum is 50 tags.

HTTP Status Code: 400

TagResource

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- · AWS SDK for Python
- AWS SDK for Ruby V3

TagResource 60

TranslateDocument

Translates the input document from the source language to the target language. This synchronous operation supports text, HTML, or Word documents as the input document. TranslateDocument supports translations from English to any supported language, and from any supported language to English. Therefore, specify either the source language code or the target language code as "en" (English).

If you set the Formality parameter, the request will fail if the target language does not support formality. For a list of target languages that support formality, see Setting formality in the Amazon Translate Developer Guide.

Request Syntax

```
{
    "Document": {
        "Content": blob,
        "ContentType": "string"
},
    "Settings": {
        "Brevity": "string",
        "Formality": "string",
        "Profanity": "string"
},
    "SourceLanguageCode": "string",
    "TargetLanguageCode": "string",
    "TerminologyNames": [ "string"]
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Document

The content and content type for the document to be translated. The document size must not exceed 100 KB.

Type: **Document** object

Required: Yes

Settings

Settings to configure your translation output. You can configure the following options:

- Brevity: not supported.
- Formality: sets the formality level of the output text.
- Profanity: masks profane words and phrases in your translation output.

Type: TranslationSettings object

Required: No

SourceLanguageCode

The language code for the language of the source text. For a list of supported language codes, see Supported languages in the Amazon Translate Developer Guide.

To have Amazon Translate determine the source language of your text, you can specify auto in the SourceLanguageCode field. If you specify auto, Amazon Translate will call Amazon Comprehend to determine the source language.

Note

If you specify auto, you must send the TranslateDocument request in a region that supports Amazon Comprehend. Otherwise, the request returns an error indicating that autodetect is not supported.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 5.

Required: Yes

TargetLanguageCode

The language code requested for the translated document. For a list of supported language codes, see Supported languages.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 5.

Required: Yes

TerminologyNames

The name of a terminology list file to add to the translation job. This file provides source terms and the desired translation for each term. A terminology list can contain a maximum of 256 terms. You can use one custom terminology resource in your translation request.

Use the ListTerminologies operation to get the available terminology lists.

For more information about custom terminology lists, see <u>Custom terminology</u> in the Amazon Translate Developer Guide.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^([A-Za-z0-9-]_?)+\$

Required: No

Response Syntax

```
{
   "AppliedSettings": {
      "Brevity": "string",
      "Formality": "string",
      "Profanity": "string"
   },
   "AppliedTerminologies": [
      {
         "Name": "string",
         "Terms": [
            {
               "SourceText": "string",
                "TargetText": "string"
            }
         ]
      }
   ],
   "SourceLanguageCode": "string",
   "TargetLanguageCode": "string",
   "TranslatedDocument": {
      "Content": blob
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AppliedSettings

Settings to configure your translation output. You can configure the following options:

- Brevity: reduces the length of the translation output for most translations. Available for TranslateText only.
- Formality: sets the formality level of the translation output.
- Profanity: masks profane words and phrases in the translation output.

Type: TranslationSettings object

AppliedTerminologies

The names of the custom terminologies applied to the input text by Amazon Translate to produce the translated text document.

Type: Array of AppliedTerminology objects

SourceLanguageCode

The language code of the source document.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 5.

TargetLanguageCode

The language code of the translated document.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 5.

TranslatedDocument

The document containing the translated content. The document format matches the source document format.

Type: TranslatedDocument object

Errors

For information about the errors that are common to all actions, see Common Errors.

InternalServerException

An internal server error occurred. Retry your request.

HTTP Status Code: 500

InvalidRequestException

The request that you made is not valid. Check your request to determine why it's not valid and then retry the request.

HTTP Status Code: 400

LimitExceededException

The specified limit has been exceeded. Review your request and retry it with a quantity below the stated limit.

HTTP Status Code: 400

ResourceNotFoundException

The resource you are looking for has not been found. Review the resource you're looking for and see if a different resource will accomplish your needs before retrying the revised request.

HTTP Status Code: 400

ServiceUnavailableException

The Amazon Translate service is temporarily unavailable. Wait a bit and then retry your request.

HTTP Status Code: 500

TooManyRequestsException

You have made too many requests within a short period of time. Wait for a short time and then try your request again.

HTTP Status Code: 400

UnsupportedLanguagePairException

Amazon Translate does not support translation from the language of the source text into the requested target language. For more information, see <u>Supported languages</u> in the Amazon Translate Developer Guide.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- · AWS SDK for Python
- AWS SDK for Ruby V3

TranslateText

Translates input text from the source language to the target language. For a list of available languages and language codes, see <u>Supported languages</u> in the Amazon Translate Developer Guide.

Request Syntax

```
{
    "Settings": {
        "Brevity": "string",
        "Formality": "string",
        "Profanity": "string"
},

"SourceLanguageCode": "string",
    "TargetLanguageCode": "string",
    "TerminologyNames": [ "string"],
    "Text": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

Settings

Settings to configure your translation output. You can configure the following options:

- Brevity: reduces the length of the translated output for most translations.
- Formality: sets the formality level of the output text.
- Profanity: masks profane words and phrases in your translation output.

Type: TranslationSettings object

Required: No

SourceLanguageCode

The language code for the language of the source text. For a list of language codes, see Supported languages in the Amazon Translate Developer Guide.

TranslateText 67

To have Amazon Translate determine the source language of your text, you can specify auto in the SourceLanguageCode field. If you specify auto, Amazon Translate will call Amazon Comprehend to determine the source language.



Note

If you specify auto, you must send the TranslateText request in a region that supports Amazon Comprehend. Otherwise, the request returns an error indicating that autodetect is not supported.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 5.

Required: Yes

TargetLanguageCode

The language code requested for the language of the target text. For a list of language codes, see Supported languages in the Amazon Translate Developer Guide.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 5.

Required: Yes

TerminologyNames

The name of a terminology list file to add to the translation job. This file provides source terms and the desired translation for each term. A terminology list can contain a maximum of 256 terms. You can use one custom terminology resource in your translation request.

Use the ListTerminologies operation to get the available terminology lists.

For more information about custom terminology lists, see Custom terminology in the Amazon Translate Developer Guide.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 256.

TranslateText

```
Pattern: ^([A-Za-z0-9-]_?)+$
```

Required: No

Text

The text to translate. The text string can be a maximum of 10,000 bytes long. Depending on your character set, this may be fewer than 10,000 characters.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10000.

Pattern: [\P{M}\p{M}]{1,10000}

Required: Yes

Response Syntax

```
{
   "AppliedSettings": {
      "Brevity": "string",
      "Formality": "string",
      "Profanity": "string"
   },
   "AppliedTerminologies": [
         "Name": "string",
         "Terms": [
            {
                "SourceText": "string",
                "TargetText": "string"
            }
         ]
      }
   ],
   "SourceLanguageCode": "string",
   "TargetLanguageCode": "string",
   "TranslatedText": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AppliedSettings

Optional settings that modify the translation output.

Type: TranslationSettings object

AppliedTerminologies

The names of the custom terminologies applied to the input text by Amazon Translate for the translated text response.

Type: Array of AppliedTerminology objects

SourceLanguageCode

The language code for the language of the source text.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 5.

TargetLanguageCode

The language code for the language of the target text.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 5.

TranslatedText

The translated text.

Type: String

Length Constraints: Maximum length of 20000.

Pattern: [\P{M}\p{M}]{0,20000}

Errors

For information about the errors that are common to all actions, see Common Errors.

DetectedLanguageLowConfidenceException

The confidence that Amazon Comprehend accurately detected the source language is low. If a low confidence level is acceptable for your application, you can use the language in the exception to call Amazon Translate again. For more information, see the DetectDominantLanguage operation in the Amazon Comprehend Developer Guide.

HTTP Status Code: 400

InternalServerException

An internal server error occurred. Retry your request.

HTTP Status Code: 500

InvalidRequestException

The request that you made is not valid. Check your request to determine why it's not valid and then retry the request.

HTTP Status Code: 400

ResourceNotFoundException

The resource you are looking for has not been found. Review the resource you're looking for and see if a different resource will accomplish your needs before retrying the revised request.

HTTP Status Code: 400

ServiceUnavailableException

The Amazon Translate service is temporarily unavailable. Wait a bit and then retry your request.

HTTP Status Code: 500

TextSizeLimitExceededException

The size of the text you submitted exceeds the size limit. Reduce the size of the text or use a smaller document and then retry your request.

HTTP Status Code: 400

TooManyRequestsException

You have made too many requests within a short period of time. Wait for a short time and then try your request again.

HTTP Status Code: 400

UnsupportedLanguagePairException

Amazon Translate does not support translation from the language of the source text into the requested target language. For more information, see <u>Supported languages</u> in the Amazon Translate Developer Guide.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- · AWS SDK for Python
- AWS SDK for Ruby V3

UntagResource

Removes a specific tag associated with an Amazon Translate resource. For more information, see Tagging your resources in the Amazon Translate Developer Guide.

Request Syntax

```
{
    "ResourceArn": "string",
    "TagKeys": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

ResourceArn

The Amazon Resource Name (ARN) of the given Amazon Translate resource from which you want to remove the tags.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: Yes

TagKeys

The initial part of a key-value pair that forms a tag being removed from a given resource. Keys must be unique and cannot be duplicated for a particular resource.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

UntagResource 73

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Errors.

ConcurrentModificationException

Another modification is being made. That modification must complete before you can make your change.

HTTP Status Code: 400

InternalServerException

An internal server error occurred. Retry your request.

HTTP Status Code: 500

InvalidParameterValueException

The value of the parameter is not valid. Review the value of the parameter you are using to correct it, and then retry your operation.

HTTP Status Code: 400

ResourceNotFoundException

The resource you are looking for has not been found. Review the resource you're looking for and see if a different resource will accomplish your needs before retrying the revised request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++

UntagResource 74

- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

UntagResource 75

UpdateParallelData

Updates a previously created parallel data resource by importing a new input file from Amazon S3.

Request Syntax

```
{
    "ClientToken": "string",
    "Description": "string",
    "Name": "string",
    "ParallelDataConfig": {
        "Format": "string",
        "S3Uri": "string"
    }
}
```

Request Parameters

For information about the parameters that are common to all actions, see Common Parameters.

The request accepts the following data in JSON format.

ClientToken

A unique identifier for the request. This token is automatically generated when you use Amazon Translate through an AWS SDK.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[a-zA-Z0-9-]+\$

Required: Yes

Description

A custom description for the parallel data resource in Amazon Translate.

Type: String

Length Constraints: Maximum length of 256.

Pattern: $[\P{M}\p{M}]{0,256}$

Required: No

<u>Name</u>

The name of the parallel data resource being updated.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^([A-Za-z0-9-]_?)+\$

Required: Yes

ParallelDataConfig

Specifies the format and S3 location of the parallel data input file.

Type: ParallelDataConfig object

Required: Yes

Response Syntax

```
{
   "LatestUpdateAttemptAt": number,
   "LatestUpdateAttemptStatus": "string",
   "Name": "string",
   "Status": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

$\underline{\textbf{LatestUpdateAttemptAt}}$

The time that the most recent update was attempted.

Type: Timestamp

LatestUpdateAttemptStatus

The status of the parallel data update attempt. When the updated parallel data resource is ready for you to use, the status is ACTIVE.

Type: String

Valid Values: CREATING | UPDATING | ACTIVE | DELETING | FAILED

<u>Name</u>

The name of the parallel data resource being updated.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^([A-Za-z0-9-]_?)+\$

Status

The status of the parallel data resource that you are attempting to update. Your update request is accepted only if this status is either ACTIVE or FAILED.

Type: String

Valid Values: CREATING | UPDATING | ACTIVE | DELETING | FAILED

Errors

For information about the errors that are common to all actions, see Common Errors.

${\bf Concurrent Modification Exception}$

Another modification is being made. That modification must complete before you can make your change.

HTTP Status Code: 400

ConflictException

There was a conflict processing the request. Try your request again.

HTTP Status Code: 400

InternalServerException

An internal server error occurred. Retry your request.

HTTP Status Code: 500

InvalidParameterValueException

The value of the parameter is not valid. Review the value of the parameter you are using to correct it, and then retry your operation.

HTTP Status Code: 400

InvalidRequestException

The request that you made is not valid. Check your request to determine why it's not valid and then retry the request.

HTTP Status Code: 400

LimitExceededException

The specified limit has been exceeded. Review your request and retry it with a quantity below the stated limit.

HTTP Status Code: 400

ResourceNotFoundException

The resource you are looking for has not been found. Review the resource you're looking for and see if a different resource will accomplish your needs before retrying the revised request.

HTTP Status Code: 400

TooManyRequestsException

You have made too many requests within a short period of time. Wait for a short time and then try your request again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

Data Types

The following data types are supported:

- AppliedTerminology
- Document
- EncryptionKey
- InputDataConfig
- JobDetails
- Language
- OutputDataConfig
- ParallelDataConfig
- ParallelDataDataLocation
- ParallelDataProperties
- Tag
- Term
- TerminologyData
- TerminologyDataLocation
- TerminologyProperties
- TextTranslationJobFilter
- TextTranslationJobProperties

Data Types 80

- <u>TranslatedDocument</u>
- TranslationSettings

Data Types 81

AppliedTerminology

The custom terminology applied to the input text by Amazon Translate for the translated text response. This is optional in the response and will only be present if you specified terminology input in the request. Currently, only one terminology can be applied per TranslateText request.

Contents

Name

The name of the custom terminology applied to the input text by Amazon Translate for the translated text response.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^([A-Za-z0-9-]_?)+\$

Required: No

Terms

The specific terms of the custom terminology applied to the input text by Amazon Translate for the translated text response. A maximum of 250 terms will be returned, and the specific terms applied will be the first 250 terms in the source text.

Type: Array of <u>Term</u> objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AppliedTerminology 82

Document

The content and content type of a document.

Contents

Content

The Contentfield type is Binary large object (blob). This object contains the document content converted into base64-encoded binary data. If you use one of the AWS SDKs, the SDK performs the Base64-encoding on this field before sending the request.

Type: Base64-encoded binary data object

Length Constraints: Maximum length of 102400.

Required: Yes

ContentType

Describes the format of the document. You can specify one of the following:

- text/html The input data consists of HTML content. Amazon Translate translates only the text in the HTML element.
- text/plain The input data consists of unformatted text. Amazon Translate translates every character in the content.
- application/vnd.openxmlformatsofficedocument.wordprocessingml.document - The input data consists of a Word document (.docx).

Type: String

Length Constraints: Maximum length of 256.

Pattern: $^[-\w.]+\/[-\w.+]+$ \$

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

Document 83

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

Document 84

EncryptionKey

The encryption key used to encrypt this object.

Contents

Id

The Amazon Resource Name (ARN) of the encryption key being used to encrypt this object.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 400.

```
Pattern: (arn:aws((-us-gov)|(-iso)|(-iso-b)|(-cn))?:kms:)?([a-z]{2}-[a-z]+(-[a-z]+)?-\d:)?(\d{12}:)?(((key/)?[a-zA-Z0-9-_]+)|(alias/[a-zA-Z0-9:/_-]+))
```

Required: Yes

Type

The type of encryption key used by Amazon Translate to encrypt this object.

Type: String

Valid Values: KMS

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

EncryptionKey 85

InputDataConfig

The input configuration properties for requesting a batch translation job.

Contents

ContentType

Describes the format of the data that you submit to Amazon Translate as input. You can specify one of the following multipurpose internet mail extension (MIME) types:

- text/html: The input data consists of one or more HTML files. Amazon Translate translates only the text that resides in the html element in each file.
- text/plain: The input data consists of one or more unformatted text files. Amazon Translate translates every character in this type of input.
- application/vnd.openxmlformatsofficedocument.wordprocessingml.document: The input data consists of one or more Word documents (.docx).
- application/vnd.openxmlformatsofficedocument.presentationml.presentation: The input data consists of one or more PowerPoint Presentation files (.pptx).
- application/vnd.openxmlformats-officedocument.spreadsheetml.sheet: The input data consists of one or more Excel Workbook files (.xlsx).
- application/x-xliff+xml: The input data consists of one or more XML Localization Interchange File Format (XLIFF) files (.xlf). Amazon Translate supports only XLIFF version 1.2.

Important

If you structure your input data as HTML, ensure that you set this parameter to text/ html. By doing so, you cut costs by limiting the translation to the contents of the html element in each file. Otherwise, if you set this parameter to text/plain, your costs will cover the translation of every character.

Type: String

Length Constraints: Maximum length of 256.

Pattern: $^[-\w.]+\/[-\w.+]+$ \$

InputDataConfig

Required: Yes

S3Uri

The URI of the AWS S3 folder that contains the input files. Amazon Translate translates all the files in the folder and all its sub-folders. The folder must be in the same Region as the API endpoint you are calling.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: $s3://[a-z0-9][\.\-a-z0-9]{1,61}[a-z0-9](/.*)$?

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

InputDataConfig 87

JobDetails

The number of documents successfully and unsuccessfully processed during a translation job.

Contents

DocumentsWithErrorsCount

The number of documents that could not be processed during a translation job.

Type: Integer

Required: No

InputDocumentsCount

The number of documents used as input in a translation job.

Type: Integer

Required: No

TranslatedDocumentsCount

The number of documents successfully processed during a translation job.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

JobDetails 88

Language

A supported language.

Contents

LanguageCode

Language code for the supported language.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 5.

Required: Yes

LanguageName

Language name of the supported language.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

Language 89

OutputDataConfig

The output configuration properties for a batch translation job.

Contents

S3Uri

The URI of the S3 folder that contains a translation job's output file. The folder must be in the same Region as the API endpoint that you are calling.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: $s3://[a-z0-9][\.\-a-z0-9]{1,61}[a-z0-9](/.*)$?

Required: Yes

EncryptionKey

The encryption key used to encrypt this object.

Type: EncryptionKey object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

OutputDataConfig 90

ParallelDataConfig

Specifies the format and S3 location of the parallel data input file.

Contents

Format

The format of the parallel data input file.

Type: String

Valid Values: TSV | CSV | TMX

Required: No

S3Uri

The URI of the Amazon S3 folder that contains the parallel data input file. The folder must be in the same Region as the API endpoint you are calling.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: $s3://[a-z0-9][\.\-a-z0-9]{1,61}[a-z0-9](/.*)$?

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ParallelDataConfig 91

ParallelDataDataLocation

The location of the most recent parallel data input file that was successfully imported into Amazon Translate.

Contents

Location

The Amazon S3 location of the parallel data input file. The location is returned as a presigned URL to that has a 30-minute expiration.

Important

Amazon Translate doesn't scan all input files for the risk of CSV injection attacks. CSV injection occurs when a .csv or .tsv file is altered so that a record contains malicious code. The record begins with a special character, such as =, +, -, or @. When the file is opened in a spreadsheet program, the program might interpret the record as a formula and run the code within it.

Before you download an input file from Amazon S3, ensure that you recognize the file and trust its creator.

Type: String

Length Constraints: Maximum length of 10000.

Pattern: [\P{M}\p{M}]{0,10000}

Required: Yes

RepositoryType

Describes the repository that contains the parallel data input file.

Type: String

Length Constraints: Maximum length of 10000.

Pattern: [\P{M}\p{M}]{0,10000}

Required: Yes

ParallelDataDataLocation

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ParallelDataDataLocation 93

ParallelDataProperties

The properties of a parallel data resource.

Contents

Arn

The Amazon Resource Name (ARN) of the parallel data resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

CreatedAt

The time at which the parallel data resource was created.

Type: Timestamp

Required: No

Description

The description assigned to the parallel data resource.

Type: String

Length Constraints: Maximum length of 256.

Pattern: $[\P{M}\p{M}]{0,256}$

Required: No

EncryptionKey

The encryption key used to encrypt this object.

Type: EncryptionKey object

Required: No

FailedRecordCount

The number of records unsuccessfully imported from the parallel data input file.

Type: Long

Required: No

ImportedDataSize

The number of UTF-8 characters that Amazon Translate imported from the parallel data input file. This number includes only the characters in your translation examples. It does not include characters that are used to format your file. For example, if you provided a Translation Memory Exchange (.tmx) file, this number does not include the tags.

Type: Long

Required: No

ImportedRecordCount

The number of records successfully imported from the parallel data input file.

Type: Long

Required: No

LastUpdatedAt

The time at which the parallel data resource was last updated.

Type: Timestamp

Required: No

LatestUpdateAttemptAt

The time that the most recent update was attempted.

Type: Timestamp

Required: No

LatestUpdateAttemptStatus

The status of the most recent update attempt for the parallel data resource.

Type: String

Valid Values: CREATING | UPDATING | ACTIVE | DELETING | FAILED

Required: No

Message

Additional information from Amazon Translate about the parallel data resource.

Type: String

Required: No

Name

The custom name assigned to the parallel data resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^([A-Za-z0-9-]_?)+\$

Required: No

ParallelDataConfig

Specifies the format and S3 location of the parallel data input file.

Type: ParallelDataConfig object

Required: No

SkippedRecordCount

The number of items in the input file that Amazon Translate skipped when you created or updated the parallel data resource. For example, Amazon Translate skips empty records, empty target texts, and empty lines.

Type: Long

Required: No

SourceLanguageCode

The source language of the translations in the parallel data file.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 5.

Required: No

Status

The status of the parallel data resource. When the parallel data is ready for you to use, the status is ACTIVE.

Type: String

Valid Values: CREATING | UPDATING | ACTIVE | DELETING | FAILED

Required: No

TargetLanguageCodes

The language codes for the target languages available in the parallel data file. All possible target languages are returned as an array.

Type: Array of strings

Length Constraints: Minimum length of 2. Maximum length of 5.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

Tag

A key-value pair that adds as a metadata to a resource used by Amazon Translate.

Contents

Key

The initial part of a key-value pair that forms a tag associated with a given resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

Value

The second part of a key-value pair that forms a tag associated with a given resource.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

Tag 98

Term

The term being translated by the custom terminology.

Contents

SourceText

The source text of the term being translated by the custom terminology.

Type: String

Length Constraints: Maximum length of 10000.

Pattern: [\P{M}\p{M}]{0,10000}

Required: No

TargetText

The target text of the term being translated by the custom terminology.

Type: String

Length Constraints: Maximum length of 10000.

Pattern: [\P{M}\p{M}]{0,10000}

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

Term 99

TerminologyData

The data associated with the custom terminology. For information about the custom terminology file, see Creating a Custom Terminology in the Amazon Translate Developer Guide.

Contents

File

The file containing the custom terminology data. Your version of the AWS SDK performs a Base64-encoding on this field before sending a request to the AWS service. Users of the SDK should not perform Base64-encoding themselves.

Type: Base64-encoded binary data object

Length Constraints: Maximum length of 10485760.

Required: Yes

Format

The data format of the custom terminology.

Type: String

Valid Values: CSV | TMX | TSV

Required: Yes

Directionality

The directionality of your terminology resource indicates whether it has one source language (uni-directional) or multiple (multi-directional).

UNI

The terminology resource has one source language (for example, the first column in a CSV file), and all of its other languages are target languages.

MULTI

Any language in the terminology resource can be the source language or a target language. A single multi-directional terminology resource can be used for jobs that translate different language pairs. For example, if the terminology contains English and Spanish terms, it can be used for jobs that translate English to Spanish and Spanish to English.

TerminologyData 100

When you create a custom terminology resource without specifying the directionality, it behaves as uni-directional terminology, although this parameter will have a null value.

Type: String

Valid Values: UNI | MULTI

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

TerminologyData 101

TerminologyDataLocation

The location of the custom terminology data.

Contents

Location

The Amazon S3 location of the most recent custom terminology input file that was successfully imported into Amazon Translate. The location is returned as a presigned URL that has a 30minute expiration.

Important

Amazon Translate doesn't scan all input files for the risk of CSV injection attacks. CSV injection occurs when a .csv or .tsv file is altered so that a record contains malicious code. The record begins with a special character, such as =, +, -, or @. When the file is opened in a spreadsheet program, the program might interpret the record as a formula and run the code within it.

Before you download an input file from Amazon S3, ensure that you recognize the file and trust its creator.

Type: String

Length Constraints: Maximum length of 10000.

Pattern: $[\P{M}\p{M}]{0,10000}$

Required: Yes

RepositoryType

The repository type for the custom terminology data.

Type: String

Length Constraints: Maximum length of 10000.

Pattern: [\P{M}\p{M}]{0,10000}

Required: Yes

TerminologyDataLocation 102

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

TerminologyDataLocation 103

TerminologyProperties

The properties of the custom terminology.

Contents

Arn

The Amazon Resource Name (ARN) of the custom terminology.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

CreatedAt

The time at which the custom terminology was created, based on the timestamp.

Type: Timestamp

Required: No

Description

The description of the custom terminology properties.

Type: String

Length Constraints: Maximum length of 256.

Pattern: [\P{M}\p{M}]{0,256}

Required: No

Directionality

The directionality of your terminology resource indicates whether it has one source language (uni-directional) or multiple (multi-directional).

UNI

The terminology resource has one source language (the first column in a CSV file), and all of its other languages are target languages.

TerminologyProperties 104

MULTI

Any language in the terminology resource can be the source language.

Type: String

Valid Values: UNI | MULTI

Required: No

EncryptionKey

The encryption key for the custom terminology.

Type: EncryptionKey object

Required: No

Format

The format of the custom terminology input file.

Type: String

Valid Values: CSV | TMX | TSV

Required: No

LastUpdatedAt

The time at which the custom terminology was last update, based on the timestamp.

Type: Timestamp

Required: No

Message

Additional information from Amazon Translate about the terminology resource.

Type: String

Required: No

Name

The name of the custom terminology.

TerminologyProperties 105

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^([A-Za-z0-9-]_?)+\$

Required: No

SizeBytes

The size of the file used when importing a custom terminology.

Type: Integer

Required: No

SkippedTermCount

The number of terms in the input file that Amazon Translate skipped when you created or updated the terminology resource.

Type: Integer

Required: No

SourceLanguageCode

The language code for the source text of the translation request for which the custom terminology is being used.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 5.

Required: No

TargetLanguageCodes

The language codes for the target languages available with the custom terminology resource. All possible target languages are returned in array.

Type: Array of strings

Length Constraints: Minimum length of 2. Maximum length of 5.

Required: No

TerminologyProperties 106

TermCount

The number of terms included in the custom terminology.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

TerminologyProperties 107

TextTranslationJobFilter

Provides information for filtering a list of translation jobs. For more information, see ListTextTranslationJobs.

Contents

JobName

Filters the list of jobs by name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: $^([\p{L}\p{Z}\p{N}_.:/=+\-%@]*)$ \$

Required: No

JobStatus

Filters the list of jobs based by job status.

Type: String

Valid Values: SUBMITTED | IN_PROGRESS | COMPLETED | COMPLETED_WITH_ERROR | FAILED | STOP_REQUESTED | STOPPED

TATELD | STOT_REQUESTED |

Required: No

SubmittedAfterTime

Filters the list of jobs based on the time that the job was submitted for processing and returns only the jobs submitted after the specified time. Jobs are returned in descending order, newest to oldest.

Type: Timestamp

Required: No

SubmittedBeforeTime

Filters the list of jobs based on the time that the job was submitted for processing and returns only the jobs submitted before the specified time. Jobs are returned in ascending order, oldest to newest.

TextTranslationJobFilter 108

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

TextTranslationJobFilter 109

TextTranslationJobProperties

Provides information about a translation job.

Contents

DataAccessRoleArn

The Amazon Resource Name (ARN) of an AWS Identity Access and Management (IAM) role that granted Amazon Translate read access to the job's input data. For more information, see Prerequisite permissions in the Amazon Translate Developer Guide.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: arn:aws(-[^:]+)?:iam::[0-9]{12}:role/.+

Required: No

EndTime

The time at which the translation job ended.

Type: Timestamp

Required: No

InputDataConfig

The input configuration properties that were specified when the job was requested.

Type: InputDataConfig object

Required: No

JobDetails

The number of documents successfully and unsuccessfully processed during the translation job.

Type: JobDetails object

Required: No

JobId

The ID of the translation job.

TextTranslationJobProperties 110

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: $^([\p{L}\p{Z}\p{N}_.:/=+\-%@]*)$ \$

Required: No

JobName

The user-defined name of the translation job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: $^([\p{L}\p{Z}\p{N}_.:/=+\-%@]*)$ \$

Required: No

JobStatus

The status of the translation job.

Type: String

Valid Values: SUBMITTED | IN_PROGRESS | COMPLETED | COMPLETED_WITH_ERROR |

FAILED | STOP_REQUESTED | STOPPED

Required: No

Message

An explanation of any errors that may have occurred during the translation job.

Type: String

Required: No

OutputDataConfig

The output configuration properties that were specified when the job was requested.

Type: OutputDataConfig object

Required: No

TextTranslationJobProperties 111

ParallelDataNames

A list containing the names of the parallel data resources applied to the translation job.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^([A-Za-z0-9-]_?)+\$

Required: No

Settings

Settings that modify the translation output.

Type: TranslationSettings object

Required: No

SourceLanguageCode

The language code of the language of the source text. The language must be a language supported by Amazon Translate.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 5.

Required: No

SubmittedTime

The time at which the translation job was submitted.

Type: Timestamp

Required: No

TargetLanguageCodes

The language code of the language of the target text. The language must be a language supported by Amazon Translate.

Type: Array of strings

Array Members: Minimum number of 1 item.

TextTranslationJobProperties 112

Length Constraints: Minimum length of 2. Maximum length of 5.

Required: No

TerminologyNames

A list containing the names of the terminologies applied to a translation job. Only one terminology can be applied per StartTextTranslationJob request at this time.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^([A-Za-z0-9-]_?)+\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

TranslatedDocument

The translated content.

Contents

Content

The document containing the translated content.

Type: Base64-encoded binary data object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

TranslatedDocument 114

TranslationSettings

Settings to configure your translation output. You can configure the following options:

- Brevity: reduces the length of the translation output for most translations. Available for TranslateText only.
- Formality: sets the formality level of the translation output.
- Profanity: masks profane words and phrases in the translation output.

Contents

Brevity

When you turn on brevity, Amazon Translate reduces the length of the translation output for most translations (when compared with the same translation with brevity turned off). By default, brevity is turned off.

If you turn on brevity for a translation request with an unsupported language pair, the translation proceeds with the brevity setting turned off.

For the language pairs that brevity supports, see <u>Using brevity</u> in the Amazon Translate Developer Guide.

Type: String

Valid Values: ON

Required: No

Formality

You can specify the desired level of formality for translations to supported target languages. The formality setting controls the level of formal language usage (also known as <u>register</u>) in the translation output. You can set the value to informal or formal. If you don't specify a value for formality, or if the target language doesn't support formality, the translation will ignore the formality setting.

If you specify multiple target languages for the job, translate ignores the formality setting for any unsupported target language.

TranslationSettings 115

For a list of target languages that support formality, see <u>Supported languages</u> in the Amazon Translate Developer Guide.

Type: String

Valid Values: FORMAL | INFORMAL

Required: No

Profanity

You can enable the profanity setting if you want to mask profane words and phrases in your translation output.

To mask profane words and phrases, Amazon Translate replaces them with the grawlix string "?\$#@\$". This 5-character sequence is used for each profane word or phrase, regardless of the length or number of words.

Amazon Translate doesn't detect profanity in all of its supported languages. For languages that don't support profanity detection, see <u>Unsupported languages</u> in the Amazon Translate Developer Guide.

If you specify multiple target languages for the job, all the target languages must support profanity masking. If any of the target languages don't support profanity masking, the translation job won't mask profanity for any target language.

Type: String

Valid Values: MASK

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

TranslationSettings 116

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see <u>Signing AWS API requests</u> in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: access_key/YYYYMMDD/region/service/aws4_request.

For more information, see Create a signed AWS API request in the IAM User Guide.

Common Parameters 117

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see Elements of an AWS API request signature in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see <u>AWS services that work with IAM</u> in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Common Parameters 118

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see <u>Create a signed AWS API request</u> in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

Common Errors 119

InvalidClientTokenId

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 400

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

Common Errors 120