



## Ozone+® Spin EE

### Application:

Ozone+ SPIN EE oil is recommended for lubrication of high speed spindles and machine tools spindle bearing & also in timing gears. Positive displacement blowers and trucker's mechanism and hydraulic system of precision machine tools.

### Type & Gradation:

Energy Efficient Spindle Oils (12, 22)

### Description:

Ozone+ SPIN EE Oil is premium grade high performance textile machinery oil. It is especially designed and developed to meet the spindle lubrication requirement and is Energy Efficient Spindle lubricant for the frames. Its special chemical composition possesses excellent chemical & oxidation stability and antiwear, antifoam and antirust characteristics.

### Features & Benefits:

1. Potentially power saving.
2. High wear protection.
3. Excellent oxidation resistance & thermal stability.
4. High resistance to rust & corrosion.

### Pack Size Available:

5ltrs. 10ltrs, 20ltrs. 210ltrs.

# Certificate of Analysis

## **Ozone+® Spin EE** **Physical Properties**

| Physical Properties                             | 12             | 22             |
|-------------------------------------------------|----------------|----------------|
| Appearance                                      | Bright & Clear | Bright & Clear |
| Kinematic<br>Viscosity@40°C, mm <sup>2</sup> /s | 11-14          | 20-24          |
| Viscosity Index                                 | 90 Min.        | 90 Min.        |
| Density @29.5 °C, kg/l                          | 0.81 -0.87     | 0.81 -0.87     |
| Flash Point(COC) °C,                            | 180 Min.       | 180 Min.       |
| Pour Point                                      | <-3            | <-3            |

### **Health and safety**

Based on available information this product is not expected to produce adverse effects on health when used for the intended application and the recommendation if disposing of the product, take care to protect the environment.