Without volume mount :

```yaml
version: '3'

services:
  test-web:
    build:
      context: .
      dockerfile: Dockerfile
    entrypoint:
          - /usr/local/bin/entrypoint.sh
    ports:
      - "3010:3010"
    command: /usr/local/bin/entrypoint.sh test-web

  test-list:
    build:
      context: .
      dockerfile: Dockerfile
    entrypoint:
          - /usr/local/bin/entrypoint.sh
    ports:
      - "4010:4010"
    command: /usr/local/bin/entrypoint.sh test-list

  test-detail:
    build:
      context: .
      dockerfile: Dockerfile
    entrypoint:
          - /usr/local/bin/entrypoint.sh
    ports:
      - "4020:4020"
    command: /usr/local/bin/entrypoint.sh test-detail
test-productrating:
    build:
      context: .
      dockerfile: Dockerfile
    entrypoint:
          - /usr/local/bin/entrypoint.sh
    ports:
      - "4030:4030"
    command: /usr/local/bin/entrypoint.sh test-productrating
```

```yaml
  test-api:
    build:
      context: .
      dockerfile: Dockerfile
    entrypoint:
          - /usr/local/bin/entrypoint.sh
    ports:
      - "4040:4040"
    command: /usr/local/bin/entrypoint.sh test-api

  nginx:
    image: 27863dd9c9fe
  depends_on:
      - test-web
      - test-api
      - test-listapi
      - test-detailapi
      - test-productapi

networks:
  default:
    name: test
```
docker image build -t test-imag Dockerfile1

Mount volume :

```yaml
version: '3'

services:
  test-web:
    build:
      context: .
      dockerfile: Dockerfile
    entrypoint: /usr/local/bin/entrypoint.sh test-web
    ports:
      - "3010:3010"
    volumes:
      -
/home/cloudpanel/htdocs/mono-test/ubuy_mono_repo/:/home/cloudpanel/htdocs/mono-test/ubuy_mono_repo/

  test-list:
```

```yaml
    build:
      context: .
      dockerfile: Dockerfile
    entrypoint: /usr/local/bin/entrypoint.sh test-list
    ports:
      - "4010:4010"
    volumes:
      -
/home/cloudpanel/htdocs/mono-test/ubuy_mono_repo/:/home/cloudpanel/htdocs/mono-test/ubuy_mono_repo/
  test-detail:
    build:
      context: .
      dockerfile: Dockerfile
    entrypoint: /usr/local/bin/entrypoint.sh test-detail
    ports:
      - "4020:4020"
    volumes:
      -
/home/cloudpanel/htdocs/mono-test/ubuy_mono_repo/:/home/cloudpanel/htdocs/mono-test/ubuy_mono_repo/
  test-productrating:
    build:
      context: .
      dockerfile: Dockerfile
    entrypoint: /usr/local/bin/entrypoint.sh test-productrating
    ports:
      - "4030:4030"
    volumes:
      -
/home/cloudpanel/htdocs/mono-test/ubuy_mono_repo/:/home/cloudpanel/htdocs/mono-test/ubuy_mono_repo/
  test-api:
    build:
      context: .
      dockerfile: Dockerfile
    entrypoint: /usr/local/bin/entrypoint.sh test-api
    ports:
      - "4040:4040"
    volumes:
      -
/home/cloudpanel/htdocs/mono-test/ubuy_mono_repo/:/home/cloudpanel/htdocs/mono-test/ubuy_mono_repo/
  nginx:
```

```yaml
    image: 27863dd9c9fe
    depends_on:
      - test-web
      - test-api
      - test-list
      - test-detail
      - test-productrating

networks:
  default:
    name: test
```