

```

ser www-data;
worker_processes auto;
pid /run/nginx.pid;
include /etc/nginx/modules-enabled/*.conf;

events {
    worker_connections 768;
    # multi_accept on;
}

http {

    map $http_cloudfront_viewer_country $cf_country {
        default "";
        ~(.+) $ $1;
    }

    log_format main '$http_x_forwarded_for - $remote_user [$time_local] '
        '"$request_method $scheme://$host$request_uri $server_protocol" '
        '$status $body_bytes_sent "$http_referer" '
        '"$http_user_agent" $request_time '
        '"$cf_country"';
    ##
    # Basic Settings
    ##

    sendfile on;
    tcp_nopush on;
    tcp_nodelay on;
    keepalive_timeout 65;
    types_hash_max_size 2048;
    # server_tokens off;

    # server_names_hash_bucket_size 64;
    # server_name_in_redirect off;

    include /etc/nginx/mime.types;
    default_type application/octet-stream;

    ##
    # SSL Settings
    ##

```

```
ssl_protocols TLSv1 TLSv1.1 TLSv1.2 TLSv1.3; # Dropping SSLv3, ref: POODLE
ssl_prefer_server_ciphers on;

##
# Logging Settings
##

access_log /var/log/nginx/access.log;
error_log /var/log/nginx/error.log;
##
# Gzip Settings
##

gzip on;

gzip_vary on;
gzip_proxied any;
gzip_comp_level 8;
gzip_buffers 16 8k;
gzip_http_version 1.1;
gzip_types text/plain text/css application/json application/javascript text/xml application/xml
application/xml+rss text/javascript;
#gzip_types text/plain application/javascript application/x-javascript text/javascript
text/xml text/css;

##
# Virtual Host Configs
##

include /etc/nginx/conf.d/*.conf;
include /etc/nginx/sites-enabled/*;
}
```