

PostgreSQL - GROUP BY

The PostgreSQL **GROUP BY** clause is used in collaboration with the SELECT statement to group together those rows in a table that have identical data. This is done to eliminate redundancy in the output and/or compute aggregates that apply to these groups.

The GROUP BY clause follows the WHERE clause in a SELECT statement and precedes the ORDER BY clause.

Syntax

The basic syntax of GROUP BY clause is given below. The GROUP BY clause must follow the conditions in the WHERE clause and must precede the ORDER BY clause if one is used.

```
SELECT column-list
FROM table_name
WHERE [ conditions ]
GROUP BY column1, column2....columnN
ORDER BY column1, column2....columnN
```

You can use more than one column in the GROUP BY clause. Make sure whatever column you are using to group, that column should be available in column-list.

Example

Consider the table COMPANY having records as follows –

```
# select * from COMPANY;
 id | name  | age | address  | salary
-----+-----+-----+-----+-----
  1 | Paul  |  32 | California | 20000
  2 | Allen |  25 | Texas     | 15000
  3 | Teddy |  23 | Norway    | 20000
  4 | Mark  |  25 | Rich-Mond | 65000
  5 | David |  27 | Texas     | 85000
  6 | Kim   |  22 | South-Hall | 45000
  7 | James |  24 | Houston   | 10000
(7 rows)
```

If you want to know the total amount of salary of each customer, then GROUP BY query would be as follows –

```
testdb=# SELECT NAME, SUM(SALARY) FROM COMPANY GROUP BY NAME;
```

This would produce the following result –

name	sum
Teddy	20000
Paul	20000
Mark	65000
David	85000
Allen	15000
Kim	45000
James	10000

(7 rows)

Now, let us create three more records in COMPANY table using the following INSERT statements –

```
INSERT INTO COMPANY VALUES (8, 'Paul', 24, 'Houston', 20000.00);
INSERT INTO COMPANY VALUES (9, 'James', 44, 'Norway', 5000.00);
INSERT INTO COMPANY VALUES (10, 'James', 45, 'Texas', 5000.00);
```

Now, our table has the following records with duplicate names –

id	name	age	address	salary
1	Paul	32	California	20000
2	Allen	25	Texas	15000
3	Teddy	23	Norway	20000
4	Mark	25	Rich-Mond	65000
5	David	27	Texas	85000
6	Kim	22	South-Hall	45000
7	James	24	Houston	10000
8	Paul	24	Houston	20000
9	James	44	Norway	5000
10	James	45	Texas	5000

(10 rows)

Again, let us use the same statement to group-by all the records using NAME column as follows –

```
testdb=# SELECT NAME, SUM(SALARY) FROM COMPANY GROUP BY NAME ORDER BY NAME;
```

This would produce the following result –

name	sum
Allen	15000
David	85000
James	20000
Kim	45000
Mark	65000
Paul	40000
Teddy	20000

(7 rows)

Let us use ORDER BY clause along with GROUP BY clause as follows –

```
testdb=# SELECT NAME, SUM(SALARY)
        FROM COMPANY GROUP BY NAME ORDER BY NAME DESC;
```

This would produce the following result –

name	sum
Teddy	20000
Paul	40000
Mark	65000
Kim	45000
James	20000
David	85000
Allen	15000

(7 rows)