

# 3sm-web App Summary

Repo-based one-page overview

Evidence source: Angular app, routes, services, environments, and repo docs.

## What it is

3sm-web is an Angular 16 single-page business application with login, JWT auth, route-guarded modules, and REST-backed CRUD workflows. Repo evidence shows modules for account and instance management, users and roles, product and tax masters, sales and inventory flows, finance, and DigiCard/VCard features.

## Who it's for

Primary persona: internal admin and operations staff managing account-scoped or instance-scoped business data.

Formal persona definition: Not found in repo.

## What it does

- Provides login plus forgot-password flows, then stores JWT, user data, and permissions in localStorage.
- Shows a route-guarded dashboard and admin screens for accounts, instances, users, user roles, city, GST, and VAT.
- Supports product, customer, and supplier management through dedicated lazy-loaded feature modules.
- Runs sales and inventory-sales workflows, including summaries, invoice numbering, edit flows, and printable sales output.
- Handles purchase, finance, receipts redirects, and ledger screens for products and sales.
- Includes DigiCard and public card routes, plus a VCard area backed by a separate VCard API base URL.

## How it works

- Frontend: Angular SPA (`AppModule`) with lazy-loaded feature modules under `/pages` and a separate `/login` module.
- Access control: `RoleGuard` checks authentication plus resource/action permissions; Super Admin gets full access.
- Auth/data flow: login calls `/auth/login`; `AuthInterceptor` adds the token to API requests and logs out on HTTP 401.
- State: token, user profile, email, and login permissions are cached in localStorage; `PermissionService` normalizes permission keys for route and UI checks.
- Services/backend: feature services use `HttpClient` against `environment.apiUrl` (`https://api.connectsite.in` in default env). RBAC docs describe account-level vs instance-level scope and related `/rbac/...` endpoints.
- Persistence layer / database technology: Not found in repo. SQL files are present, but live backend storage is not defined here.

## How to run

- Install dependencies: `npm install`.
- Start the app: `npm start`.
- Open `http://localhost:4200/`.
- Optional local API config: `npm run start:server` uses `environment.local-server.ts`.