

SQL String Functions Notes

UPPER()

Converts a string to uppercase.

Example: `SELECT UPPER('devvrat');` → DEVVRAT

LOWER()

Converts a string to lowercase.

Example: `SELECT LOWER('DEVVRAT');` → devvrat

LENGTH()

Returns the number of characters.

Example: `SELECT LENGTH('DEVVRAT');` → 7

TRIM()

Removes spaces from both sides.

Example: `SELECT TRIM(' Hello ');` → Hello

LTRIM()

Removes spaces from the left.

Example: `SELECT LTRIM(' Hello');` → Hello

RTRIM()

Removes spaces from the right.

Example: `SELECT RTRIM('Hello ');` → Hello

CONCAT()

Joins strings together.

Example: `SELECT CONCAT('Hello', ' ', 'World');` → Hello World

SUBSTRING()

Extracts part of a string.

Example: `SELECT SUBSTRING('DEVVRAT',1,3);` → DEV

LEFT()

Returns characters from the left.

Example: `SELECT LEFT('DEVVRAT',3);` → DEV

RIGHT()

Returns characters from the right.

Example: `SELECT RIGHT('DEVVRAT',3);` → RAT

REPLACE()

Replaces one substring with another.

Example: `SELECT REPLACE('I love SQL','SQL','Python');` → I love Python

POSITION()

Returns the position of a substring.

Example: `SELECT POSITION('@' IN 'dev@gmail.com');` → 4

CHAR_LENGTH()

Returns the number of characters.

Example: `SELECT CHAR_LENGTH('DEVVRAT');` → 7

REVERSE()

Reverses a string.

Example: `SELECT REVERSE('HELLO');` → OLLEH

INITCAP() (PostgreSQL)

Capitalizes the first letter of each word.

Example: `SELECT INITCAP('devvrat tiwari');` → Devvrat Tiwari

LPAD()

Pads characters on the left.

Example: `SELECT LPAD('123',5,'0');` → 00123

RPAD()

Pads characters on the right.

Example: `SELECT RPAD('123',5,'0');` → 12300

SPLIT_PART() (PostgreSQL)

Splits a string by a delimiter.

Example: `SELECT SPLIT_PART('dev@gmail.com','@',2);` → gmail.com

LIKE Operator

Pattern matching:

'A%' = starts with A

'%h' = ends with h

'%man%' = contains man

'_____' = exactly 5 characters

Most Important Functions for Data Analysts

UPPER(), LOWER(), TRIM(), CONCAT(), SUBSTRING(), REPLACE(), LIKE, LEFT(), RIGHT(), SPLIT_PART().