

Windows Event Collector Functions

The following list briefly describes the functions that are used in Windows Event Collector.

In this section

EcClose

Closes a handle received from other Event Collector functions.

EcDeleteSubscription

Deletes an existing subscription.

EcEnumNextSubscription

Continues the enumeration of the subscriptions registered on the local machine.

EcGetObjectArrayProperty

Retrieves property values for the event sources of a subscription.

EcGetObjectArraySize

Retrieves the number of indexes of the array of property values for the event sources of a subscription.

EcGetSubscriptionProperty

Retrieves a property value from a subscription object.

EcGetSubscriptionRunTimeStatus

Retrieves the run time status information for an event source of a subscription or the subscription itself.

EcInsertObjectArrayElement

Inserts an empty object into an array of property values for the event sources of a subscription.

EcOpenSubscriptionEnum

Creates a subscription enumerator to enumerate all registered subscriptions on the local machine.

EcOpenSubscription

Opens an existing subscription or creates a new subscription.

EcSaveSubscription

Saves subscription configuration information.

EcSetObjectArrayProperty

Sets a property value in an array of property values for the event sources of a subscription.

EcSetSubscriptionProperty

Sets new values or updates existing values of a subscription.

EcRemoveObjectArrayElement

Removes an element from an array of objects that contain property values for the event sources of a subscription.

EcRetrySubscription

Retries connecting to the event source of a subscription that is not connected.

© 2018 Microsoft