



JAKARTA EE

Jakarta Web Services Metadata

Jakarta Web Services Metadata Team,
<https://projects.eclipse.org/projects/ee4j.jaxws>

3.0-RC2, May 29, 2020

Table of Contents

Eclipse Foundation Specification License	1
Disclaimers	2
1. Scope	3
Jakarta Web Services Metadata Specification, Version 2.1	4
2. Introduction	5
2.1. 1.1 Expert Group Members	5
2.2. 1.2 Acknowledgements	6
2.3. 1.3 Conventions	6
2.4. 1.4 Objectives	6
3. 2 Concepts	8
3.1. 2.1 Programming Model Overview	8
3.2. 2.2 Development Models	8
4. 2.2.1 Start with Java	9
5. 2.2.2 Start with WSDL	10
6. 2.2.3 Start with WSDL and Java	11
6.1. 2.3 Processor Responsibilities	11
6.2. 2.4 Runtime Responsibilities	11
6.3. 2.5 Metadata Use	12
7. 2.5.1 Error Checking	13
8. 2.5.2 Default Values	14
8.1. 2.6 Web Services Metadata	14
9. 2.6.2 Binding Annotations	16
10. 2.6.3 Handler Annotations	17
11. 3 Server Programming Model	18
11.1. 3.1 Service Implementation Bean	18
11.2. 3.2 Service Endpoint Interface	18
11.3. 3.3 Web Method	19
12. 4 Web Services Metadata	20
13. 4.1.2 Annotation Type Definition	24
14. 4.2.2 Annotation Type Definition	26
15. Resulting WSDL:	27
16. 4.3.2 Annotation Type Definition	28
17. 4.4.2 Annotation Type Definition	31
18. Resulting WSDL:	33
18.1. 4.5 Annotation: javax.jws.WebResult	35
19. 4.5.1 Description	36

20. 4.5.2 Annotation Type Definition	38
21. Resulting WSDL:	39
22. 4.6.2 Annotation Type Definition	42
23. Java Source:	43
24. Located in /home/mywork/src/com/jsr181/examples/	44
25. Handler Chain Configuration File	45
26. Located in /home/mywork/src/com/jsr181/examples/config/	46
27. 4.7.2 Annotation Type Definition	50
28. 4.7.3 Examples	51
29. Example 1 – RPC/LITERAL	52
30. Java source:	53
31. Resulting WSDL:	54
32. Example 2 – DOCUMENT/LITERAL/BARE	56
33. Java source:	57
34. Resulting WSDL:	58
35. Example 3 – DOCUMENT/LITERAL/WRAPPED	60
36. Java source:	61
37. Resulting WSDL:	62
37.1. 4.8 Annotation: javax.jws.soap.SOAPMessageHandlers	64
38. 5 Java Mapping To XML/WSDL	65
38.1. 5.1 Service Endpoint Interface	65
38.2. 5.2 Web Service Class Mapping	65
38.3. 5.3 Web Method Mapping	66
39. 6 SOAP Binding	67
39.1. 6.1 Operation Modes	67
40. 6.1.1 RPC Operation Style	68
41. 6.1.2 Document Operation Style	69
42. 6.1.3 Document “Wrapped” Style	70
43. 6.1.4 Document “Bare” Style	71
43.1. 6.2 Headers	71
44. 7 Using JSR-181 Annotations to Affect the Shape of the WSDL	73
44.1. 7.1 RPC Literal Style	73
45. Java source:	74
46. Resulting WSDL:	76
46.1. 7.2 Document Literal Style	80
47. Java source:	81
48. Resulting WSDL:	82
49. 8 References	88

50. Appendix A: Relationship to Other Standards	89
51. Appendix B: Handler Chain Configuration File Schema	90
52. Appendix C: Non-Normative Examples of Alternate Binding Annotations.....	91
53. C.1.2 Annotation Type Definition.....	92
54. C.1.3 Example	93
55. Appendix D: Change Log	94

Specification: Jakarta Web Services Metadata

Version: 3.0-RC2

Status: DRAFT

Release: May 29, 2020

Copyright (c) 2019 Eclipse Foundation.

Eclipse Foundation Specification License

By using and/or copying this document, or the Eclipse Foundation document from which this statement is linked, you (the licensee) agree that you have read, understood, and will comply with the following terms and conditions:

Permission to copy, and distribute the contents of this document, or the Eclipse Foundation document from which this statement is linked, in any medium for any purpose and without fee or royalty is hereby granted, provided that you include the following on ALL copies of the document, or portions thereof, that you use:

- link or URL to the original Eclipse Foundation document.
- All existing copyright notices, or if one does not exist, a notice (hypertext is preferred, but a textual representation is permitted) of the form: "Copyright (c) [\$date-of-document] Eclipse Foundation, Inc. [\[url to this license\]](#)"

Inclusion of the full text of this NOTICE must be provided. We request that authorship attribution be provided in any software, documents, or other items or products that you create pursuant to the implementation of the contents of this document, or any portion thereof.

No right to create modifications or derivatives of Eclipse Foundation documents is granted pursuant to this license, except anyone may prepare and distribute derivative works and portions of this document in software that implements the specification, in supporting materials accompanying such software, and in documentation of such software, PROVIDED that all such works include the notice below. HOWEVER, the publication of derivative works of this document for use as a technical specification is expressly prohibited.

The notice is:

"Copyright (c) 2018 Eclipse Foundation. This software or document includes material copied from or derived from [title and URI of the Eclipse Foundation specification document]."

Disclaimers

THIS DOCUMENT IS PROVIDED "AS IS," AND THE COPYRIGHT HOLDERS AND THE ECLIPSE FOUNDATION MAKE NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR TITLE; THAT THE CONTENTS OF THE DOCUMENT ARE SUITABLE FOR ANY PURPOSE; NOR THAT THE IMPLEMENTATION OF SUCH CONTENTS WILL NOT INFRINGE ANY THIRD PARTY PATENTS, COPYRIGHTS, TRADEMARKS OR OTHER RIGHTS.

THE COPYRIGHT HOLDERS AND THE ECLIPSE FOUNDATION WILL NOT BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF ANY USE OF THE DOCUMENT OR THE PERFORMANCE OR IMPLEMENTATION OF THE CONTENTS THEREOF.

The name and trademarks of the copyright holders or the Eclipse Foundation may NOT be used in advertising or publicity pertaining to this document or its contents without specific, written prior permission. Title to copyright in this document will at all times remain with copyright holders.

Chapter 1. Scope

Jakarta Web Services Metadata defines a programming model for Web Services in Java, use of metadata, a non-normative processing model for metadata annotated web service source files, runtime requirements for a container, and annotations used for WSDL, binding, and configuration.

Jakarta Web Services Metadata Specification, Version 2.1

Copyright (c) 2002, 2019 Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Chapter 2. Introduction

This specification defines a simplified programming model that facilitates and accelerates the development of enterprise Web Services. Java EE standard deployment technologies, APIs, and protocols require the Java EE developer to master a substantial amount of information. This JSR reduces the amount of information required to implement Web Services on Java EE by using metadata to specify declaratively the Web Services that each application provides. The metadata annotates the Java source file that implements the Web Service. Although the metadata is human-readable and editable with a simple text editor, graphical development tools can represent and edit the Java source file with higher levels of abstraction specific to Web Services. These tools represent a simpler and more powerful development environment than do traditional coding tools that are used to develop source code with low level APIs.

This specification relies on the JSR-175 specification “A Program Annotation Facility for the Java™ Programming Language” for the Web Services metadata that annotates a Web Service implementation. This document uses JSR-175 features as described in the Public Draft Specification of JSR-175.

JSR-181 defines the syntax and semantics of Java Web Service (JWS) metadata and default values and implementers are expected to provide tools that map the annotated Java classes onto a specific runtime environment. This specification does not define a Java environment in which Web Services are run; however, the use of a J2SE 5.0 compiler is assumed. In particular, it is assumed in JSR-181 that features such as JAX-WS 2.0 and JSR-109, along with the compiler and language extensions from JSR-175, are present.

A JSR-181 implementation **MUST** produce a deployable JWS application that can run in the target Java environment. The deployed application **MUST** exhibit the proper behavior described by the Web Services metadata and Java source code. Any two JSR-181 processors starting from the same valid annotated JWS file **MUST** produce equivalent Web Service applications, even though they may deploy in very different Java environments. This consistency ensures portability of JSR-181 compliant Java files.

2.1. 1.1 Expert Group Members

The following people have been part of the JSR-181 Expert Group

Alexander Aptus (Togethersoft Corporation)

John Bossons

Charles Campbell

Shih-Chang Chen (Oracle)

Alan Davies (SeeBeyond Technology Corp)

Stuart Edmondston (BEA Systems)

John Harby

RajivMordani (Sun Microsystems)

Michael Morton (IBM)

Simon Nash (IBM)

Mark Pollack

Srividya Rajagopalan (Nokia)

Krishna Sankar (Cisco Systems)

Manfred Schneider (SAP AG)

John Schneider (BEA Systems)

Kalyan Seshu (Paramati Technologies)

Rahul Sharma (Motorola)

Michael Shenfield (Research In Motion)

Evan Simeone (PalmSource)

Brian Zotter (BEA Systems)

2.2. 1.2 Acknowledgements

Manoj Cheenath (BEA Systems), Don Ferguson (BEA Systems), Chris Fry (BEA Systems), Neal Yin (BEA Systems), Beverley Talbott (BEA Systems), Matt Mihic, Jim Trezzo, Doug Kohlert (Sun Microsystems), Jitendra Kotamraju (Sun Microsystems), and Rama Pulavarthi (Sun Microsystems) have all provided valuable technical input to this specification.

2.3. 1.3 Conventions

The keywords ‘MUST’, ‘MUST NOT’, ‘REQUIRED’, ‘SHALL’, ‘SHALL NOT’, ‘SHOULD’, ‘SHOULD NOT’, ‘RECOMMENDED’, ‘MAY’, and ‘OPTIONAL’ in this document are to be interpreted as described in RFC 2119[11].

2.4. 1.4 Objectives

The following objectives describe the scope of this specification:

- Define an annotated Java syntax for programming Web Service applications.

- Provide a simplified model for Web Service development that facilitates and accelerates development.
- Provide a syntax that is amenable to manipulation by tools.
- Define a standard for building and deploying Web Services without requiring knowledge and implementation of generalized APIs and deployment descriptors.

This specification addresses the need to simplify:

- Development of server applications that conform both to basic SOAP and WSDL standards.
- Building Web Services that can be deployed with the core Web Services APIs and existing J2EE standards.
- Separate control of public Web Service message contracts and private implementation signatures, because in practice public and private formats evolve on different schedules.

It is not a goal of this specification to support every feature or to enable the creation of every Web Service that it is possible to write within existing specifications (JAX-WS 2.0 [5] provides finer control over the resultant Web Service). The goal is to make it easy to build the most common types of Web Services.

Chapter 3. 2 Concepts

This section summarizes the following concepts and processes of the JSR-181 specification:

- Programming model for JSR-181 Web Services
- Use of metadata in JSR-181
- Non-normative processing model for a JWS file
- Runtime requirements for a JSR-181 container
- Annotations used for WSDL, binding and configuration

The metadata is formally described in section 4.

3.1. 2.1 Programming Model Overview

JSR-181, along with JAX-WS and JSR-109, defines a programming model for building a Web Service. A developer who builds a Web Service with these technologies is required to write and manage several artifacts: a WSDL document describing the external Web Service contract; a service endpoint interface defining the Java representation of the Web Service interface; a service implementation bean containing the Web Service implementation; and one or more deployment descriptors linking the WSDL, interface, and implementation into a single artifact. JSR-181 simplifies this model by allowing the developer to write only the service implementation bean - *actual business logic* – and use annotations to generate the remaining artifacts.

3.2. 2.2 Development Models

JSR-181 defines several different models of Web Service development. Only the Start with Java development model is REQUIRED by implementations.

Chapter 4. 2.2.1 Start with Java

Following the “Start with Java” development model, the developer begins by writing a Java class to expose as a Web Service. The developer then runs this Java class through the JSR-181 processor, which produces WSDL, schema, and other deployment artifacts from the annotated Java code. By default, the WSDL produced from the Java source follows the Java to XML/WSDL mapping defined by JAX-WS 2.0. However, the developer may customize the generated WSDL through annotations on the Java source. For example, the developer may use the `@WebService.name` annotation to set explicitly the name of the `wsdl:portType` representing the Web Service.

JSR-181 also supports a development model where the service is defined in Java but the messages and types are defined in XML schema. In this model, the developer starts by defining a set of types and elements in XML schema. The schema definitions are passed through a “schema to Java” compiler to produce a corresponding set of Java types. The resulting Java types are then used as parameters and return values on methods in an annotated service implementation bean. The WSDL produced from this service implementation bean imports or directly includes the schema definitions that match the Java types used by the service.

Chapter 5. 2.2.2 Start with WSDL

Following the “start with WSDL” development model, the developer uses JSR-181 to implement a predefined WSDL interface. Typically, this process begins with the developer passing a pre-existing WSDL 1.1 file through an implementation-supplied tool to produce a service endpoint interface that represents the Java contract, along with Java classes that represent the schema definitions and message parts contained in the WSDL. The developer then writes a service implementation bean that implements the service endpoint interface. In this model, JSR-181 annotations supply implementation details that are left out of the original WSDL contract, such as binding or service location information.

Chapter 6. 2.2.3 Start with WSDL and Java

Following the “start with WSDL and Java” development model, the developer uses JSR-181 annotations to associate a service implementation bean with an existing WSDL contract. In this model, the JSR-181 annotations map constructs on the Java class or interface to constructs on the WSDL contract. For example, the developer could use the `@WebMethod.operationName` annotation to associate a method on the service implementation bean with a predefined `wsdl:operation`. A JSR-181 implementation that supports this model **MUST** provide feedback when a service implementation bean no longer adheres to the contract defined by the original WSDL. The form that this feedback takes depends on the implementation. For example, a source editing tool might provide feedback by highlighting the offending annotations, while a command line tool might generate warnings or fail to process a service implementation bean that does not match the associated WSDL.

6.1. 2.3 Processor Responsibilities

The term “JSR-181 processor” denotes the code that processes the annotations in a JSR-181 JWS file to create a runnable Web Service. Typically this involves generating the WSDL and schemas that represent the service and its messages and the deployment descriptors that configure the service for the target runtime. It may also result in the generation of additional source artifacts.

This specification does not require implementations to follow a particular processing model. An implementation **MAY** use whatever processing model is appropriate to its environment, as long as it produces a running Web Service with the proper contract and runtime behavior. For example, one implementation might process the JSR-181 annotations directly within the Java compiler to generate a deployable Web Service as the output of compilation; another might provide tools to convert a compiled service implementation bean into a set of artifacts that can be deployed into the container; and a third might configure its runtime container directly off the Java source or class file. Each implementation is conformant with JSR-181 as long as it produces a Web Service with the proper runtime behavior.

6.2. 2.4 Runtime Responsibilities

The runtime environment provides lifecycle management, concurrency management, transport services, and security services. This specification defines the set of annotations that a developer may use to specify declaratively the behavior of an application, but does not define a specific runtime environment or container. Instead, the JSR-181 processor is responsible for mapping the annotated Java classes onto a specific runtime environment. This specification envisions – but does not require – several such runtime environments:

- Automatic deployment to a server directory – This is a “drag and drop” deployment model, similar to that used by JSPs. The annotated JWS file is copied in source or class form to a directory monitored by the container. The container examines the annotations in the file to build a WSDL and configures the runtime machinery required for dispatching. This approach provides a simplified deployment model for prototyping and rapid application development (RAD).

- Automatic deployment with external overrides – Similar to approach a), but with the addition of an external configuration file containing overrides to annotations. The additional configuration file allows an administrator to customize the behavior or configuration of the Web Service – such as the endpoint URL - without changing the Java source.
- Generation of Java EE 5 Web Services - In this model, a tool uses the metadata in the annotated Java class to generate a Java EE 5 Web Service based on JSR-109 and JAX-WS. The initial Web Service is generated from the annotated Java source, and the result can be further customized through standard deployment tools, including JSR-88 deployment plans. This feature allows customization of externally modifiable properties at deployment or runtime, without requiring access to the source file for modification and recompilation.

6.3. 2.5 Metadata Use

The metadata that annotates the service implementation bean conforms to the JSR-175 specification and the specific JSR-181 *annotation type* declarations that are defined in this specification in conjunction with the JSR-175 metadata facility. These *annotation type* declarations are contained in packages that MUST be imported by every JSR-181 JWS source file. JSR-175 provides the syntax for expressing the annotation element declarations that are in these packages. This JSR specifies the contents of the `javax.jws` and `javax.jws.soap` packages (see attached APIs).

Developers use a standard Java compiler with support for JSR-175 to compile and validate the service implementation bean. The compiler uses the annotation type declarations in the `javax.jws` and `javax.jws.soap` packages to check for syntax and type mismatch errors in the Web Service metadata. The result of compilation is a Java `.class` file containing the Web Service metadata along with the compiled Java code. The class file format for these annotations is specified by JSR-175. Any Web Service metadata that this JSR designates as runtime-visible is also accessible through the standard `java.lang.reflect` classes from the run-time environment.

Chapter 7. 2.5.1 Error Checking

Although the compiler can check for syntax and type errors by using the annotation type declaration, syntactically valid metadata may still contain semantic errors. Implementations **MUST** provide a validation mechanism to perform additional semantic checking to ensure that a service implementation bean is correct. The validation **MAY** be performed in a separate tool or as part of deployment.

Examples of semantic checks include:

- Ensuring that annotation values match extended types. The Java compiler can ensure that a particular annotation member-value is of the type specified in the annotation type declaration. However, JSR-175 restricts annotations to simple types such as primitives, Strings, and enums. As a result, the compiler cannot ensure that, for example, an annotation member is a valid URL. It can only verify that the member is a String. The JSR-181 implementation **MUST** perform the additional type checking to ensure that the value is a valid URL.
- Ensuring that annotations match the code. For example, the developer **MAY** use the `@Oneway` annotation to indicate that a particular operation does not produce an output message. If the operation is marked `@Oneway`, it **MUST NOT** have a return value or out/in-out parameters. The JSR-181 implementation **MUST** provide feedback if this constraint is violated.
- Ensuring that annotations are consistent with respect to other annotations. For example, it is not legal to annotate a method with the `@Oneway` annotation unless there is also a corresponding `@WebMethod` annotation. The JSR-181 implementation **MUST** ensure these constraints are met.

Note: Certain types of errors **MAY** only be caught when the Web Service is deployed or run.

Chapter 8. 2.5.2 Default Values

JSR-181 defines appropriate defaults for most annotation members. This feature exempts the JWS author from providing tags for the most common Web Service definitions. Although this specification uses the JSR-175 default mechanism wherever possible, this mechanism is only suitable for defining defaults that are constant values. In contrast, many actual default values are not constants but are instead computed from the Java source or other annotations. For example, the default value for the `@WebService.name` annotation is the simple name of the Java class or interface. This value cannot be represented directly as a JSR-175 default. In scenarios where JSR-175 defaults are not sufficient to describe the required default, a “marker” constant is used instead. When the JSR-181 processor encounters this marker constant, the processor treats the member-value as though it had the computed default described in Section 4. For example, when the JSR-181 processor encounters a `@WebService.name` annotation with a value of `""` (the empty string), it behaves as though the name of the Web Service were the name of the Java class.

8.1. 2.6 Web Services Metadata

JSR-181 metadata describes declaratively how the logic of a service implementation bean is exposed over networking protocols as a Web Service. The `@WebService` tag marks a Java class as implementing a Web Service. `@WebMethod` tags identify the individual methods of the Java class that are exposed externally as Web Service operations, as illustrated in the following example. The example uses JSR-175 syntax and the *annotation type* declarations defined in the `javax.jws` and `javax.jws.soap` packages.

```
import javax.jws.WebService;
import javax.jws.WebMethod;

@WebService

public class HelloWorldService

\{

@WebMethod

public String helloWorld()

\{

return "Hello World!";

}

}
```

Most of these metadata tags have reasonable defaults, which are explicitly called out in Section 4. Most of these metadata tags have reasonable defaults, which are explicitly called out in this document. The

JWS author can avoid providing tags for the most common Web Service definitions.

Sections 2.6.1 through 2.6.3 describe the types of annotations provided by JSR-181. **2.6.1 WSDL Mapping Annotations**

WSDL mapping annotations control the mapping from Java source onto WSDL constructs. As described in *2.2 Development Models*, this specification supports both a “start with Java” and a “start with WSDL” development model. In “start with Java,” the WSDL mapping annotations control the shape of the WSDL generated from the Java source. In “start with WSDL,” the WSDL mapping annotations associate the Java source with pre-existing WSDL constructs.

Chapter 9. 2.6.2 Binding Annotations

Binding annotations specify the network protocols and message formats that are supported by the Web Service. For example, the presence of a `@SOAPBinding` annotation tells the processor to make the service available over the SOAP 1.1 message. Fields on this annotation allow the developer to customize the way the mapping of the implementation object onto SOAP messages.

JSR-181 defines a single set of annotations that map the implementation object to the SOAP protocol binding. JSR-181 implementations *MAY* support additional binding annotations for other protocols. Non-normative examples of such binding annotations can be found in Appendix C.

Chapter 10. 2.6.3 Handler Annotations

Handler annotations allow the developer to extend a Web Service with additional functionality that runs before and after the business methods of the Web Service.

Chapter 11. 3 Server Programming Model

This section describes the server programming model for JSR-181. The JSR-181 server programming model is a simplification of the existing Java EE Web Services server programming models, as defined in JAX-WS and JSR-109. JSR-181 simplifies these models by allowing the developer to focus on business logic and using annotations to generate related artifacts.

11.1. 3.1 Service Implementation Bean

A developer who implements Web Services with JSR-181 is responsible for implementing the service implementation bean containing the Web Service's business logic. A JSR-181 service implementation bean **MUST** meet the following requirements:

- The implementation bean **MUST** be an outer public class, **MUST NOT** be final, and **MUST NOT** be abstract.
- The implementation bean **MUST** have a default public constructor.
- The implementation **MUST NOT** define a `finalize()` method.
- The implementation bean **MUST** include a `@WebService` class-level annotation, indicating that it implements a Web Service. More information on the `@WebService` annotation may be found in 4.1 Annotation: `javax.jws.WebService`.
- The implementation bean **MAY** reference a service endpoint interface by using the `@WebService.endpointInterface` annotation. If the implementation bean references a service endpoint interface, it **MUST** implement all the methods on the service endpoint interface. If the implementation bean references a service endpoint interface, that service endpoint interface is used to determine the abstract WSDL contract (portType and bindings). In this case, the service implementation bean **MUST NOT** include any JSR-181 annotations other than `@WebService` and `@HandlerChain`. In addition, the `@WebService` annotation **MUST NOT** include the name annotation element. More information on the `@WebService.endpointInterface` annotation element may be found in 4.1 Annotation: `javax.jws.WebService`.
- If the implementation bean does not reference a service endpoint interface by using the `@WebService.endpointInterface` annotation, the bean class implicitly defines a service endpoint interface (SEI). The SEI **MUST** meet the requirements specified in JAX-WS 2.0 [5], section 3.3

11.2. 3.2 Service Endpoint Interface

A JSR-181 service implementation bean **MAY** reference a service endpoint interface, thus separating the contract definition from the implementation. A JSR-181 service endpoint interface **MUST** meet the requirements specified in JAX-WS 2.0 [5], section 3.4, with the following exceptions:

- The service endpoint interface **MUST** be an outer public interface.
- The service endpoint interface **MUST** include a `@WebService` annotation, indicating that it is

defining the contract for a Web Service.

- The service endpoint interface MAY extend `java.rmi.Remote` either directly or indirectly, but is not REQUIRED to do so.
- All methods on the service endpoint interface, including methods inherited from super-interfaces, are mapped to WSDL operations regardless of whether they include a `@WebMethod` annotation. A method MAY include a `@WebMethod` annotation to customize the mapping to WSDL, but is not REQUIRED to do so.
- The service endpoint interface MAY include other JSR-181 annotations to control the mapping from Java to WSDL.
- The service endpoint interface MUST NOT include the JSR-181 annotation elements `portName`, `serviceName` and `endpointInterface` of the annotation `@WebService`.

11.3. 3.3 Web Method

A method will be exposed as a Web Service operation, making it part of the Web Service's public contract according to rules specified in *3.1 Service Implementation Bean* or in *3.2 Service Endpoint Interface* if the service implementation bean implements a service endpoint interface. An exposed method MUST meet the following requirements.

- The method MUST be public.
- The method's parameters, return value, and exceptions MUST follow the rules defined in JAX-WS 2.0 [5], section 3.6).
- The method MAY throw `java.rmi.RemoteException`, but is not REQUIRED to do so.

Chapter 12. 4 Web Services Metadata

This section contains the specifications of each individual Web Service metadata items. Both the *annotation type* declarations (using JSR-175 syntax) and usage examples are given for each metadata item.

4.1 Annotation: *javax.jws.WebService*

4.1.1 Description

Marks a Java class as implementing a Web Service, or a Java interface as defining a Web Service interface.

Member-Value	Meaning	Default
name	The name of the Web Service. Used as the name of the <code>wsdl:portType</code> when mapped to WSDL 1.1	Simple name of the Java class or interface

targetNamespace	<p>If the <code>@WebService.targetNamespace</code> annotation is on a service endpoint interface, the targetNamespace is used for the namespace for the <code>wsdl:portType</code> (and associated XML elements).</p> <p>If the <code>@WebService.targetNamespace</code> annotation is on a service implementation bean that does NOT reference a service endpoint interface (through the <code>endpointInterface</code> annotation element), the targetNamespace is used for both the <code>wsdl:portType</code> and the <code>wsdl:service</code> (and associated XML elements).</p> <p>If the <code>@WebService.targetNamespace</code> annotation is on a service implementation bean that does reference a service endpoint interface (through the <code>endpointInterface</code> annotation element), the targetNamespace is used for only the <code>wsdl:service</code> (and associated XML elements).</p>	Implementation-defined, as described in JAX-WS 2.0 [5], section 3.2.
serviceName	<p>The service name of the Web Service. Used as the name of the <code>wsdl:service</code> when mapped to WSDL 1.1.</p> <p>This member-value is not allowed on endpoint interfaces.</p>	Simple name of the Java class + "Service"
Member-Value	Meaning	Default

portName	<p>Used as the name of the wsdl:port when mapped to WSDL 1.1.</p> <p>This member-value is not allowed on endpoint interfaces.</p>	@WebService.name + "Port"
wsdlLocation	<p>The location of a pre-defined WSDL describing the service. The wsdlLocation is a URL (relative or absolute) that refers to a pre-existing WSDL file. The presence of a wsdlLocation value indicates that the service implementation bean is implementing a pre-defined WSDL contract. The JSR-181 tool MUST provide feedback if the service implementation bean is inconsistent with the portType and bindings declared in this WSDL. Note that a single WSDL file might contain multiple portTypes and multiple bindings. The annotations on the service implementation bean determine the specific portType and bindings that correspond to the Web Service.</p>	None

endpointInterface	<p>The complete name of the service endpoint interface defining the service's abstract Web</p> <p>Service contract. This annotation allows the developer to separate the interface contract from the implementation. If this annotation is present, the service endpoint interface is used to determine the abstract WSDL contract (portType and bindings). The service endpoint interface MAY include JSR-181 annotations to customize the mapping from Java to WSDL.</p> <p>The service implementation bean MAY implement the service endpoint interface, but is not REQUIRED to do so.</p> <p>This member-value is not allowed on endpoint interfaces.</p>	<p>None.</p> <p>The Web Service contract is generated from annotations on the service implementation bean. If a service endpoint interface is required by the target environment, it will be generated into an implementation-defined package with an implementation-defined name.</p>
-------------------	---	--

Chapter 13. 4.1.2 Annotation Type Definition

```
@Retention(value=RetentionPolicy.RUNTIME)
```

```
@Target({TYPE})
```

```
public @interface WebService \{
```

```
String name() default "";
```

```
String targetNamespace() default "";
```

```
String serviceName() default "";
```

```
String portName() default "";
```

```
String wsdlLocation() default "";
```

```
String endpointInterface() default "";
```

```
};
```

4.1.3 Example

Java source:

```
/**
```

- Annotated Implementation Object

```
*/
```

```
@WebService(
```

```
name = "EchoService",
```

```
targetNamespace    =    "http://www.openuri.org/2004/04/HelloWorld[http://www.openuri.org/2004/04/HelloWorld]"
```

```
)
```

```
public class EchoServiceImpl \{
```

```
@WebMethod
```

```
public String echo(String input) \{
```

```
return input;
```

```
}
```

}

4.2 Annotation: *javax.jws.WebMethod*

4.2.1 Description

Customizes a method that is exposed as a Web Service operation. The `WebMethod` annotation includes the following member-value pairs:

Member-Value	Meaning	Default
<code>operationName</code>	Name of the <code>wsdl:operation</code> matching this method.	Name of the Java method
<code>action</code>	The action for this operation. For SOAP bindings, this determines the value of the soap action.	
<code>exclude</code>	<p>Marks a method to NOT be exposed as a web method. Used to stop an inherited method from being exposed as part of this web service.</p> <p>If this element is specified, other elements MUST NOT be specified for the <code>@WebMethod</code>.</p>	False

This member-value is not allowed on endpoint interfaces.

Chapter 14. 4.2.2 Annotation Type Definition

```
@Retention(value=RetentionPolicy.RUNTIME)
```

```
@Target({METHOD})
```

```
public @interface WebMethod {\
```

```
String operationName() default "";
```

```
String action() default "" ;
```

```
boolean exclude() default false;
```

```
};
```

4.2.3 Example

Java source:

```
@WebService
```

```
public class MyWebService {\
```

```
@WebMethod(operationName = "echoString", action="urn:EchoString")
```

```
public String echo(String input) {\
```

```
return input;
```

```
}
```

```
}
```

Chapter 15. Resulting WSDL:

```

<definitions>

<portType name="MyWebService">

<operation name="echoString"/>

<input message="echoString"/>

<output message="echoStringResponse"/>

</operation>

</portType>

<binding name="PingServiceHttpSoap" type="MyWebService">

<operation name="echoString">

<soap:operation soapAction="urn:EchoString"/>

</operation>

</binding>

</definitions>

```

4.3 Annotation: *javax.jws.Oneway*

4.3.1 Description

Indicates that the given web method has only an input message and no output. Typically, a oneway method returns the thread of control to the calling application prior to executing the actual business method. A JSR-181 processor is REQUIRED to report an error if an

operation marked `@Oneway` has a return value, declares any checked exceptions or has any INOUT or OUT parameters.

Chapter 16. 4.3.2 Annotation Type Definition

```
@Retention(value=RetentionPolicy.RUNTIME)
```

```
@Target({METHOD})
```

```
public @interface Oneway \{
```

```
};
```

4.3.3 Example

Java source:

```
@WebService
```

```
public class PingService \{
```

```
@WebMethod
```

```
@Oneway
```

```
public void ping() \{
```

```
}
```

```
};
```

Resulting WSDL:

```
<definitions>
```

```
<message name="ping"/>
```

```
<portType name="PingService">
```

```
<operation name="ping">
```

```
<input message="ping"/>
```

```
</operation>
```

```
</portType>
```

```
</definitions>
```

4.4 Annotation: *javax.jws.WebParam*

4.4.1 Description

Customizes the mapping of an individual parameter to a Web Service message part and XML element.

Member-Value	Meaning	Default
name	Name of the parameter.	@WebMethod.operation
		Name, if the operation is
	If the operation is rpc style and	document style and the
	@WebParam.partName has not been	parameter style is
	specified, this is name of the	BARE, and the
	wsdl:part representing the	parameter does not map
	parameter.	to a header, and the
	<p>If the operation is document style or the parameter maps to a header, this is the local name of the XML element representing the parameter.</p> <p>A name MUST be specified if the operation is document style, the parameter style is BARE, and the mode is OUT or INOUT.</p>	<p>mode is IN or INOUT.</p> <p>@WebMethod operation Name+"Response", if the operation is document style and the parameter style is BARE, and the parameter does not map to a header, and the mode is OUT.</p> <p>Otherwise, the default is argN, where N represents the index of the parameter in the method signature (starting at arg0).</p>
partName	<p>The name of the wsdl:part representing this parameter. This is only used if the operation is rpc style or if the operation is document style and the parameter style is BARE.</p>	@WebParam.name

targetNamespace	<p>The XML namespace for the parameter.</p> <p>Only used if the operation is document style or the parameter maps to a header.</p> <p>If the target namespace is set to “”, this represents the empty namespace.</p>	<p>The empty namespace, if the operation is document style, the parameter style is WRAPPED, and the parameter does not map to a header.</p> <p>Otherwise, the default is the targetNamespace for the Web Service.</p>
mode	<p>The direction in which the parameter is flowing. One of IN, OUT, or INOUT. The OUT and INOUT modes may only be specified for parameter types that conform to the definition of Holder types (JAX-WS 2.0 [5], section 2.3.3). Parameters that are Holder Types MUST be OUT or INOUT.</p>	<p>IN if not a Holder type. INOUT if a Holder type.</p>
header	<p>If true, the parameter is pulled from a message header rather than the message body.</p>	<p>False</p>

Chapter 17. 4.4.2 Annotation Type Definition

```
@Retention(value=RetentionPolicy.RUNTIME)
```

```
@Target({PARAMETER})
```

```
public @interface WebParam {\
```

```
    public enum Mode {\
```

```
        IN,
```

```
        OUT,
```

```
        INOUT
```

```
    };
```

```
    String name() default "";
```

```
    String partName() default "";
```

```
    String targetNamespace() default "";
```

```
    Mode mode() default Mode.IN;
```

```
    boolean header() default false;
```

```
};
```

4.4.3 Example

Java Source:

```
@WebService(targetNamespace="http://www.openuri.org/jsr181/WebParamExam[http://www.openuri.org/jsr181/WebParamExam]
```

```
    ple")
```

```
@SOAPBinding(style=SOAPBinding.Style.RPC)
```

```
public class PingService {\
```

```
    @WebMethod(operationName = "PingOneWay")
```

```
    @Oneway
```

```
    public void ping(PingDocument ping) {\
```

```
    }
```

```
@WebMethod(operationName = "PingTwoWay") public void ping(
```

```
@WebParam(mode=WebParam.Mode.INOUT)
```

```
PingDocumentHolder ping) {\
```

```
}
```

```
@WebMethod(operationName = "SecurePing")
```

```
@Oneway
```

```
public void ping(
```

```
PingDocument ping,
```

```
@WebParam(header=true)
```

```
SecurityHeader secHeader) {\
```

```
}
```

```
};
```

Chapter 18. Resulting WSDL:

<definitions

xmlns="http://schemas.xmlsoap.org/wsdl/<http://schemas.xmlsoap.org/wsdl/>]"

xmlns:tns="http://www.openuri.org/jsr181/WebParamExample(<http://www.openuri.org/jsr181/WebParamExample>)]"

xmlns:wsdl="http://www.openuri.org/jsr181/WebParamExample(<http://www.openuri.org/jsr181/WebParamExample>)]" xmlns:s="http://www.w3.org/2001/XMLSchema(<http://www.w3.org/2001/XMLSchema>)]" xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/<http://schemas.xmlsoap.org/wsdl/soap/>]" targetNamespace="http://www.openuri.org/jsr181/WebParamExample(<http://www.openuri.org/jsr181/WebParamExample>)]">

<types>

<s:schema elementFormDefault="qualified"

targetNamespace="http://www.openuri.org/jsr181/WebParamExample(<http://www.openuri.org/jsr181/WebParamExample>)]"> <s:complexType name="PingDocument">

1. ..

</s:complexType>

<s:complexType name="SecurityHeader">

1. ..

</s:complexType>

<s:element name="SecurityHeader" type="SecurityHeader"/>

</s:schema>

</ types>

<message name="PingOneWay">

<part name="arg0" type="tns:PingDocument"/>

</message>

<message name="PingTwoWay">

<part name="arg0" type="tns:PingDocument"/>

</message>

```

<message name="PingTwoWayResponse">

<part name="arg0" type="tns:PingDocument"/>

</message>

<message name="SecurePing">

<part name="arg0" type="tns:PingDocument"/> <part name="arg1" element="tns:SecurityHeader"/>
</message>

<portType name="PingService">

<operation name="PingOneWay">

<input message="tns:PingOneWay"/>
</operation>

<operation name="PingTwoWay">

<input message="tns:PingTwoWay"/>

<output message="tns:PingTwoWayResponse"/>

</operation>

<operation name="SecurePing">

<input message="tns:SecurePing"/>
</operation>

</portType>

<binding name="PingServiceHttpSoap" type="tns:PingService"> <soap:binding style="rpc"
transport="http://schemas.xmlsoap.org/soap/http" http://schemas.xmlsoap.org/soap/http"/> <operation
name="PingOneWay">

<soap:operation soapAction="http://openuri.org/PingOneWay" http://openuri.org/PingOneWay"/>

<input>

<soap:body parts="arg0" use="literal"/>

</input>

</operation>

<operation name="PingTwoWay">

```

```
<soap:operation soapAction="http://openuri.org/PingTwoWay[http://openuri.org/PingTwoWay]">
<input>
<soap:body parts="arg0" use="literal"/>
</input>
<output>
<soap:body parts="arg0" use="literal"/>
</output>
</operation>
<operation name="SecurePing">
<soap:operation soapAction="http://openuri.org/SecurePing[http://openuri.org/SecurePing]">
<input>
<soap:body parts="arg0" use="literal"/>
<soap:header message="SecurePing" part="arg1"
use="literal"/>
</input>
</operation>
</binding>
</definitions>
```

18.1. 4.5 Annotation: javax.jws.WebResult

Chapter 19. 4.5.1 Description

Customizes the mapping of the return value to a WSDL part and XML element.

Member-Value	Meaning	Default
name	Name of return value.	@WebParam.operation
		Name+"Response," if
	If the operation is rpc style and	the operation is
	@WebResult.partName has not been	document style and the
	specified, this is the name of the	parameter style is
	wsdl:part representing the return value.	BARE.
		Otherwise, the default is
	If the operation is document style or the return value maps to a header, this is the local name of the XML element representing the return value.	"return."
partName	The name of the wsdl:part representing this return value. This is only used if the operation is rpc style, or if the operation is document	@WebResult.name
	style and the parameter style is BARE.	
targetNamespace	The XML namespace for the return value.	The empty namespace, if the operation is document style, the

	Only used if the operation is	parameter style is
	document style or the return value	WRAPPED, and the
	maps to a header. If the target namespace is set to “”, this represents the empty	return value does not map to a header, Otherwise, the default is
	namespace.	the targetNamespace for the Web Service.
header	If true, the parameter is in the message header rather than the message body.	False

Chapter 20. 4.5.2 Annotation Type Definition

```
@Retention(value=RetentionPolicy.RUNTIME)
```

```
@Target({METHOD})
```

```
public @interface WebResult {\
```

```
String name() default "";
```

```
String partName() default "";
```

```
String targetNamespace() default "";
```

```
boolean header() default false;
```

```
};
```

4.5.3 Example

Java Source:

```
@WebService
```

```
public class CustomerService {\
```

```
@WebMethod
```

```
@WebResult(name="CustomerRecord")
```

```
public CustomerRecord locateCustomer(
```

```
@WebParam(name="FirstName") String firstName,
```

```
@WebParam(name="LastName") String lastName,
```

```
@WebParam(name="Address") USAddress addr)
```

```
}
```

```
};
```

Chapter 21. Resulting WSDL:

```
<definitions>

<types>

<complexType name="CustomerRecord">

...

</complexType>

<complexType name="USAddress">

...

</complexType>

<element name="locateCustomer">

<complexType>

<sequence>

<element name="FirstName" type="xs:string"/>

<element name="LastName" type="xs:string"/>

<element name="Address" type="USAddress"/>

</sequence>

</complexType>

</element>

<element name="locateCustomerResponse">

<complexType>

<sequence>

<element name="CustomerRecord" type="CustomerRecord"/>

</sequence>

</complexType>

</element>
```

```

</types>

<message name="locateCustomer">

<part name="parameters" element="tns:locateCustomer"/>

</message>

<message name="locateCustomerResponse">

<part name="parameters" element="tns:locateCustomerResponse"/>

</message>

<portType name="CustomerService">

<operation name="locateCustomer">

<input message="tns:locateCustomer"/>

<output message="tns:locateCustomerResponse"/>

</operation>

</portType>

</definitions>

```

4.6 Annotation: *javax.jws.HandlerChain*

4.6.1 Description

The `@HandlerChain` annotation associates the Web Service with an externally defined handler chain (JAX-WS 2.0 [5], Section 9).

It is an error to combine this annotation with the `@SOAPMessageHandlers` annotation.

The `@HandlerChain` annotation MAY be present on the endpoint interface and service implementation bean. The service implementation bean's `@HandlerChain` is used if `@HandlerChain` is present on both.

The `@HandlerChain` annotation MAY be specified on the type only. The annotation target includes METHOD and FIELD for use by JAX-WS 2.0 [5]. A JSR-181 Processor is REQUIRED to report an error if the `@HandlerChain` annotation is used on a method.

The `@HandlerChain` annotation contains the following member-values:

Member-Value	Meaning	Default

File	<p>Location of the handler chain file. The location supports 2 formats.</p> <ul style="list-style-type: none"> • An absolute java.net.URL in externalForm. (ex: http://myhandlers.foo.com/handlerfile1.xml) 	None
	<ul style="list-style-type: none"> • A relative path from the source file or class file. (ex: bar/handlerfile1.xml) 	
name	<p>Deprecated as of JSR-181 2.0 with no replacement.</p> <p>The name was originally used to associate a JAX-RPC handler in a handler chain with the web service it is declared in. JAX-WS handlers are associated to Web Services through elements in the handler chain itself. In this version, the name is ALWAYS ignored.</p> <p>This member-value will be permanently removed in a future version of JSR-181.</p>	””

Chapter 22. 4.6.2 Annotation Type Definition

```
@Retention(value=RetentionPolicy.RUNTIME)
```

```
@Target(\{TYPE, METHOD, FIELD\})
```

```
public @interface HandlerChain \{
```

```
String file();
```

```
String name() default "";
```

```
};
```

4.6.3 Examples

Example 1

Chapter 23. Java Source:

Chapter 24. Located in /home/mywork/src/com/jsr181/examples/

```
package com.jsr181.examples
```

```
@WebService
```

```
@HandlerChain(file="config/ProjectHandlers.xml")
```

```
public class MyWebService {\
```

```
};
```

Chapter 25. Handler Chain Configuration File

Chapter 26. Located in /home/mywork/src/com/jsr181/examples/config/

```
<?xml          version="1.0"          encoding="UTF-8"          standalone="yes"?>          <bindings
wsdlLocation="http://localhost:8080/jaxrpc-fromwsdl_handler/test?wsdl[http://localhost:8080/jaxrpc-
fromwsdl\_handler/test?wsdl]"

xmlns="http://java.sun.com/xml/ns/jaxws[http://java.sun.com/xml/ns/jaxws]">

<bindings node="ns1:definitions"

xmlns:ns1="http://schemas.xmlsoap.org/wsdl/http://schemas.xmlsoap.org/wsdl/">
<package name="fromwsdl.handler.client"/>
</bindings>

<bindings
node="ns1:definitions/ns1:types/xs:schema[@targetNamespace='urn:test:types']"

xmlns:xs="http://www.w3.org/2001/XMLSchema[http://www.w3.org/2001/XMLSchema]"
xmlns:ns1="http://schemas.xmlsoap.org/wsdl/http://schemas.xmlsoap.org/wsdl/">

<ns2:schemaBindings   xmlns:ns2="http://java.sun.com/xml/ns/jaxb[http://java.sun.com/xml/ns/jaxb]">
<ns2:package name="fromwsdl.handler.client"/>

</ns2:schemaBindings>

</bindings>

<bindings>

<handler-chains xmlns="http://java.sun.com/xml/ns/javaee[http://java.sun.com/xml/ns/javaee]">

<handler-chain>

<handler>

<handler-

class>fromwsdl.handler.common.BaseLogicalHandler</handler-class>

<init-param>

<param-name>handlerName</param-name>
```

```

<param-value>client0</param-value>

</init-param>

</handler>

</handler-chain>

<handler-chain>

<port-name-pattern xmlns:ns2="urn:test">ns2:Report*</port-name-
pattern>

<handler>

<handler-
class>fromwsdl.handler.common.BaseLogicalHandler</handler-class>

<init-param>

<param-name>handlerName</param-name>

<param-value>client2</param-value>

</init-param>

</handler>

</handler-chain>

<handler-chain>

<port-name-pattern
xmlns:ns2="urn:test">ns2:ReportServicePort</port-name-pattern>

<handler>

<handler-
class>fromwsdl.handler.common.BaseSOAPHandler</handler-class>

<init-param>

<param-name>handlerName</param-name>

<param-value>client6</param-value>

```

```
</init-param>

</handler>

</handler-chain>

<handler-chain>

<protocol-bindings>##SOAP11_HTTP</protocol-bindings>

<handler>

<handler-

class>fromwsdl.handler.common.BaseSOAPHandler</handler-class>

<init-param>

<param-name>handlerName</param-name>

<param-value>client7</param-value>

</init-param>

<soap-role>http://sun.com/client/role1</soap-role>

<soap-role>http://sun.com/client/role2</soap-role>

</handler>

</handler-chain>

<handler-chain>

<protocol-bindings>##SOAP11_HTTP</protocol-bindings>

<handler>

<handler-

class>fromwsdl.handler.common.BaseLogicalHandler</handler-class>

<init-param>

<param-name>handlerName</param-name>

<param-value>client3</param-value>

</init-param>
```

`</handler>``</handler-chain>``</handler-chains>``</bindings>``</bindings`

4.7 Annotation: *javax.jws.soap.SOAPBinding*

4.7.1 Description

Specifies the mapping of the Web Service onto the SOAP message protocol. Section 6 *SOAP Binding* describes the effects of this annotation on generated Web Services. The `SOAPBinding` annotation has a target of `TYPE` and `METHOD`. The annotation may be placed on a method if and only if the `SOAPBinding.style` is `DOCUMENT`. Implementations **MUST** report an error if the `SOAPBinding` annotation is placed on a method with a `SOAPBinding.style` of `RPC`. Methods that do not have a `SOAPBinding` annotation accept the `SOAPBinding` behavior defined on the type.

The `@SOAPBinding` annotation includes the following member-value pairs.

Member-Value	Meaning	Default
Style	Defines the encoding style for messages send to and from the Web Service. One of	DOCUMENT
	DOCUMENT or RPC.	
Use	Defines the formatting style for messages sent to and from the Web Service. One of LITERAL or ENCODED.	LITERAL
parameterStyle	Determines whether method parameters represent the entire message body, or whether the parameters are elements wrapped inside a top-level element named after the operation.	WRAPPED

Chapter 27. 4.7.2 Annotation Type Definition

```
@Retention(value=RetentionPolicy.RUNTIME)
```

```
@Target(\{TYPE, METHOD\})
```

```
public @interface SOAPBinding \{
```

```
    public enum Style \{
```

```
        DOCUMENT,
```

```
        RPC
```

```
    };
```

```
    public enum Use \{
```

```
        LITERAL,
```

```
        ENCODED
```

```
    };
```

```
    public enum ParameterStyle \{
```

```
        BARE,
```

```
        WRAPPED
```

```
    }
```

```
    Style style() default Style.DOCUMENT;
```

```
    Use use() default Use.LITERAL;
```

```
    ParameterStyle parameterStyle() default ParameterStyle.WRAPPED;
```

```
}
```

Chapter 28. 4.7.3 Examples

Chapter 29. Example 1 – RPC/LITERAL

Chapter 30. Java source:

```
@WebService(targetNamespace="http://www.openuri.org/jsr181/SoapBindingE\[http://www.openuri.org/jsr181/SoapBindingE\]
```

```
ample1")
```

```
@SOAPBinding(
```

```
style = SOAPBinding.Style.RPC,
```

```
use = SOAPBinding.Use.LITERAL)
```

```
public class ExampleService {\
```

```
@WebMethod
```

```
public String concat(String first, String second, String third) {\
```

```
return first + second + third;
```

```
}
```

```
}
```

Chapter 31. Resulting WSDL:

<definitions

xmlns="http://schemas.xmlsoap.org/wsdl/<http://schemas.xmlsoap.org/wsdl/>]"

xmlns:tns="http://www.openuri.org/jsr181/SoapBindingExample1(<http://www.openuri.org/jsr181/SoapBindingExample1>)" xmlns:s="http://www.w3.org/2001/XMLSchema(<http://www.w3.org/2001/XMLSchema>)" xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/<http://schemas.xmlsoap.org/wsdl/soap/>]"

targetNamespace="http://www.openuri.org/jsr181/SoapBindingExample1(<http://www.openuri.org/jsr181/SoapBindingExample1>)">

<message name="concat">

<part name="first" type="xs:string"/>

<part name="second" type="xs:string"/>

<part name="third" type="xs:string"/>

</message>

<message name="concatResponse">

<part name="return" type="xs:string"/>

</message>

<portType name="ExampleService">

<operation name="concat">

<input message="tns:concat"/>

<output message="tns:concatResponse"/>

</operation>

</portType>

<binding name="ExampleServiceHttpSoap" type="ExampleService">

<soap:binding style="rpc"

transport="http://schemas.xmlsoap.org/soap/http(<http://schemas.xmlsoap.org/soap/http>)"/>

<operation name="concat">

<soap:operation

```
soapAction="http://www.openuri.org/jsr181/SoapBindingExample1/concat[http://www.openuri.org/jsr181/SoapBindingExample1/concat]">
```

```
<input>
```

```
<soap:body parts="first second third" use="literal"/>
```

```
</input>
```

```
<output>
```

```
<soap:body parts="return" use="literal"/>
```

```
</output>
```

```
</binding>
```

```
</definitions>
```

Chapter 32. Example 2 – DOCUMENT/LITERAL/BARE

Chapter 33. Java source:

```
@WebService(targetNamespace="http://www.openuri.org/jsr181/SoapBindingE\[http://www.openuri.org/jsr181/SoapBindingE\]
```

```
xample2")
```

```
@SOAPBinding(parameterStyle=SOAPBinding.ParameterStyle.BARE)
```

```
public class DocBareService \{
```

```
@WebMethod( operationName="SubmitPO" )
```

```
public SubmitPOResponse submitPO(SubmitPORequest submitPORequest) \{
```

```
}
```

```
}
```

Chapter 34. Resulting WSDL:

<definitions

xmlns="http://schemas.xmlsoap.org/wsdl/<http://schemas.xmlsoap.org/wsdl/>]"

xmlns:tns="http://www.openuri.org/jsr181/SoapBindingExample2(<http://www.openuri.org/jsr181/SoapBindingExample2>)" xmlns:s="http://www.w3.org/2001/XMLSchema(<http://www.w3.org/2001/XMLSchema>)" xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/<http://schemas.xmlsoap.org/wsdl/soap/>]"

targetNamespace="http://www.openuri.org/jsr181/SoapBindingExample2(<http://www.openuri.org/jsr181/SoapBindingExample2>)">

<types>

<s:schema elementFormDefault="qualified"

targetNamespace="http://www.openuri.org/jsr181/SoapBindingExample2(<http://www.openuri.org/jsr181/SoapBindingExample2>)">

<s:element name="SubmitPORequest">

1. ..

</s:element>

<s:element name="SubmitPOResponse">

1. ..

</s:element>

</s:schema>

</types>

<message name="SubmitPO">

<part name="parameters" element="tns:SubmitPORequest"/>

</message>

<message name="SubmitPOResponse">

<part name="parameters" element="tns:SubmitPOResponse"/>

</message>

<portType name="DocBareService">

```

<operation name="SubmitPO">

<input message="tns:SubmitPO"/>

<output message="tns:SubmitPOResponse"/>

</operation>

</portType>

<binding name="DocBareServiceHttpSoap" type="ExampleService">

<soap:binding style="document"

transport="http://schemas.xmlsoap.org/soap/http[http://schemas.xmlsoap.org/soap/http]">

<operation name="SubmitPO">

<soap:operation

soapAction="http://www.openuri.org/jsr181/SoapBindingExample2/SubmitPO[http://www.openuri.org/jsr181/SoapBindingExample2/SubmitPO]"

/>

<input>

<soap:body parts="parameters" use="literal"/>

</input>

<output>

<soap:body parts="parameters" use="literal"/>

</output>

</binding>

</definitions>

```

Chapter 35. Example 3 – DOCUMENT/LITERAL/WAPPED

Chapter 36. Java source:

```

@WebService(targetNamespace="http://www.openuri.org/jsr181/http://www.openuri.org/jsr181/]
SoapBindingExample3")

@SOAPBinding(
    style = SOAPBinding.Style.DOCUMENT,
    use = SOAPBinding.Use.LITERAL,
    parameterStyle = SOAPBinding.ParameterStyle.WRAPPED) public class DocWrappedService

@WebMethod(operationName = "SubmitPO")

@WebResult(name="PurchaseOrderAck")

public PurchaseOrderAck submitPO(

@WebParam(name="PurchaseOrder") PurchaseOrder purchaseOrder) \{

}

}

```

Chapter 37. Resulting WSDL:

<definitions

xmlns="http://schemas.xmlsoap.org/wsdl/<http://schemas.xmlsoap.org/wsdl/>]"

xmlns:tns="http://www.openuri.org/jsr181/SoapBindingExample3(<http://www.openuri.org/jsr181/SoapBindingExample3>)" xmlns:s="http://www.w3.org/2001/XMLSchema(<http://www.w3.org/2001/XMLSchema>)" xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/<http://schemas.xmlsoap.org/wsdl/soap/>]" targetNamespace="http://www.openuri.org/jsr181/<http://www.openuri.org/jsr181/>

SoapBindingExample3">

<types>

<s:schema elementFormDefault="qualified"

targetNamespace="http://www.openuri.org/jsr181/SoapBindingExample3(<http://www.openuri.org/jsr181/SoapBindingExample3>)">

<s:element name="SubmitPO">

<complexType>

<sequence>

<element name="PurchaseOrder"

type="tns:PurchaseOrder"/>

1. . .

</s:element>

<s:element name="SubmitPOResponse">

1. . .

</s:element>

</s:schema>

</types>

<message name="SubmitPO">

<part name="parameters" element="tns:SubmitPO"/>

</message>

```

<message name="SubmitPOResponse">

<part name="parameters" type="tns:SubmitPOResponse"/>

</message>

<portType name="DocWrappedService">

<operation name="SubmitPO">

<input message="tns:SubmitPO"/>

<output message="tns:SubmitPOResponse"/>

</operation>

</portType>

<binding name="ExampleServiceHttpSoap" type="ExampleService">

<soap:binding style="document"

transport="http://schemas.xmlsoap.org/soap/http[http://schemas.xmlsoap.org/soap/http]">

<operation name="SubmitPO">

<soap:operation

soapAction="http://www.openuri.org/jsr181/SoapBindingExample3/SubmitPO[http://www.openuri.org/jsr181/SoapBindingExample3/SubmitPO]"

/>

<input>

<soap:body parts="parameters" use="literal"/>

</input>

<output>

<soap:body parts="parameters" use="literal"/>

</output>

</binding>

</definitions>

```

37.1. 4.8 Annotation: **javax.jws.soap.SOAPMessageHandlers**

Deprecated as of JSR-181 2.0 with no replacement.

This annotation was originally used to create a JAX-RPC handler chain. In this version, the annotation is ALWAYS ignored.

This annotation will be permanently removed in a future version of JSR-181.

Chapter 38. 5 Java Mapping To XML/WSDL

A key goal of JSR-181 is to influence the shape of WSDL generated from a JWS. This section defines the mapping from Java to XML/WSDL. By default, JSR-181 follows the Java to XML/WSDL mapping defined in JAX-WS 2.0 [5] section 3), except as noted in this section. Implementations MAY extend or supplement this mapping, for example, by adding more complete schema support or supporting alternate binding frameworks such as JAXB or SDO (JSR-235). Annotations for such extensions are out-of-scope for this specification.

38.1. 5.1 Service Endpoint Interface

JAX-WS defines a service endpoint interface as the Java representation of an abstract WSDL contract. A service endpoint interface MAY include the following JSR-181 annotations to customize its mapping to WSDL:

- `@WebService.name`, `@WebService.targetNamespace`, and

`@WebService.wsdlLocation`

- `@WebMethod` (all annotation elements)
- `@Oneway`
- `@WebParam` (all annotation elements)
- `@WebResult` (all annotation elements)
- `@SOAPBinding` (all annotation elements)

A service endpoint interface maps to a `wsdl:portType` element within the `wsdl:definitions` for the containing package. The local name and namespace of the `wsdl:portType` map to the values of the service endpoint interface's `@WebService.name` and `@WebService.targetNamespace` annotation elements, respectively.

38.2. 5.2 Web Service Class Mapping

A service implementation bean maps to its own WSDL document, `wsdl:portType`, and `wsdl:service`. If the service implementation bean references a service endpoint interface through the `@WebService.endpointInterface` annotation, the `wsdl:portType` and `wsdl:binding` sections are mapped according to that service endpoint interface. Otherwise, the following rules apply:

- The `wsdl:definitions targetNamespace` maps to the value of the `@WebService.targetNamespace` member-value.
- The local name of the `wsdl:portType` maps to the value of the `@WebService.name` member-value.
- The local name of the `wsdl:service` maps to the value of the `@WebService.serviceName` member-value.

- The `wsdl:service` MUST contain a distinct `wsdl:port` for every transport endpoint supported by the service.
- Each `wsdl:port` MUST be of the same `wsdl:portType`, but MAY have different bindings.
- The local name of the `wsdl:port` maps to the value of the `@WebService.portName` member-value.
- The name `wsdl:binding` sections is not significant and are left implementation-defined.

38.3. 5.3 Web Method Mapping

Each exposed web method in a JSR-181 annotated class or interface is mapped to a `wsdl:operation` on the class/interface WSDL `portType`. The `wsdl:operation` local name maps to the value of the `@WebMethod.operationName` member-value, if [@WebMethod.operationName](#) is present. If `@WebMethod.operationName` is not present, the `wsdl:operation` local name is mapped from the name of the Java method according to the rules defined in JAX-WS 2.0 [5], section 3.5.

The mapped `wsdl:operation` contains both `wsdl:input` and `wsdl:output` elements, unless the method is annotated as `@Oneway`. `@Oneway` methods have only a `wsdl:input` element.

Java types used as method parameters, return values, and exceptions are mapped according to the rules defined in JAX-WS 2.0 [5], section 3.6.

Chapter 39. 6 SOAP Binding

This section defines a standard mapping from a service endpoint interface or service implementation bean to the SOAP 1.1 binding. Implementers MAY also support other bindings, but these bindings are non-standard. If JSR-181 implementation supports bindings other than SOAP 1.1, it MUST include a mechanism to selectively enable or disable these bindings.

By default JSR-181 follows the SOAP binding defined in JAX-WS 2.0 [5], section 10.

39.1. 6.1 Operation Modes

JSR-181 implementations are REQUIRED to support the following WS-I compliant operation modes:

- Operations with the rpc style and literal use (rpc/literal)
- Operations with the document style and literal use (document/literal).

Implementations MAY optionally support operation modes with the encoded use (document or rpc style). The developer MAY indicate which operation mode is in effect by specifying the appropriate `@SOAPBinding.style` and `@SOAPBinding.use` annotations at the class or interface level.

Chapter 40. 6.1.1 RPC Operation Style

In the RPC operation style, the parameters and return values map to separate parts on the WSDL input and output messages. The `@WebParam.mode` annotation determines the messages in which a particular parameter appears. IN parameters appear as parts in the input message, OUT parameters appear as parts in the output message, and INOUT parameters appear as parts in both messages. The order of parameters in the method signature determines the order of the parts in the input and output message. The return value is the first part in the output message.

In the `rpc/literal` operation mode, each message part refers to a concrete schema type. The schema type is derived from the Java type for the parameter, as described in section 5 - Java Mapping To XML/WSDL.

Chapter 41. 6.1.2 Document Operation Style

In the document operation style, the input and output WSDL messages have a single part referencing a schema element that defines the entire body. JSR-181 implementations **MUST** support both the “wrapped” and “bare” styles of document / literal operation. The developer may specify which of these styles is in effect for a particular operation by using the `@SOAPBinding.parameterStyle` annotation.

Chapter 42. 6.1.3 Document “Wrapped” Style

In the “wrapped” operation style, the input and output messages contain a single part which refers (through the *element* attribute) to a global element declaration (the *wrapper*)

of complexType defined using the xsd:sequence compositor. The global element declaration for the input message has a local name equal to @WebMethod.operationName. The global element declaration for the output message (if it exists) has a local name equal to @WebMethod.operationName + “Response”. Both global element declarations appear in the @WebService.targetNamespace.

Non-header method parameters and return values map to child elements of the global element declarations defined for the method. The order of parameters in the parameter list determines the order in which the equivalent child elements appear in the operation’s global element declarations.

The @WebParam.name and @WebParam.targetNamespace annotation elements determine the QName of a parameter’s child element, while the @WebResult.name and @WebResult.targetNamespace annotations determines the QName of the return value’s child element. The schema type for each child element is derived from the type of the Java parameter or return value, as described in section 5 *Java Mapping To XML/WSDL*.

Chapter 43. 6.1.4 Document “Bare” Style

In the “bare” operation style, the input and output messages contain a single part which refers (through the *element* attribute) to an element that is mapped from the method parameter and return value. The QName of the input body element is determined by the values of the `@WebParam.name` and `@WebParam.targetNamespace` annotations on the method parameter, and the QName of the output body element is determined by the values of the `@WebResult.name` and `@WebResult.targetNamespace` annotations. The schema types for the input and output body elements are derived from the types of the Java parameter or return values, as described in section 5 *Java Mapping To XML/WSDL*.

Web Services that use the document “bare” style MUST adhere to the following restrictions:

- If the operation is marked `@Oneway`, it MUST have a void return value, a single non-header parameter marked as IN, and zero or more header parameters.
- If the operation is not marked `@Oneway`, it may have one of the following forms:
 - A non-header parameter marked as IN, a non-header parameter marked as OUT, a void return value, and zero or more header parameters.
 - A single non-header parameters marked as IN_OUT, a void return value, and zero or more header parameters.
 - A single non-header parameter marked as IN, non-void return value and zero or more header parameters.
- The XML elements for the input and output messages MUST be unique across all operations on the Web Service. Consequently, either every document “bare” operation on the Web Service MUST take and return Java types that map to distinct elements, or the developer MUST use the `@WebParam` and `@WebResult`

annotations to explicitly specify the QNames of the input and output XML elements for each operation.

43.1. 6.2 Headers

Parameters annotated with the `@WebParam.header` annotation element map to SOAP headers instead of elements in the SOAP body. Header parameters appear as parts in the operation’s input message, output message, or both depending on the value of the `@WebParam.mode` annotation element. Header parameters are included as `soap:header` elements in the appropriate `wsdl:input` and `wsdl:output` sections of the binding operation. Headers are always literal. The `@WebParam.name` and `@WebParam.targetNamespace` annotations determine the QName of the XML element representing the header.

Results annotated with the `@WebResult.header` annotation element map to SOAP headers instead of elements in the SOAP body. Header results appear as parts in the operation’s output message. Header results are included as `soap:header` elements in the appropriate `wsdl:output` sections of the binding operation. Headers are always literal. The `@WebResult.name` and `@WebResult.targetNamespace` annotations determine the QName of the XML element representing the header. This QName MUST be

unique within all headers of the method.

Chapter 44. 7 Using JSR-181 Annotations to Affect the Shape of the WSDL

44.1. 7.1 RPC Literal Style

Below is a complete example of a java source file with annotations followed by the resulting WSDL:

Chapter 45. Java source:

```

import javax.jws.*;

import javax.jws.soap.*;

@WebService(

name="ExampleWebService",

targetNamespace="http://openuri.org/11/2003/ExampleWebService[http://openuri.org/11/2003/ExampleWebService]") @SOAPBinding(style=SOAPBinding.Style.RPC, use=SOAPBinding.Use.LITERAL)
public class ExampleWebServiceImpl {

    @WebMethod(action="urn:login")
    @WebResult(name="Token")
    public LoginToken login(

        @WebParam(name="UserName") String username,

        @WebParam(name="Password") String password) {

    }

    @WebMethod (action="urn:createCustomer")

    @WebResult(name="CustomerId")

    public String createCustomer(

        @WebParam(name="Customer") Customer customer,

        @WebParam(name="Token", header=true) LoginToken token) {

    }

    @WebMethod(action="urn:notifyTransfer")

    @Oneway

    public void notifyTransfer(

        @WebParam(name="CustomerId") String customerId,

        @WebParam(name="TransferData") TransferDocument transferData,

        @WebParam(name="Token", header=true) LoginToken token) {

    }

```

```
};
```

Chapter 46. Resulting WSDL:

<definitions

name="ExampleWebServiceImplServiceDefinitions"

targetNamespace="http://openuri.org/11/2003/ExampleWebService[<http://openuri.org/11/2003/ExampleWebService>]" xmlns="http://schemas.xmlsoap.org/wsdl/<http://schemas.xmlsoap.org/wsdl/>"
 xmlns:tns="http://openuri.org/11/2003/ExampleWebService[<http://openuri.org/11/2003/ExampleWebService>]" xmlns:xs="http://www.w3.org/2001/XMLSchema[<http://www.w3.org/2001/XMLSchema>]" xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/<http://schemas.xmlsoap.org/wsdl/soap/>]">

<types>

<xs:schema elementFormDefault="qualified"

targetNamespace="http://openuri.org/11/2003/ExampleWebService[<http://openuri.org/11/2003/ExampleWebService>]">

<xs:complexType name="LoginToken">

...

</xs:complexType>

<xs:complexType name="Customer">

...

</xs:complexType>

<xs:complexType name="TransferDocument">

...

</xs:complexType>

<xs:element name="Token" type="LoginToken"/>

</xs:schema>

</types>

<message name="createCustomer">

<part name="Customer" type="tns:Customer"/>

<part element="tns:Token" name="token"/>

</message>

```

<message name="createCustomerResponse">

<part name="CustomerId" type="xs:string"/> </message>

<message name="notifyTransfer">

<part name="CustomerId" type="xs:string"/>

<part name="TransferData" type="tns:TransferDocument"/>

<part name="token" element="tns:Token"/>

</message>

<message name="login">

<part name="UserName" type="xs:string"/> <part name="Password" type="xs:string"/> </message>

<message name="loginResponse">

<part name="Token" type="tns:LoginToken"/>

</message>

<portType name="ExampleWebService">

<operation name="createCustomer"

parameterOrder="Customer token">

<input message="tns:createCustomer"/>

<output message="tns:createCustomerResponse"/>

</operation>

<operation name="notifyTransfer"

parameterOrder="CustomerId TransferData token">

<input message="tns:notifyTransfer"/>

</operation>

<operation name="login"

parameterOrder="UserName Password">

<input message="tns:login"/>

<output message="tns:loginResponse"/>

</operation>

```

```
</portType>

<binding name="ExampleWebServiceImplServiceSoapBinding" type="tns:ExampleWebService">

  <soap:binding style="rpc"

    transport="http://schemas.xmlsoap.org/soap/http" http://schemas.xmlsoap.org/soap/http"/>

    <operation name="createCustomer">

      <soap:operation soapAction="urn:createCustomer" style="rpc"/>

      <input>

        <soap:body

          namespace="http://openuri.org/11/2003/ExampleWebService" http://openuri.org/11/2003/ExampleWebService]"

            parts="Customer"

            use="literal"/>

          <soap:header

            message="tns:createCustomer"

            part="token"

            use="literal"/>

          </input>

          <output>

            <soap:body

              namespace="http://openuri.org/11/2003/ExampleWebService" http://openuri.org/11/2003/ExampleWebService]"

                parts="CustomerId"

                use="literal"/>

            </output>

          </operation>

          <operation name="notifyTransfer">
```

```

<soap:operation soapAction="urn:notifyTransfer" style="rpc"/>

<input>

<soap:body

namespace="http://openuri.org/11/2003/ExampleWebService[http://openuri.org/11/2003/ExampleWebService]"

parts="CustomerId TransferData"

use="literal"/>

<soap:header

message="tns:notifyTransfer"

part="token"

use="literal"/>

</input>

</operation>

<operation name="login">

<soap:operation soapAction="urn:login" style="rpc"/>

<input>

<soap:body

namespace="http://openuri.org/11/2003/ExampleWebService[http://openuri.org/11/2003/ExampleWebService]"

parts="UserName Password"

use="literal"/>

</input>

<output>

<soap:body

namespace="http://openuri.org/11/2003/ExampleWebService[http://openuri.org/11/2003/ExampleWebService]"

parts="Token"

```

```
use="literal"/>

</output>

</operation>

</binding>

<service name="ExampleWebServiceServiceImplService">

  <port

    binding="s1:ExampleWebServiceServiceImplServiceSoapBinding"

    name="ExampleWebServiceSoapPort">

      <soap:address

        location="http://localhost:7001/ExampleWebServiceImpl/ExampleWebService[http://localhost:7001/ExampleWebServiceImpl/ExampleWebService]

        Impl"/>

      </port>

    </service>

  </definitions>
```

46.1. 7.2 Document Literal Style

Below is a complete example of a java source file with annotations followed by the resulting WSDL:

Chapter 47. Java source:

```

import javax.jws.*;

import javax.jws.soap.*;

@WebService(

name="ExampleWebService",

targetNamespace="http://openuri.org/11/2003/ExampleWebService[http://openuri.org/11/2003/ExampleWebService]")
@SOAPBinding(style=SOAPBinding.Style.DOCUMENT,
use=SOAPBinding.Use.LITERAL) public class ExampleWebServiceImpl {

@WebMethod(action="urn:login")

@WebResult(name="Token")
public LoginToken login(

@WebParam(name="UserName") String username,

@WebParam(name="Password") String password) {\

}

@WebMethod (action="urn:createCustomer")

@WebResult(name="CustomerId")

public String createCustomer(

@WebParam(name="Customer") Customer customer,

@WebParam(name="Token", header=true) LoginToken token) {\

}

@WebMethod(action="urn:notifyTransfer")

@Oneway

public void notifyTransfer(

@WebParam(name="CustomerId") String customerId, @WebParam(name="TransferData")
TransferDocument transferData, @WebParam(name="Token", header=true) LoginToken token) {\

}

};

```

Chapter 48. Resulting WSDL:

```
<?xml version='1.0' encoding='UTF-8'?>

<definitions

name="ExampleWebServiceImplServiceDefinitions"

targetNamespace="http://openuri.org/11/2003/ExampleWebService[http://openuri.org/11/2003/ExampleWebService]"
    xmlns="http://schemas.xmlsoap.org/wsdl/http://schemas.xmlsoap.org/wsdl/"
    xmlns:tns="http://openuri.org/11/2003/ExampleWebService[http://openuri.org/11/2003/ExampleWebService]"
    xmlns:xs="http://www.w3.org/2001/XMLSchema[http://www.w3.org/2001/XMLSchema]"
    xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/http://schemas.xmlsoap.org/wsdl/soap/]">

<types>

<xs:schema attributeFormDefault="unqualified"

targetNamespace="http://openuri.org/11/2003/ExampleWebService[http://openuri.org/11/2003/ExampleWebService]">

<xs:complexType name="LoginToken">

...

</xs:complexType>

<xs:complexType name="Customer">

...

</xs:complexType>

<xs:complexType name="TransferDocument">

...

</xs:complexType>

<xs:element name="Token" type="tns:LoginToken"/>

<xs:element name="createCustomer">

<xs:complexType>

<xs:sequence>

<xs:element name="Customer" type="tns:Customer"/>
```

```
</xs:sequence>

</xs:complexType>

</xs:element>

<xs:element name="createCustomerResponse">

  <xs:complexType>

    <xs:sequence>

      <xs:element name="CustomerId" type="xs:string"/>

    </xs:sequence>

  </xs:complexType>

</xs:element>

<xs:element name="notifyTransfer">

  <xs:complexType>

    <xs:sequence>

      <xs:element name="CustomerId" type="xs:string"/>

      <xs:element name="TransferData"

type="tns:TransferDocument"/>

    </xs:sequence>

  </xs:complexType>

</xs:element>

<xs:element name="login">

  <xs:complexType>

    <xs:sequence>

      <xs:element name="UserName" type="xs:string"/>

      <xs:element name="Password" type="xs:string"/>

    </xs:sequence>
```

```
</xs:complexType>

</xs:element>

<xs:element name="loginResponse">

  <xs:complexType>

    <xs:sequence>

      <xs:element name="Token" type="tns:LoginToken"/>

    </xs:sequence>

  </xs:complexType>

</xs:element>

</xs:schema>
</types>

<message name="createCustomer">

  <part element="tns:createCustomer" name="parameters"/>

  <part element="tns:Token" name="token"/>

</message>

<message name="createCustomerResponse">

  <part element="tns:createCustomerResponse" name="parameters"/>

</message>

<message name="notifyTransfer">

  <part element="tns:notifyTransfer" name="parameters"/>

  <part element="tns:Token" name="token"/>

</message>

<message name="login">

  <part element="tns:login" name="parameters"/>

</message>

<message name="loginResponse">
```

```

<part element="tns:loginResponse" name="parameters"/>

</message>

<portType name="ExampleWebService">

  <operation name="createCustomer" parameterOrder="parameters token">

    <input message="tns:createCustomer"/>

    <output message="tns:createCustomerResponse"/>

  </operation>

  <operation name="notifyTransfer" parameterOrder="token">

    <input message="tns:notifyTransfer"/>

  </operation>

  <operation name="login" parameterOrder="parameters">

    <input message="tns:login"/>

    <output message="tns:loginResponse"/>

  </operation>

</portType>

<binding name="ExampleWebServiceImplServiceSoapBinding" type="tns:ExampleWebService">

  <soap:binding style="document"

transport="http://schemas.xmlsoap.org/soap/http[http://schemas.xmlsoap.org/soap/http]"/>

  <operation name="createCustomer">

    <soap:operation soapAction="urn:createCustomer"

style="document"/>

    <input>

      <soap:body parts="parameters" use="literal"/>

      <soap:header message="tns:createCustomer" part="token"

use="literal"/>

```

```
</input>

<output>

<soap:body parts="parameters" use="literal"/>

</output>

</operation>

<operation name="notifyTransfer">

<soap:operation soapAction="urn:notifyTransfer"

style="document"/>

<input>

<soap:body parts="parameters" use="literal"/>

<soap:header message="tns:notifyTransfer" part="token"

use="literal"/>

</input>

</operation>

<operation name="login">

<soap:operation soapAction="urn:login" style="document"/>

<input>

<soap:body parts="parameters" use="literal"/>

</input>

<output>

<soap:body parts="parameters" use="literal"/>

</output>

</operation>

</binding>

<service name="ExampleWebServiceImplService">
```

```
<port binding="tns:ExampleWebServiceImplServiceSoapBinding"
name="ExampleWebServiceSoapPort">
  <soap:address
location="http://localhost:7001/ExampleWebServiceImpl/ExampleWebService[http://localhost:7001/ExampleWebServiceImpl/ExampleWebService]
Impl"/>
</port>
</service>
</definitions>
```

Chapter 49. 8 References

1. JSR-175 A Metadata Facility for the Java™ Programming Language <http://jcp.org/en/jsr/detail?id=175>
2. JSR-88 J2EE Application Deployment
<http://jcp.org/en/jsr/detail?id=88>
3. XML Schema 1.0
<http://www.w2.org/TR/xmlschema-1/http://www.w3.org/TR/xmlschema-1/>
4. J2EE 1.4
<http://jcp.org/en/jsr/detail?id=151>
5. JAX-WS 2.0
<http://www.jcp.org/en/jsr/detail?id=224>
6. Implementing Enterprise Web Services 1.1 (was JSR-109) <http://www.jcp.org/en/jsr/detail?id=921>
7. Web Services Definition Language (WSDL) 1.1
<http://www.w3.org/TR/wsdl>
8. Simple Object Access Protocol (SOAP) 1.1 <http://www.w3.org/TR/2000/NOTE-SOAP-20000508/http://www.w3.org/TR/2000/NOTE-SOAP-20000508/>
9. Apache AXIS "JWS" drop-in deployment of Web Services
10. BEA WebLogic Workshop "JWS" annotated Java Web Services
11. RFC 2119: Keywords for use in RFCs to Indicate Requirement Levels
<http://www.ietf.org/rfc/rfc2119.txt>
12. Common Annotations for the Java Platform
<http://www.jcp.org/en/jsr/detail?id=250>

Chapter 50. Appendix A: Relationship to Other Standards

JSR-181 relies on Java standards, Web Services standards, XML standards and Internet standards.

Java Language standards: J2SE 5.0 is needed for the JSR-175 defined Metadata Facility.

Java runtime and container standards: JSR-181 does not define a container or runtime environment – implementers provide tools to map the Java classes to specific runtime environments. The functionality of the Java EE 5 containers is assumed. The features provided by JAX-WS 2.0 are needed for the Web Services runtime as well as the mapping conventions; Java to XML/WSDL and WSDL/XML to Java. An optional mapping to JSR-109 deployment descriptors is provided in JSR-181.

Web Services standards: SOAP 1.1 and WSDL 1.1 are used to describe the Web Service and define the XML messages.

XML standards: The XML language and the XML Schema 1.0 are an integral part of JSR-181.

Internet standards: HTTP and HTTP/S provide basic protocols for Web Services.

Chapter 51. Appendix B: Handler Chain Configuration File Schema

The XML Schema for the handler chain configuration file is described at <http://java.sun.com/xml/ns/javaee/javaee-web-services-metadata-handler-2.0.xsd>

Chapter 52. Appendix C: Non-Normative Examples of Alternate Binding Annotations

This section defines non-normative examples of annotations for bindings to non-standard protocols and transports.

C.1 Annotation Name: `HttpGetBinding`

C.1.1 Description

Non-normative example of an alternate binding – in this case a raw HTTP binding as specified in WSDL 1.1 [7] section 4.

Member-Value	Meaning	Default
location	The location of the HTTP GET endpoint. When defined at the class level, defines as the base URI for all operations on the service. When defined at the method level, defines the URI for a particular operation relative to the base URI for the service.	Implementation-defined

Chapter 53. C.1.2 Annotation Type Definition

```
@Target(\{TYPE, METHOD\})
```

```
public @interface HttpGetBinding {\
```

```
String location() default "";
```

```
}
```


Chapter 54. C.1.3 Example

```
@WebService
```

```
@HttpGetBinding(location="MyWebServices")
```

```
public class MyWebServiceImpl {\
```

```
    @WebMethod
```

```
    @HttpGetBinding(location="ExampleOperation")
```

```
    public void myOperation() {\
```

```
    }
```

```
};
```

Chapter 55. Appendix D: Change Log

Version 2.1

- Changed specification version and license information.
- Updated Handler Chain Configuration File Schema in Appendix B to fix errors, add missing elements, and make it valid.
- Updated Section 3.1 to clarify the explanation of when an SEI is implicitly defined by an implementation bean. The revised text refers to the appropriate section 3.3 in the JAX-WS 2.0 specification for the actual SEI rules.
- Updated the table in Section 4.4.1 describing the default "name" member value of the `javax.jws.WebParam` annotation to resolve the issue reported in https://jax-ws.dev.java.net/issues/show_bug.cgi?id=710. The requirement to specify a name for "document" style, parameter style "BARE", and mode "OUT" or "INOUT" is lifted and default rules are defined. This change is consistent with section 3.6.2.2 of the JAX-WS 2.0 specification.

Version 2.0

- Added `@WebResult.header`.
- A document "bare" style operation can have a void return type and a Holder as a parameter. The Holder of course would have to be INOUT. It could also have 2 parameters one IN and one OUT.
- Changed `@SOAPBinding` to be configurable on a per operation basis rather than on the entire interface.
- Made `@HandlerChain.name` and `@SOAPMessageHandlers` deprecated.
- Added support for JAX-WS.
- Updated section 3.1 Service Implementation Bean, Item 6 to state that exposing all public methods if not `@WebMethod` annotations are declared to include consideration of annotation inheritance.
- Changed default of `@WebResult.name` to `@WebMethod.operationName` "Response" for Doc/lit/bare operations.
- Clarified `@WebService.targetNamespace` usage
- Clarified `@WebParam.mode` usage.
- Added `@WebMethod.exclude`.
- Explicitly stated that if an implementation bean references an endpoint interface, it must implement all the methods in the service endpoint interface.
- Changed `@WebParam.name` to default to `arg0`, `arg1`, etc (based on position in the method signature).
- Added `@WebParam.partName` and `@WebResult.partName` to specify part name used in the binding.

- Added requirement that the name for headers must be unique with an operation.
- Clarified that a target namespace of "" maps to the empty namespace, not the web service namespace.
- For doc/lit bare, require that any INOUT or OUT parameters must have a `@WebParam.name` specified to avoid name clashes with the input parameter.
- Added `@WebService.portName` for the `wsdl:port`
- Updated Handler schema
- Added document/literal example to Using JSR-181 annotation to affect the shape of the WSDL
- Included various editorial changes.

Version 0.9.4

- Allowing `@HandlerChain` and `@SOAPMessageHandler` on implementation when an `endpointInterface` is used.

Version 0.9.3

- Using RFC 2119 Keyword convention.
- Added Retention annotation to spec annotation definitions.
- Fixed various Java and XML syntax errors.
- Changed Implementation Bean to expose all public method by default.
- WSDL generation is REQUIRED.
- Clarified support for Start with WSDL, and Start with WSDL and Java development modes as OPTIONAL.
- Clarified [@HandlerChain.file](#) attribute syntax and processing requirements.

Version 0.9.2

- Removed security annotations as these will be defined by JSR-250 – Common Annotations.

Version 0.9.1

- Changed default name of `@WebResult` to be "return" instead of "result".
- Fixed various Java and XML syntax errors.