# FULL STACK DEVELOPMENT - I (FSD-1)

## Question Bank Solutions — Unit 4: Cascading Style Sheets (CSS) (Sr. No. 236 to 253)

*For Reference Only*

**Question 236:** Write CSS to get following formatting for the paragraph.
i) text-color-green
ii) text-indentation-2cm
iii) font-courier
iv) font-style-italic
v) text-case-Uppercase

**Solution Code:**

```
/* External or Internal CSS Rule */
p {
    color: green;
    text-indent: 2cm;
    font-family: 'Courier New', Courier, monospace;
    font-style: italic;
    text-transform: uppercase;
}

/* Complete HTML Document Demonstration */
<!DOCTYPE html>
<html>
<head>
    <title>Paragraph Formatting</title>
    <style>
        p.formatted {
            color: green;
            text-indent: 2cm;
            font-family: 'Courier New', Courier, monospace;
            font-style: italic;
            text-transform: uppercase;
        }
    </style>
</head>
<body>
    <p class="formatted">
        This paragraph demonstrates green text color, 2cm indentation, courier font family, italic
style, and uppercase capitalization.
    </p>
</body>
</html>
```

**Question 237:** Write down HTML/CSS code to create table with 5 rows and 3 columns. Even no. of rows display in green color and odd no. of rows display in yellow color. Use External CSS file.

**Solution Code:**

```
/* File 1: ts.css (External CSS) */
table {
    border-collapse: collapse;
    width: 60%;
    margin: 20px auto;
    font-family: Arial, sans-serif;
}

th, td {
    border: 1px solid black;
    padding: 10px;
    text-align: center;
}

tr:nth-child(even) {
    background-color: green;
    color: white;
}

tr:nth-child(odd) {
    background-color: yellow;
    color: black;
}

/* ------------------------------------------------- */
<!-- File 2: index.html (Linked HTML File) -->
<!DOCTYPE html>
<html>
<head>
    <title>5x3 Alternating Color Table</title>
    <link rel="stylesheet" type="text/css" href="ts.css">
</head>
<body>
    <h2 align="center">5 Rows x 3 Columns Table</h2>
    <table>
        <tr>
            <td>Row 1 - Col 1 (Odd)</td>
            <td>Row 1 - Col 2</td>
            <td>Row 1 - Col 3</td>
        </tr>
        <tr>
            <td>Row 2 - Col 1 (Even)</td>
            <td>Row 2 - Col 2</td>
            <td>Row 2 - Col 3</td>
        </tr>
        <tr>
            <td>Row 3 - Col 1 (Odd)</td>
            <td>Row 3 - Col 2</td>
```

```
            <td>Row 3 - Col 3</td>
        </tr>
        <tr>
            <td>Row 4 - Col 1 (Even)</td>
            <td>Row 4 - Col 2</td>
            <td>Row 4 - Col 3</td>
        </tr>
        <tr>
            <td>Row 5 - Col 1 (Odd)</td>
            <td>Row 5 - Col 2</td>
            <td>Row 5 - Col 3</td>
        </tr>
    </table>
</body>
</html>
```

**Question 238:** How can a style rule be defined with an id red heading that gives red color to heading h1 with text of heading right aligned?

**Solution Code:**

```
#red_heading {
    color: red;
    text-align: right;
}

h1#red_heading {
    color: red;
    text-align: right;
}

<!DOCTYPE html>
<html>
<head>
    <title>ID Selector Demonstration</title>
    <style>
        #red_heading {
            color: red;
            text-align: right;
        }
    </style>
</head>
<body>
    <h1 id="red_heading">This is a Right-Aligned Red Heading</h1>
</body>
</html>
```

**Question 239:** Write a code to demonstrate the use of text-indent, word-spacing, letter-spacing properties.

**Solution Code:**

```
<!DOCTYPE html>
<html>
<head>
    <title>CSS Text Spacing Properties</title>
    <style>
        .indent-demo {
            text-indent: 40px;
            border: 1px solid #aaa;
            padding: 10px;
            margin-bottom: 15px;
        }

        .word-demo {
            word-spacing: 15px;
            border: 1px solid #aaa;
            padding: 10px;
            margin-bottom: 15px;
        }

        .letter-demo {
            letter-spacing: 5px;
            border: 1px solid #aaa;
            padding: 10px;
        }
    </style>
</head>
<body>
    <h2>Demonstration of Text Spacing Properties</h2>

    <p class="indent-demo">
        <b>text-indent (40px):</b> This first line starts with a 40px horizontal indentation,
whereas all subsequent wrapped lines align flush to the left boundary.
    </p>

    <p class="word-demo">
        <b>word-spacing (15px):</b> Notice the wide gaps between each individual word in this
sentence.
    </p>

    <p class="letter-demo">
        <b>letter-spacing (5px):</b> Character tracking is expanded with 5px between each letter.
    </p>
</body>
</html>
```

**Question 240:** Write a code to demonstrate use of CSS margin property.

**Solution Code:**

```
<!DOCTYPE html>
```

```
<html>
<head>
    <title>CSS Margin Demonstration</title>
    <style>
        .container {
            border: 2px dashed black;
            background-color: #f0f0f0;
            padding: 10px;
        }

        .box1 {
            background-color: lightblue;
            border: 1px solid blue;
            margin-top: 20px;
            margin-right: 40px;
            margin-bottom: 20px;
            margin-left: 50px;
            padding: 10px;
        }

        .box2 {
            background-color: lightgreen;
            border: 1px solid green;
            margin: 15px 30px 15px 30px;
            padding: 10px;
        }

        .box3 {
            background-color: lightcoral;
            border: 1px solid red;
            width: 50%;
            margin: 20px auto;
            text-align: center;
            padding: 10px;
        }
    </style>
</head>
<body>
    <h2>CSS Margin Property Examples</h2>
    <div class="container">
        <div class="box1">Box 1: margin-left: 50px; margin-top: 20px;</div>
        <div class="box2">Box 2: Shorthand margin: 15px 30px 15px 30px;</div>
        <div class="box3">Box 3: Centered with margin: 20px auto;</div>
    </div>
</body>
</html>
```

**Question 241:** Write an External CSS with following rules.
i) To make all the headers with normal font and having size 150%.
ii) To display the paragraphs in arial font with bold style.

Show the use of above css with html file by linking it.

**Solution Code:**

```
/* File 1: styles.css (External CSS) */

h1, h2, h3, h4, h5, h6 {
    font-style: normal;
    font-weight: normal;
    font-size: 150%;
}

p {
    font-family: Arial, sans-serif;
    font-weight: bold;
}

/* ------------------------------------------------- */
<!-- File 2: index.html (HTML Document linking styles.css) -->
<!DOCTYPE html>
<html>
<head>
    <title>Linked External Stylesheet</title>
    <!-- Linking External CSS -->
    <link rel="stylesheet" type="text/css" href="styles.css">
</head>
<body>
    <h1>Heading Level 1 (Normal Font, Size 150%)</h1>
    <h2>Heading Level 2 (Normal Font, Size 150%)</h2>

    <p>
        This paragraph is displayed using Arial font family with bold style, as dictated by the
external stylesheet.
    </p>
</body>
</html>
```

**Question 242:** Define a class which defines a text alignment style to be left. Show how this same style can be applied to multiple tags?

**Solution Code:**

```
<!DOCTYPE html>
<html>
<head>
    <title>Class Selector on Multiple Tags</title>
    <style>
        .align-left {
            text-align: left;
        }
        .demo-box {
```

```
            border: 1px solid #666;
            padding: 10px;
            margin: 10px 0;
            background-color: #fafafa;
        }
    </style>
</head>
<body>
    <!-- Applying .align-left to <h1> tag -->
    <h1 class="align-left">Heading aligned to Left</h1>

    <!-- Applying .align-left to <p> tag -->
    <p class="align-left">
        This paragraph text is left-aligned using the exact same class.
    </p>

    <!-- Applying .align-left to <div> container -->
    <div class="align-left demo-box">
        <b>Inside Div:</b> Content inside this container is left-aligned.
    </div>

    <!-- Applying .align-left to <h3> tag -->
    <h3 class="align-left">Sub-heading also aligned to Left</h3>
</body>
</html>
```

**Question 243:** Write a code to demonstrate the use of text-transform and text-decoration properties.

**Solution Code:**

```
<!DOCTYPE html>
<html>
<head>
    <title>text-transform & text-decoration Demo</title>
    <style>
        .uppercase-text { text-transform: uppercase; }
        .lowercase-text { text-transform: lowercase; }
        .capitalize-text { text-transform: capitalize; }

        .underline-text   { text-decoration: underline; }
        .overline-text    { text-decoration: overline; }
        .strikethrough    { text-decoration: line-through; }
        .no-decor-link    { text-decoration: none; color: blue; }
    </style>
</head>
<body>
    <h2>CSS text-transform Demonstrations:</h2>
    <p class="uppercase-text">this sentence was typed lowercase but renders uppercase.</p>
    <p class="lowercase-text">THIS SENTENCE WAS TYPED UPPERCASE BUT RENDERS LOWERCASE.</p>
    <p class="capitalize-text">each word in this sentence starts with a capital letter.</p>
```

```
    <hr>

    <h2>CSS text-decoration Demonstrations:</h2>
    <p class="underline-text">This text has an underline decoration beneath it.</p>
    <p class="overline-text">This text has an overline decoration above it.</p>
    <p class="strikethrough">This text has a strikethrough line-through decoration.</p>
    <p><a href="#test" class="no-decor-link">Hyperlink with text-decoration: none (no
underline)</a></p>
</body>
</html>
```

**Question 244:** Write following style in separate CSS file.
1) write one paragraph using <p> tag..color of first line of paragraph should be green and text is italic.
2) when you select any text of heading ,background color of selected text will become grey.
create one ordered list which is start with capital roman letters. color of list should be green and font-size should be 30px.

**Solution Code:**

```
/* File 1: styles.css (Separate CSS File) */

p::first-line {
    color: green;
    font-style: italic;
}

h1::selection, h2::selection, h3::selection, h4::selection, h5::selection, h6::selection {
    background-color: grey;
    color: white;
}

ol {
    color: green;
    font-size: 30px;
}

/* ------------------------------------------------ */
<!-- File 2: index.html -->
<!DOCTYPE html>
<html>
<head>
    <title>CSS Pseudo-elements & Ordered List</title>
    <link rel="stylesheet" type="text/css" href="styles.css">
</head>
<body>
    <h1>Select This Heading Text With Your Mouse (Turns Grey)</h1>

    <p>
        The first line of this paragraph will appear in green italic text automatically.<br>
        This second line and all following lines will return to standard text color and style.
```

```
    </p>

    <ol type="I">
        <li>Full Stack Development</li>
        <li>Database Management Systems</li>
        <li>Operating Systems</li>
    </ol>
</body>
</html>
```

**Question 245:** Write HTML/CSS script to display 2 sections of 40% width using  tag. Both these sections are having title & description. Both these  should be horizontally adjecent to each other.

**Solution Code:**

```
<!DOCTYPE html>
<html>
<head>
<style>
div {
    display: inline-block;
    width: 40%;
    border: 1px solid blue;
    margin:10px
}
</style>
</head>
<body>

<div>
    <h2>Section 1</h2>
    <p>This is the description of the first section.</p>
</div>

<div>
    <h2>Section 2</h2>
    <p>This is the description of the second section.</p>
</div>

</body>
</html>
```

**Question 246:** Write HTML/CSS code for the following:
i) Set the background color for the hover and active link states to 'Yellow'.
ii) Set 'paper.jpg' as the background image of the page.

**Solution Code:**

```
<!DOCTYPE html>
<html>
<head>
    <title>Link States & Background Image</title>
    <style>

        body {
            background-image: url('paper.jpg');
            background-repeat: no-repeat;
            background-size: cover;
        }


        a:hover, a:active {
            background-color: yellow;
            color: darkred;
        }
    </style>
</head>
<body>
    <h2>Link Pseudo-classes and Background Demo</h2>
    <p>Hover or click on the links below to see their background turn yellow:</p>

    <p><a href="#home">Home Navigation Link</a></p>
    <p><a href="#course">Course Materials Link</a></p>
</body>
</html>
```

**Question 247:** Write HTML/CSS code having  element styled as a perfect circle. Then, using CSS, apply a lightblue shadow around it.

**Solution Code:**

```
<!DOCTYPE html>
<html>
<head>
    <title>CSS Circle with Box Shadow</title>
    <style>
        .circle-box {
            width: 160px;
            height: 160px;
            background-color: deepskyblue;
            border-radius: 50%;
            /* Lightblue shadow around the circle */
            box-shadow: 0px 0px 30px lightblue;
```

```
        }
    </style>
</head>
<body>
    <h2 align="center">Perfect Circle with Lightblue Shadow</h2>
    <div class="circle-box"></div>
</body>
</html>
```

**Question 248:** Write HTML & CSS code to design registration form having fields like Name, Password, Contact Number, Gender, Submit button & Reset Button. Follow below requirements:

- While clicking on Name text, background-color of its input field change to light-green.
- While hovering on password & Contact number text, font-size of its input fields will increase respectively.
- While clicking on gender fields, background-color of the text should change to blue.
- Both submit & reset button text should bold & italic, while hovering.

**Solution Code:**

```
<!DOCTYPE html>
<html>
<head>
    <title>Interactive Registration Form</title>
    <style>
        input[name="fullname"]:focus {
            background-color: lightgreen;
        }
        input[type="password"]:hover,
        input[name="contact"]:hover {
            font-size: 18px;
        }

        label:active{
            background-color: blue;
            color: white;
            padding: 2px 6px;
        }

        input[type="submit"]:hover,
        input[type="reset"]:hover {
            font-weight: bold;
            font-style: italic;
            cursor: pointer;
        }
    </style>
</head>
<body>
    <form action="register.jsp" method="post">
        <h2>Registration Form</h2>
```

```
        <p>
            <label>Name:</label><br>
            <input type="text" name="fullname" placeholder="Click to focus">
        </p>

        <p>
            <label>Password:</label><br>
            <input type="password" name="password" placeholder="Hover to increase size">
        </p>

        <p>
            <label>Contact Number:</label><br>
            <input type="tel" name="contact" placeholder="Hover to increase size">
        </p>

        <p>
            Gender:<br>
   <label for="male">  <input type="radio" id="male" name="gender" value="Male">Male </label>
             
    <label for="female"><input type="radio" id="female" name="gender"
value="Female">Female</label>
        </p>

        <p>
            <input type="submit" value="Submit">
            <input type="reset" value="Reset">
        </p>
    </form>
</body>
</html>
```

**Question 249:** Write HTML & CSS script to design a signup form having fields like Username, password, choices of sports like Cricket, Hockey, Badminton & Tennis. Include gender field, submit and reset buttons. Follow below requirements:
i) While hovering username & password, its background should turn yellow color and pink color respectively.
ii) While clicking sports and gender fields, text should turn to red color.
iii) Both submit and reset button text should turn blue, while hovering.
iv) Use appropriate selectors.

**Solution Code:**

```
<!DOCTYPE html>
<html>
<head>
    <title>Signup Form with CSS Selectors</title>
    <style>
        input[name="username"]:hover {
            background-color: yellow;
        }
        input[name="password"]:hover {
```

```
            background-color: pink;
        }
        label:active{
            color: red;
            font-weight: bold;
        }
        input[type="submit"]:hover,
        input[type="reset"]:hover {
            color: blue;
            cursor: pointer;
        }
    </style>
</head>
<body>
    <form action="signup.jsp" method="post">
        <h2>Signup Form</h2>

        <p>
            <label>Username:</label><br>
            <input type="text" name="username" placeholder="Hover for yellow">
        </p>

        <p>
            <label>Password:</label><br>
            <input type="password" name="password" placeholder="Hover for pink">
        </p>

        <p>
            <b>Sports Choices (Click to turn text red):</b><br>

            <label for="cric"><input type="checkbox" id="cric" name="sports"
value="Cricket">Cricket</label><br>

            <label for="hock"> <input type="checkbox" id="hock" name="sports"
value="Hockey">Hockey</label><br>

            <label for="badm">  <input type="checkbox" id="badm" name="sports"
value="Badminton">Badminton</label><br>

            <label for="tenn">  <input type="checkbox" id="tenn" name="sports"
value="Tennis">Tennis</label>
        </p>

        <p>
            <b>Gender (Click to turn text red):</b><br>
            <input type="radio" id="g_male" name="gender" value="Male">
            <label for="g_male">Male</label>
             
            <input type="radio" id="g_female" name="gender" value="Female">
            <label for="g_female">Female</label>
        </p>

        <p>
```

```
            <input type="submit" value="Submit">
            <input type="reset" value="Reset">
        </p>
    </form>
</body>
</html>
```

**Question 250:** Write the following styles in separate CSS file and also show how to link this CSS file in HTML file and show use of styles.
i) The headings should have normal font style and font's size should be 120%.
ii) Define class arial for paragraph which defines font family arial and font style bold having 3cm spacing for paragraph initialization.
iii) Apply background color orange and apply a background image 'nature.jpg' and it should be repeated horizontaly only.

**Solution Code:**

```
/* File 1: styles.css (Separate CSS File) */

h1, h2, h3, h4, h5, h6 {
    font-style: normal;
    font-size: 120%;
}


p.arial {
    font-family: Arial, sans-serif;
    font-weight: bold;
    text-indent: 3cm;
}

body {
    background-color: orange;
    background-image: url('nature.jpg');
    background-repeat: repeat-x;
}

/* ------------------------------------------------ */
<!-- File 2: index.html -->
<!DOCTYPE html>
<html>
<head>
    <title>Linked CSS File Demo</title>
    <!-- Linking the separate CSS file -->
    <link rel="stylesheet" type="text/css" href="styles.css">
</head>
<body>
    <h1>Heading Level 1 (Normal Font Style, Size 120%)</h1>
    <h2>Heading Level 2 (Normal Font Style, Size 120%)</h2>
```

```
    <p class="arial">
        This paragraph belongs to class arial. It is displayed in bold Arial font and features a
3cm text indentation on its initial line.
    </p>

    <p>
        This is a regular paragraph without the class arial.
    </p>
</body>
</html>
```

**Question 251:** Write the HTML/CSS code to design a web page that contains a  element with a border, some padding, and a background image. The background should appear only within the content and padding area of the element, and it must not extend into the border space.

**Solution Code:**

```
<html>
<head>
    <style>
        .custom-box {
            width: 450px;
            height: 200px;
            border: 12px dotted #333333;
            padding: 25px;
            background-image: url('scene.jpg');
            background-repeat: no-repeat;
            background-size: cover;
            background-clip: padding-box;
        }
    </style>
</head>
<body>
    <div class="custom-box">
        Notice that the background image covers this padding and content area, but does not extend
underneath the 12px dashed border area.
    </div>
</body>
</html>
```

**Question 252:** Write the HTML/CSS code to create a simple 3-column product grid. Each column should display a smartwatch with a product name below it. All images should have the same height and fit the width of their columns.

**Solution Code:**

```
<!DOCTYPE html>
<html>
<head>
    <title>3-Column Product Grid</title>
    <style>
        .product-grid {
            display: grid;
            grid-template-columns: repeat(3, 1fr);
            gap: 20px;
            max-width: 900px;
        }

        .product-card {
            border: 1px solid #ccc;
            padding: 15px;
            text-align: center;
            background-color: #fdfdfd;
        }

        .product-card img {
            width: 100%;
            height: 220px;
        }
    </style>
</head>
<body>
    <h2 align="center">Smartwatch Collection (3-Column Grid)</h2>

    <div class="product-grid">
        <!-- Column 1 -->
        <div class="product-card">
            <img src="smartwatch1.jpg" alt="Apple Watch Series 9">
            <div class="product-name">Apple Watch Series 9</div>
        </div>

        <!-- Column 2 -->
        <div class="product-card">
            <img src="smartwatch2.jpg" alt="Samsung Galaxy Watch 6">
            <div class="product-name">Samsung Galaxy Watch 6</div>
        </div>

        <!-- Column 3 -->
        <div class="product-card">
            <img src="smartwatch3.jpg" alt="Garmin Venu 3">
            <div class="product-name">Garmin Venu 3</div>
        </div>
    </div>
</body>
</html>
```

**Question 253:** Write the following styles in separate CSS file and also show how to link this CSS file in HTML

file and show use of styles.
i) The headings should have normal font style and font's size should be 240% also right aligned.
ii) Define a class container for paragraph which defines font family times new roman and font style bold with green color text having 2cm spacing for paragraph initialization.
iii) Apply background image 'nature.jpg' and it should be repeated vertically only.

**Solution Code:**

```
/* File 1: styles.css (Separate CSS File) */

h1, h2, h3, h4, h5, h6 {
    font-style: normal;
    font-size: 240%;
    text-align: right;
}

p.container {
    font-family: 'Times New Roman', Times, serif;
    font-weight: bold;
    color: green;
    text-indent: 2cm;
}

body {
    background-image: url('nature.jpg');
    background-repeat: repeat-y;
}

/* ------------------------------------------------- */
<!-- File 2: index.html -->
<!DOCTYPE html>
<html>
<head>
    <title>Linked External Stylesheet Demo</title>
    <!-- Linking external CSS file -->
    <link rel="stylesheet" type="text/css" href="styles.css">
</head>
<body>
    <h1>Right Aligned Heading (240% Size)</h1>

    <p class="container">
        This paragraph utilizes class container. It is rendered in green Times New Roman bold font
and features a 2cm initialization spacing on the first line.
    </p>

    <p>
        This is standard paragraph text demonstrating the repeating vertical nature background
behind the document.
    </p>
</body>
</html>
```