FORMULA SHEET - DIGITAL

1 Operational amplifier

1.1 Gain:

$$Av = \frac{V_{out}}{V_{in}} \qquad \qquad Av = \left(\frac{Rf}{R_{in}}\right) \qquad \qquad Av = \left(1 + \frac{Rf}{R_{in}}\right)$$

1.2 Voltage:

$$\begin{split} V_{out} &= V_{in} \times \left(1 + \frac{Rf}{R_{in}}\right) & V_{out} = V_{in} \times \left(-\frac{Rf}{R_{in}}\right) & V_{out} = -\left(V_i - V_x\right) A v \\ V_{out} &= -\left(V_1 + V_2 + V_3\right) & V_{out} = -V_i \times A v & Vref = Vcc\left(\frac{R1}{R1 + R2}\right) \\ Vo &= -Vi\left(\frac{1}{j2\pi fRC}\right) & Vo &= -R_fC\left(\frac{\Delta V_i}{\Delta t}\right) & V_{out} = -\left(V_{i1}\frac{Rf}{R_1} + V_{i2}\frac{Rf}{R_2} + V_{i3}\frac{Rf}{R_3}....\right) \end{split}$$

1.3 Time:

$$T_1 = 0.693(R_2 + R_1)C$$
 $T = RC$ $T = R_fC$ $T = 0.693 \times R_2C$ $T = 0.693RC$ $T = 1.1R_2C$

1.4 Frequency:

$$f = \frac{1}{2R_fC}$$
 $f = \frac{1,44}{(R_1 + 2R_2)C}$

1.5 Duty cycle:

Duty cycle =
$$\frac{R_1 + R_2}{(R_1 + 2R_2)} \times 100\%$$

2 Logic

MOD
$$X = 2^N$$
 Counting steps = $2^N - 1$ $N = \sqrt{MOD X}$