

Типове, функции, граматики

Калин Георгиев

16 октомври 2019 г.

Типове в езиците за програмиране

Абстрактна необходимост

- Моделиране
- Различни физически характеристики на свойствата на реалните обекти
- Физически и абстрактни свойства (тегло vs. име)

- Авто къща
- Авто морта
- Завод



Абстрактна необходимост

- Моделиране
 - Различни физически характеристики на свойствата на реалните обекти
 - Физически и абстрактни свойства (тегло vs. име)
- Авто къща
 - Авто морга
 - Завод



Абстрактна необходимост

- Моделиране
- Различни физически характеристики на свойствата на реалните обекти
- Физически и абстрактни свойства (тегло vs. име)

- Авто къща
- Авто морта
- Завод



Абстрактна необходимост

- Моделиране
- Различни физически характеристики на свойствата на реалните обекти
- Физически и абстрактни свойства (тегло vs. име)

- Авто къща
- Авто морта
- Завод



Машинна необходимост

- Обем памет

$$\begin{array}{r}
 127_{10} = \begin{array}{|c|c|c|c|c|c|} \hline 1 & 1 & 1 & 1 & 1 & 1_2 \\ \hline \end{array} \\
 128_{10} = \begin{array}{|c|c|c|c|c|c|} \hline 1 & 0 & 0 & 0 & 0 & 0 \\ \hline \end{array} 0_2
 \end{array}$$

- Приближено представяне на неизброими типове

$$123.45 = \overbrace{12345}^{\text{мантиса}} * \underbrace{10^{-2}}_{\text{експонента}}$$

- Диапазон (range) vs. точност (precision)
- Как представяме 1/3

Машинна необходимост

- Обем памет

$$\begin{array}{r}
 127_{10} = \begin{array}{|c|c|c|c|c|c|} \hline 1 & 1 & 1 & 1 & 1 & 1_2 \\ \hline \end{array} \\
 128_{10} = \begin{array}{|c|c|c|c|c|c|} \hline 1 & 0 & 0 & 0 & 0 & 0_2 \\ \hline \end{array}
 \end{array}$$

- Приближено представяне на неизброими типове

$$123.45 = \overbrace{12345}^{\text{мантиса}} * \underbrace{10^{-2}}_{\text{експонента}}$$

- Диапазон (range) vs. точност (precision)
- Как представяме 1/3

Машинна необходимост

- Обем памет

$$\begin{array}{r}
 127_{10} = \begin{array}{|c|c|c|c|c|c|} \hline 1 & 1 & 1 & 1 & 1 & 1_2 \\ \hline \end{array} \\
 128_{10} = \begin{array}{|c|c|c|c|c|c|} \hline 1 & 0 & 0 & 0 & 0 & 0_2 \\ \hline \end{array}
 \end{array}$$

- Приближено представяне на неизброими типове

$$123.45 = \overbrace{12345}^{\text{мантиса}} * \underbrace{10^{-2}}_{\text{експонента}}$$

- Диапазон (range) vs. точност (precision)
- Как представяме 1/3

Машинна необходимост

- Обем памет

$$\begin{array}{r}
 127_{10} = \begin{array}{|c|c|c|c|c|c|} \hline 1 & 1 & 1 & 1 & 1 & 1_2 \\ \hline \end{array} \\
 128_{10} = \begin{array}{|c|c|c|c|c|c|c|} \hline 1 & 0 & 0 & 0 & 0 & 0 & 0_2 \\ \hline \end{array}
 \end{array}$$

- Приближено представяне на неизброими типове

$$123.45 = \overbrace{12345}^{\text{мантиса}} * \underbrace{10^{-2}}_{\text{експонента}}$$

- Диапазон (range) vs. точност (precision)
- Как представяме 1/3

Примери

```
int main ()
{
    int int_a = 1, int_b = 2;
    double dbl_a = 1, dbl_b = 2;
    char chr_a = 'a', chr_b = 'b';

    cout << int_a / int_b << endl;
    cout << dbl_a / dbl_b << endl;
    cout << chr_a << endl;

    int_a = 'a'; //int_a = chr_a;
    cout << int_a << endl;

    chr_a = 65;
    cout << chr_a << endl;

    return 0;
}
```

Математическа характеристика

Множество допустими стойности (Носител - D)

- Мъж, Жена
- 0..255
- $(\mathcal{R}, \mathcal{R}, \mathcal{R})$

Операции

- $f : D \times D \rightarrow D$
- $f(x, y) = x + y$

Предикати

- $p : D \rightarrow \{tt, ff\}$
- $p(x) = |x|_2 == 0$

Математическа характеристика

Множество допустими стойности (Носител - D)

- Мъж, Жена
- 0..255
- $(\mathcal{R}, \mathcal{R}, \mathcal{R})$

Операции

- $f : D \times D \rightarrow D$
- $f(x, y) = x + y$

Предикати

- $p : D \rightarrow \{tt, ff\}$
- $p(x) = |x|_2 == 0$

Математическа характеристика

Множество допустими стойности (Носител - D)

- Мъж, Жена
- 0..255
- $(\mathcal{R}, \mathcal{R}, \mathcal{R})$

Операции

- $f : D \times D \rightarrow D$
- $f(x, y) = x + y$

Предикати

- $p : D \rightarrow \{tt, ff\}$
- $p(x) = |x|_2 == 0$

Математическа характеристика

Множество допустими стойности (Носител - D)

- Мъж, Жена
- 0..255
- $(\mathcal{R}, \mathcal{R}, \mathcal{R})$

Операции

- $f : D \times D \rightarrow D$
- $f(x, y) = x + y$

Предикати


- $p : D \rightarrow \{tt, ff\}$
- $p(x) = |x|_2 == 0$

Функции. Подпрограми

Функции в математиката


- Дефиниционна област (Domain)
- Множество на стойностите (Range)
- $f : \text{Domain} \rightarrow \text{Range}$

$$f(x) = x^2$$




Функции в математиката

$$f(x, y) = x^2 + y^2$$



Подпрограми



Лице на триъгълник по три страни

$$a, b, c \in \mathcal{R}$$

$$S = \sqrt{\frac{a+b+c}{2} \frac{b+c-a}{2} \frac{a+c-b}{2} \frac{a+b-c}{2}} = \sqrt{p(p-a)(p-b)(p-c)} \in \mathcal{R}$$

$$s : \mathcal{R} \times \mathcal{R} \times \mathcal{R} \rightarrow \mathcal{R}$$

$$s(a, b, c) = \sqrt{p(p-a)(p-b)(p-c)}$$

Лице на триъгълник по три страни

$$a, b, c \in \mathcal{R}$$

$$S = \sqrt{\frac{a+b+c}{2} \frac{b+c-a}{2} \frac{a+c-b}{2} \frac{a+b-c}{2}} = \sqrt{p(p-a)(p-b)(p-c)} \in \mathcal{R}$$

$$s : \mathcal{R} \times \mathcal{R} \times \mathcal{R} \rightarrow \mathcal{R}$$

$$s(a, b, c) = \sqrt{p(p-a)(p-b)(p-c)}$$

Лице на триъгълник по три страни

$$a, b, c \in \mathcal{R}$$

$$S = \sqrt{\frac{a+b+c}{2} \frac{b+c-a}{2} \frac{a+c-b}{2} \frac{a+b-c}{2}} = \sqrt{p(p-a)(p-b)(p-c)} \in \mathcal{R}$$


$$s : \mathcal{R} \times \mathcal{R} \times \mathcal{R} \rightarrow \mathcal{R}$$

$$s(a, b, c) = \sqrt{p(p-a)(p-b)(p-c)}$$

Съответната функция

$$s : \mathcal{R} \times \mathcal{R} \times \mathcal{R} \rightarrow \mathcal{R}$$

$$s(a, b, c) = \sqrt{p(p-a)(p-b)(p-c)}$$



Съответната подпрограма

$$s : \mathcal{R} \times \mathcal{R} \times \mathcal{R} \rightarrow \mathcal{R}$$
$$s(a, b, c) = \sqrt{p(p-a)(p-b)(p-c)}$$

```
double triangleSurface (double a, double b, double c)

{
    double p = (a+b+c)/2;
    double surface = sqrt (p*(p-a)*(p-b)*(p-c));

    return surface;
}
```


Съответната подпрограма

$$s : \mathcal{R} \times \mathcal{R} \times \mathcal{R} \rightarrow \mathcal{R}$$
$$s(a, b, c) = \sqrt{p(p-a)(p-b)(p-c)}$$

```
double triangleSurface (double a, double b, double c)
```

```
{  
    double p = (a+b+c)/2;  
    double surface = sqrt (p*(p-a)*(p-b)*(p-c));  
  
    return surface;  
}
```

Съответната подпрограма

$$s : \mathcal{R} \times \mathcal{R} \times \mathcal{R} \rightarrow \mathcal{R}$$
$$s(a, b, c) = \sqrt{p(p-a)(p-b)(p-c)}$$

```
double triangleSurface (double a, double b, double c)

{
    double p = (a+b+c)/2;
    double surface = sqrt (p*(p-a)*(p-b)*(p-c));

    return surface;
}
```

Програма - потребител

```
int main ()
{
    double a,b,c,a1,b1,c1;

    cout << "Sides_of_ABC:";
    cin >> a >> b >> c;
    cout << "Sides_of_DEF:"
    cin >> a1 >> b1 >> c1;

    if (triangleSurface(a,b,c) < triangleSurface (a1,b1,c1))
    {
        cout << "Yes,_ABC_takes_less_space!" << endl;
    } else {
        cout << "No,_ABC_does_not_take_less_space!" << endl;
    }

    return 0;
}
```

Вградени числови функции

```
#include <cmath>
```

- `abs(x)`, `fabs(x)`
- `sin(x)`, `cos(x)`, `tan(x)`, `asin(x)`, `acos(x)`, `atan(x)`, `exp(x)`, `log(x)`, `log10(x)`
- `ceil(x)`, `floor(x)`
- `sqrt(x)`, `pow(x, n)`

Вградени числови функции

```
#include <cmath>
```

- `abs(x)`, `fabs(x)`
- `sin(x)`, `cos(x)`, `tan(x)`, `asin(x)`, `acos(x)`, `atan(x)` `exp(x)`, `log(x)`, `log10(x)`
- `ceil(x)`, `floor(x)`
- `sqrt(x)`, `pow(x, n)`

Съвсем малко теория

Формални граматики

the cat meows.

the dog barks at the cat.

the student lies to the teacher.

- Азбука: $\Sigma = \{a..z\}$
- Нетерминални символи: **{Verb, Object, Subject, Prep, Sentence}**
- Продукционни правила:

Object \rightarrow *cat|dog|student*

Subject \rightarrow *cat|dog|teacher*

Verb \rightarrow *meows|barks|lies*

Prep \rightarrow *to|at*

Sentence \rightarrow *the* **Object** **Verb**

Sentence \rightarrow *the* **Object** **Verb** **Prep** *the* **Subject**

Формални граматики

the cat meows.

the dog barks at the cat.

the student lies to the teacher.

- Азбука: $\Sigma = \{a..z\}$
- Нетерминални символи: **{Verb, Object, Subject, Prep, Sentence}**
- Продукционни правила:

Object \rightarrow *cat|dog|student*

Subject \rightarrow *cat|dog|teacher*

Verb \rightarrow *meows|barks|lies*

Prep \rightarrow *to|at*

Sentence \rightarrow *the* **Object** **Verb**

Sentence \rightarrow *the* **Object** **Verb** **Prep** *the* **Subject**

Формални граматики

the cat meows.

the dog barks at the cat.

the student lies to the teacher.

- Азбука: $\Sigma = \{a..z\}$
- Нетерминални символи: **{Verb, Object, Subject, Prep, Sentence}**
- Продукционни правила:

Object $\rightarrow cat|dog|student$

Subject $\rightarrow cat|dog|teacher$

Verb $\rightarrow meows|barks|lies$

Prep $\rightarrow to|at$

Sentence $\rightarrow the \quad \textbf{Object} \quad \textbf{Verb}$

Sentence $\rightarrow the \quad \textbf{Object} \quad \textbf{Verb} \quad \textbf{Prep} \quad the \quad \textbf{Subject}$

Извод на the cat meows at the dog

Object → cat|dog|student

Subject → cat|teacher

Verb → meows|barks|lies

Prep → to|at

Sentence → the Object Verb Prep the Subject

Sentence → the Object Verb Prep the Subject

Object → cat

Sentence → the cat Verb Prep the Subject

Verb → meows

Sentence → the cat meows Prep the Subject

Prep → at

Sentence → the cat meows at the Subject

Subject → dog

Sentence → the cat meows at the dog

Извод на the cat meows at the dog

Object → cat|dog|student

Subject → cat|teacher

Verb → meows|barks|lies

Prep → to|at

Sentence → the Object Verb Prep the Subject

Sentence → the Object Verb Prep the Subject

Sentence → the **Object** **Verb** **Prep** the **Subject**

Object → cat

Sentence → the cat **Verb** **Prep** the **Subject**

Verb → meows

Sentence → the cat meows **Prep** the **Subject**

Prep → at

Sentence → the cat meows at the **Subject**

Subject → dog

Sentence → the cat meows at the dog

Извод на the cat meows at the dog

Object → cat|dog|student

Subject → cat|teacher

Verb → meows|barks|lies

Prep → to|at

Sentence → the Object Verb Prep the Subject

Sentence → the Object Verb Prep the Subject

Sentence → the Object Verb Prep the Subject

Object → cat

Sentence → the cat Verb Prep the Subject

Verb → meows

Sentence → the cat meows Prep the Subject

Prep → at

Sentence → the cat meows at the Subject

Subject → dog

Sentence → the cat meows at the dog

Извод на the cat meows at the dog

Object → cat|dog|student

Subject → cat|teacher

Verb → meows|barks|lies

Prep → to|at

Sentence → the Object Verb Prep the Subject
 the the the the the the

Sentence → the **Object** **Verb** **Prep** the **Subject**

Object → cat

Sentence → the cat **Verb** **Prep** the **Subject**

Verb → meows

Sentence → the cat meows **Prep** the **Subject**

Prep → at

Sentence → the cat meows at the **Subject**

Subject → dog

Sentence → the cat meows at the dog

Извод на the cat meows at the dog

Object \rightarrow cat|dog|student
 Subject \rightarrow cat|teacher
 Verb \rightarrow meows|barks|lies
 Prep \rightarrow to|at
 Sentence \rightarrow the Object Verb Prep the Subject
 Sentence \rightarrow the Object Verb Prep the Subject

Sentence \rightarrow the Object Verb Prep the Subject

Object \rightarrow cat

Sentence \rightarrow the cat Verb Prep the Subject

Verb \rightarrow meows

Sentence \rightarrow the cat meows Prep the Subject

Prep \rightarrow at

Sentence \rightarrow the cat meows at the Subject

Subject \rightarrow dog

Sentence \rightarrow the cat meows at the dog

Извод на the cat meows at the dog

Object → cat|dog|student
 Subject → cat|teacher
 Verb → meows|barks|lies
 Prep → to|at
 Sentence → the Object Verb Prep the Subject

Sentence → the Object Verb Prep the Subject

Object → cat

Sentence → the cat Verb Prep the Subject

Verb → meows

Sentence → the cat meows Prep the Subject


Prep → at

Sentence → the cat meows at the Subject

Subject → dog

Sentence → the cat meows at the dog

Синтактично дърво



Мета-език на Бекус-Наур

- $\langle \textit{digit} \rangle ::= 0|1|2|3|4|5|6|7|8|9$
- $\langle \textit{unsignedint} \rangle ::= \langle \textit{digit} \rangle^+$
- $\langle \textit{integer} \rangle ::= [+|-] \langle \textit{unsignedint} \rangle$
- $\langle \textit{identifier} \rangle ::= _ (\langle \textit{letter} \rangle | \langle \textit{digit} \rangle | _)^*$
- $\langle \textit{identifier} \rangle ::= \langle \textit{leter} \rangle (\langle \textit{letter} \rangle | \langle \textit{digit} \rangle | _)^*$