#### Двумерни масиви и вложени цикли for

Калин Георгиев

22 октомври 2015 г.

Двумерна информация

# Таблици

	Мъже	Жени		
1990	48.75%	49.06%		
2000	49.06%	50.94%		

### Матрици

$$A = \begin{pmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{pmatrix}$$

$$\begin{pmatrix} a_{1,1} & a_{1,2} & a_{1,3} \\ a_{2,1} & a_{2,2} & a_{3,3} \\ a_{3,1} & a_{3,2} & a_{3,3} \end{pmatrix}$$

### Матрици

$$A = \begin{pmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{pmatrix}$$
$$\begin{pmatrix} a_{1,1} & a_{1,2} & a_{1,3} \\ a_{2,1} & a_{2,2} & a_{3,3} \\ a_{3,1} & a_{3,2} & a_{3,3} \end{pmatrix}$$

### Двумерни масиви



$$\begin{pmatrix} a_{1,1} & a_{1,2} & a_{1,3} \\ a_{2,1} & a_{2,2} & a_{3,3} \\ a_{3,1} & a_{3,2} & a_{3,3} \end{pmatrix}$$

### Двумерни масиви

a[0][0]	a[0][1]	a[0][2]
a[1][0]	a[1][1]	a[1][2]
a[2][0]	a[2][1]	a[2][2]

$$\begin{pmatrix} a_{1,1} & a_{1,2} & a_{1,3} \\ a_{2,1} & a_{2,2} & a_{3,3} \\ a_{3,1} & a_{3,2} & a_{3,3} \end{pmatrix}$$

### Двумерни масиви

a[0][0]	a[0][1]	a[0][2]
a[1][0]	a[1][1]	a[1][2]
a[2][0]	a[2][1]	a[2][2]

$$\begin{pmatrix} a_{1,1} & a_{1,2} & a_{1,3} \\ a_{2,1} & a_{2,2} & a_{3,3} \\ a_{3,1} & a_{3,2} & a_{3,3} \end{pmatrix}$$

#### int a[3][3];

				a[2][1]	



int a[3][3];

a[0][0]	a[0][1]	a[0][2]
a[1][0]	a[1][1]	a[1][2]
a[2][0]	a[2][1]	a[2][2]

				a[2][1]	

a[0][0]	a[0][1]	a[0][2]
a[1][0]	a[1][1]	a[1][2]
a[2][0]	a[2][1]	a[2][2]

 0	1	2	3	4	5	6	7	8	
 a[0][0]	a[0][1]	a[0][2]	a[1][0]	a[1][1]	a[1][2]	a[2][0]	a[2][1]	a[2][2]	

a[0][0]	a[0][1]	a[0][2]
a[1][0]	a[1][1]	a[1][2]
a[2][0]	a[2][1]	a[2][2]

 0	1	2	3	4	5	6	7	8	
 a[0][0]	a[0][1]	a[0][2]	a[1][0]	a[1][1]	a[1][2]	a[2][0]	a[2][1]	a[2][2]	

### Операции с двумерни масиви

• Дефиниране чрез тип и измерения:

```
int arr[10][50];
```

• Достъп до всеки отделен елемент:

```
int b = arr[1][2];
cin >> arr[3][5];
b = arr[4][1] + arr[2][1];
```

### Операции с двумерни масиви

• Дефиниране чрез тип и измерения:

```
int arr[10][50];
```


• Достъп до всеки отделен елемент:

```
int b = arr[1][2];
cin >> arr[3][5];
b = arr[4][1] + arr[2][1];
```

## Обхождане на фиксиран ред

```
for (int colCount = 0; colCount < 4; colCount++)</pre>
  cout << "arr[2]["
         << rowCount << "]=";
  cin >> arr[2][colCount];
                                                          a[0][3]
}
                                     a[0][0]
                                            a[0][1]
                                     a[1][0]
                                            a[1][1]
                                                          a[1][3]
                        row = 2
```

### Обхождане на всички редове



```
for (int rowCount = 0, rowCount < 4; rowCount++)</pre>
  for (int colCount = 0; colCount < 4; colCount++)</pre>
     cout << "arr["
           << rowCount << "]["
           << colCount << "]=";
     cin >> arr[rowCount][colCount];
}
              row = 0
              row = 1
                              a[2][0]
                                    a[2][1]
              row = 2
                              a[3][0]
                                   a[3][1]
                                         a[3][2]
              row = 3
                                               a[3][3]
```

```
for (int rowCount = 0, rowCount < 4; rowCount++)</pre>
  for (int colCount = 0; colCount < 4; colCount++)</pre>
     cout << "arr["
           << rowCount << "]["
           << colCount << "]=";
     cin >> arr[rowCount][colCount];
}
                              a[0][0]
                                    a[0][1]
              row = 0
              row = 1
              row = 2
                              a[3][0]
                                   a[3][1]
                                         a[3][2]
              row = 3
                                               a[3][3]
```

```
for (int rowCount = 0, rowCount < 4; rowCount++)</pre>
  for (int colCount = 0; colCount < 4; colCount++)</pre>
     cout << "arr["
           << rowCount << "]["
           << colCount << "]=";
     cin >> arr[rowCount][colCount];
}
                             a[0][0]
                                   a[0][1]
              row = 0
                             a[1][0]
                                   a[1][1]
              row = 1
              row = 2
              row = 3
```

```
for (int rowCount = 0, rowCount < 4; rowCount++)</pre>
  for (int colCount = 0; colCount < 4; colCount++)</pre>
     cout << "arr["
           << rowCount << "]["
           << colCount << "]=";
     cin >> arr[rowCount][colCount];
}
                              a[0][0]
                                    a[0][1]
              row = 0
                              a[1][0]
                                    a[1][1]
              row = 1
                              a[2][0]
                                    a[2][1]
              row = 2
              row = 3
                                                      4□ ト 4 同 ト 4 直 ト 4 直 ・ 9 Q (*)
```

Благодаря за вниманието!

