

MainWindow

	MMS	CANSAS	DIFF	UNIT
CELL_VOLTAGE_01	3.877	3.88	-0.003	V
CELL_VOLTAGE_02	3.588	3.573	0.015	V
CELL_VOLTAGE_03	2.308	2.342	-0.034	V
CELL_VOLTAGE_04	3.579	3.578	0.001	V
CELL_VOLTAGE_05	3.469	3.462	0.007	V
CELL_VOLTAGE_06	3.607	3.608	-0.001	V
CELL_VOLTAGE_07	3.407	3.404	0.003	V
CELL_VOLTAGE_08	3.543	3.541	0.002	V
CELL_VOLTAGE_09	2.972	2.979	-0.007	V
CELL_VOLTAGE_10	3.637	3.628	0.009	V
CELL_VOLTAGE_11	3.442	3.446	-0.004	V
CELL_VOLTAGE_12	3.641	3.64	0.001	V
CELL_VOLTAGE_13	3.615	3.622	-0.007	V
CELL_VOLTAGE_14	3.604	3.603	0.001	V

	MMS	CANSAS	DIFF	UNIT
EXT_TEMPERATURE_01	120.0	119.822	0.178	C
EXT_TEMPERATURE_02	120.0	120.0	0.0	C
EXT_TEMPERATURE_03	120.0	119.822	0.178	C
EXT_TEMPERATURE_04	120.0	120.0	0.0	C
INT_TEMPERATURE_01	33.3	-	-	C

LOAD DBC

START LOGGING

MCU state:MCU_Standby

CELL_14CELL_13

CELL_12CELL_11

CELL_10CELL_9

CELL_8CELL_7

CELL_6CELL_5

CELL_4CELL_3

CELL_2CELL_1

LOOP

cell controller:1+

balancing:0TOGGLE

SW-Version:unknownREQUEST

SEND VALUES

START SW-TEST

SW-Test-Report: unknown

Voltage Display

Tempeprature Display

- Start Communication
- Start Data Recording
- MCU-State
- individual Cell Selection
- Toggle Loop
- Selection Cell Controller
- Balancing-Switch
- get SW-Version
- sent CAN-Messages
- Start SW-Test
- SW-Test Feedback