Local Sandbox

A visual setup guide for Oracle-guided iOS tools, bounded local reasoning, and verifiable execution.

Oracle guidance | Shortcuts executor | Scoped file access | Xcode companion

---

BUILD ORDER

1. Folder
2. Dispatcher
3. Provider
4. Runner
5. Receipt
6. Siri

BUDGETS

6 steps initially
3 failures maximum
2 identical failures stop
One model at a time

IDENTITY

Web: ChatGPT or Apple
Native: Apple sign-in
Folder: separate permission

1

Use one executor and interchangeable reasoning

Oracle prepares a compact task. A micro-model or frontier provider proposes one tool call. A deterministic dispatcher validates and executes it. Readback evidence becomes a receipt. Siri is a voice entry and Apple-owned orchestrator.

2

Open the private observation dashboard

https://local-sandbox.ctyy4wd4c2.chatgpt.site - authenticate with ChatGPT or configured app-level Apple sign-in. The hosting provider can require its own access gate first. The online sandbox saves text files, policy, progress, and receipts. It is not a live mount of iCloud Drive.

3

Choose the iPhone path

For Shortcuts-only use, configure the recipes on the following pages. For native use, open ios/LocalSandbox.xcodeproj in Xcode, choose your developer team, enable Sign in with Apple, build to your device, then sign in to prepare an on-device workspace. Selecting an iCloud folder is optional.

What is ready, and what is still required

The macOS verifier parses the Swift sources and compiles and runs portable native crypto, account and sync, autosave, and recursive-filesystem contracts. Those checks do not build the full Xcode app, run a simulator, sign the app, or install it on an iPhone. Live Apple configuration, device acceptance, external app Shortcuts actions, real GitHub account sync, and App Review remain release gates.

01 / Prepare Workspace

Create the approved folders and the first test file.

Sequential | Compact context | Typed results | User-owned policy

SHORTCUT

Prepare Workspace

ROLE

Create the root

INPUTS

Goal, compact state, latest result, saved policy.

OUTPUT

One action or one typed result. Keep detailed traces on disk.

APPROVAL

Install/configure on iPhone. Grant folder and notification access through iOS. Never infer permission from model text.

1 **Folder**
In Files create iCloud Drive / Shortcuts / LocalSandbox. This is the only folder the dispatcher uses.

2 **Create Folder**
Create config, state, workspace, logs, and output inside it.

3 **Text**
Status: pending

4 **Save File**
Save as workspace/test.txt. Disable overwrite.

5 **Dictionary**
Return root = LocalSandbox and ready = true.

Acceptance check
All five folders exist and workspace/test.txt contains Status: pending.

02 / Tool Dispatcher

Validate one tool call, apply it, and return a compact result.

Sequential | Compact context | Typed results | User-owned policy

SHORTCUT

Tool Dispatcher

ROLE

Execute one action

INPUTS

Goal, compact state, latest result, saved policy.

OUTPUT

One action or one typed result. Keep detailed traces on disk.

APPROVAL

Install/configure on iPhone. Grant folder and notification access through iOS. Never infer permission from model text.

1 **Get Dictionary from Input**

Read tool, arguments, run_id, and call_id. Reject missing fields.

2 **If**

Allow only file.read, file.list, file.create, file.append, file.patch, device.clipboard_get, device.clipboard_set, and device.notify.

3 **Match Text**

Allow only workspace, config, state, logs, or output relative paths. Reject absolute paths, backslashes, empty segments, dot and dot-dot segments, and encoded path characters. Never accept a root from the model.

4 **Get File from Folder**

Resolve below the fixed LocalSandbox folder. file.read uses Get Text; file.list uses Get Contents of Folder and returns names. Limit reads to 8,000 characters.

5 **Match Text / Replace Text**

For patches, reread the current file and compare the expected hash where available. Require exactly one literal old-text match. Disable regular expressions in Replace Text.

6 **Save File**

Create refuses existing files. Before append or patch, save a backup in output. Perform one sequential mutation, then reread to verify.

7 **Show Notification / Clipboard**

Dispatch the requested device action. Clipboard reads occur only in a user-initiated run.

Tool Dispatcher / continued

Validate one tool call, apply it, and return a compact result.

Same shortcut | Continue in order | Validate | Record evidence

---

SHORTCUT

Tool Dispatcher

ROLE

Execute one action

INPUTS

Goal, compact state, latest result, saved policy.

OUTPUT

One action or one typed result. Keep detailed traces on disk.

APPROVAL

Install/configure on iPhone. Grant folder and notification access through iOS. Never infer permission from model text.

8

Dictionary

Return ok, tool, call_id, result, error_code, retryable. Unknown tools return INVALID_ARGUMENT.

Acceptance check

Traversal and ambiguous patches are rejected. A valid patch changes exactly one match.

03 / Agent Step - Local

Ask Locally AI for one structured action.

Sequential | Compact context | Typed results | User-owned policy

SHORTCUT

Agent Step - Local

ROLE

Micro-model reasoning

INPUTS

Goal, compact state, latest result, saved policy.

OUTPUT

One action or one typed result. Keep detailed traces on disk.

APPROVAL

Install/configure on iPhone. Grant folder and notification access through iOS. Never infer permission from model text.

1 **Get Dictionary from Input**

Read goal, policy, capsule, and last_result.

2 **Text**

Use config/oracle.md, relevant tool schemas, the goal, capsule, and latest result. Stay within contextChars. Character count is a proxy; measure tokens in a runtime with a tokenizer.

3 **Ask Locally AI**

Select an installed local model. Pass the previous Text output. This requires Locally AI to expose its Shortcuts action. For LM Link use its verified in-app Shortcuts action through the same adapter. If no text action is available, use the manual return flow.

4 **Get Dictionary from Input**

Require a JSON object with kind = tool or final. Reject prose and markdown fences.

5 **Stop and Output**

Return the action. The model never executes it.

Acceptance check

One valid JSON action is returned. Invalid JSON consumes a failure and gets one repair attempt.

04 / Agent Step - ChatGPT

Use your signed-in ChatGPT app through Shortcuts.

Sequential | Compact context | Typed results | User-owned policy

SHORTCUT

Agent Step - ChatGPT

ROLE

Subscription app guidance

INPUTS

Goal, compact state, latest result, saved policy.

OUTPUT

One action or one typed result. Keep detailed traces on disk.

APPROVAL

Install/configure on iPhone. Grant folder and notification access through iOS. Never infer permission from model text.

1

Open ChatGPT

Sign in to the ChatGPT app with your existing account. Local Sandbox never receives its credentials.

2

Create Shortcut

Name it Agent Step - ChatGPT. In Apps, choose the text-returning ChatGPT action offered by your installed version. Pass Shortcut Input to it.

3

If unavailable

Use Open App to open ChatGPT, paste the prompt, and return its response manually to Local Sandbox. Do not substitute an API endpoint.

4

Stop and Output

Return the app output as text. The native dispatcher validates one JSON action before executing it.

Acceptance check

The signed-in app returns one valid JSON action. A subscription is not an API key.

05 / Agent Step - Grok

Use Grok through your configured iOS Shortcut.

Sequential | Compact context | Typed results | User-owned policy

SHORTCUT

Agent Step - Grok

ROLE

App account handoff

INPUTS

Goal, compact state, latest result, saved policy.

OUTPUT

One action or one typed result. Keep detailed traces on disk.

APPROVAL

Install/configure on iPhone. Grant folder and notification access through iOS. Never infer permission from model text.

1 **Open the app**

Sign in inside Grok. Local Sandbox does not receive your subscription credentials.

2 **Create the adapter**

Name the Shortcut Agent Step - Grok. Pass Shortcut Input to the text-returning app action offered by your installed version.

3 **No action available**

Choose Open App for your installed app, paste the bounded prompt, and return the response manually. Do not assume an undocumented vendor action or URL scheme.

4 **Return**

Stop and Output one JSON tool or final action. Validate in the native dispatcher before applying.

5 **Test and save**

Run the harmless round-trip probe in Apps & Shortcuts. Save the exact name, optional iCloud share link, and your test result.

Acceptance check

A real text round-trip succeeded. Cloud app handoff is explicitly authorized. No model API key is configured.

06 / Agent Step - Grokbot

Use Grokbot through your configured iOS Shortcut.

Sequential | Compact context | Typed results | User-owned policy

SHORTCUT

Agent Step - Grokbot

ROLE

App account handoff

INPUTS

Goal, compact state, latest result, saved policy.

OUTPUT

One action or one typed result. Keep detailed traces on disk.

APPROVAL

Install/configure on iPhone. Grant folder and notification access through iOS. Never infer permission from model text.

1 **Open the app**

Sign in inside Grokbot. Local Sandbox does not receive your subscription credentials.

2 **Create the adapter**

Name the Shortcut Agent Step - Grokbot. Pass Shortcut Input to the text-returning app action offered by your installed version.

3 **No action available**

Choose Open App for your installed app, paste the bounded prompt, and return the response manually. Do not assume an undocumented vendor action or URL scheme.

4 **Return**

Stop and Output one JSON tool or final action. Validate in the native dispatcher before applying.

5 **Test and save**

Run the harmless round-trip probe in Apps & Shortcuts. Save the exact name, optional iCloud share link, and your test result.

Acceptance check

A real text round-trip succeeded. Cloud app handoff is explicitly authorized. No model API key is configured.

07 / Agent Step - Claude

Use Claude through your configured iOS Shortcut.

Sequential | Compact context | Typed results | User-owned policy

SHORTCUT

Agent Step - Claude

ROLE

App account handoff

INPUTS

Goal, compact state, latest result, saved policy.

OUTPUT

One action or one typed result. Keep detailed traces on disk.

APPROVAL

Install/configure on iPhone. Grant folder and notification access through iOS. Never infer permission from model text.

1 **Open the app**

Sign in inside Claude. Local Sandbox does not receive your subscription credentials.

2 **Create the adapter**

Name the Shortcut Agent Step - Claude. Pass Shortcut Input to the text-returning app action offered by your installed version.

3 **No action available**

Choose Open App for your installed app, paste the bounded prompt, and return the response manually. Do not assume an undocumented vendor action or URL scheme.

4 **Return**

Stop and Output one JSON tool or final action. Validate in the native dispatcher before applying.

5 **Test and save**

Run the harmless round-trip probe in Apps & Shortcuts. Save the exact name, optional iCloud share link, and your test result.

Acceptance check

A real text round-trip succeeded. Cloud app handoff is explicitly authorized. No model API key is configured.

08 / Agent Step - Apple

Use the companion app’s Foundation Models action.

Sequential | Compact context | Typed results | User-owned policy

SHORTCUT

Agent Step - Apple

ROLE

Apple Intelligence

INPUTS

Goal, compact state, latest result, saved policy.

OUTPUT

One action or one typed result. Keep detailed traces on disk.

APPROVAL

Install/configure on iPhone. Grant folder and notification access through iOS. Never infer permission from model text.

1 **Run App Intent**

Select Local Sandbox -> Plan One Step after installing the native companion.

2 **Text**

Pass the compact goal, state, relevant tools, and last result. Reserve space for output.

3 **If**

Check model availability. When unavailable, stop this run and return its reason. Start a new task with an explicitly selected provider; never switch the active route.

4 **Get Dictionary from Input**

Validate the same action contract. The dispatcher owns execution.

Acceptance check

The provider reports availability. Siri starts actions; Foundation Models performs the model step.

09 / Local Sandbox

Run sequential actions, repair failures, and checkpoint progress.

Sequential | Compact context | Typed results | User-owned policy

SHORTCUT

Local Sandbox

ROLE

Own the agent loop

INPUTS

Goal, compact state, latest result, saved policy.

OUTPUT

One action or one typed result. Keep detailed traces on disk.

APPROVAL

Install/configure on iPhone. Grant folder and notification access through iOS. Never infer permission from model text.

1

Shortcut Input / Ask for Input

Accept text from Siri, the Share Sheet, or the dashboard. Generate UUID. Load config/policy.json.

2

Get Battery Level

Record initial level. Before each step, stop below batteryReserve or when observed level drop reaches batteryBudget. Charging can mask consumption; this measures level drop only.

3

Save File

Write state/active.json with run_id, task, step, failure counts, and last completed call ID.

4

Repeat

Repeat up to maxSteps. Call one selected Agent Step. Never run concurrent model steps.

5

If / Run Shortcut

For kind = tool call Tool Dispatcher. Record its call ID and result before another model call.

6

If

Retry transient reads once. Repair invalid JSON once. Reread on patch mismatch. Permission denial blocks. Stop at 3 failures or 2 identical failures. Never blindly retry an uncertain mutation.

7

Text

Compact to goal, completed steps, next action, file versions, constraints, and failures. Target a 200–500 token capsule; keep the trace on disk.

Local Sandbox / continued

Run sequential actions, repair failures, and checkpoint progress.

Same shortcut | Continue in order | Validate | Record evidence

---

SHORTCUT

Local Sandbox

ROLE

Own the agent loop

INPUTS

Goal, compact state, latest result, saved policy.

OUTPUT

One action or one typed result. Keep detailed traces on disk.

APPROVAL

Install/configure on iPhone. Grant folder and notification access through iOS. Never infer permission from model text.

8

If

For kind = final reread changed files to verify. Without evidence return blocked.

9

Run Shortcut

Run Finish Run for every exit, including step or failure exhaustion.

Acceptance check
Read -> patch -> reread -> verified receipt. Two identical failures terminate the run.

10 / Finish Run

Save the evidence and say what happened.

Sequential | Compact context | Typed results | User-owned policy

SHORTCUT

Finish Run

ROLE

Receipt and notification

INPUTS

Goal, compact state, latest result, saved policy.

OUTPUT

One action or one typed result. Keep detailed traces on disk.

APPROVAL

Install/configure on iPhone. Grant folder and notification access through iOS. Never infer permission from model text.

1 **Dictionary**

Create id, goal, status, origin = shortcut, summary, steps, failures, durationMs, createdAt, trace. Status is verified, blocked, or cancelled.

2 **Save File**

Write logs/<run-id>.json. Raw traces stay outside the next prompt.

3 **Show Notification**

If enabled, show status and a short summary.

4 **Stop and Output**

Return the receipt. Use Import receipt in the dashboard. Native runs retain receipts in the selected folder.

Acceptance check
A blocked run also produces a receipt with its reason.

11 / Siri + Share Sheet

Expose the same runner through voice and sharing.

Sequential | Compact context | Typed results | User-owned policy

SHORTCUT

Siri + Share Sheet

ROLE

Launch from anywhere

INPUTS

Goal, compact state, latest result, saved policy.

OUTPUT

One action or one typed result. Keep detailed traces on disk.

APPROVAL

Install/configure on iPhone. Grant folder and notification access through iOS. Never infer permission from model text.

1

Shortcut Details

Enable Show in Share Sheet for text. Name the runner Local Sandbox.

2

Siri

Say “Siri, Local Sandbox.” Siri launches the shortcut with its existing permissions.

3

Settings

On a supported iPhone assign Shortcuts -> Local Sandbox to the Action Button.

4

Add to Home Screen

In Safari use Share -> Add to Home Screen for this dashboard. Use the native app for Apple sign-in and scoped iCloud access.

Acceptance check
Voice and shared text use the same runner, policy, and limits.

Native setup / Xcode

Apple identity, scoped iCloud access, and local execution are separate capabilities.

iOS 26+ / test 27 | SwiftUI | App Intents | Foundation Models

OPEN

ios/LocalSandbox.xcodeproj

SIGNING

Select an Apple Developer team and a unique bundle ID.

CAPABILITIES

Sign in with Apple is declared. The system folder picker grants scoped access.

RELEASE GATE

Run on a supported iPhone. Simulator battery readings are unavailable, so resource admission blocks there.

1

Build and sign

Use Xcode with an SDK and device support matching your installed iOS release. The deployment target is iOS 26; the iOS 27.0 device acceptance matrix is explicit. Set DEVELOPMENT_TEAM and a unique PRODUCT_BUNDLE_IDENTIFIER in Signing & Capabilities. The project contains no signing identity or private key.

2

Sign in with Apple

AuthenticationServices binds the native Apple credential to a nonce. The app can exchange the identity token for a 15-minute, device-only bearer for the same opaque workspace owner. The server supports standalone Apple sign-in and deliberate linking to a ChatGPT-owned workspace. It never merges accounts by email. Production Apple identifiers, keys, domain, and accounts still require live qualification.

3

Select your sandbox

In native Settings choose iCloud Drive / Shortcuts / LocalSandbox through the system folder picker. The app stores a scoped bookmark and coordinates file reads and writes. A revoked or unavailable folder blocks execution.

4

Configure a provider

Installing the native app registers its App Shortcuts automatically. Saved and explicit choices never substitute. Best local considers only Apple and Locally. Cold start applies only while neither has comparable evidence: it targets available Apple, otherwise Locally, but blocks until that route is task-qualified. As soon as either has comparable evidence, measured ranking applies and an ineligible selected route blocks. Each run fixes its provider before the first action. Provider authentication stays in each app. Local validation does not prove provider login, active model, response origin, or Shortcut contents.

5

Test the actual device

Run the model contract test against workspace/test.txt. Verify file contents, app receipt, interruption behavior, permission denial, battery reserve, cancellation, and thermal admission. Inspect the checkpoint after a crash before starting another run.

Resource policy / exact meaning

Your sliders authorize stop thresholds and model context choices, not OS-level resource reservations.

Consent | Measurement | Admission | Cancellation

DEFAULT POLICY

15% battery drop
20% reserve
35% app memory target
6 steps
3 failures

CLOUD

Off by default. Selecting an app does not authorize sending it your task.

CONTEXT

6,000 characters is a proxy, not a guaranteed token count. Measure tokenizer counts in qualified runtimes.

1

Battery

The runner reads the current battery percentage before and during a model step. It stops below the reserve or at the observed level-drop budget. While charging, that drop is not a measurement of consumed energy.

2

Memory

The native monitor reads this app process footprint relative to physical memory. It does not observe separate Foundation Models services or another local-provider app. iOS owns allocation and can terminate work earlier.

3

Thermal and cancellation

Serious or critical thermal pressure requests cancellation. Cooperative cancellation can take time; the runner rechecks limits before a tool runs. The web dashboard never displays fabricated live device telemetry.

4

Failure recovery

Invalid JSON and patch conflicts return to the model within the failure budget. Edits require a fresh hash and one literal old-text match. Call journals record pending before mutation and refuse uncertain replays. An interrupted run must be reviewed.

5

Evidence-driven qualification

Run strict-json, read-tool, list-tool, patch-tool, and bounded-context. The first suite needs all five completed probe types, at least four schema-valid responses, at least four passing assertions, and zero integrity faults. The protected ledger stores at most 240 attempts. Scores use only the 20 freshest attempts and require both pass rates to stay at or above 80 percent.

App handoffs / native stack

Use a persistent task checkpoint while iOS switches between the apps you already use.

App accounts | No model API | One action | Return to Oracle

ACCOUNT

Sign in inside ChatGPT, Grok, Grokbot, Claude, or Locally.

INSTALLATION

Native App Shortcuts register with the installed app. A personal Shortcut needs review and Apple confirmation.

CAPABILITY

No undocumented vendor action, scheme, or subscription scope is assumed.

1

Begin or Run

Add Local Sandbox - Begin Oracle Task or Run Bounded Task. Supply Goal and choose Saved provider, Best local, Apple Intelligence, Locally, ChatGPT, Grok, Grokbot, or Claude. Saved and explicit choices stay pinned. The selected route cannot switch mid-run.

2

Decode and run provider

Use Get Dictionary from Input. Send only payload to the user-reviewed provider Shortcut and save its output as raw Response. Authentication stays in that provider app. Local Sandbox validates only the returned challenge response; it does not attest the response source, Shortcut contents, or login state. Record live visual device evidence.

3

Apply Validated Action

Pass the returned raw Response to Local Sandbox - Apply Validated Action. It validates and executes one tool inside the saved resource, cloud, clipboard, path, hash, step, and failure boundaries, then returns another version 1 JSON envelope. An unattended flow does not display a separate content-review screen. Decode that output with Get Dictionary from Input.

4

Continue or finish

If phase is awaiting_response, read payload and send only that text to the same provider Shortcut. Otherwise retain or import the receipt stored in payload and stop. Set Repeat to the saved maximum steps. The receipt records provider, Siri/App Shortcut origin, action order, and hashes for both handoff directions.

5

Measure and apply

Run Begin Provider Check, send only payload to the user-reviewed provider action, then use Record Provider Check with the raw response. Every route requires five probe types, at least 80 percent schema and assertion pass rates, zero integrity faults, all tool probes, and enough context. An external Siri route also requires an observed App Intent return for every probe. This records only that returned text reached Record Provider Check. It does not prove unattended execution or provider, account, or model provenance. Live physical-device evidence qualifies unattended operation. Manual return is never eligible for unattended Siri. Oracle ranks schema validation, assertion quality, lower observed App Intent handoff time, then a fixed provider order. The metric is not inference latency.

GitHub / compare and sync

Connect repository access separately from your model app subscriptions.

Settings | Compare | Commit | Worktree

AUTHENTICATION

Fine-grained GitHub token: selected repository, Contents read/write.

CREDENTIAL STORAGE

Web: this tab only. Native: device Keychain. No token enters a model prompt.

CONFLICT RULE

Branch movement blocks publishing. No force push.

1

Connect GitHub

Open Settings - GitHub authentication and sync. Create a fine-grained token on GitHub for the intended repository, then paste it in the password field. The app verifies the account name.

2

Save a worktree target

Enter owner/repository, an existing branch, and a regular repository file path. The local-sandbox/phone branch is a suggestion; it must exist before inspection.

3

Compare both files

Select the sandbox file and Compare with GitHub. Inspect the remote commit and both contents. The branch and path are bound to this comparison.

4

Publish or import

Commit sandbox to GitHub creates a new commit based on the compared branch. Import GitHub version uses the sandbox file revision. Refresh and compare again after any conflict.

5

Use a real Git worktree

Pull the published branch on its computer, or export a worktree patch before publishing. Run scripts/worktree-sync.py with the patch and --worktree absolute-path. Review the dry run, then add --apply. The branch, base commit, origin, paths, and hashes must match.

Updates / move to your next iPhone

Keep configuration and evidence while changing devices or installing a newer build.

Version 0.3 | Preserve data | Detect again | Signed updates

LOWER-DEVICE PATH

Select a lower-device test iPhone, such as iPhone 14 Pro, in the release matrix. Keep the native workspace and Siri App Intents through configured Shortcuts; Apple Intelligence is not assumed available.

POSITIVE MODEL TARGET

On iPhone 18 Pro Max, qualify the selected Apple provider through Foundation Models online and in Airplane Mode.

NEW DEVICE

Sign in with Apple, select the same iCloud folder, test adapters again.

RELEASE GATE

No real iOS 27 execution or App Store approval is claimed.

1

Apple capability menu

The native app reads SystemLanguageModel availability at routing time. Best local uses a cold-start target only while neither route has comparable evidence, then ranks comparable, task-qualified Apple and Locally candidates as soon as either has a suite; it never selects cloud. Every runnable route still requires current five-probe evidence. Saved and explicit choices fail instead of substituting another provider.

2

Transfer the workspace

The protected ledger stores at most 240 attempts. Qualification scores use only the 20 freshest attempts from seven days. One provider-probe pair can record once per UTC day. Device, full OS version and build, app version and build, or adapter changes start a new epoch. Repeat the checks on the new device.

3

Update the dashboard device report

In native Settings export the device report. Save the JSON and import it in web Settings. The web labels it as an imported snapshot; it does not infer hardware from a browser user agent.

4

Update the app safely

Install signed Xcode, TestFlight, or App Store updates. There is no runtime download-and-execute app patcher. Site releases preserve the database and compare-and-swap file revisions. public/updates.json identifies this version.

5

Update Shortcut stacks

A published iCloud share link opens Apple's Add Shortcut screen. The user must review and confirm the workflow and permissions. Without a published signed link, Open blank editor installs nothing. A link opening is not provider qualification and does not let Local Sandbox inspect the workflow.

Release / every aspect is a goal

The complete goal map is also available in the dashboard as an exportable checklist.

Web | Device | Apple | Distribution

DISTRIBUTION

No App Store submission is claimed. Apple signing, store metadata, screenshots, privacy labels, support details, and App Review are required.

REPOSITORY

Source is downloadable. A publication script is included. GitHub publication is reported only after a successful remote push.

1 **Oracle guidance**
Task decomposition, compact instructions, recovery advice, and evidence-based completion. Status: Implemented.

2 **Observation dashboard**
Persistent policy, setup progress, online text workspace, and receipt inspection. Status: Implemented.

3 **Shortcuts stack**
Eleven visual recipes for executor, runner, providers, receipts, and Siri. Status: Device setup.

4 **Editable sandbox**
Online file tools and native access to a user-selected iCloud folder. Status: Native validation.

5 **Resource consent**
Battery-drop budget, reserve, memory target, steps, and cloud consent. Status: Implemented.

6 **Context engineering**
One action per turn, bounded results, state capsule, single model. Status: Implemented.

7 **Retry and recovery**
Typed failures, patch rereads, no blind mutation retries, terminal budgets. Status: Implemented.

8 **Subscription app providers**
ChatGPT, Grok, Grokbot, and Claude use named Shortcuts with their own signed-in app accounts. Status: Device setup.

Release goals / continued

Preserve the same execution contract across every provider.

Track | Test | Approve | Release

READINESS

Passing portable Swift contracts and a full Xcode device build are different evidence levels.

DO NOT SKIP

Real device checks and Apple account configuration.

9 **Locally AI / LM Link**
Named Shortcuts adapter using the external app’s installed integration. Status: Device setup.

10 **Apple Intelligence**
Availability-aware native Foundation Models provider. Status: Native validation.

11 **Siri**
App Intents and a named runner with system-owned orchestration. Status: Native validation.

12 **Apple sign-in**
Native AuthenticationServices and credential-state check. Requires a signed app and developer capability. Status: Apple setup.

13 **iCloud connection**
System folder picker with scoped access, separate from identity. Status: Apple setup.

14 **Xcode / App Store**
Native source and build configuration. Signing, device tests, and App Review are pending. Status: Release gate.

15 **GitHub worktree sync**
Compare, commit with branch conflict protection, import, and export hash-checked worktree patches. Status: Implemented.

16 **Versioned updates**
Preserve data and preferences; signed native app updates and revision-checked site edits. Status: Implemented.

Release goals / continued

Preserve the same execution contract across every provider.

Track | Test | Approve | Release

READINESS

Passing portable Swift contracts and a full Xcode device build are different evidence levels.

DO NOT SKIP

Real device checks and Apple account configuration.

17

GitHub publication

Source export and publication script; repository creation depends on connected capability. Status: Release gate.

On device / private workspace

A separate local web workspace with an encrypted editor and session notebook.

Local storage | Password unlock | Offline shell | Export backup

---

OPEN

Site / local / index.html. This vault is independent of the online dashboard.

IDENTITY

A vault password is not Apple sign-in, a passkey, or Face ID.

DEVICE TESTING

Offline Home Screen behavior has not been tested on an iPhone here.

1

Create the vault

Open On-device workspace from the dashboard. Choose at least 12 characters. Files and transferred messages are encrypted before browser storage. No file content or password is sent to the dashboard server.

2

Save to Home Screen

In Safari use Share, Add to Home Screen, and Open as Web App where offered. Open once online to download the shell. The native Xcode app is a separate installation.

3

Edit and record sessions

Use Code to create and save text files. Oracle session records prompts and returned text you explicitly transfer. It cannot read the private conversation history in your provider apps.

4

Back up before moving devices

Settings exports an encrypted backup. Restore with the same vault password. Clearing website data or losing the password can lose access. There is no password recovery.

5

Own the web app

Host public/local on your own HTTPS origin. Export and restore the encrypted backup when changing origins. The local app needs no model API or dashboard backend.

Repair / missing Shortcut

A saved name is a dependency, not an installed workflow.

Create | Save exact name | Test on phone | Then run

OBSERVED FAILURE

The user saw: Could not find Agent Step - Local.

ROOT CAUSE

The old run link targeted a name that had not been installed.

ONE TAP

Requires a real shared Shortcut link. No fabricated installer is bundled.

1

Prepare native files

After Apple sign-in the native source prepares a protected local workspace. Settings can switch to a selected Files or iCloud folder. Existing folders are not copied or deleted by switching.

2

Find the app actions

Installing the native app registers nine iOS 26 App Shortcuts, including Begin Provider Check, Record Provider Check, Qualify Apple Intelligence, and Apply Oracle Recommendation. iOS 27 also registers Run Long Apple Task. Every protected action requires local authentication on the executing iPhone; only data-free Open Local Sandbox may run locked. The native Shortcuts link opens this app's actions; it does not install a personal provider workflow.

3

Build the provider adapter

Save Agent Step - Local in Shortcuts using the text action actually exposed by your installed Locally app. Pass Shortcut Input into it and Stop and Output the result. If no action exists, use manual transfer.

4

Validate before running

Complete all five distinct device-local probes in one epoch. Both schema-validation and assertion-pass rates must be at least 80 percent, with zero integrity faults. Local Sandbox cannot inspect Shortcut contents, prove returned-response provenance or provider login, or observe another provider app's live model activity. The native app gates new work with its own qualification, run, pending-response, and applying-response state. After deliberate terminal-receipt import, the dashboard shows the validated committed route and ordered handoff hashes; it receives no live native or provider activity.

5

Publish a real installer

Use the tested Shortcut sharing flow to obtain an iCloud link or Apple-validated export. Add that link in Settings. Apple presents installation and permission prompts on each phone.

Sources / implementation notes

Primary documentation checked 11 September 2026. Source sections are named for direct verification.

Apple | OpenAI | Reference guide | Traceable

REFERENCE

User-supplied iOS_ChatGPT_Local_Agent_Setup_Guide.pdf, pp. 1-5. Its structure and bounded loop are retained; no model availability claims were assumed.

SDK BASELINE

The project targets documented iOS 26 APIs. Later system features must be qualified on the actual device.

1 **Apple: run a shortcut from a URL**

Shortcuts User Guide, “Run a shortcut from a URL.” A run URL starts an existing personal Shortcut and does not install it. https://support.apple.com/guide/shortcuts/run-a-shortcut-from-a-url-apd624386f42/ios

2 **Apple: App Intents interactions**

App Intents, 'Accelerating app interactions with App Intents' and 'ShortcutsLink.' The app registers its native actions. The link opens this app's Shortcuts page and does not confirm a personal workflow install. https://developer.apple.com/documentation/appintents/app-shortcuts

3 **Apple: App Intent parameters**

App Intents, “Adding parameters to an app intent.” Parameter summaries keep Goal and Provider visible in Shortcuts. https://developer.apple.com/documentation/appintents/adding-parameters-to-an-app-intent

4 **Apple: App Intent execution modes**

App Intents, “supportedModes.” Immediate foreground mode brings the app forward before device authentication and protected file actions. It does not extend runtime. https://developer.apple.com/documentation/appintents/appintent/supportedmodes

5 **Apple: App Intent authentication**

App Intents, “authenticationPolicy” and “requiresLocalDeviceAuthentication.” Protected actions require the executing iPhone to unlock; an unlocked originating device is not sufficient. https://developer.apple.com/documentation/appintents/intentauthenticationpolicy/requireslocaldeviceauthentication

6 **Apple: long-running intents**

App Intents, “LongRunningIntent.” iOS 27 extended execution uses performBackgroundTask, regular progress, and cancellation cleanup. https://developer.apple.com/documentation/appintents/longrunningintent

Sources / continued

Source provenance and implementation boundaries.

Primary sources | Exact sections | Date checked | Evidence

7 **Apple: Xcode system requirements**
Xcode 27 RC requires macOS 26.6 or later and provides the iOS 27 SDK and device support used by this release gate. https://developer.apple.com/xcode/system-requirements/

8 **Apple: cross-app orchestration**
WWDC26 Apple Intelligence Group Lab, 00:08:18 cross-app intent routing; 00:13:26 background limits; 01:00:09 on-device context. https://developer.apple.com/videos/play/wwdc2026/8011/

9 **Apple: Sign in with Apple for the web**
Account Help, “Associate your website to your app.” Local Sandbox implements the Services ID flow at /api/auth/apple/*. Production use still needs a Services ID associated with a primary App ID, a registered domain and return URL, and server secrets. https://developer.apple.com/help/account/capabilities/configure-sign-in-with-apple-for-the-web/

10 **Apple: Foundation Models**
Developer Documentation, Foundation Models framework overview. Availability must be checked at runtime. https://developer.apple.com/documentation/foundationmodels

11 **GitHub: branch conflict handling**
REST API endpoints for Git references, “Update a reference,” force=false. This refuses non-fast-forward updates. https://docs.github.com/en/rest/git/refs#update-a-reference

12 **GitHub: authentication**
Managing personal access tokens, fine-grained tokens and resource-owner/repository permissions. https://docs.github.com/en/authentication/keeping-your-account-and-data-secure/managing-your-personal-access-tokens

Sources / continued

Source provenance and implementation boundaries.

Primary sources | Exact sections | Date checked | Evidence

13

Apple: device availability

How to get Apple Intelligence, “Device requirements” and “Turn on Apple Intelligence,” published July 7, 2026. iPhone 15 Pro or newer supported families; runtime availability is still checked. https://support.apple.com/en-us/121115

14

Implementation evidence

See docs/APPLE-AUTH.md, docs/RELEASE.md, scripts/verify-release.mjs, tests/apple-auth.test.ts, tests/apple-native-auth.test.ts, and the portable Swift contract suites. The verifier records only executed checks. No device, thermal, model-quality, or live Apple-login result is claimed.