

## WEEK-1

(1BM21CS059)

**Create the above tables by properly specifying the primary keys and the foreign keys.**

```
create database 1bm21cs045_insurance;  
use 1bm21cs045_insurance;
```

```
create table person (  
  driver_id varchar(10),  
  name varchar(30),  
  address varchar(30),  
  primary key(driver_id)  
);  
desc person;
```

```
create table car(  
  reg_num varchar(10),  
  model varchar(10),  
  year int,  
  primary key(reg_num)  
);
```

```
create table accident(  
  report_num int,  
  accident_date date,  
  location varchar(20),  
  primary key(report_num)  
);  
create table owns(  
  driver_id varchar(10),  
  reg_num varchar(10),  
  primary key(driver_id,reg_num),  
  foreign key(driver_id)references person(driver_id),  
  foreign key(reg_num)references car(reg_num)  
);  
create table participated(  
  driver_id varchar(10),  
  reg_num varchar(10),  
  report_num int,  
  damage_amount int,  
  primary key(driver_id,reg_num,report_num),  
  foreign key(driver_id) references person(driver_id),
```

```
foreign key(reg_num)references car(reg_num),
foreign key(report_num) references accident(report_num)
);
```

### Enter at least five tuples

```
insert into accident values(11,'2003-01-01','Mysore road' );
insert into accident values(12,'2004-02-02','South end circle' );
insert into accident values(13,'2003-01-21','Bull temple road' );
insert into accident values(14,'2008-02-17','Mysore road' );
insert into accident values(15,'2004-03-05','Kanakpura road' );
insert into person values('A01','Richard','Srinivas nagar');
insert into person values('A02','Pradeep','Rajaji nagar');
insert into person values('A03','Smith','Ashok nagar');
insert into person values('A04','Venu','N R Colony');
insert into person values('A05','Jhon','Hanumanth nagar');
insert into car values('KA052250','Indica',1990);
insert into car values('KA031181','Lancer',1957);
insert into car values('KA095477','Toyota',1998);
insert into car values('KA053408','Honda',2008);
insert into car values('KA041702','Audi',2005);
insert into owns values('A01','KA052250');
insert into owns values('A02','KA053408');
insert into owns values('A03','KA095477');
insert into owns values('A04','KA031181');
insert into owns values('A05','KA041702');
insert into participated values('A01','KA052250',11,10000);
insert into participated values('A02','KA053408',12,50000);
insert into participated values('A03','KA095477',13,25000);
insert into participated values('A04','KA031181',14,3000);
insert into participated values('A05','KA041702',15,5000);
```

select \*from person;

Result Grid			
Filter Rows:			
Edit:			
	driver_id	name	address
▶	A01	Richard	Srinivas nagar
	A02	Pradeep	Rajaji nagar
	A03	Smith	Ashok nagar
	A04	Venu	N R Colony
	A05	Jhon	Hanumanth nagar
✱	NULL	NULL	NULL

person 1 × car 2 owns 3 accident 4 participated 5

select \*from car;

Result Grid			
	reg_num	model	year
▶	KA031181	Lancer	1957
	KA041702	Audi	2005
	KA052250	Indica	1990
	KA053408	Honda	2008
	KA095477	Toyota	1998
•	NULL	NULL	NULL

person 1 car 2 × owns 3 accident 4 participated 5

Output

select \*from owns;

Result Grid			
	driver_id	reg_num	
▶	A04	KA031181	
	A05	KA041702	
	A01	KA052250	
	A02	KA053408	
	A03	KA095477	
•	NULL	NULL	

person 1 car 2 owns 3 × accident 4 participated 5

Output

select \*from accident;

Result Grid			
	report_num	accident_date	location
▶	11	2003-01-01	Mysore road
	12	2004-02-02	South end circle
	13	2003-01-21	Bull temple road
	14	2008-02-17	Mysore road
	15	2004-03-05	Kanakpura road
•	NULL	NULL	NULL

person 1 car 2 owns 3 accident 4 × participated 5

select \*from participated;

Result Grid				
	driver_id	reg_num	report_num	damage_amount
▶	A01	KA052250	11	10000
	A02	KA053408	12	50000
	A03	KA095477	13	25000
	A04	KA031181	14	3000
	A05	KA041702	15	5000
•	NULL	NULL	NULL	NULL

person 1 car 2 owns 3 accident 4 participated 5 ×

Output

## Display Accident date and location

SQL> select accident\_date,location from accident;

Result Grid		Filter Rows:
accident_date	location	
2003-01-01	Mysore road	
2004-02-02	South end circle	
2003-01-21	Bull temple road	
2008-02-17	Mysore road	
2004-03-05	Kanakpura road	

accident 2 x

**Update the damage amount to 25000 for the car with a specific reg\_num (example 'KA053408' ) for which the accident report number was 12.**

SQL> update participated set damage\_amount=25000  
where reg\_num='KA053408' and report\_num=12;

select \*from participated;

Result Grid		Filter Rows:	Edit:
driver_id	reg_num	report_num	damage_amount
A01	KA052250	11	10000
A02	KA053408	12	25000
A03	KA095477	13	25000
A04	KA031181	14	3000
A05	KA041702	15	5000
NULL	NULL	NULL	NULL

participated 6 x

**Add a new accident to the database.**

SQL> insert into accident values(16,'2008-03-08','Domlur');

select \*from accident;

Result Grid		Filter Rows:	Edit:
report_num	accident_date	location	
11	2003-01-01	Mysore road	
12	2004-02-02	South end circle	
13	2003-01-21	Bull temple road	
14	2008-02-17	Mysore road	
15	2004-03-05	Kanakpura road	
16	2008-03-08	Domlur	
NULL	NULL	NULL	


accident 7 x

**Find the total number of people who owned cars that were involved in accidents in 2008.**

SQL>select count(distinct driver\_id)

from participated a, accident b

where a.report\_num=b.report\_num and b.accident\_date like '%08%';



Result Grid | Filter Rows: | Export: | Wrap Cell Content


count(distinct driver_id)
1

Result 9 x

## TO DO

**Display Accident date and location.**

SQL> select accident\_date,location from accident;




Result Grid | Filter Rows: | Export

accident_date	location
2003-01-01	Mysore road
2004-02-02	South end circle
2003-01-21	Bull temple road
2008-02-17	Mysore road
2004-03-05	Kanakpura road
2008-03-08	Domlur

**Display driver id who did an accident with damage amount greater than or equal to Rs.25000.**

SQL>select driver\_id from participated  
where damage\_amount>=25000;



Result Grid | Filter Rows: | Export: | Wrap Cell Content: |

driver_id
A02
A03

participated 10 x