

Service Report API Specification

Authentication

Use a static API key passed via the `X-API-Key` header. No login/session required.

```
X-API-Key: <your-api-key>
```

- For **development**: please provide us a working API key so we can start integration immediately.
- For **production**: ATP staff will generate and manage their own API keys from your system for security purposes.

The API should return `401 Unauthorized` if the key is missing or invalid:

```
{ "error": "Unauthorized", "message": "Invalid or missing API key" }
```

Endpoint

```
POST /api/service-report.php
Content-Type: application/json
X-API-Key: <your-api-key>
```

Request DTO (Filter)

```
{
  "categories": ["RPS", "SN", "PM", "UP", "OTH", "MR", "INST"],
  "statuses": [
    "Other 1", "Other 2", "New", "Waiting Reply", "Closed", "On Hold",
    "In Progress", "Resolved", "Follow Up", "Cancel", "Appointment Made",
    "Repeat-1", "Repeat-2"
  ],
  "zones": [1, 2, 3, 5, 14],
  "parts_supplies": "No Request | Request | null",
  "date_from": "2026-04-01",
  "date_to": "2026-04-13",
  "date_field": "created_at | last_update",
  "tracking_id": "RPS-260413-016",
  "location": "TLDM TG PENGELIH",
  "last_replier": "HAZIQ",
  "technician": "Saifudin",
  "page": 1,
  "page_size": 25
}
```

Request Field Details

Field	Type	Required	Description
categories	string[]	No	Filter by category codes. Values: RPS, SN, PM, UP, OTH, MR, INST. Omit or empty array = all.
statuses	string[]	No	Filter by status. Values: other 1, other 2, New, waiting Reply, Closed, On Hold, In Progress, Resolved, Follow Up, Cancel, Appointment Made, Repeat-1, Repeat-2. Omit or empty = all.
zones	int[]	No	Filter by zone numbers (1-20). Omit or empty = all.
parts_supplies	string	No	"No Request", "Request", or null for all.
date_from	string	No	Start date, format YYYY-MM-DD.
date_to	string	No	End date, format YYYY-MM-DD.
date_field	string	No	Which date column to filter on. "created_at" (default) or "last_update".
tracking_id	string	No	Filter by tracking ID. Partial match / contains search (e.g. "260413" matches RPS-260413-016). null = all.
location	string	No	Filter by customer name or address. Partial match / contains search. null = all.
last_replier	string	No	Filter by last replier name. null = all.
technician	string	No	Filter by technician name. null = all.
page	int	No	Page number, default 1.
page_size	int	No	Records per page, default 25.

Response DTO

```
{
  "total_records": 67007,
  "page": 1,
  "page_size": 25,
  "data": [
    {
      "location": "TLDM TG PENGELIH\n\nTG PENGELIH KOTA TINGGI 0 JOHOR",
      "technician": "HAZIQ",
      "issue_message": "Print Quality (Blur, Dark Line) - print get line",
    }
  ]
}
```

```

    "status": "In Progress",
    "device": "IRADV DX C3830i\n\n(2XH01059)",
    "parts_supplies": "",
    "total_bk": null,
    "total_cl": null,
    "zone": 2,
    "tracking_id": "RPS-260413-016",
    "created_at": "2026-04-13 09:54:25",
    "last_update": "2026-04-13 09:54:25",
    "last_replier": "HAZIQ",
    "replies": null
  }
]
}

```

Response Field Details

Field	Type	Description
total_records	int	Total matching records (for pagination)
page	int	Current page number
page_size	int	Records per page
data	object[]	Array of service report entries
data[].location	string	Customer name + full address
data[].technician	string	Assigned technician name
data[].issue_message	string	Issue / message description
data[].status	string	Current status
data[].device	string	Device model + serial number in parentheses
data[].parts_supplies	string	Parts/supplies info, empty string if none
data[].total_bk	int\ null	Total BK count
data[].total_cl	int\ null	Total CL count
data[].zone	int	Zone number
data[].tracking_id	string	Tracking ID (e.g. RPS-260413-016)
data[].created_at	string	Created datetime YYYY-MM-DD HH:mm:ss
data[].last_update	string	Last update datetime YYYY-MM-DD HH:mm:ss
data[].last_replier	string	Name of last replier
data[].replies	int\ null	Reply count

Example cURL

```
curl -X POST https://your-domain.com/api/service-report.php \  
-H "Content-Type: application/json" \  
-H "X-API-Key: YOUR_API_KEY_HERE" \  
-d '{  
  "categories": ["RPS"],  
  "statuses": ["In Progress", "New"],  
  "zones": [2, 14],  
  "date_from": "2026-04-01",  
  "date_to": "2026-04-13",  
  "date_field": "created_at",  
  "page": 1,  
  "page_size": 25  
'
```