Force.com Source Scanner Results

Job Type: Portal
Preset: PortalAll
Scan Id: a0OKX000001JSby2AG
Description: N/A
Email Address: dhairya@pravadhlabs.com
Security Issues: 56
Service Version: v3.2
Scan Start: 2026-09-27 21:06:40
Quality Issues: 0
CxEngine: 9.7
Scan End: 2026-09-28 02:11:42

For any questions about this service, please consult our scanner help page at https://security.secure.force.com/security/tools/forcecom/scannerhelp (https://security.secure.force.com/security/tools/forcecom/scannerhelp)

Query	Group	Issues
Apex SOQL SOSL User Mode Missing	Apex Medium Security Risk	2
Apex CRUD Violation	Apex High Security Risk	7
Apex CSRF In Aura LWC	Apex Medium Security Risk	5
Sharing	Apex Serious Security Risk	8
Apex CRUD Create Violation	Apex Serious Security Risk	23
Apex CRUD Update Violation	Apex Serious Security Risk	11
Disallowed Password APIs	Apex Critical Security Risk	No Issues Found
Lightning API Version	Apex Critical Security Risk	No Issues Found
Reflected XSS	Apex Critical Security Risk	No Issues Found
Stored XSS	Apex Critical Security Risk	No Issues Found
SOQL SOSL Injection	Apex Critical Security Risk	No Issues Found
Client DOM XSS	JavaScript High Risk	No Issues Found
Client DOM Stored Code Injection	JavaScript High Risk	No Issues Found
Client DOM Code Injection	JavaScript High Risk	No Issues Found

Client DOM Stored XSS	JavaScript High Risk	No Issues Found
CRUD Delete	Apex Serious Security Risk	No Issues Found
URL Redirection Attack	Apex Serious Security Risk	No Issues Found
XSRF	Apex Serious Security Risk	No Issues Found
FLS Create	Apex Serious Security Risk	No Issues Found
FLS Update	Apex Serious Security Risk	No Issues Found
Client Overly Permissive Message Posting	JavaScript Low Visibility	No Issues Found
Hardcoding Of Trigger New	Apex Code Quality	No Issues Found
Async Future Method Inside Loops	Apex Code Quality	No Issues Found
Test Methods With No Assert	Apex Code Quality	No Issues Found
Bulkify Apex Methods Using Collections In Methods	Apex Code Quality	No Issues Found
SOSL SOQL Statments Inside Loops	Apex Code Quality	No Issues Found
Multiple Trigger On same sObject	Apex Code Quality	No Issues Found
Queries With No Where Or Limit Clause	Apex Code Quality	No Issues Found
DML Statements Inside Loops	Apex Code Quality	No Issues Found
Hardcoding References To Static Resources	Apex Code Quality	No Issues Found
Hardcoding Ids	Apex Code Quality	No Issues Found
Multiple Forms In Visualforce Page	Apex Code Quality	No Issues Found

Query: Apex CRUD Violation

This query looks for CRUD operations that are performed without checking for isAccessible(), isUpdateable() orisDeletable(). When an object uses WhoId, WhatId, ParentId, LinkedEntityId

fields an additional CRUD check should also be performed on the parent object along with the CRUD and FLS checks on the child object and fields.

Reference:

https://developer.salesforce.com/docs/atlas.en-us.apexcode.meta/apexcode/apex_classes_perms_enforcing.htm (https://developer.salesforce.com/docs/atlas.en-us.apexcode.meta/apexcode/apex_classes_perms_enforcing.htm)

Apex CRUD Violation result path 1: Similarity Id: -2048313781

Object: `requests` in file: `classes/DocSignCancelEnvelopeAction.cls`

```
L 13: global static List<String> cancel(List<Request> requests) {
```

Object: `requests` in file: `classes/DocSignCancelEnvelopeAction.cls`

```
L 15: for (Request r : requests) {
```

Object: `r` in file: `classes/DocSignCancelEnvelopeAction.cls`

```
L 16: DocSign_Envelope__c e = DocSignEnvelopeService.findByKeyOrId(r
```

Object: `keyorid` in file: `classes/DocSignEnvelopeService.cls`

```
L 247: public static DocSign_Envelope__c findByKeyOrId(String keyOrI
```

Object: `keyorid` in file: `classes/DocSignEnvelopeService.cls`

```
L 251: String k = keyOrId.trim();
```

Object: `k` in file: `classes/DocSignEnvelopeService.cls`

```
L 253: if (k.length() == 15 || k.length() == 18) {
```

Object: `k` in file: `classes/DocSignEnvelopeService.cls`

```
L 263: WHERE Envelope_Key__c = :k OR Name = :k OR Id = :asId
```

Object: `select` in file: `classes/DocSignEnvelopeService.cls`

```
L 260: List<DocSign_Envelope__c> envs = [
```

Object: `envs` in file: `classes/DocSignEnvelopeService.cls`

```
L 266: if (envs.isEmpty()) {
```

Object: `envs` in file: `classes/DocSignEnvelopeService.cls`

```
L 269: return envs[0];
```

Object: `findbykeyorid` in file: `classes/DocSignCancelEnvelopeAction.cls`

```
L 16: DocSign_Envelope__c e = DocSignEnvelopeService.findByKeyOrId(r
```

Object: `e` in file: `classes/DocSignCancelEnvelopeAction.cls`

```
L 17: DocSignEnvelopeService.cancel(e.Id, r.reason);
```

Object: `envelopeid` in file: `classes/DocSignEnvelopeService.cls`

```
L 272: public static void cancel(Id envelopeId, String reason) {
```

Object: `envelopeid` in file: `classes/DocSignEnvelopeService.cls`

```
L 273: DocSign_Envelope__c env = getEnvelope(envelopeId);
```

Object: `envelopeid` in file: `classes/DocSignEnvelopeService.cls`

```
L 232: public static DocSign_Envelope__c getEnvelope(Id envelopeId)
```

Object: `envelopeid` in file: `classes/DocSignEnvelopeService.cls`

```
L 238: WHERE Id = :envelopeId OR Envelope_Key__c = :String.valueOf(e
```

Object: `select` in file: `classes/DocSignEnvelopeService.cls`

```
L 233: List<DocSign_Envelope__c> envs = [
```

Object: `envs` in file: `classes/DocSignEnvelopeService.cls`

```
L 241: if (envs.isEmpty()) {
```

Object: `envs` in file: `classes/DocSignEnvelopeService.cls`

```
L 244: return envs[0];
```

Object: `getenvelope` in file: `classes/DocSignEnvelopeService.cls`

```
L 273: DocSign_Envelope__c env = getEnvelope(envelopeId);
```

Object: `env` in file: `classes/DocSignEnvelopeService.cls`

```
L 279: DocSignLifecycle.afterCancel(env.Id, reason);
```

Object: `envelopeid` in file: `classes/DocSignLifecycle.cls`

```
L 6: public static void afterCancel(Id envelopeId, String reason) {
```

Object: `envelopeid` in file: `classes/DocSignLifecycle.cls`

```
L 7: DocSign_Envelope__c env = load(envelopeId);
```

Object: `envelopeid` in file: `classes/DocSignLifecycle.cls`

```
L 87: public static DocSign_Envelope__c load(Id envelopeId) {
```

Object: `envelopeid` in file: `classes/DocSignLifecycle.cls`

```
L 91: FROM DocSign_Envelope__c WHERE Id = :envelopeId WITH SYSTEM_MO
```

Object: `select` in file: `classes/DocSignLifecycle.cls`

```
L 88: return [
```

Object: `load` in file: `classes/DocSignLifecycle.cls`

```
L 7: DocSign_Envelope__c env = load(envelopeId);
```

Object: `env` in file: `classes/DocSignLifecycle.cls`

```
L 8: List<DocSign_Recipient__c> notified = invalidate(env);
```

Object: `env` in file: `classes/DocSignLifecycle.cls`

```
L 74: public static List<DocSign_Recipient__c> invalidate(DocSign_En
```

Object: `env` in file: `classes/DocSignLifecycle.cls`

```
L 77: for (DocSign_Recipient__c r : env.Recipients__r) {
```

Object: `r` in file: `classes/DocSignLifecycle.cls`

```
L 79: contacted.add(r);
```

Object: `contacted` in file: `classes/DocSignLifecycle.cls`

```
L 84: return contacted;
```

Object: `invalidate` in file: `classes/DocSignLifecycle.cls`

```
L 8: List<DocSign_Recipient__c> notified = invalidate(env);
```

Object: `notified` in file: `classes/DocSignLifecycle.cls`

```
L 14: for (DocSign_Recipient__c r : notified) {
```

Object: `r` in file: `classes/DocSignLifecycle.cls`

```
L 15: msgs.add(DocSignEmailService.notice(r.Email__c, 'Cancelled: ' +
```

Object: `toaddress` in file: `classes/DocSignEmailService.cls`

```
L 56: public static Messaging.SingleEmailMessage notice(String toAdd
```

Object: `toaddress` in file: `classes/DocSignEmailService.cls`

```
L 58: return build(toAddress, subject, html, atts);
```

Object: `toaddress` in file: `classes/DocSignEmailService.cls`

```
L 61: private static Messaging.SingleEmailMessage build(String toAdd
```

Object: `toaddress` in file: `classes/DocSignEmailService.cls`

```
L 63: m.setToAddresses(new List<String>{ toAddress });
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 64: m.setSubject(subject.left(250));
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 65: m.setHtmlBody(wrap(innerHtml));
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 66: m.setPlainTextBody(innerHtml.replaceAll('<[^>]+>', ' ').replac
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 67: m.setSaveAsActivity(false);
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 68: m.setUseSignature(false);
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 71: m.setOrgWideEmailAddressId(owea);
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 78: return m;
```

Object: `build` in file: `classes/DocSignEmailService.cls`

```
L 53: return build(r.Email__c, subject, String.join(b, ''), null);
```

Object: `signingrequest` in file: `classes/DocSignRoutingService.cls`

```
L 47: msgs.add(DocSignEmailService.signingRequest(env, r, DocSignEma
```

Object: `msgs` in file: `classes/DocSignRoutingService.cls`

```
L 50: List<Messaging.SendEmailResult> results = DocSignEmailService.
```

Object: `msgs` in file: `classes/DocSignEmailService.cls`

```
L 81: public static List<Messaging.SendEmailResult> send(List<Messag
```

Object: `msgs` in file: `classes/DocSignEmailService.cls`

```
L 82: if (msgs == null || msgs.isEmpty()) {
```

Object: `msgs` in file: `classes/DocSignEmailService.cls`

```
L 86: return Messaging.sendEmail(msgs, false);
```

Apex CRUD Violation result path 2: Similarity Id: 1959093540

Object: `payload` in file: `classes/DocSignRecordController.cls`

```
L 327: public static DocSignEnvelopeService.SendResult send(String pa
```

Object: `settoaddresses` in file: `classes/DocSignEmailService.cls`

```
L 63: m.setToAddresses(new List<String>{ toAddress });
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 64: m.setSubject(subject.left(250));
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 65: m.setHtmlBody(wrap(innerHtml));
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 66: m.setPlainTextBody(innerHtml.replaceAll('<[^>]+>', ' ').replace
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 67: m.setSaveAsActivity(false);
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 68: m.setUseSignature(false);
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 71: m.setOrgWideEmailAddressId(owea);
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 78: return m;
```

Object: `build` in file: `classes/DocSignEmailService.cls`

```
L 53: return build(r.Email__c, subject, String.join(b, ''), null);
```

Object: `signingrequest` in file: `classes/DocSignRoutingService.cls`

```
L 47: msgs.add(DocSignEmailService.signingRequest(env, r, DocSignEma
```

Object: `msgs` in file: `classes/DocSignRoutingService.cls`

```
L 50: List<Messaging.SendEmailResult> results = DocSignEmailService.
```

Object: `msgs` in file: `classes/DocSignEmailService.cls`

```
L 81: public static List<Messaging.SendEmailResult> send(List<Messag
```

Object: `msgs` in file: `classes/DocSignEmailService.cls`

```
L 82: if (msgs == null || msgs.isEmpty()) {
```

Object: `msgs` in file: `classes/DocSignEmailService.cls`

```
L 86: return Messaging.sendEmail(msgs, false);
```

Apex CRUD Violation result path 3: Similarity Id: -206675810

Object: `requests` in file: `classes/DocSignSendForSignatureAction.cls`

```
L 34: global static List<Result> send(List<Request> requests) {
```

Object: `settoaddresses` in file: `classes/DocSignEmailService.cls`

```
L 63: m.setToAddresses(new List<String>{ toAddress });
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 64: m.setSubject(subject.left(250));
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 65: m.setHtmlBody(wrap(innerHtml));
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 66: m.setPlainTextBody(innerHtml.replaceAll('<[^>]+>', ' ').replac
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 67: m.setSaveAsActivity(false);
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 68: m.setUseSignature(false);
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 71: m.setOrgWideEmailAddressId(owea);
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 78: return m;
```

Object: `build` in file: `classes/DocSignEmailService.cls`

```
L 53: return build(r.Email__c, subject, String.join(b, ''), null);
```

Object: `signingrequest` in file: `classes/DocSignRoutingService.cls`

```
L 47: msgs.add(DocSignEmailService.signingRequest(env, r, DocSignEma
```

Object: `msgs` in file: `classes/DocSignRoutingService.cls`

```
L 50: List<Messaging.SendEmailResult> results = DocSignEmailService.
```

Object: `msgs` in file: `classes/DocSignEmailService.cls`

```
L 81: public static List<Messaging.SendEmailResult> send(List<Messag
```

Object: `msgs` in file: `classes/DocSignEmailService.cls`

```
L 82: if (msgs == null || msgs.isEmpty()) {
```

Object: `msgs` in file: `classes/DocSignEmailService.cls`

```
L 86: return Messaging.sendEmail(msgs, false);
```

Apex CRUD Violation result path 4: Similarity Id: -645176336

Object: `toaddress` in file: `classes/DocSignHomeController.cls`

```
L 159: public static DocSignEmailHealth.TestResult sendTestEmail(Str
```

Object: `toaddress` in file: `classes/DocSignHomeController.cls`

```
L 161: return DocSignEmailHealth.sendTest(toAddress);
```

Object: `toaddress` in file: `classes/DocSignEmailHealth.cls`

```
L 106: public static TestResult sendTest(String toAddress) {
```

Object: `toaddress` in file: `classes/DocSignEmailHealth.cls`

```
L 110: String to = toAddress == null ? '' : toAddress.trim();
```

Object: `to` in file: `classes/DocSignEmailHealth.cls`

```
L 115: to,
```

Object: `toaddress` in file: `classes/DocSignEmailService.cls`

```
L 56: public static Messaging.SingleEmailMessage notice(String toAdd
```

Object: `toaddress` in file: `classes/DocSignEmailService.cls`

```
L 58: return build(toAddress, subject, html, atts);
```

Object: `toaddress` in file: `classes/DocSignEmailService.cls`

```
L 61: private static Messaging.SingleEmailMessage build(String toAdd
```

Object: `toaddress` in file: `classes/DocSignEmailService.cls`

```
L 63: m.setToAddresses(new List<String>{ toAddress });
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 64: m.setSubject(subject.left(250));
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 65: m.setHtmlBody(wrap(innerHtml));
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 66: m.setPlainTextBody(innerHtml.replaceAll('<[^>]+>', ' ').replac
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 67: m.setSaveAsActivity(false);
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 68: m.setUseSignature(false);
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 71: m.setOrgWideEmailAddressId(owea);
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 78: return m;
```

Object: `build` in file: `classes/DocSignEmailService.cls`

```
L 53: return build(r.Email__c, subject, String.join(b, ''), null);
```

Object: `signingrequest` in file: `classes/DocSignRoutingService.cls`

```
L 47: msgs.add(DocSignEmailService.signingRequest(env, r, DocSignEma
```

Object: `msgs` in file: `classes/DocSignRoutingService.cls`

```
L 50: List<Messaging.SendEmailResult> results = DocSignEmailService.
```

Object: `msgs` in file: `classes/DocSignEmailService.cls`

```
L 81: public static List<Messaging.SendEmailResult> send(List<Messag
```

Object: `msgs` in file: `classes/DocSignEmailService.cls`

```
L 82: if (msgs == null || msgs.isEmpty()) {
```

Object: `msgs` in file: `classes/DocSignEmailService.cls`

```
L 86: return Messaging.sendEmail(msgs, false);
```

Apex CRUD Violation result path 5: Similarity Id: -1402323356

Object: `envelopeid` in file: `classes/DocSignWorkspaceController.cls`

```
L 222: public static Integer resendEnvelope(Id envelopeId) {
```

Object: `envelopeid` in file: `classes/DocSignWorkspaceController.cls`

```
L 224: return DocSignEnvelopeService.resend(envelopeId);
```

Object: `envelopeid` in file: `classes/DocSignEnvelopeService.cls`

```
L 282: public static Integer resend(Id envelopeId) {
```

Object: `envelopeid` in file: `classes/DocSignEnvelopeService.cls`

```
L 283: DocSign_Envelope__c env = getEnvelope(envelopeId);
```

Object: `envelopeid` in file: `classes/DocSignEnvelopeService.cls`

```
L 232: public static DocSign_Envelope__c getEnvelope(Id envelopeId)
```

Object: `envelopeid` in file: `classes/DocSignEnvelopeService.cls`

```
L 238: WHERE Id = :envelopeId OR Envelope_Key__c = :String.valueOf(e
```

Object: `select` in file: `classes/DocSignEnvelopeService.cls`

```
L 233: List<DocSign_Envelope__c> envs = [
```

Object: `envs` in file: `classes/DocSignEnvelopeService.cls`

```
L 241: if (envs.isEmpty()) {
```

Object: `envs` in file: `classes/DocSignEnvelopeService.cls`

```
L 244: return envs[0];
```

Object: `getenvelope` in file: `classes/DocSignEnvelopeService.cls`

```
L 283: DocSign_Envelope__c env = getEnvelope(envelopeId);
```

Object: `env` in file: `classes/DocSignEnvelopeService.cls`

```
L 291: return DocSignRoutingService.sendCurrentGroup(env.Id, 'resend
```

Object: `envelopeid` in file: `classes/DocSignRoutingService.cls`

```
L 17: public static Integer sendCurrentGroup(Id envelopeId, String k
```

Object: `envelopeid` in file: `classes/DocSignRoutingService.cls`

```
L 27: WHERE Envelope__c = :envelopeId AND Routing_Order__c = :env.Cu
```

Object: `select` in file: `classes/DocSignRoutingService.cls`

```
L 24: List<DocSign_Recipient__c> recips = [
```

Object: `recips` in file: `classes/DocSignRoutingService.cls`

```
L 30: if (recips.isEmpty()) {
```

Object: `recips` in file: `classes/DocSignRoutingService.cls`

```
L 36: for (DocSign_Recipient__c r : recips) {
```

Object: `r` in file: `classes/DocSignRoutingService.cls`

```
L 38: r.Token_Hash__c = DocSignTokenService.hash(token);
```

Object: `r` in file: `classes/DocSignRoutingService.cls`

```
L 42: r.Failed_Access_Attempts__c = 0;
```

Object: `r` in file: `classes/DocSignRoutingService.cls`

```
L 46: r.Sent_Date__c = now;
```

Object: `r` in file: `classes/DocSignRoutingService.cls`

```
L 47: msgs.add(DocSignEmailService.signingRequest(env, r, DocSignEma
```

Object: `r` in file: `classes/DocSignEmailService.cls`

```
L 33: public static Messaging.SingleEmailMessage signingRequest(DocS
```

Object: `r` in file: `classes/DocSignEmailService.cls`

```
L 53: return build(r.Email__c, subject, String.join(b, ''), null);
```

Object: `toaddress` in file: `classes/DocSignEmailService.cls`

```
L 61: private static Messaging.SingleEmailMessage build(String toAdd
```

Object: `toaddress` in file: `classes/DocSignEmailService.cls`

```
L 63: m.setToAddresses(new List<String>{ toAddress });
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 64: m.setSubject(subject.left(250));
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 65: m.setHtmlBody(wrap(innerHtml));
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 66: m.setPlainTextBody(innerHtml.replaceAll('<[^>]+>', ' ').replac
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 67: m.setSaveAsActivity(false);
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 68: m.setUseSignature(false);
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 71: m.setOrgWideEmailAddressId(owea);
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 78: return m;
```

Object: `build` in file: `classes/DocSignEmailService.cls`

```
L 53: return build(r.Email__c, subject, String.join(b, ''), null);
```

Object: `signingrequest` in file: `classes/DocSignRoutingService.cls`

```
L 47: msgs.add(DocSignEmailService.signingRequest(env, r, DocSignEma
```

Object: `msgs` in file: `classes/DocSignRoutingService.cls`

```
L 50: List<Messaging.SendEmailResult> results = DocSignEmailService.
```

Object: `msgs` in file: `classes/DocSignEmailService.cls`

```
L 81: public static List<Messaging.SendEmailResult> send(List<Messag
```

Object: `msgs` in file: `classes/DocSignEmailService.cls`

```
L 82: if (msgs == null || msgs.isEmpty()) {
```

Object: `msgs` in file: `classes/DocSignEmailService.cls`

```
L 86: return Messaging.sendEmail(msgs, false);
```

Apex CRUD Violation result path 6: Similarity Id: 756821788

Object: `requests` in file: `classes/DocSignResendEnvelopeAction.cls`

```
L 11: global static List<Integer> resend(List<Request> requests) {
```

Object: `requests` in file: `classes/DocSignResendEnvelopeAction.cls`

```
L 13: for (Request r : requests) {
```

Object: `r` in file: `classes/DocSignResendEnvelopeAction.cls`

```
L 14: DocSign_Envelope__c e = DocSignEnvelopeService.findByKeyOrId(r
```

Object: `keyorid` in file: `classes/DocSignEnvelopeService.cls`

```
L 247: public static DocSign_Envelope__c findByKeyOrId(String keyOrI
```

Object: `keyorid` in file: `classes/DocSignEnvelopeService.cls`

```
L 251: String k = keyOrId.trim();
```

Object: `k` in file: `classes/DocSignEnvelopeService.cls`

```
L 253: if (k.length() == 15 || k.length() == 18) {
```

Object: `k` in file: `classes/DocSignEnvelopeService.cls`

```
L 263: WHERE Envelope_Key__c = :k OR Name = :k OR Id = :asId
```

Object: `select` in file: `classes/DocSignEnvelopeService.cls`

```
L 260: List<DocSign_Envelope__c> envs = [
```

Object: `envs` in file: `classes/DocSignEnvelopeService.cls`

```
L 266: if (envs.isEmpty()) {
```

Object: `envs` in file: `classes/DocSignEnvelopeService.cls`

```
L 269: return envs[0];
```

Object: `findbykeyorid` in file: `classes/DocSignResendEnvelopeAction.cls`

```
L 14: DocSign_Envelope__c e = DocSignEnvelopeService.findByKeyOrId(r
```

Object: `e` in file: `classes/DocSignResendEnvelopeAction.cls`

```
L 15: out.add(DocSignEnvelopeService.resend(e.Id));
```

Object: `envelopeid` in file: `classes/DocSignEnvelopeService.cls`

```
L 282: public static Integer resend(Id envelopeId) {
```

Object: `envelopeid` in file: `classes/DocSignEnvelopeService.cls`

```
L 283: DocSign_Envelope__c env = getEnvelope(envelopeId);
```

Object: `envelopeid` in file: `classes/DocSignEnvelopeService.cls`

```
L 232: public static DocSign_Envelope__c getEnvelope(Id envelopeId)
```

Object: `envelopeid` in file: `classes/DocSignEnvelopeService.cls`

```
L 238: WHERE Id = :envelopeId OR Envelope_Key__c = :String.valueOf(e
```

Object: `select` in file: `classes/DocSignEnvelopeService.cls`

```
L 233: List<DocSign_Envelope__c> envs = [
```

Object: `envs` in file: `classes/DocSignEnvelopeService.cls`

```
L 241: if (envs.isEmpty()) {
```

Object: `envs` in file: `classes/DocSignEnvelopeService.cls`

```
L 244: return envs[0];
```

Object: `getenvelope` in file: `classes/DocSignEnvelopeService.cls`

```
L 283: DocSign_Envelope__c env = getEnvelope(envelopeId);
```

Object: `env` in file: `classes/DocSignEnvelopeService.cls`

```
L 291: return DocSignRoutingService.sendCurrentGroup(env.Id, 'resend
```

Object: `envelopeid` in file: `classes/DocSignRoutingService.cls`

```
L 17: public static Integer sendCurrentGroup(Id envelopeId, String k
```

Object: `envelopeid` in file: `classes/DocSignRoutingService.cls`

```
L 27: WHERE Envelope__c = :envelopeId AND Routing_Order__c = :env.Cu
```

Object: `select` in file: `classes/DocSignRoutingService.cls`

```
L 24: List<DocSign_Recipient__c> recips = [
```

Object: `recips` in file: `classes/DocSignRoutingService.cls`

```
L 30: if (recips.isEmpty()) {
```

Object: `recips` in file: `classes/DocSignRoutingService.cls`

```
L 36: for (DocSign_Recipient__c r : recips) {
```

Object: `r` in file: `classes/DocSignRoutingService.cls`

```
L 38: r.Token_Hash__c = DocSignTokenService.hash(token);
```

Object: `r` in file: `classes/DocSignRoutingService.cls`

```
L 42: r.Failed_Access_Attempts__c = 0;
```

Object: `r` in file: `classes/DocSignRoutingService.cls`

```
L 46: r.Sent_Date__c = now;
```

Object: `r` in file: `classes/DocSignRoutingService.cls`

```
L 47: msgs.add(DocSignEmailService.signingRequest(env, r, DocSignEma
```

Object: `r` in file: `classes/DocSignEmailService.cls`

```
L 33: public static Messaging.SingleEmailMessage signingRequest(DocS
```

Object: `r` in file: `classes/DocSignEmailService.cls`

```
L 53: return build(r.Email__c, subject, String.join(b, ''), null);
```

Object: `toaddress` in file: `classes/DocSignEmailService.cls`

```
L 61: private static Messaging.SingleEmailMessage build(String toAdd
```

Object: `toaddress` in file: `classes/DocSignEmailService.cls`

```
L 63: m.setToAddresses(new List<String>{ toAddress });
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 64: m.setSubject(subject.left(250));
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 65: m.setHtmlBody(wrap(innerHtml));
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 66: m.setPlainTextBody(innerHtml.replaceAll('<[^>]+>', ' ').replac
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 67: m.setSaveAsActivity(false);
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 68: m.setUseSignature(false);
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 71: m.setOrgWideEmailAddressId(owea);
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 78: return m;
```

Object: `build` in file: `classes/DocSignEmailService.cls`

```
L 53: return build(r.Email__c, subject, String.join(b, ''), null);
```

Object: `signingrequest` in file: `classes/DocSignRoutingService.cls`

```
L 47: msgs.add(DocSignEmailService.signingRequest(env, r, DocSignEma
```

Object: `msgs` in file: `classes/DocSignRoutingService.cls`

```
L 50: List<Messaging.SendEmailResult> results = DocSignEmailService.
```

Object: `msgs` in file: `classes/DocSignEmailService.cls`

```
L 81: public static List<Messaging.SendEmailResult> send(List<Messag
```

Object: `msgs` in file: `classes/DocSignEmailService.cls`

```
L 82: if (msgs == null || msgs.isEmpty()) {
```

Object: `msgs` in file: `classes/DocSignEmailService.cls`

```
L 86: return Messaging.sendEmail(msgs, false);
```

Apex CRUD Violation result path 7: Similarity Id: 12262372

Object: `envelopeid` in file: `classes/DocSignWorkspaceController.cls`

```
L 213: public static void cancelEnvelope(Id envelopeId, String reaso
```

Object: `envelopeid` in file: `classes/DocSignWorkspaceController.cls`

```
L 215: DocSignEnvelopeService.cancel(envelopeId, reason);
```

Object: `envelopeid` in file: `classes/DocSignEnvelopeService.cls`

```
L 272: public static void cancel(Id envelopeId, String reason) {
```

Object: `envelopeid` in file: `classes/DocSignEnvelopeService.cls`

```
L 273: DocSign_Envelope__c env = getEnvelope(envelopeId);
```

Object: `envelopeid` in file: `classes/DocSignEnvelopeService.cls`

```
L 232: public static DocSign_Envelope__c getEnvelope(Id envelopeId)
```

Object: `envelopeid` in file: `classes/DocSignEnvelopeService.cls`

```
L 238: WHERE Id = :envelopeId OR Envelope_Key__c = :String.valueOf(e
```

Object: `select` in file: `classes/DocSignEnvelopeService.cls`

```
L 233: List<DocSign_Envelope__c> envs = [
```

Object: `envs` in file: `classes/DocSignEnvelopeService.cls`

```
L 241: if (envs.isEmpty()) {
```

Object: `envs` in file: `classes/DocSignEnvelopeService.cls`

```
L 244: return envs[0];
```

Object: `getenvelope` in file: `classes/DocSignEnvelopeService.cls`

```
L 273: DocSign_Envelope__c env = getEnvelope(envelopeId);
```

Object: `env` in file: `classes/DocSignEnvelopeService.cls`

```
L 279: DocSignLifecycle.afterCancel(env.Id, reason);
```

Object: `envelopeid` in file: `classes/DocSignLifecycle.cls`

```
L 6: public static void afterCancel(Id envelopeId, String reason) {
```

Object: `envelopeid` in file: `classes/DocSignLifecycle.cls`

```
L 7: DocSign_Envelope__c env = load(envelopeId);
```

Object: `envelopeid` in file: `classes/DocSignLifecycle.cls`

```
L 87: public static DocSign_Envelope__c load(Id envelopeId) {
```

Object: `envelopeid` in file: `classes/DocSignLifecycle.cls`

```
L 91: FROM DocSign_Envelope__c WHERE Id = :envelopeId WITH SYSTEM_MO
```

Object: `select` in file: `classes/DocSignLifecycle.cls`

```
L 88: return [
```

Object: `load` in file: `classes/DocSignLifecycle.cls`

```
L 7: DocSign_Envelope__c env = load(envelopeId);
```

Object: `env` in file: `classes/DocSignLifecycle.cls`

```
L 8: List<DocSign_Recipient__c> notified = invalidate(env);
```

Object: `env` in file: `classes/DocSignLifecycle.cls`

```
L 74: public static List<DocSign_Recipient__c> invalidate(DocSign_En
```

Object: `env` in file: `classes/DocSignLifecycle.cls`

```
L 77: for (DocSign_Recipient__c r : env.Recipients__r) {
```

Object: `r` in file: `classes/DocSignLifecycle.cls`

```
L 79: contacted.add(r);
```

Object: `contacted` in file: `classes/DocSignLifecycle.cls`

```
L 84: return contacted;
```

Object: `invalidate` in file: `classes/DocSignLifecycle.cls`

```
L 8: List<DocSign_Recipient__c> notified = invalidate(env);
```

Object: `notified` in file: `classes/DocSignLifecycle.cls`

```
L 14: for (DocSign_Recipient__c r : notified) {
```

Object: `r` in file: `classes/DocSignLifecycle.cls`

```
L 15: msgs.add(DocSignEmailService.notice(r.Email__c, 'Cancelled: '
```

Object: `toaddress` in file: `classes/DocSignEmailService.cls`

```
L 56: public static Messaging.SingleEmailMessage notice(String toAdd
```

Object: `toaddress` in file: `classes/DocSignEmailService.cls`

```
L 58: return build(toAddress, subject, html, atts);
```

Object: `toaddress` in file: `classes/DocSignEmailService.cls`

```
L 61: private static Messaging.SingleEmailMessage build(String toAdd
```

Object: `toaddress` in file: `classes/DocSignEmailService.cls`

```
L 63: m.setToAddresses(new List<String>{ toAddress });
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 64: m.setSubject(subject.left(250));
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 65: m.setHtmlBody(wrap(innerHtml));
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 66: m.setPlainTextBody(innerHtml.replaceAll('<[^>]+>', ' ').replac
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 67: m.setSaveAsActivity(false);
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 68: m.setUseSignature(false);
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 71: m.setOrgWideEmailAddressId(owea);
```

Object: `m` in file: `classes/DocSignEmailService.cls`

```
L 78: return m;
```

Object: `build` in file: `classes/DocSignEmailService.cls`

```
L 53: return build(r.Email__c, subject, String.join(b, ''), null);
```

Object: `signingrequest` in file: `classes/DocSignRoutingService.cls`

```
L 47: msgs.add(DocSignEmailService.signingRequest(env, r, DocSignEma
```

Object: `msgs` in file: `classes/DocSignRoutingService.cls`

```
L 50: List<Messaging.SendEmailResult> results = DocSignEmailService.
```

Object: `msgs` in file: `classes/DocSignEmailService.cls`

```
L 81: public static List<Messaging.SendEmailResult> send(List<Messag
```

Object: `msgs` in file: `classes/DocSignEmailService.cls`

```
L 82: if (msgs == null || msgs.isEmpty()) {
```

Object: `msgs` in file: `classes/DocSignEmailService.cls`

```
L 86: return Messaging.sendEmail(msgs, false);
```

Query: FLS Create

This query looks for CRUD Delete operations that are performed without checking for isCreatable() permisison before performing the Create operation on the Object and its fields.

Reference:

https://developer.salesforce.com/docs/atlas.en-us.apexcode.meta/apexcode/apex_classes_perms_enforcing.htm (https://developer.salesforce.com/docs/atlas.en-us.apexcode.meta/apexcode/apex_classes_perms_enforcing.htm)

FLS Create result path 1: Similarity Id: 232391225

Object: `left` in file: `classes/DocSignCompletionService.cls`

```
L 182: Title = title.left(255),
```

Object: `contentversion` in file: `classes/DocSignCompletionService.cls`

```
L 181: ContentVersion cv = new ContentVersion(
```

Object: `cv` in file: `classes/DocSignCompletionService.cls`

```
L 188: Database.insert(cv, AccessLevel.SYSTEM_MODE);
```

FLS Create result path 2: Similarity Id: -403451049

Object: `sanitize` in file: `classes/DocSignCompletionService.cls`

```
L 183: PathOnClient = DocSignFileService.sanitize(fileName),
```

Object: `contentversion` in file: `classes/DocSignCompletionService.cls`

```
L 181: ContentVersion cv = new ContentVersion(
```

Object: `cv` in file: `classes/DocSignCompletionService.cls`

```
L 188: Database.insert(cv, AccessLevel.SYSTEM_MODE);
```

FLS Create result path 3: Similarity Id: -846014235

Object: `data` in file: `classes/DocSignCompletionService.cls`

```
L 184: VersionData = data,
```

Object: `contentversion` in file: `classes/DocSignCompletionService.cls`

```
L 181: ContentVersion cv = new ContentVersion(
```

Object: `cv` in file: `classes/DocSignCompletionService.cls`

```
L 188: Database.insert(cv, AccessLevel.SYSTEM_MODE);
```

FLS Create result path 4: Similarity Id: 1664033101

Object: `firstpublishlocationid` in file: `classes/DocSignCompletionService.cls`

```
L 185: FirstPublishLocationId = firstPublishLocationId,
```

Object: `contentversion` in file: `classes/DocSignCompletionService.cls`

```
L 181: ContentVersion cv = new ContentVersion(
```

Object: `cv` in file: `classes/DocSignCompletionService.cls`

```
L 188: Database.insert(cv, AccessLevel.SYSTEM_MODE);
```

FLS Create result path 5: Similarity Id: -315297010

Object: `hash__c` in file: `classes/DocSignAuditService.cls`

```
L 79: ev.Hash__c = hashOf(ev);
```

Object: `ev` in file: `classes/DocSignAuditService.cls`

```
L 82: rows.add(ev);
```

Object: `rows` in file: `classes/DocSignAuditService.cls`

```
L 86: Database.insert(rows, AccessLevel.SYSTEM_MODE);
```

FLS Create result path 6: Similarity Id: -634699909

Object: `left` in file: `classes/DocSignCompletionService.cls`

```
L 208: Title = ('DocSign ' + kind + ' - ' + r.Name).left(255),
```

Object: `contentversion` in file: `classes/DocSignCompletionService.cls`

```
L 207: return new ContentVersion(
```

Object: `imagefile` in file: `classes/DocSignCompletionService.cls`

```
L 149: files.add(imageFile(envelopeId, r, 'initials', r.Initials_Ima
```

Object: `files` in file: `classes/DocSignCompletionService.cls`

```
L 154: if (files.isEmpty()) {
```

Object: `files` in file: `classes/DocSignCompletionService.cls`

```
L 157: Database.insert(files, AccessLevel.SYSTEM_MODE);
```

FLS Create result path 7: Similarity Id: -1157235052

Object: `BinaryExpr` in file: `classes/DocSignCompletionService.cls`

```
L 209: PathOnClient = 'docsign-' + kind + (png ? '.png' : '.jpg'),
```

Object: `contentversion` in file: `classes/DocSignCompletionService.cls`

```
L 207: return new ContentVersion(
```

Object: `imagefile` in file: `classes/DocSignCompletionService.cls`

```
L 149: files.add(imageFile(envelopeId, r, 'initials', r.Initials_Ima
```

Object: `files` in file: `classes/DocSignCompletionService.cls`

```
L 154: if (files.isEmpty()) {
```

Object: `files` in file: `classes/DocSignCompletionService.cls`

```
L 157: Database.insert(files, AccessLevel.SYSTEM_MODE);
```

FLS Create result path 8: Similarity Id: -933583895

Object: `base64decode` in file: `classes/DocSignCompletionService.cls`

```
L 210: VersionData = EncodingUtil.base64Decode(dataUri.substringAfte
```

Object: `contentversion` in file: `classes/DocSignCompletionService.cls`

```
L 207: return new ContentVersion(
```

Object: `imagefile` in file: `classes/DocSignCompletionService.cls`

```
L 149: files.add(imageFile(envelopeId, r, 'initials', r.Initials_Ima
```

Object: `files` in file: `classes/DocSignCompletionService.cls`

```
L 154: if (files.isEmpty()) {
```

Object: `files` in file: `classes/DocSignCompletionService.cls`

```
L 157: Database.insert(files, AccessLevel.SYSTEM_MODE);
```

FLS Create result path 9: Similarity Id: 777425060

Object: `envelopeid` in file: `classes/DocSignCompletionService.cls`

```
L 211: FirstPublishLocationId = envelopeId,
```

Object: `contentversion` in file: `classes/DocSignCompletionService.cls`

```
L 207: return new ContentVersion(
```

Object: `imagefile` in file: `classes/DocSignCompletionService.cls`

```
L 149: files.add(imageFile(envelopeId, r, 'initials', r.Initials_Ima
```

Object: `files` in file: `classes/DocSignCompletionService.cls`

```
L 154: if (files.isEmpty()) {
```

Object: `files` in file: `classes/DocSignCompletionService.cls`

```
L 157: Database.insert(files, AccessLevel.SYSTEM_MODE);
```

FLS Create result path 10: Similarity Id: -271686845

Object: `id` in file: `classes/DocSignAuditService.cls`

```
L 65: Envelope__c = env.Id,
```

Object: `docsign_audit_event__c` in file: `classes/DocSignAuditService.cls`

```
L 64: DocSign_Audit_Event__c ev = new DocSign_Audit_Event__c(
```

Object: `ev` in file: `classes/DocSignAuditService.cls`

```
L 79: ev.Hash__c = hashOf(ev);
```

Object: `ev` in file: `classes/DocSignAuditService.cls`

```
L 82: rows.add(ev);
```

Object: `rows` in file: `classes/DocSignAuditService.cls`

```
L 86: Database.insert(rows, AccessLevel.SYSTEM_MODE);
```

FLS Create result path 11: Similarity Id: -1985327645

Object: `envelope_key__c` in file: `classes/DocSignAuditService.cls`

```
L 66: Envelope_Key__c = env.Envelope_Key__c,
```

Object: `docsign_audit_event__c` in file: `classes/DocSignAuditService.cls`

```
L 64: DocSign_Audit_Event__c ev = new DocSign_Audit_Event__c(
```

Object: `ev` in file: `classes/DocSignAuditService.cls`

```
L 79: ev.Hash__c = hashOf(ev);
```

Object: `ev` in file: `classes/DocSignAuditService.cls`

```
L 82: rows.add(ev);
```

Object: `rows` in file: `classes/DocSignAuditService.cls`

```
L 86: Database.insert(rows, AccessLevel.SYSTEM_MODE);
```

FLS Create result path 12: Similarity Id: -1854673031

Object: `eventtype` in file: `classes/DocSignAuditService.cls`

```
L 67: Event_Type__c = e.eventType,
```

Object: `docsign_audit_event__c` in file: `classes/DocSignAuditService.cls`

```
L 64: DocSign_Audit_Event__c ev = new DocSign_Audit_Event__c(
```

Object: `ev` in file: `classes/DocSignAuditService.cls`

```
L 79: ev.Hash__c = hashOf(ev);
```

Object: `ev` in file: `classes/DocSignAuditService.cls`

```
L 82: rows.add(ev);
```

Object: `rows` in file: `classes/DocSignAuditService.cls`

```
L 86: Database.insert(rows, AccessLevel.SYSTEM_MODE);
```

FLS Create result path 13: Similarity Id: 693163239

Object: `seq` in file: `classes/DocSignAuditService.cls`

```
L 68: Sequence__c = seq,
```

Object: `docsign_audit_event__c` in file: `classes/DocSignAuditService.cls`

```
L 64: DocSign_Audit_Event__c ev = new DocSign_Audit_Event__c(
```

Object: `ev` in file: `classes/DocSignAuditService.cls`

```
L 79: ev.Hash__c = hashOf(ev);
```

Object: `ev` in file: `classes/DocSignAuditService.cls`

```
L 82: rows.add(ev);
```

Object: `rows` in file: `classes/DocSignAuditService.cls`

```
L 86: Database.insert(rows, AccessLevel.SYSTEM_MODE);
```

FLS Create result path 14: Similarity Id: -1202382755

Object: `recipientid` in file: `classes/DocSignAuditService.cls`

```
L 69: Recipient__c = e.recipientId,
```

Object: `docsign_audit_event__c` in file: `classes/DocSignAuditService.cls`

```
L 64: DocSign_Audit_Event__c ev = new DocSign_Audit_Event__c(
```

Object: `ev` in file: `classes/DocSignAuditService.cls`

```
L 79: ev.Hash__c = hashOf(ev);
```

Object: `ev` in file: `classes/DocSignAuditService.cls`

```
L 82: rows.add(ev);
```

Object: `rows` in file: `classes/DocSignAuditService.cls`

```
L 86: Database.insert(rows, AccessLevel.SYSTEM_MODE);
```

FLS Create result path 15: Similarity Id: 4948382

Object: `cut` in file: `classes/DocSignAuditService.cls`

```
L 70: Actor_Name__c = cut(e.actorName, 255),
```

Object: `docsign_audit_event__c` in file: `classes/DocSignAuditService.cls`

```
L 64: DocSign_Audit_Event__c ev = new DocSign_Audit_Event__c(
```

Object: `ev` in file: `classes/DocSignAuditService.cls`

```
L 79: ev.Hash__c = hashOf(ev);
```

Object: `ev` in file: `classes/DocSignAuditService.cls`

```
L 82: rows.add(ev);
```

Object: `rows` in file: `classes/DocSignAuditService.cls`

```
L 86: Database.insert(rows, AccessLevel.SYSTEM_MODE);
```

FLS Create result path 16: Similarity Id: -769261038

Object: `cut` in file: `classes/DocSignAuditService.cls`

```
L 71: Actor_Email__c = cut(e.actorEmail, 255),
```

Object: `docsign_audit_event__c` in file: `classes/DocSignAuditService.cls`

```
L 64: DocSign_Audit_Event__c ev = new DocSign_Audit_Event__c(
```

Object: `ev` in file: `classes/DocSignAuditService.cls`

```
L 79: ev.Hash__c = hashOf(ev);
```

Object: `ev` in file: `classes/DocSignAuditService.cls`

```
L 82: rows.add(ev);
```

Object: `rows` in file: `classes/DocSignAuditService.cls`

```
L 86: Database.insert(rows, AccessLevel.SYSTEM_MODE);
```

FLS Create result path 17: Similarity Id: 941435285

Object: `ts` in file: `classes/DocSignAuditService.cls`

```
L 72: Event_Timestamp__c = ts,
```

Object: `docsign_audit_event__c` in file: `classes/DocSignAuditService.cls`

```
L 64: DocSign_Audit_Event__c ev = new DocSign_Audit_Event__c(
```

Object: `ev` in file: `classes/DocSignAuditService.cls`

```
L 79: ev.Hash__c = hashOf(ev);
```

Object: `ev` in file: `classes/DocSignAuditService.cls`

```
L 82: rows.add(ev);
```

Object: `rows` in file: `classes/DocSignAuditService.cls`

```
L 86: Database.insert(rows, AccessLevel.SYSTEM_MODE);
```

FLS Create result path 18: Similarity Id: -1404772256

Object: `cut` in file: `classes/DocSignAuditService.cls`

```
L 73: IP_Address__c = cut(e.ip, 64),
```

Object: `docsign_audit_event__c` in file: `classes/DocSignAuditService.cls`

```
L 64: DocSign_Audit_Event__c ev = new DocSign_Audit_Event__c(
```

Object: `ev` in file: `classes/DocSignAuditService.cls`

```
L 79: ev.Hash__c = hashOf(ev);
```

Object: `ev` in file: `classes/DocSignAuditService.cls`

```
L 82: rows.add(ev);
```

Object: `rows` in file: `classes/DocSignAuditService.cls`

```
L 86: Database.insert(rows, AccessLevel.SYSTEM_MODE);
```

FLS Create result path 19: Similarity Id: -1037824832

Object: `cut` in file: `classes/DocSignAuditService.cls`

```
L 74: User_Agent__c = cut(e.userAgent, 255),
```

Object: `docsign_audit_event__c` in file: `classes/DocSignAuditService.cls`

```
L 64: DocSign_Audit_Event__c ev = new DocSign_Audit_Event__c(
```

Object: `ev` in file: `classes/DocSignAuditService.cls`

```
L 79: ev.Hash__c = hashOf(ev);
```

Object: `ev` in file: `classes/DocSignAuditService.cls`

```
L 82: rows.add(ev);
```

Object: `rows` in file: `classes/DocSignAuditService.cls`

```
L 86: Database.insert(rows, AccessLevel.SYSTEM_MODE);
```

FLS Create result path 20: Similarity Id: -622530702

Object: `cut` in file: `classes/DocSignAuditService.cls`

```
L 75: Document_Reference__c = cut(e.documentReference, 64),
```

Object: `docsign_audit_event__c` in file: `classes/DocSignAuditService.cls`

```
L 64: DocSign_Audit_Event__c ev = new DocSign_Audit_Event__c(
```

Object: `ev` in file: `classes/DocSignAuditService.cls`

```
L 79: ev.Hash__c = hashOf(ev);
```

Object: `ev` in file: `classes/DocSignAuditService.cls`

```
L 82: rows.add(ev);
```

Object: `rows` in file: `classes/DocSignAuditService.cls`

```
L 86: Database.insert(rows, AccessLevel.SYSTEM_MODE);
```

FLS Create result path 21: Similarity Id: -477223438

Object: `cut` in file: `classes/DocSignAuditService.cls`

```
L 76: Details__c = cut(e.details, 32000),
```

Object: `docsign_audit_event__c` in file: `classes/DocSignAuditService.cls`

```
L 64: DocSign_Audit_Event__c ev = new DocSign_Audit_Event__c(
```

Object: `ev` in file: `classes/DocSignAuditService.cls`

```
L 79: ev.Hash__c = hashOf(ev);
```

Object: `ev` in file: `classes/DocSignAuditService.cls`

```
L 82: rows.add(ev);
```

Object: `rows` in file: `classes/DocSignAuditService.cls`

```
L 86: Database.insert(rows, AccessLevel.SYSTEM_MODE);
```

FLS Create result path 22: Similarity Id: -637533983

Object: `last_event_hash__c` in file: `classes/DocSignAuditService.cls`

```
L 77: Previous_Hash__c = env.Last_Event_Hash__c
```

Object: `docsign_audit_event__c` in file: `classes/DocSignAuditService.cls`

```
L 64: DocSign_Audit_Event__c ev = new DocSign_Audit_Event__c(
```

Object: `ev` in file: `classes/DocSignAuditService.cls`

```
L 79: ev.Hash__c = hashOf(ev);
```

Object: `ev` in file: `classes/DocSignAuditService.cls`

```
L 82: rows.add(ev);
```

Object: `rows` in file: `classes/DocSignAuditService.cls`

```
L 86: Database.insert(rows, AccessLevel.SYSTEM_MODE);
```

FLS Create result path 23: Similarity Id: 1246397219

Object: `contentdocumentid` in file: `classes/DocSignFileService.cls`

```
L 40: links.add(new ContentDocumentLink(ContentDocumentId = contentD
```

Object: `links` in file: `classes/DocSignFileService.cls`

```
L 44: return links;
```

Object: `linksfor` in file: `classes/DocSignCompletionService.cls`

```
L 193: List<ContentDocumentLink> links = DocSignFileService.linksFor
```

Object: `links` in file: `classes/DocSignCompletionService.cls`

```
L 194: if (!links.isEmpty()) {
```

Object: `links` in file: `classes/DocSignCompletionService.cls`

```
L 196: Database.insert(links, false, AccessLevel.SYSTEM_MODE);
```

Query: FLS Update

This query looks for CRUD Update operations that are performed without checking for isUpdateable() permisison before performing the Update operation on the Object and its fields.

Reference:

https://developer.salesforce.com/docs/atlas.en-us.apexcode.meta/apexcode/apex_classes_perms_enforcing.htm (https://developer.salesforce.com/docs/atlas.en-us.apexcode.meta/apexcode/apex_classes_perms_enforcing.htm)

FLS Update result path 1: Similarity Id: 905403053

Object: `status__c` in file: `classes/DocSignSigningService.cls`

```
L 94: r.Status__c = 'Viewed';
```

Object: `r` in file: `classes/DocSignSigningService.cls`

```
L 99: Database.update(r, AccessLevel.SYSTEM_MODE);
```

FLS Update result path 2: Similarity Id: -507339828

Object: `viewed_date__c` in file: `classes/DocSignSigningService.cls`

```
L 97: r.Viewed_Date__c = now;
```

Object: `r` in file: `classes/DocSignSigningService.cls`

```
L 99: Database.update(r, AccessLevel.SYSTEM_MODE);
```

FLS Update result path 3: Similarity Id: -313285841

Object: `sent_date__c` in file: `classes/DocSignRoutingService.cls`

```
L 46: r.Sent_Date__c = now;
```

Object: `recips` in file: `classes/DocSignRoutingService.cls`

```
L 36: for (DocSign_Recipient__c r : recips) {
```

Object: `recips` in file: `classes/DocSignRoutingService.cls`

```
L 49: Database.update(recips, AccessLevel.SYSTEM_MODE);
```

FLS Update result path 4: Similarity Id: -1159947723

Object: `token_hash__c` in file: `classes/DocSignLifecycle.cls`

```
L 65: r.Token_Hash__c = null;
```

Object: `recips` in file: `classes/DocSignLifecycle.cls`

```
L 64: for (DocSign_Recipient__c r : recips) {
```

Object: `recips` in file: `classes/DocSignLifecycle.cls`

```
L 67: Database.update(recips, AccessLevel.SYSTEM_MODE);
```

FLS Update result path 5: Similarity Id: 918057559

Object: `token_hash__c` in file: `classes/DocSignSigningService.cls`

```
L 236: o.Token_Hash__c = null;
```

Object: `others` in file: `classes/DocSignSigningService.cls`

```
L 235: for (DocSign_Recipient__c o : others) {
```

Object: `others` in file: `classes/DocSignSigningService.cls`

```
L 238: Database.update(others, AccessLevel.SYSTEM_MODE);
```

FLS Update result path 6: Similarity Id: -948241561

Object: `failed_access_attempts__c` in file: `classes/DocSignRoutingService.cls`

```
L 42: r.Failed_Access_Attempts__c = 0;
```

Object: `r` in file: `classes/DocSignRoutingService.cls`

```
L 46: r.Sent_Date__c = now;
```

Object: `recips` in file: `classes/DocSignRoutingService.cls`

```
L 36: for (DocSign_Recipient__c r : recips) {
```

Object: `recips` in file: `classes/DocSignRoutingService.cls`

```
L 49: Database.update(recips, AccessLevel.SYSTEM_MODE);
```

FLS Update result path 7: Similarity Id: -377272028

Object: `status__c` in file: `classes/DocSignRoutingService.cls`

```
L 44: r.Status__c = 'Sent';
```

Object: `r` in file: `classes/DocSignRoutingService.cls`

```
L 46: r.Sent_Date__c = now;
```

Object: `recips` in file: `classes/DocSignRoutingService.cls`

```
L 36: for (DocSign_Recipient__c r : recips) {
```

Object: `recips` in file: `classes/DocSignRoutingService.cls`

```
L 49: Database.update(recips, AccessLevel.SYSTEM_MODE);
```

FLS Update result path 8: Similarity Id: 1860186095

Object: `token_hash__c` in file: `classes/DocSignRoutingService.cls`

```
L 38: r.Token_Hash__c = DocSignTokenService.hash(token);
```

Object: `r` in file: `classes/DocSignRoutingService.cls`

```
L 42: r.Failed_Access_Attempts__c = 0;
```

Object: `r` in file: `classes/DocSignRoutingService.cls`

```
L 46: r.Sent_Date__c = now;
```

Object: `recips` in file: `classes/DocSignRoutingService.cls`

```
L 36: for (DocSign_Recipient__c r : recips) {
```

Object: `recips` in file: `classes/DocSignRoutingService.cls`

```
L 49: Database.update(recips, AccessLevel.SYSTEM_MODE);
```

FLS Update result path 9: Similarity Id: -1752669861

Object: `value__c` in file: `classes/DocSignSigningService.cls`

```
L 148: u.Value__c = 'Signed';
```

Object: `u` in file: `classes/DocSignSigningService.cls`

```
L 189: updates.add(u);
```

Object: `updates` in file: `classes/DocSignSigningService.cls`

```
L 191: Database.update(updates, AccessLevel.SYSTEM_MODE);
```

FLS Update result path 10: Similarity Id: -906219167

Object: `signature_file_id__c` in file: `classes/DocSignCompletionService.cls`

```
L 163: u.Signature_File_Id__c = files[i].Id;
```

Object: `u` in file: `classes/DocSignCompletionService.cls`

```
L 169: upd.put(r.Id, u);
```

Object: `upd` in file: `classes/DocSignCompletionService.cls`

```
L 171: Database.update(upd.values(), AccessLevel.SYSTEM_MODE);
```

FLS Update result path 11: Similarity Id: -168519510

Object: `initials_file_id__c` in file: `classes/DocSignCompletionService.cls`

```
L 166: u.Initials_File_Id__c = files[i].Id;
```

Object: `u` in file: `classes/DocSignCompletionService.cls`

```
L 169: upd.put(r.Id, u);
```

Object: `upd` in file: `classes/DocSignCompletionService.cls`

```
L 171: Database.update(upd.values(), AccessLevel.SYSTEM_MODE);
```

Query: Sharing

All entry points to an app (Global or Controller classes) must use the 'with sharing' keyword. Classes without this keyword run without sharing if they are entry points to your code, or with the sharing policy of the caller. Do not omit the sharing declaration as this hides critical security information in side-effects that can change when code is refactored. Only declare classes as 'without sharing' if they are not entry points to your app and if they only modify objects whose security is managed by your code (such as wizard state, or fields in a site). It is a common misconception to believe that batch apex or async apex must run with the global keyword. This is not true, the only classes that must be global are those that expose webservices or are intended to be used by extension packages. All async apex should run as public in order to avoid creating privileged entry points to your app.

Reference:

https://www.salesforce.com/us/developer/docs/apexcode/Content/apex_classes_keywords_sharing.h
(https://www.salesforce.com/us/developer/docs/apexcode/Content/apex_classes_keywords_sharing.

Sharing result path 1: Similarity Id: 1900252797

Object: `docsignsigningservice` in file: `classes/DocSignSigningService.cls`

```
L 12: public without sharing class DocSignSigningService {
```

Sharing result path 2: Similarity Id: 284663965

Object: `docsignroutingservice` in file: `classes/DocSignRoutingService.cls`

```
L 6: public without sharing class DocSignRoutingService {
```

Sharing result path 3: Similarity Id: -287546979

Object: `docsignremindersender` in file: `classes/DocSignReminderSender.cls`

```
L 4: public without sharing class DocSignReminderSender {
```

Sharing result path 4: Similarity Id: -350168395

Object: `docsignlifecycle` in file: `classes/DocSignLifecycle.cls`

```
L 5: public without sharing class DocSignLifecycle {
```

Sharing result path 5: Similarity Id: 2015685725

Object: `docsignevents` in file: `classes/DocSignEvents.cls`

```
L 6: public without sharing class DocSignEvents {
```

Sharing result path 6: Similarity Id: 2109073683

Object: `docsigncompletionservice` in file: `classes/DocSignCompletionService.cls`

```
L 6: public without sharing class DocSignCompletionService {
```

Sharing result path 7: Similarity Id: -945758467

Object: `docsigncertificatebuilder` in file: `classes/DocSignCertificateBuilder.cls`

```
L 4: public without sharing class DocSignCertificateBuilder {
```

Sharing result path 8: Similarity Id: -1216158147

Object: `docsignauditservice` in file: `classes/DocSignAuditService.cls`

```
L 9: public without sharing class DocSignAuditService {
```

Query: Apex CSRF Aura LWC

Cross-site request forgery (also known as CSRF or XSRF). The web does not and cannot sufficiently verify whether a well-formed, valid, consistent request was intentionally provided by the

user who submitted the request. In effect, when a server receives a request it has no ability to determine whether that was initiated by a valid user or an attacker, leading to potential escalation of privilege attacks. This issue may be a false positive if the intention of your code is to allow unauthenticated DML operations (for example a web2case service). In Aura components, "init" sections are executed on page load and could lead to CSRF if DML operations are performed in Apex on page load.

Reference:

https://developer.salesforce.com/docs/atlas.en-us.packagingGuide.meta/packagingGuide/secure_code_violation_request_forgery.htm (https://developer.salesforce.com/docs/atlas.en-us.packagingGuide.meta/packagingGuide/secure_code_violation_request_forgery.htm)

Apex CSRF Aura LWC result path 1: Similarity Id: -1168850506

Object: `createFromUpload({ recordId: this.record...` in file: `lwc/docSignRecordPanel/docSignRecordPanel.js`

```
L 126: const res = await createFromUpload({ recordId: this.recordId,
```

Object: `createfromupload` in file: `classes/DocSignPdfPrepController.cls`

```
L 64: public static Created createFromUpload(Id recordId, Id contentl
```

Apex CSRF Aura LWC result path 2: Similarity Id: 1253221469

Object: `cloneTemplate({ templateId: id });` in file: `lwc/docSignTemplateManager/docSignTemplateManager.js`

```
L 173: await cloneTemplate({ templateId: id });
```

Object: `insert` in file: `classes/DocSignTemplateController.cls`

```
L 160: insert as user c;
```

Apex CSRF Aura LWC result path 3: Similarity Id: 1014256565

Object: `previewPdf({ templateId: this.tpl.id, re...` in file: `lwc/docSignTemplateManager/docSignTemplateManager.js`

```
L 513: const res = await previewPdf({ templateId: this.tpl.id, recor
```

Object: `previewpdf` in file: `classes/DocSignTemplateController.cls`

```
L 209: public static DocSignGenerationService.PreviewResult previewP
```

Apex CSRF Aura LWC result path 4: Similarity Id: 777267497

Object: `saveSettings({ payload: JSON.stringify(p...` in file: `lwc/docSignSettings/docSignSettings.js`

```
L 174: await saveSettings({ payload: JSON.stringify(payload) });
```

Object: `upsert` in file: `classes/DocSignHomeController.cls`

```
L 230: upsert as user s;
```

Apex CSRF Aura LWC result path 5: Similarity Id: -745394454

Object: `saveTemplate({ payload: JSON.stringify(t...` in file: `lwc/docSignTemplateManager/docSignTemplateManager.js`

```
L 321: const id = await saveTemplate({ payload: JSON.stringify(this.
```

Object: `upsert` in file: `classes/DocSignTemplateController.cls`

```
L 145: upsert as user rec;
```

Query: Apex SOQL SOSL USER MODE MISSING

USER_MODE is recommended for SOQL or SOSL operations

Reference:

https://developer.salesforce.com/docs/atlas.en-us.apexcode.meta/apexcode/apex_classes_enforce_usermode.htm (https://developer.salesforce.com/docs/atlas.en-us.apexcode.meta/apexcode/apex_classes_enforce_usermode.htm)

Apex SOQL SOSL USER MODE MISSING result path 1: Similarity Id: 1172351012

Object: `getparameters` in file: `classes/DocSignPageImageController.cls`

```
L 13: Map<String, String> p = ApexPages.currentPage().getParameters(
```

Object: `p` in file: `classes/DocSignPageImageController.cls`

```
L 14: data = imageFor(p.get('t'), p.get('v'));
```

Object: `versionid` in file: `classes/DocSignPageImageController.cls`

```
L 17: public static String imageFor(String token, String versionId)
```

Object: `versionid` in file: `classes/DocSignPageImageController.cls`

```
L 22: return DocSignSigningService.pageImage(token, versionId).subst
```

Object: `versionid` in file: `classes/DocSignSigningService.cls`

```
L 390: public static String pageImage(String rawToken, String versio
```

Object: `versionid` in file: `classes/DocSignSigningService.cls`

```
L 403: Id vid = Id.valueOf(versionId);
```

Object: `vid` in file: `classes/DocSignSigningService.cls`

```
L 404: ContentVersion cv = [SELECT VersionData FROM ContentVersion WH
```

Apex SOQL SOSL USER MODE MISSING result path 2: Similarity Id: 961642504

Object: `s` in file: `classes/DocSignSigningTest.cls`

```
L 39: Assert.areEqual(6, s.fields.size());
```

Object: `s` in file: `classes/DocSignSigningTest.cls`

```
L 41: Assert.isTrue(s.documentHtml.contains('ds-mine'));
```

Object: `s` in file: `classes/DocSignSigningTest.cls`

```
L 53: DocSignSigningService.Session done1 = DocSignSigningService.sub
```

Object: `s` in file: `classes/DocSignTestFactory.cls`

```
L 109: public static DocSignSigningService.Submission fullSubmission
```

Object: `s` in file: `classes/DocSignTestFactory.cls`

```
L 116: for (DocSignSigningService.FieldDto f : s.fields) {
```

Object: `f` in file: `classes/DocSignTestFactory.cls`

```
L 118: sub.values.put(String.valueOf(f.index), 'CEO');
```

Object: `sub` in file: `classes/DocSignTestFactory.cls`

```
L 123: return sub;
```

Object: `fullsubmission` in file: `classes/DocSignSigningTest.cls`

```
L 53: DocSignSigningService.Session done1 = DocSignSigningService.sub
```

Object: `sub` in file: `classes/DocSignSigningService.cls`

```
L 112: public static Session submit(String rawToken, Submission sub,
```

Object: `sub` in file: `classes/DocSignSigningService.cls`

```
L 141: String v = sub.values == null ? null : sub.values.get(key);
```

Object: `v` in file: `classes/DocSignSigningService.cls`

```
L 178: String t = v == null ? '' : v.trim();
```

Object: `t` in file: `classes/DocSignSigningService.cls`

```
L 182: if (t.length() > 255) {
```

Object: `t` in file: `classes/DocSignSigningService.cls`

```
L 185: u.Value__c = String.isBlank(t) ? null : t;
```

Object: `u` in file: `classes/DocSignSigningService.cls`

```
L 189: updates.add(u);
```

Object: `updates` in file: `classes/DocSignSigningService.cls`

```
L 191: Database.update(updates, AccessLevel.SYSTEM_MODE);
```

Results are provided through a partnership with Checkmarx. Checkmarx, through its suite of Source Code Analysis tools, provides powerful solutions for identifying, tracking, and fixing technical and logical security flaws. Checkmarx is the first and only company to provide Source Code Analysis for the Force.com platform. For Sales inquiries and pricing information please visit:
https://www.checkmarx.com/salesforce/ (https://www.checkmarx.com/salesforce/)
Additional details and other supported languages can be found on the Checkmarx website - https://www.checkmarx.com (https://www.checkmarx.com)