# Pravadh DocSign — Test Org Configuration and Testing Instructions

**Package:** Pravadh DocSign (namespace `prvd`), version 0.11.0 (`04tdN000000SNo5QAG`) · **Date:** 29 September 2026

## 1. Test org

| Item | Value |
|---|---|
| Org type | Developer Edition, Pravadh DocSign 0.11.0 installed (managed package) |
| Login URL | [login URL] |
| Reviewer user | System Administrator profile + **Pravadh DocSign Admin** permission set (credentials provided in the submission form) |
| App | App Launcher → **Pravadh DocSign** (tabs: Home, Templates, Documents, Envelopes, Settings) |

No further configuration is needed. Everything below is already set up.

## 2. Pre-configured items

| Item | Configuration |
|---|---|
| Signing Site | [Site URL]. Require Secure Connections (HTTPS) on; Visualforce pages `prvd__DocSignSign` and `prvd__DocSignPageImage`; the guest user has only the **Pravadh DocSign Signing Guest** permission set. The same URL is saved in DocSign → Settings → Signing Site URL. |
| Email | Setup → Deliverability → Access level: **All email**. DocSign → Settings → **Send test email** confirms delivery. |
| Sample templates (active) | [template 1 (object)], [template 2 (object)] |
| Sample records | [record 1], [record 2]. The Pravadh DocSign component is on their record pages. |
| External callouts | None. The package needs no Remote Site Settings, Named Credentials or external accounts. |

## 3. How to test

Use your own email address for signers so that you receive the signing links. A fuller walkthrough is in the attached *Solution Architecture and Usage* document, section 8.

### 3.1 Generate a document

1. Open [record 1]. In the **Pravadh DocSign** panel, choose a template and click **Generate Document**.
2. The PDF appears in the panel and under the record's Files. Open it to check the merged values.

### 3.2 Send for signature (two signers, sequential)

1. Click **Send for Signature**. Add signer 1 and signer 2 with email addresses you can access. Optionally set an access code for signer 2. Click **Send**.
2. Open signer 1's email and click the link. The signing page opens on the Salesforce Site without a Salesforce login.
3. Fill the highlighted fields, accept the electronic-records consent, draw or type a signature and click **Finish**.

4. Signer 2 then receives the email. Open the link, enter the access code if you set one, and sign.
5. After a short asynchronous step, the record's Files show the **signed PDF** and the **Certificate of Completion**. The envelope status is **Completed**.

### 3.3 Sign an uploaded PDF

1. On a record choose **Upload a PDF for signature** and upload any PDF (100 pages or fewer).
2. In the **Prepare** editor, review the suggested fields, assign them to signers, then **Save & continue** and **Send**.
3. Sign as in 3.2. Page images load one page at a time on the signing page.

### 3.4 Security and negative tests

| Test | Expected result |
|---|---|
| Decline a signing request with a reason | Envelope becomes Declined; the other links stop working. |
| Resend an envelope, then open the old link | Old link is rejected as replaced. |
| Open `…/prvd__DocSignSign?t=abc` (random token) | "Invalid link" page; no data shown. |
| `prvd__DocSignPageImage` with a valid token but another document's image id | Empty response. |
| Enter 5 wrong access codes | The link locks. |
| Edit or delete a DocSign Audit Event as an admin | Blocked by the package. |
| Save DocSign Settings as a user without Pravadh DocSign Admin | Refused. |

### 3.5 Flow

The invocable actions (Generate Document, Send for Signature, Get Signature Status, Cancel Envelope, Resend Envelope) appear in Flow Builder under **Pravadh DocSign**.

## 4. Notes

- Signing emails come from the org's default sender (or the org-wide address set in Settings). Check spam if they don't arrive.
- Contact: Dhairya Shah, Pravadh Labs — [contact email].